Soup AI Engineering Report: Qwen2.5-1.5B Fine-Tuning & Verification

Candidate: Balavignesh V.T. | GitHub: @Speedyzyzz | Hardware: NVIDIA Tesla T4 (15.00 GiB Usable)

VERDICT: SHIP

Architecture & Justification: `Qwen/Qwen2.5-1.5B-Instruct` (1.54B params, 28 layers, GQA 12Q/2KV, vocab 151,936) fine-tuned on 1,500 curated dialogues from `HuggingFaceTB/smoltalk` (1,450 train / 50 held-out eval, substantive turns ≥ 40 chars). Stack: `soup-cli[train]` v0.77.2, PyTorch, Transformers, PEFT (rsLoRA r=16, α=32 across all 7 projections = 18,464,768 params), BitsAndBytes NF4 double quantization.

1. Pre-Training Analytical Memory Budget vs. Empirical T4 Telemetry

Memory Component	Precision / Format	Analytical Formula (B=2, S=512, V=151,936)	Analytical Est.	Observed Peak	Engineering Explanation & Gap
Base Model Weights	FP16 (2 B/param)	1,543,714,304 × 2 B (lm_head tied to embed_tokens)	2,944.40 MiB	2,952 MiB	+7.6 MiB for RoPE cos/sin caches and persistent buffers.
rsLoRA Master Weights	FP32 (4 B/param)	28 layers × 659,456 params × 4 B	70.44 MiB	71 MiB	PEFT maintains FP32 master weights for AMP training (35.22 MiB on disk).
AdamW Optimizer	FP32 (m, v: 8 B/param)	18,464,768 × 8 B (adamw_torch)	140.88 MiB	142 MiB	First and second moments allocated solely for the 18.46M trainable adapter params.
Adapter Gradients	FP32 (4 B/param)	18,464,768 × 4 B	70.44 MiB	71 MiB	Unscaled FP32 gradients accumulated prior to clip_grad_norm_(1.0).
Activations (Checkpointed)	FP16 (use_cache=False)	28 × (2 × 512 × 1536 × 2 B) + single-layer recompute	410.00 MiB	424 MiB	84 MiB layer-boundary tensors + ~340 MiB single-layer backward recomputation buffer.
Logits + FP32 CE Loss	FP16 → 3× FP32	2 × 512 × 151,936 × (2 + 4 + 4 + 4) B	2,077.25 MiB	2,084 MiB	FP16 lm_head (296.75 MiB) + logits.float(), shift_logits, ∇L_CE (3 × 593.5 MiB). Dominant transient spike!
CUDA Context & Allocator	Driver + Segment Cache	CUDA driver context (~550 MiB) + caching allocator reserve	582.00 MiB	676 MiB	PyTorch caching allocator rounds block allocations into 20 MiB segments.
Peak Training Total	FP16 AMP + Grad Ckpt	Sum of active allocations + runtime context	6,295.41 MiB	6,420 MiB	+1.98% gap (+124.6 MiB) from caching allocator block reservation. 58.2% headroom.
GPU Merge Peak	FP16 Base + GEMM Clone	W_base + coexisting FP32/FP16 clone & BA accumulator	6,620.00 MiB	6,840 MiB	Transient spike while base and rsLoRA GEMM buffers coexist before safetensors write.
4-Bit NF4 Quantization	BnB NF4 + Double Quant	1.31B × 0.5625 B + 0.23B × 2 B + context	1,164.00 MiB	1,746 MiB	embed_tokens kept FP16 (445 MiB) + 703 MiB NF4 weights + context. Disk: 824 MB.

2. Proving the Model Actually Trained (verify_artifacts.py Scorecard)

Falling training loss does NOT prove learning: unmasked prompts plunge loss by memorizing deterministic templates, while export bugs can silently detach adapters. We verify 3 artifacts (Base, Merged, 4-Bit) across 6 mathematical proofs:

Verification Proof	Required Criterion	Observed Value	Status	Engineering Interpretation
1. Target Projections Frobenius Norm	Mean ||W_merged - W_base||_F > 0.01	2.216729	PASS	Active low-rank adaptation across all 196 linear layers (28 × 7).
2. Frozen Modules Frobenius Norm	Bit-exact == 0.000000	0.000000	PASS	Zero gradient leakage on embed_tokens, 57 RMSNorms, and tied lm_head.
3. SVD Rank-16 Spectral Energy	> 95.0% in top r=16 singular values	100.00% (denoised) / 99.9924% (raw)	PASS	Mathematically confirms true low-rank update, ruling out checkpoint jitter.
4. Global Cosine Similarity	Within [0.985, 0.9999]	0.999745	PASS	Preserved representation geometry; rules out catastrophic weight collapse.
5. 4-Bit Dequantized Lineage Check	||W_4bit - W_merged||_F < ||W_4bit - W_base||_F	7.0868 < 7.2882	PASS	Proves Artifact C was derived from Merged, not accidentally from Base.
6. Base Model Held-Out Perplexity	Multi-turn assistant cross-entropy (N=50)	3.1160 (5,627 tokens)	BASELINE	Evaluated on held-out dialogues with turn-by-turn prompt masking.
7. Merged FP16 Held-Out Perplexity	Strictly < Base Perplexity	2.3145 (-25.72% drop)	PASS	Substantive conversational quality gain with -0.8015 ppl drop.
8. 4-Bit NF4 Held-Out Perplexity	Quantization penalty ≤ +0.50 ppl	2.4019 (+0.0874 ppl)	PASS	Negligible degradation under 4-bit compression (1.75 GiB footprint).
9. Token KL Divergence (Merged || Base)	> 0.01 nats/tok (learned shift)	0.47676 nats/tok	PASS	77.18% Top-1 agreement confirms genuine stylistic shift from base.
10. Token KL Divergence (Merged || 4-Bit)	Fidelity preserved (> 90% Top-1 agree)	0.08292 nats/tok	PASS	90.19% Top-1 agreement confirms 4-bit output tracks unquantized FP16 teacher.
11. Active Generation EOS Termination	≥ 90% clean <|im_end|> termination	100.0% (10/10)	PASS	Distinct 4-gram ratio = 1.0000; zero infinite loops or stuttering.

Explicit Blind Spots: verify_artifacts.py measures in-domain distribution shift and weight geometry. It CANNOT verify: (1) factual truthfulness or hallucination avoidance; (2) broad reasoning retention (e.g. GSM8k math, HumanEval coding); (3) safety/jailbreak refusal preservation; (4) long-context (>512 tokens) retrieval fidelity.

Soup AI Engineering Report: Silent Failures, Audit & Verdict

Candidate: Balavignesh V.T. | Hardware: NVIDIA Tesla T4 | Repository: github.com/Speedyzyzz/soup-takehome

3. End-to-End Silent Failure Modes Audit

#	Pipeline Stage	Silent Failure Mode	Detection & Verification Procedure	Caught by Built-Ins?	Empirical Proof
1	Data → Collator	Multi-Turn Label Mask Misalignment: filtering role != 'assistant' concatenates user turns and unmasks user headers.	Tokenize turn-by-turn with build_assistant_masked_labels; assert zero <|im_start|>user headers have labels != -100.	Partially (soup data doctor checks single turns, not custom mappers).	Zero user tokens unmasked across 1,450 dialogues; loss dropped smoothly to 1.028.
2	Tokenizer & Template	Missing <|im_end|> EOS Token: omitting token 151645 causes models to generate infinitely until max_length.	Assert 151645 closes every assistant span; run greedy generation probes and verify termination.	Yes (soup data doctor flags eos_in_labels and bos_duplication).	10/10 test completions terminated at <|im_end|> in 18-36 tokens.
3	Training (T4 sm_75)	Frozen-Input Grad Detachment & FP16 Underflow: grad checkpointing on frozen base detaches gradients; raw FP16 underflows < 2^-14.	Enforce use_reentrant=False, enable_input_require_grads(), and FP16 AMP GradScaler; log step grad_norm.	Yes (soup doctor verifies Turing sm_75 and configures GradScaler).	grad_norm remained healthy (0.41-0.89) across all 362 optimizer steps.
4	Adapter Fusion	Untied Embeddings & Wrong LoRA Scaling: merge_and_unload unties lm_head (+467 MB bloat) or scales α/r instead of α/√r.	Assert config.tie_word_embeddings == True; verify SVD rank-16 energy > 99.9%.	Partially (soup merge fuses adapters but omits SVD rank checks).	lm_head and embed_tokens share identical pointers; SVD energy = 100.00%.
5	Quantization	Unsaved Quantized Weights / Base-Model Lineage: saving only tokenizer or quantizing Base instead of Merged.	Call quant_model.save_pretrained; verify ||W_4bit - W_merged||_F < ||W_4bit - W_base||_F.	No (Requires custom dequantized norm distance check).	Dequantized distance 7.0868 (to Merged) vs 7.2882 (to Base) across all layers.
6	Inference	4-Bit Outlier Clipping & Degenerate Repetition: clipping salient down_proj channels causes repetitive stuttering.	Measure token KL-divergence and distinct 4-gram diversity on greedy completions.	Partially (soup ship checks eval loss, not KL divergence or n-gram diversity).	KL(Merged || 4-Bit) = 0.08292 nats/tok; distinct 4-gram ratio = 1.0000.

4. Chronological Real-World Failures & Engineering Resolutions

#	Environment	Failure Encountered	Root Cause Analysis	Permanent Engineering Resolution
1	Colab T4	Runtime disconnected due to inactivity after 30m	Chrome background tab throttling dropped WebSocket session.	Migrated to Kaggle detached asynchronous container runs (Save & Run All).
2	Kaggle v1	Failed after 0 seconds	Raw .ipynb JSON string pasted into code cell instead of file import.	Imported native notebook via File → Upload Notebook.
3	Kaggle v1	nvidia-smi not found / PyTorch 2.11+cpu	Kaggle defaulted new notebooks to CPU prior to phone verification.	Completed SMS verification, enabled GPU T4 x2, pinned CUDA_VISIBLE_DEVICES='0'.
4	Kaggle v2	ValueError: Cannot apply chat template to empty conversation	build_multiturn_labels sliced messages[:0] on turn 0 (empty list).	Added guard: if idx == 0: prefix_ids = [] before applying chat template.
5	Kaggle v2	ImportError: Found incompatible torchao 0.10.0	Kaggle preinstalled torchao 0.10.0; PEFT 0.13 is_torchao_available raised error.	3-tier purge: rm -rf dist-packages, sys.modules['torchao']=None, monkey-patch False.
6	Kaggle v2	TypeError: TrainingArguments got unexpected 'warmup_ratio'	Transformers v5 deprecated warmup_ratio in TrainingArguments.__init__.	Replaced warmup_ratio=0.05 with exact step count warmup_steps=18.
7	Kaggle v3	Curated dataset collapsed from 2,260 to 5 dialogues	Deduplication on first_user collapsed generic openings ('Hi', 'Hello').	Hashed full transcript (' '.join(turns)) and asserted len(train)==1450, eval==50.

5. Surprises & Open Concerns

What Surprised Us: The magnitude of the FP32 vocabulary logit spike during cross-entropy loss was our biggest systems surprise. With Qwen2.5's 151,936-token vocabulary, the transient memory for FP16 logits, FP32 upcast, `shift_logits`, and backward loss gradient consumed 2.04 GiB (32.5% of total training peak). On an 8 GB consumer GPU, this single tensor causes an immediate OOM even with batch size 2 and gradient checkpointing active. Additionally, BitsAndBytes NF4 double quantization preserved an astounding 90.19% Top-1 next-token agreement with only +0.0874 perplexity penalty over the FP16 model.

What Still Concerns Us: Although the model achieved a 25.72% held-out perplexity reduction and 100% EOS termination, we are concerned about subtle multi-step reasoning degradation (catastrophic forgetting on GSM8k/HumanEval) and RLHF refusal boundary erosion. Parameter-efficient fine-tuning on benign conversational data alters self-attention routing in ways that standard in-domain perplexity checks cannot penalize. Before deploying to production, this artifact must pass a multi-task canary regression benchmark in CI.

6. AI Tools Usage & Verification Audit

We used an AI coding assistant to scaffold initial script boilerplate and report formatting, and manually verified every component: (1) **Caught Wrong LoRA Parameter Count:** The AI estimated 14.84M parameters assuming uniform projection dimensions; we derived the exact 18,464,768 parameter count by inspecting Qwen2.5's GQA 12Q/2KV head architecture ({{ ext{inter}}=8960$ across 28 layers). (2) **Caught Smoltalk Deduplication Bug:** The AI deduplicated by `first_user` turn, which collapsed 2,260 conversations to 5 because almost every dialogue opens with 'Hi'; we rewrote the deduplicator to hash the entire multi-turn transcript and enforced hard sample assertions. (3) **Caught Incompatible Warmup Flag:** The AI wrote `warmup_ratio=0.05` which crashed in Transformers v5; we replaced it with `warmup_steps=18`. (4) **Derived Memory Math:** Every byte allocation in the memory budget was calculated by hand from tensor shapes and verified against continuous 1 Hz `nvidia-smi` telemetry.

7. Final Deployment Verdict: SHIP

> **Verdict: >>> SHIP <<< (Exit Code: 0)** — Artifact B (Merged FP16) and Artifact C (4-Bit NF4) surpass all 6 verification gates: -25.72% held-out perplexity gain, 100.00% SVD rank-16 spectral energy, bit-exact frozen isolation, verified 4-bit lineage distance, 100% EOS termination, and 50.9% VRAM headroom on NVIDIA Tesla T4. Recommended for staging deployment conditional on full GSM8k/Safety canary execution in CI.