

# Using Dynamic Analysis to Generate Disjunctive Invariants

ThanhVu Nguyen et al.

May 19, 2020

# Introduction

- ▶ Invariants: defect detection, program verification and program repair.
- ▶ Find the invariants: static or dynamic, and their pros and cons.
- ▶ Conjunctive, polynomial and convex invariants  $\Rightarrow$  Disjunctive program properties

# Disjunctive Program

## Example

`if ( $p$ ) {  $a = 1$ ; } else {  $a = 2$ ; }`

Neither  $a = 1$  nor  $a = 2$  is an invariant, but  
 $(p \wedge a = 1) \vee (\neg p \wedge a = 2)$  is an invariant.

# Overview


- ▶ Existing invariant inference algorithm.
- ▶ Max-Plus invariants and a way to infer them.
- ▶ Using  $k$ -induction to verifying candidate invariants.
- ▶ Experiment results.

# Motivating Example

## Example (1)

```
void ex1(int x){  
    int y=5;  
    if (x>y) x=y;  
    while [L] (x ≤ 10){  
        if (x ≥ 5)  
            y=y+1;  
        x=x+1;  
    }  
    assert (y==11);  
}
```

$x$	$y$
-1	5
$\vdots$	$\vdots$
5	5
6	6
$\vdots$	$\vdots$
11	11



A program with branch and a executing trace starting from  $x = -1$ . Invariant at location L is

$$(x < 5 \wedge y = 5) \vee (5 \leq x \leq 11 \wedge x = y)$$

# Conjunctive Invariant

From the given trace, existing tools like Daikon and DIG can generate conjunctive invariant below:

$$11 \geq x$$

$$11 \geq y \geq 5$$

$$y \geq x$$

which is over-approximating and cannot express the disjunctive behavior.

# Algorithm Overview

Max-plus inequality: e.g.  $\max(x, y + 1) \geq 1$

By constructing a max-plus polyhedra over the trace points, we obtain relations simplified to

$$\begin{array}{rclcl} 11 & \geq & x & \geq & -1 \\ 11 & \geq & y & \geq & 5 \\ 0 & \geq & x - y & \geq & -6 \end{array}$$

$$(x < 5 \wedge 5 \geq y) \vee (x \geq 5 \wedge x \geq y)$$

Then use **k-induction** to remove the spurious relations

$x - y \geq -6, x \geq -1$ . Further, the prover proves that  $11 \geq x$  is redundant.

$$11 \geq y \geq 5$$

$$0 \geq x - y$$

$$(x < 5 \wedge 5 \geq y) \vee (x \geq 5 \wedge x \geq y)$$

# Invariant Inference Algorithm




DIG: A Dynamic Invariant Generator for Polynomial and Array Invariants

General polyhedra inequality:

$$c_1 t_1 + \dots + c_n t_n \geq 0$$

Octagonal Inequalities:

$$c_1 t_1 + c_2 t_2 \geq k$$





# Max-Plus Invariant


To model disjunctive invariant, we use formulas representing max-plus polyhedra. i.e. a non-convex hull which is convex in the sense of max-plus algebra. Formally, max-plus relation can be expressed as:

$$\max(c_0, c_1 + v_1, \dots, c_n + v_n) \geq \max(d_0, d_1 + v_1, \dots, d_n + v_n)$$

$$c_i, d_i \in \mathbb{R} \cup \{-\infty\}$$

It is obvious that  $\max(x, y) > n$  is equivalent to  $(x \geq y \wedge x > n) \vee (y > x \wedge y > n)$ . Hence,...

# Geometric Shape of Max-Plus Invariant



**Figure 3:** (a) Three possible shapes of a max-plus line segment:  $\max(x + a, b) \geq y$  (top),  $\max(y + a, b) \geq x$  (right),  $\max(x + a, y + b) \geq 0$  (left) and (b) a max-plus convex hull built over four points using these line segments.

Convex on max-plus algebra: for any two points of the max-plus polyhedra, there is a max-plus line segment connecting these two points.

# Dynamically Infer Max-Plus Invariants

Input: set of variables  $V$ , set of traces  $X$ , max degree  $d$

Output: A set  $S$  of polynomial inequalities.

$T \leftarrow \text{genTerms}(V, d)$

$P \leftarrow \text{genPoints}(T, X)$

$H \leftarrow \text{createMaxPlusPolyhedron}(P)$


$S \leftarrow \text{extractFacets}(H)$

return  $S$ .

# Inferring Example

```
void ex1(int x){  
  int y=5;  
  if (x>y) x=y;  
  while[L](x ≤ 10){  
    if(x ≥ 5)  
      y=y+1;  
    x=x+1;  
  }  
  assert(y==11);  
}
```

$x$	$y$
-1	5
$\vdots$	$\vdots$
5	5
6	6
$\vdots$	$\vdots$
11	11



$$\begin{array}{rclcl} 11 & \geq & x & \geq & -1 \\ 11 & \geq & y & \geq & 5 \\ 0 & \geq & x - y & \geq & -6 \\ \max(0, x - 5) & \geq & y - 5 & & \end{array}$$

Conjunctions of formulas above is equivalent to

$$(x < 5 \wedge 5 = y) \vee (5 \leq x \leq 11 \wedge x = y)$$

# Weak Max-Plus Invariants

Traditional min max invariant complexity:  $O(n^k)$ <sup>1</sup>.

We define a weak max relation to be of the form:

$$\max(c_0, c_1 + v_1, \dots, c_k + v_k) \geq v_j + d$$

$$v_j + d \geq \max(c_0, c_1 + v_1, \dots, c_k + v_k)$$

where  $c_i \in \{0, -\infty\}$

Difference of weak version: Only performs in the form

$\max(x, b) \geq y$  and  $\max(y, b) \geq x$

---

<sup>1</sup>Inferring Min and Max Invariants Using Max-plus Polyhedra 

## Example of Finding Weak Max-Plus Invariant

Points:  $\{(x - 1, y_1), \dots, (x_n, y_n)\}$  in 2D.

For the form  $\max(c_0, x + c_1, y + c_2) \geq x + d$ , there are 8 versions depending on the value of  $c_i$ . Same for the other direction and different variable.

Then compute parameter  $d$  by using the points. e.g.

$$\max(y, 0) \geq x + d$$

then,  $d = \min(\max(y_i, 0) - x_i)$

Number of inequalities:  $O(k2^{k+2})$


Time complexity:  $O(n2^k)$

# Min-Plus Invariant

Min relation is of the form

$$\min(c_0, c_1 + v_1, \dots, c_n + v_n) \geq \min(d_0, d_1 + v_1, \dots, d_n + v_n)$$

Shapes:



Min-plus:

$$\min(c_0, c_1 + v_1, \dots, c_k + v_k) \geq v_j + d$$

$$v_j + d \geq \min(c_0, c_1 + v_1, \dots, c_k + v_k)$$

where  $c_i \in \{0, +\infty\}$

## Combine Max-Plus and Min-Plus

```
int ex2(int x){  
    int y, b;  
    if (x>=0) {y=x+1;}  
    else {y=x-1;}  
    b=(y>10);  
    [L]  
    return b;  
}
```

$x$	$y$	$b$
-50	-51	0
-33	-34	0
9	10	0
10	11	1
12	13	1
40	41	1

The invariant of this program at location  $L$  is

$$y \leq 10 \Leftrightarrow b = 0$$

can be described equivalently by

$$\max(y - 10, 0) \geq b \text{ and } b + 10 \geq \min(y, 11)$$



# Verifying Candidate Invariant

In the algorithm we use  $k$ -induction to verify the invariant and remove spurious invariant.

**k-Induction:**  $k$  base cases are specified, and  $k$  previous instance are available to prove the inductive step.

$$M = (I, T)$$

$$I \wedge T_1 \wedge \cdots \wedge T_k \Rightarrow p_0 \wedge \cdots \wedge p_k$$

$$p_n \wedge T_{n+1} \wedge \cdots \wedge p_{n+k} \wedge T_{n+k+1} \Rightarrow p_{n+k+1}$$

Sound, not complete.

# k-Induction Example

## Example (2)

$$M = (I, T)$$

$$I : x_0 = 0 \wedge y_0 = 1 \wedge z_0 = 2.$$

$$T_n : x_n = y_{n-1} \wedge y_n = z_{n-1} \wedge z_n = x_{n-1}$$

Standard induction:  $I \Rightarrow p_0$ ,  $p_i \wedge T_{i+1} \not\Rightarrow p_{i+1}$ .

3-Inductive:  $I \wedge T_1 \wedge T_2 \wedge T_3 \Rightarrow p_0 \wedge p_1 \wedge p_2 \wedge p_3$ .

$$p_i \wedge T_{i+1} \wedge p_{i+1} \wedge T_{i+2} \wedge p_{i+2} \wedge T_{i+3} \Rightarrow p_{i+3}$$

## Code: k-Induction

```
input  :  $I, T, p$   
output:  $\{proved, disproved, unproved\}$   
  
for  $k = 0$  to maxK do  
  | // base case  
  | if  $k = 0$  then  $S_b.assert(I)$  else  $S_b.assert(T_k)$   
  | if  $\neg S_b. entail(p_k)$  then return  $(disproved, S_b.cex)$   
  | // induction step  
  |  $S_s.assert(p_k, T_{k+1})$   
  | if  $\neg S_s. entail(p_{k+1})$  then return  $proved$   
return  $unproved$ 
```

## Code: KIP

```
input  :  $S, L, P$ 
output:  $P_i, P_r, P_d, P_u$ 
 $I, T \leftarrow \text{vcgen}(S, L)$ 
 $P_p \leftarrow \emptyset; P_d \leftarrow \emptyset; P_u \leftarrow \emptyset$ 
repeat
   $\text{New}_p \leftarrow \emptyset; \text{New}_u \leftarrow \emptyset$ 
  foreach  $p \in P$  do
     $r \leftarrow \text{kprove}(I, T, p)$ 
    if  $r = \text{proved}$  then
       $P_p.\text{add}(p); \text{New}_p.\text{add}(p)$ 
    else if  $r = \text{unproved}$  then  $\text{New}_u.\text{add}(p)$ 
    else  $P_d.\text{add}(p)$ 
   $\text{KIP}.\text{addLemmas}(\text{New}_p)$ 
   $P \leftarrow \text{New}_u$ 
until  $\text{New}_p = \emptyset \vee \text{New}_u = \emptyset$ 
 $P_u \leftarrow P$ 
 $P_i, P_r = \text{check\_redundancy}(P_p)$ 
return  $P_i, P_r, P_d, P_u$ 
```

# Experiment Result

Prog	Loc	Var	Gen	T <sub>Gen</sub>	Val	T <sub>Val</sub>	Hoare
ex1	1	2	15	0.2	4	1.5	✓
strncpy	1	3	69	1.1	4	7.7	✓
oddeven3	1	6	286	3.7	8	16.0	✓
oddeven4	1	8	867	12.7	22	46.0	✓
oddeven5	1	10	2334	56.8	52	1319.4	✓
bubble3	1	6	249	4.1	8	4.9	✓
bubble4	1	8	832	11.7	22	47.6	✓
bubble5	1	10	2198	53.9	52	938.2	✓
partd3	4	5	479	10.5	10	50.8	✓
partd4	5	6	1217	23.3	15	181.1	✓
partd5	6	7	2943	53.3	21	418.1	✓
parti3	4	5	464	10.3	10	45.5	✓
parti4	5	6	1148	22.4	15	165.1	✓
parti5	6	7	2954	53.6	21	405.6	✓
<b>total</b>			16055	317.6	264	3647.5	14/14