

# Discussion

May 16, 2020


# Limitation of Nested Ranking Functions

## Example

```
while ( $x > 0 \vee y > 0$ )  
{if ( $y > 0$ ) :  $y' = y - 1$ ;  $x' = x$ ; else :  $x' = x - 1$ ;
```

# Blocks

Idea: use terms of the loop guard to split the space into *blocks*.



# Cyclic Dependency and Irregular Split

## Example

**while**  $(x > 0 \vee y > 0)$

**{if**  $(y > 0) : y' = y - 2; x' = x; \mathbf{else} : y' = y + 1; x' = x - 1; \mathbf{}}$

Start with  $x = 1, y = 5$


A possible single linear ranking function  $f(x, y) = x + 3y$ .

This example demonstrates the blocks may be split by the ranking function.

i.e. in last example the regular split is just a coincidence.

# Blocks

Use the terms of a loop



# Multiphase Cyclic Dependency

## Example

```
while ( $x > 0 \vee y > 0$ )  
{if ( $y > 0$ ) :  $x' = x - 2z$ ;  $y' = y$ ;  $z' = z + 1$ ;  
  else :  $x' = x + z$ ;  $y' = y - 1$ ;  $z' = z$ ; }
```

Start from  $x = 1, y = 8, z = -2$ .

# Guess $f_1$ for Multiphase Ranking Function

Idea: although some ranking functions are not the borders of the blocks, we still wish to use the guard to guess the phases.

After a guess, conjunct the negation of the guard into the loop for next guess.

The example below shows that this idea is not feasible.

## Example

```
while ( $x > 0 \vee y > 0$ )  
{if ( $y > 0$ ) :  $y' = y - 1$ ;  $x' = 5$ ;  
  else :  $x' = x - 1$ ;  $y = 5$ ; }
```

The loop is not terminating but...

# Attempt to Merge the blocks

Idea: if we find the jump-in-and-out situations of the execution between two blocks, we consider it as one.

Problem: One cannot tell it is the problem of the inability of multiphase ranking function for this loop, or it is really that these two blocks should be merged.