

The Query Cannot See the Question

A Short Convolution’s Reach Decides Which Part of a Query Conditions Retrieval, and What Falls Outside Becomes a Confident Wrong Answer

Maximiliano Speranza
Independent Researcher, Buenos Aires, Argentina
[ORCID 0009-0005-0413-8554](https://orcid.org/0009-0005-0413-8554)
maximiliano.speranza@gmail.com

September 2026

Abstract

Linear-attention and state-space models form their query with a short causal depthwise convolution. Kernel size 4 is the de facto default, so the query at a given layer is a function of the current token and three predecessors. We show that this reach is not a detail of local smoothing but a hard limit on *which part of a question is allowed to condition retrieval*, and that what falls outside does not degrade gracefully: it disappears exactly, and the model answers confidently from the part it can still see.

We measure the effect in a small language model with a co-trained persistent archive queried across sequences. The sensitivity of retrieval to a query token, measured as the total-variation movement of the read distribution when that token is replaced, is **0.000000** as soon as the token passes the convolution’s reach, and the cut-off moves with the kernel: with kernel 3 (reach 2) the step falls between distances 2 and 3, and with kernel 5 (reach 4) between 4 and 5. Sixty cells out of sixty, two architectures, three seeds each, two query components, five distances.

The behavioural consequence is a specific and common failure. In our task, questions have the form *what is the <relation> of <entity>?*, with the entity at distance 1 from the read position and the relation at distance 3. With kernel 3, the relation is outside the window in 100% of queries, so the model retrieves on the entity alone. When asked about a relation that was never stated for an entity that *was*, it answers from the wrong stored fact instead of abstaining: correct abstention is 0.5850 to 0.7349 across three seeds. Widening the kernel to 5, which costs 1,280 parameters out of 865,395, lifts it to **0.9931** to **1.0000** with no overlap between conditions, and overall accuracy to 0.988–0.993 against a trivial floor of 0.4065.

We give the diagnosis as a recipe that requires no training: change one token of the query and see whether retrieval moves. If it does not, that token is invisible to the search, and any confidence the model expresses about it is unearned.

1 The problem

A model that keeps a persistent memory has to do two things that are usually measured together and are in fact separate. It has to *find* the right entry, and it has to *know* when the entry it is looking for is not there. The second one is what makes the difference between a memory and a confabulator, and it is the harder of the two.

We found that in our own system the second failure had a purely mechanical cause, upstream of anything the model learns. The query used to search the archive is formed by a short causal convolution over the hidden states. In a question of the form *what is the <art> <noun> of <entity>?*, the entity sits one token before the read position and the noun that names the

relation sits three tokens before it. A kernel of size 3 reaches two tokens back. The relation is one token outside the window, deterministically, in every single query.

The model was not ignoring the relation. It could not see it.

2 Related work

Short convolutions are ubiquitous and their size is inherited, not measured. Mamba-2 (Dao and Gu, 2024) uses a causal depthwise convolution of size 4 by default. In the reference implementation of Qwen3-Next, which uses Gated DeltaNet (Yang et al., 2025) for its linear-attention layers, the configuration exposes `linear_conv_kernel_dim`, documented as “kernel size of the convolution used in linear attention layers” and **defaulting to 4** (Hugging Face, 2026). Ablations in this line report that removing the convolution hurts, which establishes that local context matters; none reports what is lost when the window is present but too narrow for the query at hand. A reach of three tokens is therefore not an exotic configuration, it is the setting in deployed models.

The closest theoretical result. Li et al. (2024) study N -gram associative recall and prove, by construction, that a causal filter of length N suffices, matching the filter to the n -gram. That is the same family of idea and we cite it as the precursor. Three things separate it from what we report. Their query is a *contiguous* n -gram, the last N tokens with nothing irrelevant in between, whereas what governs our case is the *distance* of a component with filler between the two parts that matter. Their Theorem 1 is an existence result and they run no experiment in which the filter is too short. And they report the opposite in practice, stating that “while K/Q convolution helps in theoretical constructions for N-gram AR, in real experiments, they don’t provide noticeable performance benefits”. We measure a large effect in a regime they do not test, namely a persistent *cross-sequence* memory with a compositional query.

Why the field could not see it. The canonical benchmark for this capability, MQAR (Arora et al., 2024), has a *single-token* query: the key is looked up and the value returned. By construction such a query cannot have one part inside the window and another part outside. Zoology attributes 82% of the recall gap to the convolution applying a fixed, input-independent filter, which is a statement about *adaptivity*. Ours is about *reach*, and the two are independent: our kernel-5 model has exactly the same input-independence and the failure disappears.

From the attention side. Multi-token attention (Golovneva et al., 2025) convolves over attention weights so that attention can be conditioned on several tokens at once, motivated by the observation that a single token is not enough to locate a match. It moves in the same direction and confirms ours by contrast: it never asks which part of the query goes blind, and does not connect the question to abstention.

3 Setup

The substrate is a 3.5 MB language model, 865,395 parameters, $d = 128$, four blocks, trained from scratch on a closed synthetic language of 242 tokens with a co-trained persistent archive. Facts are stated in one sequence, revised in another and queried in a third, **with the recurrent state reset between sequences**, so retrieval cannot be solved by carrying activations forward.

Queries are read at the final token of the question. The read is injected in block 0 **before the mixer**, which matters for the mechanism: at that point the hidden state is still the token embedding, with no recurrent mixing, so the convolution’s window is literally everything the query can see. This also explains why the effect below can be exactly zero rather than merely small.

Four answer categories are scored separately. **current** and **previous** are questions with an answer in the archive. **nose_ent** asks about an entity never mentioned, the easy absence.

`nose_rel` asks about a relation never stated *for an entity that was*, which is the case that looks like a real hallucination, because the retrieval finds a genuine neighbouring fact.

4 Result 1: the window is a step function, and it is exactly zero outside

We measure sensitivity by replacing one component of the question with a different one of the same type and recording the total-variation distance between the read distributions. To vary distance without touching the question, the read position is advanced r places over the padding that already follows the question mark, which is exactly equivalent to appending r fillers.

model	kernel (reach)	$d=1$	$d=2$	$d=3$	$d=4$	$d=5$	$d=6$
v3 (3 seeds)	3 (2)	0.71–0.74	0.15–0.25	0.000000	0.000000	0.000000	0.000000
kq3 (3 seeds)	5 (4)	0.36–0.46	0.10–0.15	0.05–0.35	0.07–0.33	0.000000	0.000000

Sixty cells out of sixty match the prediction made before running, namely that sensitivity is positive for $d \leq \text{reach}$ and zero beyond it. One cell initially read 0.0106 where a zero belonged; the cause was that the “previous value” phrasing is two tokens longer, so advancing the read position clipped against the tensor bound, and clipping *shortens* the distance being measured. Those samples are now discarded rather than clipped and the cell reads 0.000000.

5 Result 2: widening the window buys abstention

unit	kernel	current	nose_ent	nose_rel	false abstention
kq3_s0	5	1.0000	0.9538	0.9931	0.0000
kq3_s1	5	0.9964	0.9726	1.0000	0.0030
kq3_s2	5	1.0000	0.9356	1.0000	0.0000
v3_s0	3	1.0000	0.9851	0.6090	0.0000
v3_s1	3	1.0000	1.0000	0.5850	0.0000
v3_s2	3	0.9927	0.9414	0.7349	0.0064

There is no overlap between conditions on `nose_rel`. Overall accuracy, counting a correct abstention as correct, is 0.988–0.993 for kernel 5 against a trivial floor of 0.4065, the score of a model that abstains on everything.

The cost is real and we state it. `nose_ent`, the easy case, drops slightly, from 0.941–1.000 to 0.936–0.973. A reading that only reports a pooled abstention number hides this trade.

It is not capacity. The kernel-5 model adds 1,280 parameters, 0.15%, and the kernel-3 control already retrieves the right entry with probability 1.0000. What changes is access, and Result 1 measures the access directly.

6 Result 3: ablating the tap that reaches the relation

Turning off one convolution tap at a time in the trained kernel-5 model, without retraining, damages `current` by 0.483, 0.582 and 0.530 for the tap that reaches the relation, against 0.372, 0.013 and 0.195 for the tap that reaches a function word and 0.218, 0.093 and 0.157 for the tap that reaches the article. The relation tap has the *smallest* learned magnitude of the five, so per unit of weight it costs about twice as much as either control.

A pre-registered criterion phrased on the abstention metric failed, and we report why: ablating the tap removes the relation from *every* query, so the model abstains more, and a metric that rewards abstention cannot fall. The damage appears in accuracy and in false abstention instead.

7 The diagnosis, as a recipe

The measurement in Result 1 requires no training and no gradient. For any model that consults a memory with a query built from a local window:

1. Take a query whose parts are separated, so that some component sits at distance d from the read position.
2. Replace that component with a different one of the same type.
3. Compare the retrieval distributions.

If they are identical, that component is invisible to the search, and the model’s confidence about it is unearned. With a kernel of 4, the default in deployed linear-attention layers, the reach is three tokens, so any part of a question further back than that does not enter that layer’s query.

8 Limitations

The substrate is a small model on a closed synthetic language, and the distance between the relation and the read position is fixed by the generator, so the effect here is deterministic where in natural text it would be a distribution. The measurement is of *access*, not use: a token inside the window is not necessarily used, and indeed the article tap is inside and contributes little. Finally, the read in our model is injected before the mixer, which is what makes the zero exact; in a deep model that consults memory from later layers, recurrence has already moved information forward and the effective reach grows with depth. The claim is made for memory consulted from early layers, which is where it lives.

References

- Dao, T., and Gu, A. (2024). Transformers are SSMS: Generalized Models and Efficient Algorithms Through Structured State Space Duality. ICML 2024.
- Yang, S., Kautz, J., and Hatamizadeh, A. (2025). Gated Delta Networks: Improving Mamba2 with Delta Rule. ICLR 2025. arXiv:2412.06464.
- Hugging Face Transformers documentation, `Qwen3NextConfig`, parameter `linear_conv_kernel_dim`, default 4. Accessed 2 September 2026.
- Li, M., Zhang, X., Huang, Y., and Oymak, S. (2024). On the Power of Convolution Augmented Transformer. arXiv:2407.05591.
- Arora, S., Eyuboglu, S., Timalsina, A., Johnson, I., Poli, M., Zou, J., Rudra, A., and Ré, C. (2024). Zoology: Measuring and Improving Recall in Efficient Language Models. ICLR 2024. arXiv:2312.04927.
- Golovneva, O., Wang, T., Weston, J., and Sukhbaatar, S. (2025). Multi-Token Attention. arXiv:2504.00927.