

Customers

Customer-Id	name
1	Rhoti
1	Mbehi

ORDERS

Order-Id	Customer-Id	amount
101	1	300
102	1	150
103	3	500

SYNTAX: SELECT A. Customer-Id,
A. name,
B. amount

FROM Customers AS A

INNER JOIN Orders AS B


ON A. Customer-Id = B. Customer-Id;

Customer-Id	name	amount
1	Rhoti	200
1	Rhoti	150

LEFT JOIN

→ Returns everything from the LEFT Table,
and adds matches from the Right Table.

- If no matches, Right side becomes Null.



→ Returns everything on the left table.

SELECT Column(s) specified

FROM Table1 AS A → left table

LEFT JOIN Table2 AS B → Right table

ON A. Common-Column = B. Common-Column;

SQL JOINS

RELATIONAL Database. → Structured Data.

101	102	103	104	105	106

101	102	103	104	105	106

Relationship

Primary Key - Is a unique identifier
 - different in each Row
 - Not Repeated.

Foreign Key -
 - Can Be Repeated.

Primary key in another Table.

Customers primary key.

Customer - Id	Name
1	Rhofi
2	Abali

ORDERS

Order - Id	Customer - Id	Amount
101	1	300
102	1	150
103	3	500

* Customer - Id is the foreign key in the Table. Because of Repeated key Primary Key.

* Basic INNER JOIN

- Returns rows where the key exists in both tables.
- We Join two or more table on Common Column.

SYNTAX:

SELECT A. Column 1 → Taking this Column from table 1
 A. Column 2
B. Column 1



FROM table 1 AS A → Taking this Column from table 2,
 INNER JOIN table 2 AS B
 ON A. Common - Column = B. Common - Column.

→ To join tables, There must be Common Columns.

SQL JOINS

- Primary Key - It is a column that uniquely identify each Row.
- No Duplicates.

Customers

Customer_Id	Name
1	Rohit
2	Lena

Customer

Customer_Id name

orders

Customer_Id amount

Foreign Key -


Orders → Primary key

foreign key

Order Id	Customer_Id	Amount
101	1	300
102	1	150
103	2	500

INNER JOIN

→ Allows us to join two or more tables on a common column that gives us the rows that are matching in both tables.



Whenever you combine tables there must be something common.

You can select any columns from either of the tables.

SYNTAX

SELECT Column 1,
Column 2,
Column 3,

FROM table 1 AS A

INNER JOIN table 2 AS B

ON A.Common-Column = B.Common-Column

Cont...

SELECT A. Customer_id,
A. name,
B. amount
FROM Customers AS A — LEFT table / Base table.
LEFT JOIN orders AS B
ON A. Customer_id = B. Customer_id;

Customer_id	name	amount
1	Rohi	300
1	ROPHI	150
2	MBALI	NULL

CORRECTION

SELECT

emp_name,
department,
Salary,

CASE

WHEN Salary > 80000 THEN 'Senior IT'

or

WHEN department = 'IT' AND Salary > 80000 THEN 'Senior IT'

WHEN department = 'HR' AND Salary > 55000 THEN 'Experienced HR'

ELSE 'Staff'

END AS Position_Level
FROM Employees;




FEBRUARY 4: Data Analytics Cases

• Data Collection Process.

Whenever the Data is collected at the back end, it creates ^{Unique} Data ID.
ID is a unique information that cannot be shared or accessed by someone.

- Data Base: is a Place where we store data.
- Data warehouse is a Place where we store databases.
- Data Source: we collect Data from Different Sources.



Memory Card Served as a Database.

For a memory card to play songs it had to be connected to Data Management System.

Data Base management systems is what we use to access the database at the back end. eg - Server

Data Base Management System is a system that we use to manage the Data within the Database.

Data management system helps us to Control, Manage system and Read Data.

With a Database management system you can manipulated data i.e. insert, delete, update and Access.

Example: Layers of Database Management!

- Cashier Tills are Recording data - Serve as Database.
- Warehouse - Serves as a Database Management at the Back end.
- Not everyone has an access to Database at the Backend.

The Purchasing Process - is an Online Transactional Processing. (OLTP)

The Purchasing information is transferred to the Headquarters through Channel or servers called ETL.

ETL stands for: Extract, Transform, Loads.

Online Transactional Database works during the Day.

Online Analytical Processing Data management works at night.

AND OPERATOR SYNTAX

- SELECT Column 1,
Column 2,
Column 3
FROM DATABASE . SCHEMA . TABLE
WHERE CONDITION 1 AND CONDITION 2;

Curro . Students . Marks

Student ID	Name	Subject	Marks
101	Rhofi	Maths	99
102	Naledi	Maths	22
103	Mbali	Geo	50
104	Aly	Acc	40

QUESTION:

- We want the name and Mark of a student doing Maths and got above 50.

Syntax.

SELECT name,
Marks

FROM Curro . Student . Marks.

WHERE SUBJECT = 'MATHS' AND MARKS > 50

ANSWER:

Name	Marks
Rhofi	99

OR STATEMENT

- Allows us to specify multiple conditions BUT only one or atleast one condition must be met.
 - eg coke or Sprite, BMW or Mercedes, TRUE or FALSE.
 - OR allows us to say we can take both or one.
- SYNTAX.

SELECT Column 1,
Column 2,
Column 3

FROM DATABASE . SCHEMA . TABLE

WHERE CONDITION 1 OR CONDITION 2;

EXERCISE: CASE STATEMENT

SELECT Product Id, Product-name, Price,
CASE

WHEN Price BETWEEN 100 AND 1000 THEN 'Mid-Range'

WHEN Price < 100 THEN 'Budget'

ELSE 'Expensive'

END AS Price-Category

FROM Products;

SQL OPERATORS.

- OPERATORS, OPERATE IN THE WHERE CLAUSE.
- WE CAN USE THE OPERATORS WITHIN OUR WHERE STATEMENTS TO FILTER OUR DATA.
- FILTERING IS ABOUT INCLUDING & EXCLUDING SPECIFIC ROWS BASED ON A SPECIFIC CONDITION.

COMPARISON OPERATORS.

OPERATOR	DESCRIPTION
=	Equal TO - EXACT.
!= <>	NOT EQUAL TO
> EXCLUSIVE.	GREATER THAN, - ABOVE. 51, 52, 53...
>= INCLUSIVE.	GREATER THAN OR EQUAL TO, INCLUDING AND ABOVE. 50, 51, 52, ...
<	LESS THAN - BELOW. 49, 48, 47, 46, ...
<=	LESS THAN OR EQUAL TO INCLUDING AND BELOW. 50, 49, 48, 47, 46, ...

LOGICAL OPERATOR.

- THESE OPERATORS ARE MADE TO HELP US BUILD LOGIC SET OF DATA.
- AND OPERATOR: IS THE STATEMENT WE USE TO JOIN TOGETHER MULTIPLE CONDITIONS.
- e.g. FISH AND CHIPS, MATHS AND SCIENCE STUDENT.
- BOTH CONDITIONS MUST BE MET IN AN AND OPERATOR.
- SYNTAX: SELECT Column 1,
Column 2,
Column 3,
FROM Database - Schema - Table