


DETAIL A



Pos.	Codice	Descrizione	Q.tà	Spessore	Materiale
1	M8 FTRE	Inserto filettato M8 FTRE	8		Acciaio
2	SPS0002855	STRUTTURA GRIGLIA	1	2 mm	DD11

NOTES:


TUTTI I BORDI DEVONO ESSERE ESENTI DA BAVE
ALL THE EDGES MUST BE BURR FREE

SUPERFICI ESENTI DA AMMACCATURE, OLIO, COLLA, GRAFFI E ALTRI DIFETTI
SURFACES MUST BE FREE FROM DENTS, OIL, GLUE, STICKER AND OTHER DEFECTS

I LEMBI DEVONO ESSERE ACCOSTATI PER EVITARE FESSURE E SALDATI
THE EDGES MUST BE PULLED TOGETHER TO AVOID CHINK AND WELDED

E' AMMESSA L'ESECUZIONE DI SCANTONATURE/DENTI/SPINE DI RIFERIMENTO PER FACILITARE IL POSIZIONAMENTO E IL PROCESSO DI SALDATURA
REFERENCE CARVES/TEETH OR PINS ARE ALLOWED IN ORDER TO GUARANTEE THE RIGHT POSITIONING AND PROPER WELDING PROCESS

Additional Notes: -

0	Emissione	a.buonaventura	a.raimondi	d.perale	13/09/2022					
Rev	Description	Made	Verified	Approved	Date					
The welding symbols for steel and aluminium alloys meet the requirements of standard UNI EN ISO 2553										
		0.5-3	>3-6	>6-30	>30-120	>120-400	>400-1000	>1000-2000	>2000-4000	Angle
Unless otherwise specified - ISO 2768 class c		±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	±4	±1°30'
		Project N°: PR22/112		Surface treatment : RAL 9005		Material:		Weight: 6,424 kg	Scale: 1:10	
				Description: GRIGLIA PROTEZIONE POSTERIORE					Page: 1 / 1	
				Customer code: -		Code GPB0009510				