GENERAL TOLERANCES
Angular dimension +-1° - Roundness range of tolerance from IT4 to IT11. Must be contained within half of dimensional tolerance.
MACHINED holes H14 shafts h14 linear values Js14 -- ROUGH holes H16 shafts h16 linear values Js16
SHEETS cutting/laser cutting/punching Js13 holes H13 bending/pressing Js14 -- ALUMINIUM DIE CASTING Savio Norm 4011_1005_00
PLASTIC MATERIALS according to DIN 16901 -- CAST IRON Savio Norm 4011_1003_00
The general tolerances for ROUGH of plastic (DIN 16901) of aluminium (4011_1005_00), of CAST IRON (4011_1003_00), must be intended H for holes, h for shafts, Js for all the other dimensions



6,3 (3,2)

MAXIMUM BURR 0,15 / BAVA MAX 0,15

CN04922		28/05/2021	00
Change	Modification details:	Date Mod:	IRP
Changes to previous release:	Obtain from:	Substitute:	
Material: DC01+A-G UNI EN 10130	Code: 4032_6152_99		
Supply state: +A-G: SURFACE A FINISHING G	Dimensions: 3.0x1250x2500		
Thermic treat.:	Hardness(T):		
Surface treat.: Fe/Zn 8 C UNI ISO 2081 free Cr VI	Hardness(S):		

DENOMINATION: SUPPORTO

Savio	Draw.: Enrico Gaiotto	Date: 11/05/2021	044513.0.0
	Mod.: Enrico Gaiotto	Sheet N°: 1/1	
	App.: Giuseppe Morini	Scale: 1:1	BRACKET

Reserved property of SAVIO MACCHINE TESSILI S.p.A. In accordance with the law, the contents of this drawing may not be re-produced or communicated to third parties.