



Ø10,5 (2x)

bei ait-deutschland:  
 Grundbeschichtung : KTL-Lackierung (schwarz) Schichtdicke 25µm +- 5µm  
 KTL-Lackierung : komplettes Bauteil  
 Farbton Deckbeschichtung : NCS S 8000-N (umbragrau)  
 Korrosivitätsklasse : C4-H nach DIN 55634

OM ANNAT EJ ANGES GÄLLER BOCKRADIE 2mm  
 IF OTHER NOT ARE GIVEN USE BENDING RADIUS 2mm  
 PAINTED ACCORDING  
 COLOUR: FREILACK **Deckbeschichtung für Außenanwendung**  
 DÄR YTKRAV EJ ANGES: KLASS C2  
 WHERE REQUIREMENTS ARE NOT GIVEN: CLASS C2  
 YTKRAV ENLIGT: NS1029  
 SURFACES REQUIREMENTS ACCORDING TO: NS1029  
 MÄTTSÄTTNING GÄLLER FÄR OMÅLAD DETALJ  
 MEASURES ARE GIVEN BEFORE PAINTING  
 FÖR KOMPLETTERANDE GEOMETRISK BESKRIVNING HÄNVISAS TILL CAD-FIL.  
 DÄR TOLERANSER EJ ANGES GÄLLER: SS-ISO 2768-1 C (GROV).  
 FOR COMPLEMENTARY GEOMETRIC DESCRIPTION, REFER TO CAD-FILE.  
 WHERE TOLERANCES NOT ARE GIVEN: SS-ISO 2768-1 C (COARSE).

Dimension T=2		Material Quality/Specification EN 10346-DX51D+Z275-B-O		Mass [kg] 0.300
Revision note		Rev by LSL	Rev Checked by RNJ	Rev date (YYYY-MM-DD) 2019-05-09
		Designer PAN	Checked by JRN	Date (YYYY-MM-DD) 2017-05-10
		Status Production		
SUPPORT PROFILE STÖDPROFIL			Format A3	Sheet
			Drawing no 015464	Rev 1