

	A	B	C	D
GENERAL TOLERANCES				
Angular dimension +1° - Roundness range of tolerance from IT4 to IT11. Must be contained within half of dimensional tolerance.				
MACHINED holes H14 shafts h14 linear values Js14 -- ROUGH holes H16 shafts h16 linear values Js16				
SHEETS cutting/laser cutting/punching Js13 holes H13 bending/pressing Js14 -- ALUMINIUM DIE CASTING Savio Norm 4011_1005_00				
6	PLASTIC MATERIALS according to DIN 16901 -- CAST IRON Savio Norm 4011_1003_00			
The general tolerances for ROUGH of plastic (DIN 16901) of aluminium (4011_1005_00), of CAST IRON (4011_1003_00), must be intended H for holes, h for shafts, Js for all the other dimensions				
5				
4				
3				
2	<div>3.2/ ()</div> <div>SMUSSI NON QUOTATI / EDGES WITHOUT DIMENSIONS : 1 x 45°</div>			
1	CN05436	Reduced hole depth to 12 mm		08/07/2022
	Change	Modification details:		Date Mod: IRP
	Changes to previous release: Changed exagon dim. .. to 17; hole .. to 12; .. to 30,5; .. to 11 (B-C/5)		Obtain from:	Substitute: 032835.0.0
	Material: 36SMnPb14+SH UNI EN 10277-3		Code: 4032_2073_99	
	Supply state: +SH: PEELED ROLLED		Dimensions:	
	Thermic treat.:		Hardness(H):	
	Surface treat.: Fe/Zn 8÷12 A HP UNI ISO 2081 free Cr VI		Hardness(S):	
	DENOMINATION: DISTANZIALE			
Savio		Draw.: Renzo Del Bianco	Date: 07/12/2021	032835.1.0
		Mod.: Renzo Del Bianco	Sheet N°: 1/1	
		App.:	Scale: 1:1	
SPACER				