

	A	B	C	D																																																										
6	GENERAL TOLERANCES																																																													
	Angular dimension $\pm 1^\circ$ - Roundness range of tolerance from IT4 to IT11. Must be contained within half of dimensional tolerance.																																																													
	MACHINED holes H14 shafts h14 linear values Js14 -- ROUGH holes H16 shafts h16 linear values Js16																																																													
	SHEETS cutting/laser cutting/punching Js13 holes H13 bending/pressing Js14 -- ALUMINIUM DIE CASTING Savio Norm 4011_1005_00																																																													
	PLASTIC MATERIALS according to DIN 16901 -- CAST IRON Savio Norm 4011_1003_00																																																													
The general tolerances for ROUGH of plastic (DIN 16901) of aluminium (4011_1005_00), of CAST IRON (4011_1003_00), must be intended H for holes, h for shafts, Js for all the other dimensions																																																														
5																																																														
4																																																														
3																																																														
2	2	4026_6127_11	1	NUT	Pressure nuts M6 Thic.2.3 FeZn8c1A	M6x11.05x4.08																																																								
	1	039412.0.A	1	WELDED COMPONENT	DC01+A-G UNI EN 10130																																																									
<table><tr><th>POS.</th><th>Code</th><th>Q.ty</th><th>Description</th><th colspan="3">Technical Description</th></tr><tr><td>CN05434</td><td colspan="4">Variato da foro d.6.2 ad asola 6.2x8</td><td>31/05/2022</td><td>01</td></tr><tr><td>Change</td><td colspan="4">Modification details:</td><td>Date Mod:</td><td>IRP</td></tr><tr><td colspan="4">Changes to previous release:</td><td>Obtain from:</td><td colspan="2">Substitute:</td></tr><tr><td colspan="4">Material:</td><td colspan="3">Code:</td></tr><tr><td colspan="4">Supply state:</td><td colspan="3">Dimensions:</td></tr><tr><td colspan="4">Thermic treat.:</td><td colspan="3">Hardness(T):</td></tr><tr><td colspan="4">Surface treat.: Fe/Zn 8÷12 A HP UNI ISO 2081 free Cr VI</td><td colspan="3">Hardness(S):</td></tr></table>							POS.	Code	Q.ty	Description	Technical Description			CN05434	Variato da foro d.6.2 ad asola 6.2x8				31/05/2022	01	Change	Modification details:				Date Mod:	IRP	Changes to previous release:				Obtain from:	Substitute:		Material:				Code:			Supply state:				Dimensions:			Thermic treat.:				Hardness(T):			Surface treat.: Fe/Zn 8÷12 A HP UNI ISO 2081 free Cr VI				Hardness(S):		
POS.	Code	Q.ty	Description	Technical Description																																																										
CN05434	Variato da foro d.6.2 ad asola 6.2x8				31/05/2022	01																																																								
Change	Modification details:				Date Mod:	IRP																																																								
Changes to previous release:				Obtain from:	Substitute:																																																									
Material:				Code:																																																										
Supply state:				Dimensions:																																																										
Thermic treat.:				Hardness(T):																																																										
Surface treat.: Fe/Zn 8÷12 A HP UNI ISO 2081 free Cr VI				Hardness(S):																																																										
1	DENOMINATION: REGGETTA SUP. GUIDA SU SPALLA PROXIMA																																																													
			Draw.: Dante Zancai	Date: 11/09/2020	039412.0.0																																																									
			Mod.: Dante Zancai	Sheet N°: 1/2																																																										
			App.: Stefano Malfante	Scale: 1:1	BRACKET																																																									

