

20-250

220

20

A	B	C	D
GENERAL TOLERANCES Angular dimension 1:1 - Roundness range of tolerance from IT4 to IT11. Must be contained within half of dimensional tolerance. MACHINED HOLES H14 shafts h14 linear values Js14 - ROUGH HOLES H16 shafts h16 linear values Js16 SHEETS cutting/laser cutting/punching JS13 holes H13 bend PLASTIC MATERIALS according to DIN 16901 - CAST IRON The general tolerances for ROUGH of plastic (DIN 16901) of005_00), of CAST IRON (4011_1003_00), must be intended H for holes, h for shafts, js for all the other dimensions			
6	4011_1005_00		
Modification details: Change: CN04979 15/10/2021 00 Changes to previous release: Obtain from: Substituted: 16270_0557_0_0 Material: Fe-300 D UNI EN 10025 Code: 4032_5071_57 Supply state: LAMINATO Dimensions: 30x20 Thermic treat.: Hardness (T): Surface treat.: Hardness(S):			
DENOMINATION: GUIDA MOTORULLI PROXIMA ES/CS			
Date: 08/10/2021 Sheet N°: 1/1 Scale: 1:1 GUIDE			
047522.0.0			

3.2 (6.3/3.2) F35 (C)

3-P.A. In accordance with the law, the contents of this drawing may not be re-produced or communicated to third parties.

Reserved property

Reserved property c

In accordance with the law, the contents of this drawing may not be re-produced or communicated to third parties.