

	A	B	C	D
6	GENERAL TOLERANCES			
	Angular dimension +-1° - Roundness range of tolerance from IT4 to IT11. Must be contained within half of dimensional tolerance.			
	MACHINED holes H14 shafts h14 linear values Js14 -- ROUGH holes H16 shafts h16 linear values Js16			
	SHEETS cutting/laser cutting/punching Js13 holes H13 bending/pressing Js14 -- ALUMINIUM DIE CASTING Savio Norm 4011_1005_00			
	PLASTIC MATERIALS according to DIN 16901 -- CAST IRON Savio Norm 4011_1003_00			
	The general tolerances for ROUGH of plastic (DIN 16901) of aluminium (4011_1005_00), of CAST IRON (4011_1003_00), must be intended H for holes, h for shafts, Js for all the other dimensions			
5				
4				
3				
2				
1				
3.2/ ( 1 x 45° )				
SMUSSI NON QUOTATI / EDGES WITHOUT DIMENSIONS : 1 x 45°				
Change		Modification details:		08/07/2022 00
				Date Mod: IRP
Changes to previous release:		Obtain from:		Substitute: 032835.0.0
Material: 36SMnPb14+SH UNI EN 10277-3		Code: 4032_2073_99		
Supply state: +SH: PEELED ROLLED		Dimensions:		
Thermic treat.:		Hardness(T):		
Surface treat.: Fe/Zn 8÷12 A HP UNI ISO 2081 free Cr VI		Hardness(S):		
DENOMINATION: DISTANZIALE TRONCONE				
1			Draw.: Carmine Barbarito	Date: 21/09/2022
			Mod.: Carmine Barbarito	Sheet N°: 1/1
			App.: Marco Pivetta	Scale: 1:1
			053446.0.0	
			SPACER	