



bei ait-deutschland:
Grundbeschichtung : KTL-Lackierung (schwarz) Schichtdicke 25µm +- 5µm
KTL-Lackierung : komplettes Bauteil
Farbton Deckbeschichtung : NCS S 8000-N (umbragrau)
Korrosivitätsklasse : C4-H nach DIN 55634

OM ANNAT EJ ANGES GÄLLER BOCKRADIE 1mm
IF OTHER NOT ARE GIVEN USE BENDING RADIUS 1mm

3 PAINTED ACCORDING TO NIBE STD NS1029
COLOUR: FREILACK **Deckbeschichtung für Außenanwendung**

PAINT THICKNESS "A" 100± 50µm **für Pulverlack**

EJ UPPMÄRKTA YTOR=KLASS C
UNMARKED SURFACES=CLASS C

MÄTTSÄTTNING GÄLLER FÖR OMÅLAD DETALJ
MEASURES ARE GIVEN BEFORE PAINTING

FÖR KOMPLETTERANDE GEOMETRISK BESKRIVNING HÄNVISAS TILL CAD-FIL.
DÄR TOLERANSER EJ ANGES GÄLLER: SS-ISO 2768-1 C (GROV).

FOR COMPLEMENTARY GEOMETRIC DESCRIPTION, REFER TO CAD-FILE.
WHERE TOLERANCES NOT ARE GIVEN: SS-ISO 2768-1 C (COARSE).



Dimension T=1		Material Quality/Specification EN 10346-DX51D+Z275-B-O		Mass [kg] 0.500
Revision note		Rev by PAN	Rev Checked by	Rev date (YYYY-MM-DD)
		Status Production	Designer PAN	Checked by LAN
		Date (YYYY-MM-DD) 2017-01-02		Format A3
		Drawing no 015436		Rev 3
COVER FRONT LOCK BOTTENBALK				