GENERAL TOLERANCES
Angular dimension +-1° - Roundness range of tolerance from IT4 to IT11. Must be contained within half of dimensional tolerance.
MACHINED holes H14 shafts h14 linear values Js14 -- ROUGH holes H16 shafts h16 linear values Js16
SHEETS cutting/laser cutting/punching Js13 holes H13 bending/pressing Js14 -- ALUMINIUM DIE CASTING Savio Norm 4011_1005_00
PLASTIC MATERIALS according to DIN 16901 -- CAST IRON Savio Norm 4011_1003_00
The general tolerances for ROUGH of plastic (DIN 16901) of aluminium (4011_1005_00), of CAST IRON (4011_1003_00), must be intended H for holes, h for shafts, Js for all the other dimensions







6.3 (3.2)

BAVA MAX 0.04
RAGGI NON QUOTATI R=2

CN04481		17/05/2021	00
Change	Modification details:	Date Mod:	IRP
Changes to previous release: AGGIUNTO FORI FISSAGGIO ELETTROVALVOLA	Obtain from:019692.0.0	Substitute: 028548.0.0	
Material: DC01+A-G UNI EN 10130	Code: 4032_6152_99		
Supply state: +A-G: SURFACE A FINISHING G	Dimensions:		
Thermic treat.:	Hardness(T):		
Surface treat.: Fe/Zn 8÷12 A HP UNI ISO 2081 free Cr VI	Hardness(S):		

DENOMINATION: REGGETTA VALVOLA

Savio	Draw.: Michele Simonatto	Date: 26/04/2021	028548.1.0
	Mod. : Michele Simonatto	Sheet N°: 1/1	
	App. : Giuseppe Morini	Scale: 1:1	BRACKET

Reserved property of SAVIO MACCHINE TESSILI S.p.A. In accordance with the law, the contents of this drawing may not be re-produced or communicated to third parties.