


Technical drawing of a shaft-hub assembly. The shaft has a diameter of $\varnothing 21$ and a length of 19. The hub has an outer diameter of $\varnothing 26$, an inner diameter of $\varnothing 22$, and a length of 26. The key has a width of 13 and a height of 16. The shaft has a 45-degree chamfer at the end. The drawing includes dimension lines and tolerances for all dimensions.

Smussi non quotati 0.5x45°
Trattamento: Fosfatazione Manganese
Mat: Acciaio EN 10025 - S235JR



Grado di lavoraz.		MOD.REV Modifiche Data DATA.REV		Trott. superfl.					Disegnatore		
()				-					G. Cavallo		
/ / / / /		-					Trott. termico		Controllato		
		-							D.D'Abrusco		
Scostamenti per quote senza indicazione di tolleranza							Smussi non quotati 1x45°				
Superfici lavorate: Angoli ±30°				Carpenteria: Angoli ±30°							
Quote:	0-20	>20-100	>100-300	>300	0-100	>100-500	>500-2000	>2000-5000	>5000	Data	
Toller.	±0,15	±0,25	±0,40	±0,80	±0,50	±0,80	±1,5	±2	±3	09-07-2020	
Denominazione Ros s.r.l. Via Crosera, 42 - Zona Industriale 33082 AZZANO DECIMO (PN) Tel. 0434 633318 r.a. - Fax 0434 640639 C.F. e P. IVA 01278530934										Formato	
Attacco Anteriore d.16 Derivato da										A2	
Scaola											
1:1											
Nr. disegno										Rev.	
OCMS103004											0