

4			3		2		1		
CL1	CL2	QTY	CA-NO.	CHANGE			DD.MM.YY	DRAW	CHECK
A	01			FIRST DRAFT			17/07/17	BA.M.	PE.A.
A	02		469413	H7: CHANGED THICKNESS / cambiato spessore (WAS / era: 1) B9: CHANGED DIMENSIONS / cambiate quote (WERE / erano: 108 AND e 80)			05/02/18	BA.M.	FA.F.
B	03		517202	UPDATED NOTES AND QUOTE SYSTEM			29.10.19	Ta.L.	Ta.L.

General notes:
Eliminate cutting edges
Perform sheet metal cutting in nitrogen
Note generali:
Eliminare bordi taglienti
Eseguire taglio lamiera in azoto






Surface preparation:
The component to be painted must be superficially cleaned to remove any traces of grease, oxidation and anything that may prevent a good adhesion of the paint film.

Preparazione delle superfici:
Il componente da verniciare deve essere sottoposto ad una pulizia superficiale per eliminare eventuali tracce di grasso, ossidazione e tutto quanto possa impedire una buona adesione del film di vernice.

Type of painting:
Cataphoresis with a thickness of 20 ÷ 35 micron
Tipo di verniciatura:
Cataforesi con spessore di 20 ÷ 35 micron

Salt spray resistance:
Cross engraving and 300 h exposure according to UNI ISO 9227
Resistenza in nebbia salina:
Incisione a croce e 300 h di esposizione secondo UNI ISO 9227

Color:
Black RAL 9005
Colore:
Nero RAL 9005

		REF./POS. DIM		() INFORMATION DIM		CAD-SYSTEM CATIA V5 R24			
PERMISSIBLE DEVIATION FOR DIM WITHOUT TOLERANCES ISO 2768-CL					VOLTAGE -	WEIGHT ESTIMATED kg 0,226	SURFACE mm ² .		
MATERIAL EN 10130-DC01 A m							MATERIAL-NO .		
							SUPPL.-DRAW	N	
SURFACE PROTECTION SEE NOTE VEDI NOTA							ECA-NO. 517202		
PART NAME RECIRCULATION METAL CAP TAPPO IN METALLO PER RICIRCOLO									
DATE 14/07/17		14/07/17	14/07/17	SCALE 1:2	OLD WEBASTO NO. .		PART-NO. 6242994 B 03		
NAME BA.M.		PE.A.	FA.F.	 	STATUS .				
MOD/DRAW		CHECK	APP						
Ros s.r.l. Via Crocera, 42 - Zona Industriale 35082 AZZANO DECIMO (PN) Tel. 0434 633318 int. - Fax 0434 640639 C.F. e P. IVA 01278530934				 	SIZE A2 420x594	MF 1			
REPLACED BY DRW.-NO. .				FROM .		REPLACEMENT FOR DRW.-NO. .		FROM .	
								PAGE 1 / 1	