









4.73 ±5%

COMM. ATTREZZATURA

FOGLIO / Sh. DI / Of

S355JR

SMUSSI N.Q.

1x45° RACC. N.Q.

R0.4

1:2

SCALA / Scale FORMATO / Size

DIS. GREZZO N. / Row Material Drawing Nr. CA.07782.A/G
DISEGNO N. / Drawing Number

CA.07782.A

| | | | | | | | | | DATA / Date | DISEGNATO / Drawn | MATERIALE / Material | |
|--|---|------------|----------------|----------------|-------------|-------------|------------------|-------------|--|-------------------|----------------------|------------|
| | | | | | | | | | 30/03/2023 | Deana F. | | S355J |
| | | | | | | | | | Piastra x bloccaggio carrello | | | SMUSSI N. |
| INDUSTRIES | | | | | | | | | | | | 1x45 |
| LA PROPRIETA' DI QUESTO DISEGNO E' TUTELATA A TERMINI DI LEGGE CON MORSA - Isola Montaggio | | | | | | | | | | | | RACC. N. |
| | E'VIETATO RIPRODURLO E/O CEDERLO A TERZI SENZA NOSTRA AUTORIZZAZIONE SCRITTA POPOGEDY OF THIS INDAMINIA IS PROTECTED ACCORDINATO TO THE I MY ASSOCII 725 NACCO | | | | | | | | | | | |
| PROPERTY OF THIS DRAWING IS PROTECTED ACCORDING TO THE LAW | | | | | | | | | 710001117201171000 | | | R0.4 |
| IS FORBIDDEN TO REPRODUCE AND/OR DISCLOSE IT TO OTHER PARTIES WITHOUT OUR WRITTEN AUTHORISATION SCOSTAMENTI DIM. OVE NON SPECIFICATI / Dim. deviation if not otherwise indicated. | | | | | | | | | RIVESTIMENTO SUPERF. / Surface Coating | | | SCALA / S |
| - PARTI RICAVATE PER GETTO /Casted Parts - RIF/Acc to - UNI EN ISO 8062 >> CT8 | | | | | | | | | Fosfatazione | | | 1:2 |
| - PARTI FORGIATE / Forged Parts - RIF/Acc to - UNI EN 10243 >> GRADE F | | | | | | | | | | | | + |
| - PARTI LAVORATE - DIM. LINEARI / Machined Parts - Linear dims. (UNI EN 22768/1) | | | | | | | | | TRATT. TERMICO FINALE / Final Heat Treatment | | | DIS. GREZZ |
| >= | 0 | 3 | 6 | 30 | 120 | 400 | 1000 | 2000 | | | | |
| < | 3 | 6 | 30 | 120 | 400 | 1000 | 2000 | - | | | | |
| + / - | 0,05 | 0,05 | 0,1 | 0,15 | 0,2 | 0,3 | 0,5 | 1,0 | PROFONDITA' TRATT. TERM./Heat Treatm. Depth | | | DISEGNO |
| - PARTI LAV | ORATE - DIM. | ANGOLARI / | Machined Parts | s - Angles (UN | EN 22768/1) | | | | | | | |
| >= | 0 | 10 | 50 | 120 | 400 | TOLLERANZ | ZE DI FORMA | E POSIZIONE | DUREZZA SUPERFICIALE / Surface Hardness | | | |
| < | 10 | 50 | 120 | 400 | - | ISO2692 | | | | | | |
| 1 / | 10 00' | Uo 3U, | Uo 3U, | ∩º 1∩' | 0° 05' | Form and po | sition toleranci | ies | | | | - |