



#

ATTENTION: CHEMICAL NICKEL-PLATING  
THICKNESS 0.01 mm  
EXECUTE: HOLES AND SLOTS +0.02 mm  
EXTERNAL DIA.S AND LENGTHS -0.02 mm

3.2  $\left( \begin{array}{c} \diagup \\ \nabla \end{array} \begin{array}{c} \diagup \\ \nabla \end{array} \begin{array}{c} \diagup \\ \nabla \end{array} \begin{array}{c} \diagup \\ \nabla \end{array} \right)$

A00	08/02/12		ext.design1
<b>Nr</b>	<b>Data\Date</b>	<b>Note\Description</b>	<b>Firma\Sign.</b>

Pezzo similare Sim. part code	Gruppo appart. Assembly code	35268222
----------------------------------	---------------------------------	----------

<b>A4</b>	Firma\Sign.	Data\Date	Materiale\Material	Finitura\Finishing	<b>EX</b>
Disegn. Drawn	PETTENON AD	09/06/2008	S235 UNI EN 10025\95	#	
Contr. Check'd			Stato\Pattern	Tratt. Termico\Heat Treatment	
Visto Apprv'd			Codice\Commercial Code     51991040	Durezza\Hardness	

Denominazione\Name	CODICE\CODE	TAV.\SHEET	Rev.\Rel.
CHIOCCOLA X CAVA 10	42106250		A00