

BENDRADIUS TO CL OF THE TUBE	R60±5
MAX OPERATING PRESSURE	38.5 MPa
CLEANING AND PACKAGING	STD 107-0006

Outer diameter - $\varnothing 30$
Wall thickness - 4
Digital shape model is basis where dimensions are omitted STD 101-0001


x) Surface free from paint

Tolerances unless otherwise stated:

General shape $\vartriangle 4 \begin{matrix} A \\ B \\ C \end{matrix}$

Wetted surface: 630 cm² A_c

Joining requirements STD 181-0004

3	1	16333810	TUBE		
2	1	15033486	PIPE CONNECTION		
1	1	15033057	WELD COLLAR		
Pos	Qty	Part No	Part name	Remarks	
Symbols, designations and general drawing methods STD 101-0005		View placement Reference arrow method ISO 128-3:2020		Document release status Released	
<p>The copying, distribution and utilization of this document as well as the communication of its contents to others without expressed authorization is prohibited. Offenders will be held liable for payment of damages. All rights reserved also in the event of the grant of a patent, utility model, design patent or design registration.</p> <div></div>				Document title PIPE HYDRAULIC 38.5MPa, Ø30x4	
				Document type DRAWING	
				Legal Owner Volvo Construction Equipment	
				Document No 16333815	Issue 02