








|   |  |   |  |  |  |  |  |   |  |              |  |  |  |   |  |
|---|--|---|--|--|--|--|--|---|--|--------------|--|--|--|---|--|
| <br>Safety characteristic<br>Cp/Cpk ≥ 1.66 |  | <br>Regulation characteristic<br>Cp/Cpk ≥ 1.66 |  | <br>Critical characteristic<br>Cp/Cpk ≥ 1 |  | <br>Mountability characteristic<br>Cp/Cpk ≥ 1 |  | <br>Quality control<br>Cp/Cpk ≥ 0.83 |  | SCALE<br>1:1 |  | MEASURE UNIT<br>S.I.   |  | VIEW<br> |  |
| DESCRIPTION<br>STAFFA PER FOTOCELLULA KUHNN L3688860_A  |  | PROJECT   |  | DATE<br>13/12/2023   |  | PAGE<br>1/1  |  | SIZE<br>A3  |  | WEIGHT       |  | TOOLING - MOLD   |  |   |  |
| PART NUMBER<br>MTL-0103_00  |  |   |  |  |  | CTO<br>MB  |  | GENERAL TOLERANCES [mm]<br>(According to UNI EN 20266-1)  |  |              |  | <br><br>Fiesse Umbertiano - Rogio - ITALY<br>Sistema Qualità Certificato<br>UNI EN ISO 9001 |  |   |  |
| MATERIAL<br>Fe360 Sp. 2mm   |  |   |  |  |  | PL<br>AF   |  | Up to 30.....+/- 0.1  |  |              |  |  |  |   |  |
| TREATMENT<br>CATAFORESI NERO RAL 9005   |  |   |  |  |  | DESIGNER<br>MC   |  | From 30 to 100.....+/- 0.2  |  |              |  |  |  |   |  |
|   |  |   |  |  |  |  |  | From 100 to 300.....+/- 0.3   |  |              |  |  |  |   |  |