


A	B	C	D
GENERAL TOLERANCES			
Angular dimension $\pm 1^\circ$ - Roundness range of tolerance from IT4 to IT11. Must be contained within half of dimensional tolerance.			
MACHINED holes H14 shafts h14 linear values Js14 -- ROUGH holes H16 shafts h16 linear values Js16			
SHEETS cutting/laser cutting/punching Js13 holes H13 bending/pressing Js14 -- ALUMINIUM DIE CASTING Savio Norm 4011_1005_00			
PLASTIC MATERIALS according to DIN 16901 -- CAST IRON Savio Norm 4011_1003_00			
The general tolerances for ROUGH of plastic (DIN 16901) of aluminium (4011_1005_00), of CAST IRON (4011_1003_00), must be intended H for holes, h for shafts, Js for all the other dimensions			



CN05123				01/10/2021	00
Change	Modification details:			Date Mod:	IRP
Changes to previous release:				Obtain from:	Substitute:
Material:	DC01+A-G UNI EN 10130			Code:	4032_6152_99
Supply state:	+A-G: SURFACE A FINISHING G			Dimensions:	
Thermic treat.:				Hardness(T):	
Surface treat.:	Fe/Zn 8÷12 A HP UNI ISO 2081 free Cr VI			Hardness(S):	
DENOMINATION: SUPPORTO GRUPPO INVERTER					
1			Draw.: Renato Scaini	Date: 18/02/2021	042727.0.0
			Mod. : Renato Scaini	Sheet N°: 1/1	
			App. : Giuseppe Morini	Scale: 1:1	PLATE