



Parts must be provided degreased, washed, dried and properly packed I PARTICOLARI DEVONO ESSERE FORNITI SGRASSATI, LAVATI, ASCIUGATI ED ADEGUATAMENTE IMBALLATI

9)							
7														
5														
3														
1	Inizio produzione Start of production							Eliminato scasso laterale Removed side split						
Change description / Descrizione modifica														
CONT. DIM. TOT.						FIRM								
CONT. DIM. PAR.	DATA					FIRM	\							
NOTE:		·												
Traditional Machining	±0.05	±0.10	±0.15	±0.20	±0.30		from / da 0.49 u	up to / fino a 1.00	0 mm	±0.05	UN	UNI EN 22768/1		
Sheet Metal up to 2 mm (included)	±0.05	±0.10	±0.15	±0.20	±0.30			up to / fino a 1.80		±0.08	Angular tolerance		ance	
Sheet Metal from 2 up to 8 mm	±0.10	±0.20	±0.30	±0.50	±0.80			up to / fino a 3.00		±0.11	Т	olleranze an	golari	
Moulding / Rubber Machining	±0.05	±0.10	±0.20	±0.60		\dashv	from / da 3.01 u	0 mm	±0.15	UN	8/2 H			
Tecnology / Tecnologia	from 0 mm up to 6 mm up to 30 mm up to 120 mm up to 400 mm up to 120 mm up to 400 mm up to 120 mm						Sheet metal's thickness / Spessore lamiera Geometrical tolerance Tolleranze geometriche							
General Tolerance / Tolleranze Generali (mm) Sheet 1 of di 1														
	Tecnology / Tecnologia					Life	cycle state / Ciclo	PRS		7 (2)	Scale / Scala			
	TRAD. MACHINING						Rilasciato	35		<u> </u>				
	Termical treatment / Trattamento termico						RoHS II - 2011/65/UE REQUESTED 2 Firma / Signature 2						Signature	
	Surface treatment / Trattamento superficiale						Color /	Modified by / Modificato da			Modify date /			
	Cataforesis industrial painting						nero/				10-Jul-2020			
	Material / Materiale						Wight / Peso Kg 3.541		Designer / Disegnatore			Spare part / Ricambio FALSE		
	C45_EN10277						3.5	Drawing Code / Codice Di						
	Denomination / Denominazione						c & hoat)	· ·			isegno	Revision		
CONFIDENTIAL	CEN III reinforcement (canvas & heat)								2300STR5			504	2	
CONFIDENTIAL	ONFIDENTIAL RINFORZO CEN III PER CANVAS E HEAT													
1														