









NOTES:

TUTTI I BORDI DEVONO ESSERE ESENTI DA BAVE ALL THE EDGES MUST BE BURR FREE

SUPERFICI ESENTI DA AMMACCATURE, OLIO, COLLA, GRAFFI E ALTRI DIFETTI SURFACES MUST BE FREE FROM DENTS, OIL, GLUE, STICKER AND OTHER DEFECTS

I LEMBI DEVONO ESSERE ACCOSTATI PER EVITARE FESSURE E SALDATI ALL'INTERNO THE EDGES MUST BE PULLED TOGETHER TO AVOID CHINK AND WELDED INSIDE

E' AMMESSA L'ESECUZIONE DI SCANTONATURE/DENTI/SPINE DI RIFERIMENTO PER FACILITARE IL POSIZIONAMENTO E IL PROCESSO DI SALDATURA REFERENCE CARVES/TEETH OR PINS ARE ALLOWED IN ORDER TO GUARANTEE THE RIGHT POSITIONING AND PROPER WELDING PROCESS

Ros s.r.l.		
Via Crosera, 42 - Zona Industriale 33082 AZZANO DECIMO (PN) Tel. 0434 633318 r.a Fax 0434 640639		
C.F. e P. IVA 01278530934		

Unless otherwise specified - ISO 2768 class c

Description

0 Emissione

±	0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	±4		±1°30	
	Sur	face tre	atment	:		Weight: Sca					
	CATA	APHORESIS	ESIS + RAL 6019				0.351 kg			1:1	
	Doc	crintion								22001	

Verified

>6-30 |>30-120 |>120-400

p.sindoni Made

The welding symbols for steel and aluminium alloys meet the requirements of standard UNI EN ISO 2553

0.5-3

±0.2

a.buonaventura s.dallacosta 19/04/2022

Approved

1/1 PIASTRA FISSAGGIO CONVOGLIATORE

Customer code: PSA0074510

Additional Notes: \\