

# Package ‘AATtools’

May 8, 2020

**Type** Package

**Title** Tools for Analyzing the Approach-Avoidance Task

**Version** 0.0.1

**Author** Sercan Kahveci

**Description** Compute approach bias scores using different scoring algorithms, compute bootstrapped and exact split-half reliability of the AAT, and compute confidence intervals for individual AAT scores.

**Depends** R ( $\geq$  3.6.1), magrittr, dplyr, doParallel

**License** GPL-3

**Encoding** UTF-8

**BugReports** <https://github.com/Spiritspeak/AATtools/issues>

**LazyData** true

**ByteCompile** true

**RoxygenNote** 7.0.2

## R topics documented:

aat.bootstrap . . . . .	1
aat.compute . . . . .	3
aat.splithalf . . . . .	4
Algorithms . . . . .	6
plot.aat.splithalf . . . . .	7
q_reliability . . . . .	8
SpearmanBrown . . . . .	9

<b>Index</b>	<b>10</b>
--------------	-----------

---

aat.bootstrap	<i>Compute bootstrapped approach-bias scores</i>
---------------	--

---

## Description

Compute bootstrapped approach-bias scores with confidence intervals.

## Usage

```
aat_bootstrap(
  ds,
  subjvar,
  pullvar,
  targetvar = NULL,
  rtvar,
  iters,
  plot = T,
  algorithm = c("aat_doublemeandiff", "aat_doublemediandiff", "aat_dscore",
    "aat_dscore_multiblock", "aat_regression", "aat_standardregression",
    "aat_doublemeanquotient", "aat_doublemedianquotient", "aat_singlemeandiff",
    "aat_singlemediandiff"),
  trialdropfunc = c("prune_nothing", "trial_prune_3SD", "trial_prune_SD_dropcases"),
  errortrialfunc = c("prune_nothing", "error_replace_blockmeanplus",
    "error_prune_dropcases"),
  ...
)
```

## Arguments

<code>ds</code>	a longformat data.frame
<code>subjvar</code>	Quoted name of the participant identifier column
<code>pullvar</code>	Quoted name of the column indicating pull trials. Pull trials should either be represented by 1, or by the second level of a factor.
<code>targetvar</code>	Name of the column indicating trials featuring the target stimulus. Target stimuli should either be represented by 1, or by the second level of a factor.
<code>rtvar</code>	Name of the reaction time column.
<code>iters</code>	Total number of desired iterations. At least 200 are required to get confidence intervals that make sense.
<code>plot</code>	Plot the bias scores and their confidence intervals after computation is complete. This gives a good overview of the data.
<code>algorithm</code>	Function (without brackets or quotes) to be used to compute AAT scores. See <a href="#">aat_doublemeandiff</a> for a list of usable algorithms.
<code>trialdropfunc</code>	Function (without brackets or quotes) to be used to exclude outlying trials in each half. <code>prune_nothing</code> excludes no trials, while <code>trial_prune_3SD</code> excludes trials deviating more than 3SD from the mean per participant.
<code>errortrialfunc</code>	Function (without brackets or quotes) to apply to an error trial. <code>error_replace_blockmeanplus</code> replaces error trial reaction times with the block mean plus an arbitrary extra amount of time. If used, the following additional arguments are required: <ul style="list-style-type: none"> <li>• <code>blockvar</code> - Quoted name of the block variable</li> <li>• <code>errorvar</code> - Quoted name of the error variable, where errors are 1 or TRUE and correct trials are 0 or FALSE</li> <li>• <code>errorbonus</code> - Amount to add to the reaction time of error trials. Default is 0.6 (recommended by Greenwald,Nosek,&amp; Banaji,2003)</li> </ul>
<code>...</code>	Other arguments, to be passed on to the algorithm functions (see <code>algorithm</code> above)

**Value**

A list, containing bootstrapped bias scores, a data frame with bootstrapped 95 the number of iterations, and a matrix of bias scores for each iteration.

**Author(s)**

Sercan Kahveci

---

aat_compute	<i>Compute simple AAT scores</i>
-------------	----------------------------------

---

**Description**

Compute simple AAT scores, with optional outlier exclusion and error trial recoding.

**Usage**

```
aat_compute(
  ds,
  subjvar,
  pullvar,
  targetvar = NULL,
  rtvar,
  algorithm = c("aat_doublemeandiff", "aat_doublemediandiff", "aat_dscore",
    "aat_dscore_multiblock", "aat_regression", "aat_standardregression",
    "aat_doublemeanquotient", "aat_doublemedianquotient", "aat_singlemeandiff",
    "aat_singlemediandiff"),
  trialdropfunc = c("prune_nothing", "trial_prune_3SD", "trial_prune_SD_dropcases"),
  errortrialfunc = c("prune_nothing", "error_replace_blockmeanplus",
    "error_prune_dropcases"),
  ...
)
```

**Arguments**

ds	a long-format data.frame
subjvar	column name of subject variable
pullvar	column name of pull/push indicator variable, must be numeric or logical (where pull is 1 or TRUE)
targetvar	column name of target stimulus indicator, must be numeric or logical (where target is 1 or TRUE)
rtvar	column name of reaction time variable
algorithm	name of preferred computation algorithm, see <a href="#">aat_doublemeandiff</a>
trialdropfunc	preferred trial exclusion method (if any)
errortrialfunc	preferred error recoding method (if any)
...	

---

aat_splithalf	<i>Compute the bootstrapped split-half reliability for approach-avoidance task data</i>
---------------	---

---

## Description

Compute bootstrapped split-half reliability for approach-avoidance task data. `aat_splithalf()` uses multicore computation, which is fast, but provides no clear output when there are errors. `aat_splithalf_singlecore()` is much slower, but more easily debugged.

## Usage

```
aat_splithalf(
  ds,
  subjvar,
  pullvar,
  targetvar = NULL,
  rtvar,
  iters,
  plot = T,
  algorithm = c("aat_doublemeandiff", "aat_doublemediandiff", "aat_dscore",
    "aat_dscore_multiblock", "aat_regression", "aat_standardregression",
    "aat_doublemedianquotient", "aat_doublemeanquotient", "aat_singlemeandiff",
    "aat_singlemediandiff"),
  trialdropfunc = c("prune_nothing", "trial_prune_3SD", "trial_prune_SD_dropcases"),
  errortrialfunc = c("prune_nothing", "error_replace_blockmeanplus",
    "error_prune_dropcases"),
  casedropfunc = c("prune_nothing", "case_prune_3SD"),
  ...
)
```

## Arguments

<code>ds</code>	a longformat data.frame
<code>subjvar</code>	Quoted name of the participant identifier column
<code>pullvar</code>	Quoted name of the column indicating pull trials. Pull trials should either be represented by 1, or by the second level of a factor.
<code>targetvar</code>	Name of the column indicating trials featuring the target stimulus. Target stimuli should either be represented by 1, or by the second level of a factor.
<code>rtvar</code>	Name of the reaction time column.
<code>iters</code>	Total number of desired iterations. At least 200 are recommended for reasonable confidence intervals; If you want to see plots of your data, 1 iteration is enough.
<code>plot</code>	Create a scatterplot of the AAT scores computed from each half of the data from the last iteration. This is highly recommended, as it helps to identify outliers that can inflate or diminish the reliability.
<code>algorithm</code>	Function (without brackets or quotes) to be used to compute AAT scores. See <a href="#">Algorithms</a> for a list of usable algorithms.

<code>trialdropfunc</code>	Function (without brackets or quotes) to be used to exclude outlying trials in each half. The way you handle outliers for the reliability computation should mimic the way you do it in your regular analyses. It is recommended to exclude outlying trials when computing AAT scores using the mean double-difference scores and regression scoring approaches, but not when using d-scores or median double-difference scores. <code>prune_nothing</code> excludes no trials, <code>trial_prune_3SD</code> excludes trials deviating more than 3SD from the mean per participant. <code>trial_prune_SD.dropcases</code> allows you to set the maximum standard deviation to include using argument <code>trialstd</code> (default is 3) and prune participants altogether if they have more than a certain proportion of outliers using argument <code>maxoutliers</code> (default is .15)
<code>errortrialfunc</code>	Function (without brackets or quotes) to apply to an error trial. <code>error_replace_blockmeanplus</code> replaces error trial reaction times with the block mean plus an arbitrary extra amount of time. If used, the following additional arguments are required: <ul style="list-style-type: none"> <li>• <code>blockvar</code> - Quoted name of the block variable</li> <li>• <code>errorvar</code> - Quoted name of the error variable, where errors are 1 or TRUE and correct trials are 0 or FALSE</li> <li>• <code>errorbonus</code> - Amount to add to the reaction time of error trials. Default is 0.6 (recommended by Greenwald, Nosek, &amp; Banaji, 2003)</li> </ul> <code>error_prune_dropcases</code> removes errors and drops participants if they have a larger proportion of errors than given by argument <code>maxerrors</code> , default is .15
<code>casedropfunc</code>	Function (without brackets or quotes) to be used to exclude outlying participant scores in each half. The way you handle outliers here should mimic the way you do it in your regular analyses. <code>prune_nothing</code> excludes no participants, while <code>case_prune_3SD</code> excludes participants deviating more than 3SD from the sample mean.
<code>...</code>	Other arguments, to be passed on to the algorithm functions (see <code>algorithm</code> above)

## Value

A list, containing the mean bootstrapped split-half reliability, bootstrapped 95 a list of data.frames used over each iteration, and a vector containing the split-half reliability of each iteration.

## Author(s)

Sercan Kahveci

## See Also

[plot.aat\\_splithalf](#)

## Examples

```
#Not Run
aat_splithalf(ds=ds2,subjvar="subjectid",pullvar="is_pull",targetvar="is_food",
             rtvar="rt",iters=1000,trialdropfunc=trial_prune_3SD,
             casedropfunc=case_prune_3SD,plot=T,algorithm=aat_dscore)
```

```
#Mean reliability: 0.521959
#Spearman-Brown-corrected r: 0.6859041
#95%CI: [0.4167018, 0.6172474]

#Regression Splithalf
aat_splithalf(ds=ds2,subjvar="subjectid",pullvar="is_pull",targetvar="is_food",
             rtvar="rt",iters=100,trialdropfunc=trial_prune_3SD,
             casedropfunc=case_prune_3SD,plot=T,algorithm=aat_regression,
             formula = "rt ~ is_pull * is_food",
             aatterm = "is_pull:is_food")
#Mean reliability: 0.5313939
#Spearman-Brown-corrected r: 0.6940003
#95%CI: [0.2687186, 0.6749176]
```

---

## Algorithms

## *AAT score computation algorithms*

---

### Description

- `aat_doublemeandiff` computes a mean-based double-difference score:  
 $(\text{mean}(\text{push\_target}) - \text{mean}(\text{pull\_target})) - (\text{mean}(\text{push\_control}) - \text{mean}(\text{pull\_control}))$
- `aat_doublemediandiff` computes a median-based double-difference score:  
 $(\text{median}(\text{push\_target}) - \text{median}(\text{pull\_target})) - (\text{median}(\text{push\_control}) - \text{median}(\text{pull\_control}))$
- `aat_dscores` computes D-scores for a 2-block design (see Greenwald, Nosek, and Banaji, 2003):  
 $((\text{mean}(\text{push\_target}) - \text{mean}(\text{pull\_target})) - (\text{mean}(\text{push\_control}) - \text{mean}(\text{pull\_control}))) / \text{sd}(\text{participant\_reaction\_times})$
- `aat_dscores_multiblock` computes D-scores for pairs of sequential blocks and averages the resulting score (see Greenwald, Nosek, and Banaji, 2003). Requires extra `blockvar` argument, indicating the name of the block variable.
- `aat_regression` and `aat_standardregression` fit regression models to participants' reaction times and extract a term that serves as AAT score. `aat_regression` extracts the raw coefficient, equivalent to a mean difference score. `aat_standardregression` extracts the t-score of the coefficient, standardized on the basis of the variability of the participant's reaction times. These algorithms can be used to regress nuisance variables out of the data before computing AAT scores. When using these functions, additional arguments must be provided:
  - `formula` - a quoted formula to fit to the data;
  - `aatterm` the quoted random effect within the subject variable that indicates the approach bias; this is usually the interaction of the pull and target terms.

### Usage

```
aat_doublemeandiff(ds, subjvar, pullvar, targetvar, rtvar, ...)

aat_doublemediandiff(ds, subjvar, pullvar, targetvar, rtvar, ...)

aat_dscores(ds, subjvar, pullvar, targetvar, rtvar, ...)

aat_dscores_multiblock(ds, subjvar, pullvar, targetvar, rtvar, blockvar, ...)
```

```

aat_regression(ds, subjvar, formula, aatterm, ...)
aat_standardregression(ds, subjvar, formula, aatterm, ...)
aat_doublemedianquotient(ds, subjvar, pullvar, targetvar, rtvar, ...)
aat_doublemeanquotient(ds, subjvar, pullvar, targetvar, rtvar, ...)
aat_singlemeandiff(ds, subjvar, pullvar, rtvar, ...)
aat_singlemediandiff(ds, subjvar, pullvar, rtvar, ...)

```

### Arguments

<code>ds</code>	A long-format data.frame
<code>subjvar</code>	Column name of the participant identifier variable
<code>pullvar</code>	Column name of the movement variable (0: avoid; 1: approach)
<code>targetvar</code>	Column name of the stimulus category variable (0: control stimulus; 1: target stimulus)
<code>rtvar</code>	Column name of the reaction time variable
<code>...</code>	Other arguments passed on by functions (ignored)
<code>blockvar</code>	name of the variable indicating block number
<code>formula</code>	A character string containing a regression formula to fit to the data to compute an AAT score
<code>aatterm</code>	The formula term representing the approach bias. Usually this is the interaction of the movement-direction and stimulus-category terms.

### Value

A data.frame containing participant number and computed AAT score.

---

<code>plot.aat_splithalf</code>	<i>Plot split-half scatterplots</i>
---------------------------------	-------------------------------------

---

### Description

Plot split-half scatterplots

### Usage

```

## S3 method for class 'aat_splithalf'
plot(x, type = c("median", "minimum", "maximum", "random"))

```

### Arguments

<code>x</code>	an aat_splithalf object
<code>type</code>	Character argument indicating which iteration should be chosen. Must be an abbreviation of "median" (default), "minimum", "maximum", or "random".

**Examples**

```
#Coming soon
```

---

q-reliability	<i>Compute psychological experiment reliability</i>
---------------	---

---

**Description**

This function can be used to compute an exact reliability score for a psychological task whose results involve a difference score. The resulting q coefficient is equivalent to the average all possible split-half reliability scores.

**Usage**

```
q-reliability(ds, subjvar, formula, aatterm = NA)
```

```
## S3 method for class 'qreliability'
plot(x)
```

**Arguments**

ds	a long-format data.frame
subjvar	name of the subject variable
formula	a formula predicting the participant's reaction time using trial-level variables such as movement direction and stimulus category
aatterm	a string denoting the term in the formula that contains the participant's approach bias

**Value**

a qreliability object, containing the reliability coefficient, and a data.frame with participants' bias scores and score variance.

**Author(s)**

Sercan Kahveci

**Examples**

```
q-reliability(ds=dataset,subjvar="subjectid",formula= rt ~ is_pull * is_food, aatterm = "is_pull:is_food")
```



---

**SpearmanBrown***Spearman-Brown corrections for Correlation Coefficients*

---

**Description**

Perform a Spearman-Brown correction on the provided correlation score.

**Usage**

```
SpearmanBrown(  
  corr,  
  ntests = 2,  
  fix.negative = c("nullify", "bilateral", "none")  
)
```

**Arguments**

<code>corr</code>	To-be-corrected correlation coefficient
<code>ntests</code>	An integer indicating how many times larger the full test is, for which the corrected correlation coefficient is being computed. When <code>ntests=2</code> , the formula will compute what the correlation coefficient would be if the test were twice as long.
<code>fix.negative</code>	Determines how to deal with a negative value. "nullify" sets it to zero, "bilateral" applies the correction as if it were a positive number, and then sets it to negative. "none" gives the raw value.

**Details**

Correct a correlation coefficient for being based on only a subset of the data.

**Value**

Spearman-Brown-corrected correlation coefficient.

# Index

aat\_bootstrap, [1](#)  
aat\_compute, [3](#)  
aat\_doublemeandiff, [2](#), [3](#)  
aat\_doublemeandiff (Algorithms), [6](#)  
aat\_doublemeanquotient (Algorithms), [6](#)  
aat\_doublemediandiff (Algorithms), [6](#)  
aat\_doublemedianquotient (Algorithms),  
[6](#)  
aat\_dscore (Algorithms), [6](#)  
aat\_dscore\_multiblock (Algorithms), [6](#)  
aat\_regression (Algorithms), [6](#)  
aat\_singlemeandiff (Algorithms), [6](#)  
aat\_singlemediandiff (Algorithms), [6](#)  
aat\_splithalf, [4](#)  
aat\_standardregression (Algorithms), [6](#)  
Algorithms, [4](#), [6](#)  
  
plot.aat\_splithalf, [5](#), [7](#)  
plot.qreliability (q-reliability), [8](#)  
  
q-reliability, [8](#)  
  
SpearmanBrown, [9](#)