

Package ‘skMisc’

November 13, 2019

Title Sercan Kahveci's Miscellaneous Functions

Version 0.01

Description Contains a wide range of functions.

Depends R (≥ 3.6.1), magrittr, dplyr, doParallel, lmerTest

Imports tidy, knitr

License GPL-3

BugReports <https://github.com/Spiritspeak/skMisc/issues>

LazyData true

ByteCompile true

RoxygenNote 6.1.1

R topics documented:

AnovaTable	2
clamp	2
coerce	3
combobulate	3
compcorr	4
CorrCrunch	4
CorTable	5
df.init	6
ExpandFormula	6
ExtractRandomTerms	7
FindTopTerms	7
logit.weightfun	8
OLcrunch	8
read.csv.folder	9
RemoveTopTerms	9
retype	10
smoothvect	11
TransformPlots	11
trypackages	12
Index	13

AnovaTable	<i>Compare multilevel models</i>
------------	----------------------------------

Description

Compare multilevel models

Usage

```
AnovaTable(..., fullmodel, models, serial = F, suppress = c("AIC",
  "deviance", "logLik"))
```

Arguments

<code>...</code>	Model objects to be compared
<code>fullmodel</code>	A model to which all other models are to be compared; only use if <code>...</code> is not specified.
<code>models</code>	Models to compare to <code>fullmodel</code> . Only use if <code>...</code> is not specified.
<code>serial</code>	If TRUE, models are compared serially; if false, all models will be compared to the first.
<code>suppress</code>	Character vector of column names to suppress in printed output.

Value

A data.frame containing model fit metrics such as AIC, BIC, marginal R-squared (the effect size of fixed effects only), conditional R-squared (the effect size of all model terms), loglikelihood, deviance, and a likelihood ratio test.

clamp	<i>clamp</i>
-------	--------------

Description

clamp

Usage

```
clamp(val, minval, maxval)
```

Arguments

<code>val</code>	The vector/matrix to clamp
<code>minval</code>	Minimum value; all lower values are clamped to this value
<code>maxval</code>	Maximum value; all higher values are clamped to this value

Value

Clamped vector.

Examples

```
clamp(0:10, 2, 8)
```

coerce	<i>coerce a vector to contain only TRUE and FALSE</i>
--------	---

Description

coerce a vector to contain only TRUE and FALSE

Usage

```
coerce(x, default = FALSE)
```

Arguments

x	Numeric/logical vector/matrix to coerce into TRUE/FALSE
default	default returned value if NULL or NA is encountered

Value

logical vector or matrix with only T and F

Examples

```
coerce(NULL)
# FALSE

coerce(c(T,F,NA,NA,T))
# T F F F T

coerce(matrix(c(T,T,F,F,NA,NA),nrow=2))
#      [,1] [,2] [,3]
# [1,] TRUE FALSE FALSE
# [2,] TRUE FALSE FALSE
```

combobulate	<i>Get all possible combinations of strings</i>
-------------	---

Description

combobulate() returns all possible combinations of the provided character strings, each combination merged into a single string.

Usage

```
combobulate(...)
```

Arguments

...	Character vectors to combobulate.
-----	-----------------------------------

Value

A character vector.

Examples

```

combobulate("Hello ",c("Sir","Madam"),",",",c("may I take your order?","what shall it be?"))
# [1] "Hello Sir, may I take your order?"
# [2] "Hello Madam, may I take your order?"
# [3] "Hello Sir, what shall it be?"
# [4] "Hello Madam, what shall it be?"

```

compcorr
Test if two correlation coefficients significantly differ

Description

Uses Fisher's r to z transformation, then performs a z-test on the resulting z-scores

Usage

```
compcorr(cor1, cor2, n1, n2)
```

Arguments

cor1, cor2	Correlation values being compared
n1, n2	Sample sizes of the correlation coefficients

Value

List containing the z-score and p-value

References

<http://vassarstats.net/rdiff.html>

CorrCrunch
Analyse the robustness of a correlation

Description

CorrCrunch() computes the minimum number of cases that need to be removed from a dataset to flip the sign of a correlation coefficient. This can be useful in distinguishing genuine correlations from spurious findings that hinge on one or two outliers. Cases are removed iteratively; in each iteration the case that maximally shrinks the correlation coefficient is removed.

Usage

```
CorrCrunch(x, y, verbose = F)
```

Arguments

x, y	Numeric vectors to correlate.
verbose	if TRUE, prints verbose output.

Value

A list containing the number of cases that need to be removed to flip the sign of the correlation coefficient; the proportion removed cases in the data; and a data.frame without these cases.

Examples

```
CorrCrunch(mtcars$mpg,mtcars$wt)
#Holdout needed to flip the sign: 19 (63.33%)
#Final r: 0.01181141
```

CorTable	<i>Create a Correlation Table</i>
----------	-----------------------------------

Description

Create a Correlation Table

Usage

```
CorTable(df, rowids, columnids, rowdf, columndf)
```

Arguments

df A data.frame.

rowids, columnids character vectors containing column names from **df** that need to be correlated.

rowdf, columndf data.frames whose columns need to be correlated. Either **df**, **rowids**, & **columnids** or **rowdf** & **columndf** are required.

Value

A formatted markdown table containing correlation coefficients, p-values, and the number and percentage of cases that need to be removed to flip the sign of each correlation coefficient.

Examples

```
CorTable(mtcars,rowids=c("mpg","disp","hp"),columnids=c("drat","wt","qsec"))

CorTable(rowdf=mtcars[,c(1,3,4)],columndf=mtcars[,5:7])
```

<code>df.init</code>	<i>Initiate an empty data frame</i>
----------------------	-------------------------------------

Description

Initiate an empty data frame

Usage

```
df.init(namelist)
```

Arguments

`namelist` A character vector of column names.

Value

A data.frame with 0 rows.

<code>ExpandFormula</code>	<i>Parse a lme4 formula and return all main effects and interactions as separate terms</i>
----------------------------	--

Description

Parse a lme4 formula and return all main effects and interactions as separate terms

Usage

```
ExpandFormula(form)
```

Arguments

`form`

Value

The same formula, but with all interactions and main effects as separate terms

Examples

```
ExpandFormula(rt ~ pull * target + (pull * target | subjectid))
#rt ~ pull + target + pull:target + (pull + target + pull:target | subjectid)
```

ExtractRandomTerms	<i>Extract random terms from a lme4 formula</i>
--------------------	---

Description

Extract random terms from a lme4 formula

Usage

```
ExtractRandomTerms(form)
```

Arguments

form	A formula
------	-----------

Value

A named list containing character vectors with random terms; names are group variables.

Examples

```
ExtractRandomTerms(grade ~ ChildIQ * TeacherSkill * SchoolType +
                    (ChildIQ * TeacherSkill | School))
#School
#[1] "ChildIQ"          "TeacherSkill"      "ChildIQ:TeacherSkill"
```

FindTopTerms	<i>Find all model terms that are not moderated by a higher-order interaction</i>
--------------	--

Description

Find all model terms that are not moderated by a higher-order interaction

Usage

```
FindTopTerms(form)
```

Arguments

form	a formula
------	-----------

Value

A character vector containing all model terms that are not moderated by a higher-order interaction.

Examples

```
FindTopTerms(speed ~ skill + weight * friction)
#[1] "skill"          "weight:friction"
```

logit.weightfun	<i>Downweight outliers</i>
-----------------	----------------------------

Description

Computes weights; trials within certain bounds of the mean receive the maximum weight while trials outside these bounds are downweighted to 0 or an optional minimum.

Usage

```
logit.weightfun(x, mean = mean(x), s = sd(x), sdist = 3,
  taper = 10, scale = c("max", "norm"), min = 0)
```

Arguments

x	A numeric vector
mean	An optional mean of the vector
s	An optional standard deviation of the vector
sdist	The number of standard deviations beyond which values should be down-weighted
taper	A number indicating how strongly values exceeding the standard deviation should taper off
scale	How the weight vector should be scaled: "norm" sets the sum to 1, "max" sets the maximum to 1.
min	A minimum weight.

Value

A numeric vector of weights

OLcrunch	<i>Crunch Outliers</i>
----------	------------------------

Description

Crunch Outliers

Usage

```
OLcrunch(x, DS = 3, hardlimit = NULL)
```

Arguments

x	Numeric vector to remove outliers from
DS	A positive numeric value. If value exceeds this many standard deviations, it is counted as an outlier
hardlimit	A numeric vector with two values. If set, values below the first value and above the second will be counted as outliers, and means/standard deviations will be computed from values within these bounds only.

Value

Vector with outlying values set to NA

read.csv.folder	<i>Read and merge all .csv files in a folder</i>
-----------------	--

Description

Read and merge all .csv files in a folder

Usage

```
read.csv.folder(folder = "./", readfunc = list(read.csv, read.csv2,
  read.table))
```

Arguments

folder	path to a folder
readfunc	list of functions that will be used to read the files; if the first function fails, the second function will be used, etc.

Value

A data.frame containing all merged .csv files

RemoveTopTerms	<i>Remove all possible models with one unmoderated term removed</i>
----------------	---

Description

Remove all possible models with one unmoderated term removed

Usage

```
RemoveTopTerms(form, randeff = "")
```

Arguments

form	A formula
randeff	The name of the group from which unmoderated terms should be removed. To remove from fixed effects, use "" (the default).

Value

A list of formulas which have one unmoderated term removed each. The name of each list item is the term which was removed.

Examples

```
RemoveTopTerms(a ~ b * c + d + (1|e))
# $d
#a ~ b + c + b:c + (1 | e)
# $`b:c`
#a ~ b + c + d + (1 | e)
```

retype

Change classes of columns in a data.frame

Description

retype() changes the class of specific columns; retype_all() changes the class of all columns of a given class.

Usage

```
retype(df, ...)
```

```
retype_all(df, from, to)
```

Arguments

df	a data frame
...	Unquoted column names, paired with the desired class, e.g. age = numeric(), language = character()
from	An empty vector of the class to convert from, or a string. Columns sharing the class of argument from will be converted to the class of argument to.
to	An empty vector of the class to convert to, or a string. Columns sharing the class of argument from will be converted to the class of argument to.
df	A data.frame

Examples

```
sapply(ToothGrowth,class)
#      len      supp      dose
#"numeric" "factor" "numeric"
NewToothGrowth <- retype(ToothGrowth, supp = character(), dose = factor())
sapply(NewToothGrowth,class)
#      len      supp      dose
#"numeric" "character" "factor"

sapply(mtcars,class)
#      mpg      cyl      disp      hp      drat      wt
# "numeric" "numeric" "numeric" "numeric" "numeric" "numeric"
#      qsec      vs      am      gear      carb
# "numeric" "numeric" "numeric" "numeric" "numeric"

newmtcars <- retype_all(mtcars,"numeric","character")
sapply(newmtcars,class)
#      mpg      cyl      disp      hp      drat
# "character" "character" "character" "character" "character"
```

```
#           wt           qsec           vs           am           gear           carb
# "character" "character" "character" "character" "character" "character"
```

smoothvect	<i>Smooth a numeric vector using a moving window algorithm</i>
------------	--

Description

Smooth a numeric vector using a moving window algorithm

Usage

```
smoothvect(vect, width = 2, both.sides = T, alg = c("mean", "gauss"))
```

Arguments

vect	
width	Over how many values should the vector be averaged?
both.sides	If TRUE (default), takes the mean of width values before and after the current index. If FALSE, only takes values ahead of the current index.

Value

Smoothed numeric vector

Examples

```
temp<- smoothvect(beaver1$temp)
plot(temp,type="l")
```

TransformPlots	<i>Title</i>
----------------	--------------

Description

Visualize how different transformations of the data will fit to a normal distribution.

Usage

```
TransformPlots(x)
```

Arguments

x	A numeric vector.
---	-------------------

Examples

```
TransformPlots(mtcars$displacement)
```

trypackages	<i>Install packages if neccesary, then load them.</i>
-------------	---

Description

Install packages if neccesary, then load them.

Usage

```
trypackages(...)
```

Arguments

...	Unquoted names of packages to try loading, and if unable, install and load.
-----	---

Examples

```
trypackages(stats,utils,compiler)
```

Index

AnovaTable, [2](#)

clamp, [2](#)

coerce, [3](#)

combobulate, [3](#)

compcorr, [4](#)

CorrCrunch, [4](#)

CorTable, [5](#)

df.init, [6](#)

ExpandFormula, [6](#)

ExtractRandomTerms, [7](#)

FindTopTerms, [7](#)

logit.weightfun, [8](#)

OLcrunch, [8](#)

read.csv.folder, [9](#)

RemoveTopTerms, [9](#)

retype, [10](#)

retype_all (retype), [10](#)

smoothvect, [11](#)

TransformPlots, [11](#)

trypackages, [12](#)