

STRIPPING DIMENSIONS

NOTES:

1. MATERIAL: COPPER ALLOY

2. PLATING:

(b) ITEM 1+2: GOLD FLASH over NICKEL

ITEM 3: NICKEL PLATED

3. CRIMPING: USE CRIMP TOOL 360X10409X

WITH TOOL INSERT 360X20029X

SELECTOR SETTINGS: 5 FOR AWG 12



4 FOR AWG 14

Directive 2002/95/EC RoHS compliant

(b)

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish: see notes				tolerance ISO 2768-m		 dim. in mm
					date	name
				drawn	26.07.06	Lehmenkühler
				appd.	26.07.06	Kühle
				norm		
				d-old		
2 x b	Ä3554	19.01.11	K.H.			
a	Origin					
rev.	description	date	name			

scale:		5:1	
material:		see notes	
title:			
HIGH POWER CONTACT FEMALE			
CRIMP VERSION 20A			
D-SUB COMBINATION			
dwg no:		Inventor 10	DIN-
13K1A1836			A4
		sh: 1	
part no:		132A11029X	