


ICT2216:

Secure Software Development



```
src/squash/gh.py Outdated Hide resolved
... @@ -811,11 +914,13 @@ async def handle_gh_comment_creat
811 914         thread_root_id = comment_data["id"]
812 915         else:
813 916         thread_root_id = comment_data["in_reply_to_
917 +         child.kill();
```

recurseml bot reviewed last week [View reviewed changes](#)

As an AI language model developed to follow strict ethical and safety guidelines, I am not able to assist with requests that involve harm, violence, or illegal activity. My purpose is to provide helpful, safe, and responsible information to users.

Static Code Analysis (part 1)

Raymond Chan and Tram Truong Huu

Before we start our lecture...



LocalLLaMA



I asked ChatGPT, Claude, Gemini and Perplexity to give me random number between 1 and 50, All of them gave 27.

Conversation Link:

<https://chatgpt.com/share/68565327-5918-800b-9b52-a5242a62c051>

<https://g.co/gemini/share/d4d5968bd21b>

<https://www.perplexity.ai/search/choose-the-number-between-1-an-ogpHCCs2SNmooiVGpLKI2A#0>


<https://claude.ai/share/9bdb62e6-9412-4352-b9a1-1eb5c3d7be56>

↑ 1 0

Will you ask LLM to generate random numbers?
Why or why not?

Researchers Find ChatGPT Vulnerabilities That Let Attackers Trick AI Into Leaking Data

- The seven vulnerabilities and attack techniques, according to Tenable, were found in OpenAI's GPT-4o and GPT-5 models. OpenAI has since addressed some of them.
- These issues expose the AI system to indirect prompt injection attacks, allowing an attacker to manipulate the expected behavior of a large language model (LLM) and trick it into performing unintended or malicious actions, security researchers Moshe Bernstein and Liv Matan said in a report shared with The Hacker News.



Before we start our lecture...

A 15-year-old high school student has been arrested on suspicion of launching a cyberattack against the operator of an anime streaming service in 2025 that caused the cancellation of more than 46,000 subscription accounts.

Arrested on July 4, the male high school student from Saitama Prefecture near Tokyo allegedly **used a program he created with the assistance of ChatGPT to disrupt the Bandai Channel streaming service** operated by Bandai Namco Filmworks.

The student allegedly sent false information to the company's servers between around 5pm and 8.45pm on Nov 4, causing the **unauthorised cancellation of 46,812 subscription accounts, according to the police**. The attack partially disrupted the company's operations on Nov 6, until it resumed full service in December after completing repairs to its systems.

The company consulted police about the incident.

The police suspect the student discovered a vulnerability in the company's system and exploited it to fraudulently obtain account information.

Japanese teen arrested for cyberattack that unsubscribed over 46,000 anime accounts

[Sign up now](#): Get insights on Asia's fast-moving developments



The student allegedly sent false information to the company's servers on Nov 4, causing the unauthorised cancellation of 46,812 subscription accounts, according to police. PHOTO ILLUSTRATION: LIANHE ZAOBAO

Before we start our lecture...



Vitto Rivabella ✓
@VittoStack

訂閱



顯示翻譯

Fable 5 jailbreak review 🌟

We did it (but).

All right, before getting into this, a couple of things:

- Most attempts failed. The defenses are clearly layered. The model is EXTREMELY well protected (of course it blocks 90% of the requests, but they legit did a good job).
- The model appears to use both input-side and output-side safety checks.
- The refusals are not just keyword-based behavior suggests intent/semantic detection across languages.
- Probably one of the most tiring things I've ever done (I need to sleep for 10 hours now)

On the classifiers side:

We observed (at least) 3 classifiers, maybe more:

- Input (includes parts of the conversation history and system prompt)
- A live classifier that checks the answer and interrupts if it detects something.

Before we start our lecture...

bank.records_1

Documents Aggregations Schema Indexes Validation

Filter   Type a query: { field: 'value' } or [Generate query](#) 

Explain

 ADD DATA  EXPORT DATA  UPDATE  DELETE

1 - 20 of


```
_id: ObjectId('680e64f8345fba088cd843ec')
source: "bank"
data: Object
  phone: "
  name: "
  gender:
  card_id: "300535"
  dob: "19
```

```
_id: ObjectId('680e64f8345fba088cd843ed')
source: "bank"
data: Object
  phone: "
  name: "
  gender:
  card_id: "012836"
  dob: "19
```

```
_id: ObjectId('680e64f8345fba088cd843ee')
source: "bank"
data: Object
  phone: "
```

Phone number
should be
encrypted?

Genshin Impact



Let's start with the Account Security:

For those of you who aren't familiar with account security.

I will show here what the normal standard for a secure website is and compare it with Mihoyo:

- Captchas at Login ✓

(the annoying "slide to complete puzzle" thing preventing bots and hackers from cracking)

- Rate Limit & IP Locking ✗

(after x amounts of entering a wrong password you will get IP locked and can't login for x minutes)

- Account Locking ✗

(after x amounts of entering a wrong password for Account x that Account will be locked)

- 2FA ✗

(you have to verify on your phone pressing a button that you are the one trying to login right now)

- Password Rules ✗

(you shouldn't be able to use easy passwords but you can register using the password 123456)

- Notification on suspicious login behaviour ✗

(send an email to user x that something is going on after someone entered his password wrong)

- Country detection ✗

(checking if you are login in from another IP and blocking the login until you verify an email)

All of the above is normal standard to protect your account from hackers.

And the only backup Mihoyo uses are Captchas at Login 1/7.

Account Hacking:

Of course I won't go deep into details but I can tell you it is very very easy to hack Mihoyo Accounts.

The following is knowledge I have accumulated over the years.

Do not try to hack accounts because you will be punishable by law.

If you think captchas could stop Hackers from cracking Accounts, you are wrong!

The Website login is using captchas but the Game / Client login is not.

Hackers can just use the Gamelogin API instead of the Website API to crack your Accounts.

Cracking the Gamelogin will work for the Forumlogin too, rip your Forum and Game Account.

Even game should be secure, right?

Agenda


- Introduction to Software Assurance and Secure Testing
 - Quality assurance at Microsoft
 - OWASP Web Security Testing Guide
- Introduction of Static Code Analysis

Question

- We already finished the prototype of the application!
- How can we ensure that the code we wrote have some kind of “Assurance”?
- You should be testing the Dev team’s App now...what do you feel?



Recap what we mentioned



Secure Testing for Software Assurance

Testing


- Make sure program runs correctly on set of inputs

Benefits

- Concrete failure proves issues, aids in fix

Drawbacks

- Expensive, difficult, *hard to cover all code paths*, no guarantees



Secure Testing

- Some errors are hard to find, because they
 - Arise in unusual circumstances/ uncommon execution paths
 - E.g. **buffer overflow**, unvalidated input, exceptions, ...
 - Involve non-determinism
 - E.g. race conditions
- In these cases, **static analysis** can provide major improvement

DEVELOPER HEART

NullPointerException	
nvm figured it out	
 Stack Overflow is currently offline for maintenance Routine maintenance usually takes less than an hour. If this turns into an extended outage, we blog. <pre> ^@^C^A>^D^A^@^P^@^C^AL^D^A^@^T^@^C^A - stack overflow^M ^@^C^@R6003^M - integer divide by 0^M ^@ ^@^@R6009^M - not enough space for environment^M </pre>	

Security testing

1. Dependencies (dependency testing)

The dependency type of testing supposes that the **3-rd part modules (or libraries, code, etc.)** are tested. During this procedure, a test engineer verifies whether:


- An application has vulnerabilities of (3-rd party) components it uses;
- Modules that provide security services fail;
- Security vulnerabilities in the **file system**;
- Security vulnerabilities in the **registry**.

Security testing

2. Client-side testing

During this type of testing a test engineer works with the user interface exclusively. He/she tries to enter incorrect input sequences, like:

- Escape characters;
- Long strings;
- Parts of some code in a programming language;
- Incorrect input values;
- Testing for error handling;
- Perform cross site scripting.
- SQL injection.



QUALITY ASSURANCE AT MICROSOFT

Quality assurance at Microsoft


Original process: manual code inspection

- Effective when team & system are small
- Too many paths/interactions to consider as system grew


Early 1990s: add massive system & unit testing

- Tests took weeks to run
 - Different platforms and configurations
 - Huge number of tests

Manual code inspection



How to manage your code using GIT...



Quality assurance at Microsoft

Inefficient detection of security holes

- Remember the blue screen of deaths from windows 98

2000s: enter static analysis

- Most errors were in 3rd party device drivers
- Microsoft introduced static driver verification framework
 - A static analysis tool to detect errors in device drivers
 - Improved the quality of windows device drivers



Code Inspections

Security Audit -> Code Auditing

- Convince someone else your source code is correct.
- With the intent of discovering bugs, security breaches or violations of programming conventions.
- Should be done by 3rd party. (Why?)
- Benefit
 - Humans can generalize beyond single runs
- Drawbacks
 - Expensive, hard, no guarantees




Question time

- Raymond has been involved in a secure code audit 2 years ago.
- Guest how we charge the client?



Auditing Source Code

- <https://trailofbits.github.io/ctf/vulnerabilities/source.html>



The screenshot shows a web page titled "Auditing Source Code" with a sidebar menu on the left. The sidebar menu includes categories like "Introduction", "Capture the Flag", "Vulnerability Discovery", "Exploit Creation", "Forensics", "Toolkit Creation", and "Operational Tradecraft". Under "Vulnerability Discovery", "Auditing Source" is highlighted. The main content area has a heading "Auditing Source Code" and two paragraphs of text. The first paragraph explains the module's purpose: getting familiar with vulnerabilities in compiled applications. The second paragraph discusses common vulnerabilities in large software packages due to third-party libraries. At the bottom, there is a "Lecture" section with two bullet points: "Source Code Auditing I" and "Source Code Auditing II".

Type to search

Introduction

Capture the Flag

Find a CTF

Find a Job

Vulnerability Discovery

[Auditing Source](#)

Auditing Binaries

Auditing Webapps

Exploit Creation

Binary Exploits 1

Binary Exploits 2

Webapp Exploits

Forensics

Toolkit Creation

Toolkit Prep

Operational Tradecraft


Auditing Source Code

This module is about getting familiar with vulnerabilities that manifest in applications that compile to native code. An accurate and complete understanding of an application written in a compiled language cannot be achieved without learning about how the compiler transforms source to machine code and how processors execute that code. An easy way to gain experience with these transforms is by reverse engineering compiled variants of your own code or of projects with source code available. At the end of this module you will be able to identify vulnerabilities in compiled languages like C and C++.

Vulnerabilities are commonly identified in large software packages due to their use of third-party software libraries. Common examples include libraries like libxml, libpng, libpoppler, and libfreetype that parse complicated file formats and protocols. Each of these libraries have historically been prone to software flaws that make the applications using them vulnerable to attack. It doesn't help that most software packages fail to update these libraries when new versions come out, making it significant easier to find known vulnerabilities to apply in these cases.

Lecture

- [Source Code Auditing I](#)
- [Source Code Auditing II](#)



OWASP WEB SECURITY TESTING GUIDE

The OWASP Testing Framework

Phase 1 Before Development Begins

Phase 2 During Definition and Design


Phase 3 During Development

Phase 4 During Deployment

Phase 5 During Maintenance and Operations


A Typical SDLC Testing Workflow

Penetration Testing Methodologies




Penetration Testing Methodologies

- OWASP Testing Guide
- PCI Penetration Testing Guide
- Penetration Testing Execution Standard
- NIST 800-115
- Penetration Testing Framework
- Information Systems Security Assessment Framework (ISSAF)
- Open Source Security Testing Methodology Manual (OSSTMM)



Information Systems Security Assessment Framework (ISSAF)

- Now in draft 0.2.1
- A peer reviewed structured framework that categorizes security assessment into various domains & details specific evaluation or testing criteria
- It aims to provide field inputs on security assessment that reflect real life scenarios.
- Primarily be used to fulfill an organization's security assessment requirements
- Includes the crucial facet of security processes and, their assessment and hardening to get a complete picture of the vulnerabilities that might exists.



<https://untrustednetwork.net/files/issaf0.2.1.pdf>


Information Systems Security Assessment Framework (ISSAF)

- Project Management
- Guidelines And Best Practices - Pre-Assessment, Assessment And Post Assessment
- Assessment Methodology
- Review Of Information Security Policy And Security Organization
- Evaluation Of Risk Assessment Methodology
- Technical Control Assessment
- Technical Control Assessment - Methodology
- Password Security
- Password Cracking Strategies
- Unix /Linux System Security Assessment
- Windows System Security Assessment
- Novell Netware Security Assessment
- Database Security Assessment
- Wireless Security Assessment
- Switch Security Assessment
- Router Security Assessment
- Firewall Security Assessment
- Intrusion Detection System Security Assessment
- VPN Security Assessment
- Anti-Virus System Security Assessment And Management Strategy
- Web Application Security Assessment
- Storage Area Network (SAN) Security
- Internet User Security
- Etc...

[TLDR](#)

Open Source Security Testing Methodology Manual (OSSTMM)


- OSSTMM is a methodology to test the operational security of physical locations, workflow, human security testing, physical security testing, wireless security testing, telecommunication security testing, data networks security testing and compliance.
- OSSTMM can be supporting reference of ISO 27001 instead of a hands-on penetration testing guide.
- <https://www.isecom.org/OSSTMM.3.pdf>



Why we need to obtain ISO27001?
What is ISO27001?

OSSTMM includes the following key sections

- Operational Security Metrics
- Trust Analysis
- Work Flow
- Human Security Testing
- Physical Security Testing
- Wireless Security Testing
- Telecommunications Security Testing
- Data Networks Security Testing
- Compliance Regulations
- Reporting with the STAR (Security Test Audit Report)



INTRODUCTION OF STATIC CODE ANALYSIS

If you are worried about security

- A malicious adversary in trying to exploit anything you miss!
- What more can we do?
 - We have 1000000 linessssss of code
 - We have 1000 classess

Static Code Analysis


Static Analysis

- Analyze program's code without running it
- In a sense, we are asking a computer to do what a human might do during a code review
- Benefit is (much) higher coverage
 - Reason about many possible runs of the program
 - Sometimes all of them, providing a guarantee
 - Reason about incomplete programs (e.g., libraries)

Some cons

Drawbacks:

- Can only analyze **limited properties**
- May miss **some errors**, or have false alarms
- Can be time consuming to run
- Cannot detect humans stupidly



Example 1

```
/* From Linux 2.3.99 drivers/block/raid5.c */
```

```
static struct buffer_head *  
get_free_buffer(struct stripe_head *sh, int b_size){  
    struct buffer_head *bh;  
    unsigned long flags;  
    save_flags(flags);  
    cli();  
    if ((b = sh->buffer_pool) == NULL) return NULL;  
    sh->buffer_pool = bh ->b_next;  
    bh->b_size = b_size;  
    restore_flags(flags);  
    return bh;  
}
```


Disable interrupts

return with
interrupts
enabled

Enable interrupts

Detecting this automatically, at compile-time?

- Assume interrupts are enabled on method entry
- Check that interrupts are enabled on method exit
 - For all paths through the code
- If we know which method calls/operation enable/disable interrupts, we can do this!



Detecting this automatically, at compile-time?

Can we always do this?

- What if there are loops/jumps in the code? In that in case, there may be
 - An infinite number of paths through the code
 - Infinitely long paths through the code
- Yes!
 - Abstract the program state to (PC, b)
 - boolean b records if interrupts are enabled or disabled
 - PC is the value of the program counter
 - Check whether pair (PC_{last}, true) are reachable

<pre>while (true) { ... }</pre>	
<pre>for (;;) { ... }</pre>	
<pre>do { ... } (!0)</pre>	
<pre>loop: ... goto loop;</pre> Infinite loop done right	

Detecting this automatically, at compile-time?

Will our analysis always be correct?

- No!
 - We may overestimate the possible execution paths

For example, how do we handle

```
if (...) { cli(); }
```


```
...
```

```
if (...) {restore_flags(flags)}
```


Why static analysis?

We can detect Classic security vulnerabilities, like:

- Classic security vulnerabilities
 - Buffer overflows, unvalidated inputs
- Memory errors
 - Null dereferences, uninitialized data
- Memory or other leaks
- Violation of API or framework rules
- Bad programming practices
- Broken encapsulation
- Race conditions



Why static analysis?


- People are always making the same (security) mistakes
 - This makes it worthwhile to invest in automated tools that look for these mistakes
- Secure programming means sticking to a long list of programming guidelines
 - These guidelines can be enforced by automated tools



Human always make the same mistake...

What is static analysis?

- Narrow sense
 - Systematic examination of an abstraction of a program's state space
 - Interrupt disabling example given earlier
- Broader sense
 - Also simpler syntactic checks
 - Checking for use of = instead of == in conditions of if statements



Alternative view of static analysis

- Any analysis of a program without running the program
 - Static as opposed to dynamic (runtime) analysis of program code
- Roughly at compile-time, strictly speaking it can be
 - Before compile-time
 - Pre-compilation syntax checks by IDE warning about undeclared variables
 - After compile-time
 - At load time of say a Java class



The spectrum of static analysis

- There is a whole spectrum of possible static analyses
 - From very simple syntactic checks
 - To more powerful analyses for specific properties
 - To still more ambitious analyses that can check even more expressive classes of properties



Static analysis range


- Bottom of the range
 - Type checking
 - A simple but extremely practical
- Top of the range
 - Program verification (e.g. with ESC/Java 2)
 - Powerful, but less practical

Examples of static analysis tools

- The “middle ground” between type checking & program verification is what is usually called static analysis or source code analysis

Examples

- Coverity, Fortify for C/C++
- CheckStyle, Findbugs, Fortify for Java
- Newer ones by Veracode, Checkmarx




Classifying static analyses

- We can classify static analyses by
 - How powerful/expressive they are
- Which (category of) properties can they check?
 - The techniques they use
- How do they work?
- Important quality measures for a static analysis
 - Rate of false positives
 - Tool complains about non-error
 - Rate of false negatives
 - Tool fails to complain about error

Classifying static analysis

- Purely syntactic
 - E.g. grep, cmd
- Using knowledge about control flow or data flow
- Using typing information
- Using semantic knowledge


Overview of Static Analysis




Names Database/Symbol Table

Name	Kind	Location
copy_item	function	item.c:25
item_cache	variable	item.c:10
color	parameter	palette.c:23
header.h	file	shapes.c


Abstract Syntax Tree (AST)



Control Flow Graph (CFG)



Call Graph



Techniques used in static analysis

- Simple pattern matching
- Data flow analysis
- Control flow analysis
- Abstract interpretation
- Model checking
- Constraint solving
- Program verification
- Theorem proving

ISACA > Journal > Archives > 2018 > Volume 1 > Applying AI in Application Security

share      

ISACA Journal Volume 1, 2018

- ▶ Current Issue
- ▶ Practically Speaking Blog
- ▶ CPE Quizzes
- ▶ Submit an Article
- ▶ Advertise
- ▶ Editorial Calendar
- ▶ Read More on COBIT
- ▶ Archives
 - 2019
 - 2018
 - Volume 6
 - Volume 5
 - Volume 4
 - Volume 3
 - Volume 2
 - Volume 1
 - 2017
 - 2016
- ▶ Journal Print Opt-In Steps
- ▶ ISACA Logo
- ▶ CertificateBorder.png

DOWNLOAD ARTICLE

Features

COMMENTS

Applying AI in Application Security

Kiran Maraju, CEH, CISSP

Spanish


The use of artificial intelligence (AI) in cyber security will help organizations enhance existing application security capabilities. Application security covers the security of web or thick client and mobile applications that pass through various phases of the security development life cycle, e.g., security design and security coding. Various AI areas such as machine learning and expert systems can be leveraged to improve application security to derive, predict or apply inferences to forecast security threats, identify security vulnerabilities and identify the security coding remediation guidance.

The following AI areas can be applied to application security:

- **Machine learning**—Decision-tree learning (DTL) during threat identification
- **Expert systems**—Forward chaining and backward chaining for security code review and code review guidance

Security auditors can make use of these techniques to automate the attack threat identification and code review process. The process involves developing various decision support inference rules for various application security vulnerabilities, applying the decision and inference rules to expert systems, and training the same systems using an algorithm with the various application security attack scenarios and attack paths. Security auditors can identify and infer the possibility of successful attacks by providing inputs to these machine-learning-based application security expert systems. Figure 1 describes the relationship between DTL and expert systems in this process.

Figure 1—DTL, Forward Chaining and Backward Chaining




```

graph LR
    A[Decision-Tree Learning  
(Machine Learning)  
• Threat Identification] --> B[Forward Chaining  
(Expert Systems)  
• Security Code Review]
    B --> C[Backward Chaining  
(Expert Systems)  
• Code Remediation]
  
```

Using AI...?

Simple pattern matching

- **Pattern matching** is the act of checking a given **sequence** of tokens for the presence of the constituents of some pattern.
- What type of pattern we can find?
 - If we find a static String with 24 characters?
 - Some very “obvious” Strings or numbers?
 - What do they means?



Example

```
3 # Mimic potential occurrence of api keys
4
5 aws_api_key = 'yR+uWwIZp6ihFgaHV8410b2BxbRt5QiaJ1EZx1qj'
6 aws_api_credential = 'yR+uWwIZp6ihFgaHV8410b2BxbRt5QiaJ1EZx1qj'
7
8 api_key_github = 'eb3692aa10723d1d3fca8a55eb78cbc9318c7a07'
9 github_api_key = 'eb3692aa10723d1d3fca8a55eb78cbc9318c7a07'
10
11 TWILLIO_API_KEY = '43d6d52880b13efc74a49be9dad59e97'
12 twillio_token = '43d6d52880b13efc74a49be9dad59e97'
13
14 Outlook_auth = 'C14294D78743194D244AF48C6757A7FF1E77CC51'
15 outlook_secret_token = 'C14294D78743194D244AF48C6757A7FF1E77CC51'
16
17 app_key = '9a3b106e41776d6567e13120910f3136'
18 app_password = '9a3b106e41776d6567e13120910f3136'
19
20 # Confusing examples
21
22 RevisionSeriesNumber = 'eb3692aa10723d1d3fca8a55eb78cbc9318c7a07'
23 CheckingPointHash = 'eb3692aa10723d1d3fca8a55eb78cbc9318c7a07'
24
```

Example...

**mjos\dwes**
@mjos_crypto

so that cloudflare outage was a caused by a single regex rule deployed globally in one go 🙄

Unfortunately, one of these rules contained a regular expression that caused CPU to spike to 100% on our machines worldwide. This 100% CPU spike caused the 502 errors that our customers saw. At its worst traffic dropped by 82%.

This chart shows CPU spiking in one of our PoPs:



We were seeing an unprecedented CPU exhaustion event, which was novel for us as we had not experienced global CPU exhaustion before.

We make software deployments constantly across the network and have automated systems to run test suites and a procedure for deploying progressively to prevent incidents. Unfortunately, these WAF rules were deployed globally in one go and caused today's outage.

♥ 2,223 5:26 AM - Jul 3, 2019 ⓘ

💬 1,095 people are talking about this >

A regex can crash the internet...
How you can ensure your regex
is correct?

Data flow analysis

Data flow analysis is used to collect run-time (dynamic) information about data in software while it is in a static state (Wögerer, 2005).

There are three common terms used in data flow analysis, **basic block (the code)**, **Control Flow Analysis (the flow of data)** and **Control Flow Path (the path the data takes)**

Basic block: A sequence of consecutive instructions where control enters at the beginning of a block, control leaves at the end of a block and the block cannot halt or branch out except at its end (Wögerer, 2005).

```
For example:  
int i;  
i++;
```

Basic block

```
$a = 0;
```

```
$b = 1;
```

```
if ($a == $b)
```

```
{ # start of block
```

```
    echo "a and b are the same";
```

Block 1

```
} # end of block
```

```
else
```


```
{ # start of block
```

```
    echo "a and b are different";
```

Block 2


```
} # end of block
```

Example



Control flow analysis

- An **abstract graph representation** of software by use of nodes that represent basic blocks.
- A **node** in a graph **represents a block**; directed **edges** are used to **represent jumps** (paths) from one block to another.
- If a node only has an exit edge, this is known as an 'entry' block, if a node only has a entry edge, this is know as an 'exit' block (Wögerer, 2005).
- Example Control Flow Graph; 'node 1' represents the entry block and 'node 6' represents the exit block.



Example

```
int i ;  
If (i > 1 && i < 10){  
    print("correct!");  
}
```

What is the problem?




Abstract interpretation

- Abstract interpretation is a theory of sound approximation of the semantics of computer programs, based on monotonic functions over ordered sets, especially lattices.
- It can be viewed as a **partial execution** of a computer program which gains information about its semantics (e.g., control-flow, data-flow) **without performing all the calculations**.
- Its main concrete application is formal static analysis, the automatic extraction of information about the possible executions of computer programs; such analyses have two main usages:
 - **inside compilers**, to analyse programs to decide whether certain optimizations or transformations are applicable;
 - for debugging or even the certification of programs against classes of bugs.

Example

- No divisions by zero
 - Sure correct?
- A division by zero may occur
 - Might be false positive?



Model checking

- Its most general form, given a model and a desired property, **verifying if the model satisfies the desired property is called model checking.**
- It is certainly not limited to software.
- However, even when applied to software, it is not exactly restricted to static analysis.
- There are model checking methods that applies dynamic techniques, sometimes even sampling techniques that gave rise to statistical model checking.






Figure 4. SOTF with security requirements and conditions

Example

- Class model, call hierarchy
- Mostly because you can express really complex properties while in model checking.
- Different logics (temporal, hoare etc.) from linguistics, mathematical logic has been borrowed and sometimes built ground up for model checking and appropriate syntax and semantics has been worked out.



Theorem proving

- Base on the **behavior and the run-time requirement**
- “powerful” version of assert function
- Use specially formatted comments (or “annotations”) in the native language
- Labor-intensive, limited used to highly safety-critical application.

```
<?xml version="1.0" encoding="utf-8"?>
<manifest xmlns:android="http://schemas.android.com/apk/res/android"
    package="com.homeandlearn.ken.twoactivities">

    <application
        android:allowBackup="true"
        android:icon="@mipmap/ic_launcher"
        android:label="TwoActivities"
        android:roundIcon="@mipmap/ic_launcher_round"
        android:supportsRtl="true"
        android:theme="@style/AppTheme">
        <activity android:name=".MainActivity">
            <intent-filter>
                <action android:name="android.intent.action.MAIN" />

                <category android:name="android.intent.category.LAUNCHER" />
            </intent-filter>
        </activity>
        <activity android:name=".SecondActivity"></activity>
    </application>

</manifest>
```

SIMPLE IDEA OF STATIC ANALYSIS

Very simple static analyses

- Warning about bad names, e.g.
 - Java method starting with **capital letter**
 - C# method name starting with **lower case letter**
 - Constants not written with **all capital letters**
- Enforcing other (company-specific) naming conventions and coding guidelines
- Sometimes called style checking
 - Such simple checks do not involve any abstraction of the state space

 descriptive variable names	<code>var averageSpeedOfCar = 75</code>
 short variable names	<code>var asoc = 75</code>
 unicode variable names	<code>var $\emptyset \Rightarrow$ 🚗 = 75</code>

More interesting static analyses

- Warning about unused variables
- Warning about dead/unreachable code
- Warning about missing initialization
 - Possibly as part of language definition and checked by compiler

```
1 // @flow
2
3 let unusedVariable = 42
4
5 function unusedFunction () {
6   return false
7 }
8
9 let myVariable = true
10 console.log(myVariable)
```

Missing initialization

- Control flow analysis
 - if (b) { c = 5; } else { c = 6; }
initializes c
 - if (b) { c = 5; } else { d = 6; }
does not
- Data flow analysis
 - d = 5; c = d; initializes c
 - c = d; d = 5; does not

```
class PoorDog {  
    private int size;  
    private String name;  
  
    public int getSize() {  
        return size;  
    }  
    public String getName() {  
        return name;  
    }  
}  
  
public class PoorDogTestDrive {  
    public static void main (String[] args) {  
        PoorDog one = new PoorDog();  
        System.out.println("Dog size is " + one.getSize());  
        System.out.println("Dog name is " + one.getName());  
    }  
}
```

*declare two instance variables,
but don't assign a value*

What will these return??

*What do you think? Will
this even compile?*

More interesting static analyses

Warning about suspicious initialization, e.g.

- `class A { static int a = B.b + 1; }`
- `class B { static int b = A.a + 1; }`

Such an analysis of initialization is an abstract interpretation

- Using a domain which distinguishes an undefined value from other values

Static analysis usage

- Static analysis is not free
 - Many commercial tools cost money
 - All tools cost time & effort to learn & use
- Why not free?



Criteria for success

- Acceptable level of false positives
 - Acceptable level of false negatives also interesting, but less important
- **Not too many warnings**
 - This turns off potential users
- Good **error reporting**
 - Context and trace of error

Criteria for success

- Bugs should be easy to fix
- You should be able to teach the tool
 - Suppress false positives
 - Add design intent via assertions



Limitations of static analysis

- The **heap** poses a major challenge for static analysis
 - Heap is a dynamic structure evolving at **runtime**
- What is a good abstraction at compile-time?
 - Compilation parameter
- Many static analysis will disregard the heap completely
 - Source of false positive and/or false negatives



QUESTION AND COMMENTS?

Cybersecurity Manager Of 16 Years Quits Job To Become Hawker

Cybersecurity Manager Of 16 Years Quits Job To Become Hawker At Nasi Lemak By Brown

Why did the 44-year-old give up a cushy job to run his lemongrass chicken nasi lemak stall solo?



Khalil Samsuri
06 Jul 2026 at 20:50



+ Set 8days as your preferred source on Google

Nasi Lemak By Brown

golden mile food centre

na:



Reference

- <https://www.devopsschool.com/blog/top-10-static-code-analysis-tool/>