

# CS-E4891 Deep Generative Models

## Lecture 1: Statistical methods

Harri Lähdesmäki

Department of Computer Science  
Aalto University

March 17, 2025

## Outline

- Divergence measures (Sections 2.7, 5.1 from (Murphy, 2023))
- Monte Carlo (Sec. 11.2)
- Importance sampling (Sec. 11.5)
- Neural network likelihood models (Sec. 16.3)
  
- Reading: parts of Sections 2.7, 5.1, 11.2, 11.5, and 16.3 from (Murphy, 2023)

# Commonly used training objectives in probabilistic modeling

- Likelihood, maximum likelihood: e.g.
  - Bernoulli distribution for binary classification (cross-entropy loss)
  - Categorical distribution for multi-class classification (cross-entropy loss)
  - Gaussian distribution for regression (a special case: MSE loss)
  - Generalized models with link function, typically for exponential family
- Bayesian inference:
  - Likelihood, prior, Bayes theorem, posterior distribution
- Divergence measures between probability distributions, e.g.:
  - $f$ -divergences: e.g. Kullback-Leibler
  - Integral probability metrics: e.g. maximum mean discrepancy (MMD)

## Divergence measures between probability distributions

- Goal: compare two probability distributions,  $P$  and  $Q$ , defined on the same space  $\mathcal{X}$
- Two settings: compute a divergence measure  $D(P, Q)$  assuming distributions are defined by
  - ➊ Probability densities  $p(\mathbf{x})$  and  $q(\mathbf{x})$ ,  $\mathbf{x} \in \mathcal{X}$
  - ➋ Samples from the distributions

$$X = \{\mathbf{x}_1, \dots, \mathbf{x}_N\}, \text{ where } \mathbf{x}_i \sim P$$
$$X' = \{\mathbf{x}'_1, \dots, \mathbf{x}'_M\}, \text{ where } \mathbf{x}'_j \sim Q$$




## Divergence measures between probability distributions

- Goal: compare two probability distributions,  $P$  and  $Q$ , defined on the same space  $\mathcal{X}$
- Two settings: compute a divergence measure  $D(P, Q)$  assuming distributions are defined by

- ➊ Probability densities  $p(\mathbf{x})$  and  $q(\mathbf{x})$ ,  $\mathbf{x} \in \mathcal{X}$
- ➋ Samples from the distributions

$$X = \{\mathbf{x}_1, \dots, \mathbf{x}_N\}, \text{ where } \mathbf{x}_i \sim P$$
$$X' = \{\mathbf{x}'_1, \dots, \mathbf{x}'_M\}, \text{ where } \mathbf{x}'_j \sim Q$$


- Two main ways to compute the divergence between a pair of distributions:
  - ➊ In terms of their ratio:  $P/Q$
  - ➋ In terms of their difference:  $P - Q$



## Convex and concave functions

A real-valued function  $f : \mathcal{X} \rightarrow \mathbb{R}$  is<sup>a</sup> **convex** if for all  $\mathbf{x}_1, \mathbf{x}_2 \in \mathcal{X}$  and for all  $0 \leq t \leq 1$ :

$$f(t\mathbf{x}_1 + (1-t)\mathbf{x}_2) \leq tf(\mathbf{x}_1) + (1-t)f(\mathbf{x}_2)$$




$$f(x) = x \log(x)$$

<sup>a</sup>Assume  $\mathcal{X}$  is a convex (sub)set, e.g.  $\mathcal{X} = \mathbb{R}$ ,  $\mathcal{X}$  is an interval in  $\mathbb{R}$ ,  $\mathcal{X} = \mathbb{R}^2$ , etc.

## Convex and concave functions

A real-valued function  $f : \mathcal{X} \rightarrow \mathbb{R}$  is<sup>a</sup> **convex** if for all  $\mathbf{x}_1, \mathbf{x}_2 \in \mathcal{X}$  and for all  $0 \leq t \leq 1$ :


$$f(t\mathbf{x}_1 + (1-t)\mathbf{x}_2) \leq tf(\mathbf{x}_1) + (1-t)f(\mathbf{x}_2)$$



$$f(x) = x \log(x)$$

A real-valued function  $f : \mathcal{X} \rightarrow \mathbb{R}$  is **concave** if for all  $\mathbf{x}_1, \mathbf{x}_2 \in \mathcal{X}$  and for all  $0 \leq t \leq 1$ :

$$f(t\mathbf{x}_1 + (1-t)\mathbf{x}_2) \geq tf(\mathbf{x}_1) + (1-t)f(\mathbf{x}_2)$$



$$f(x) = \log(x)$$

If  $f$  is convex, then  $-f$  is concave

<sup>a</sup>Assume  $\mathcal{X}$  is a convex (sub)set, e.g.  $\mathcal{X} = \mathbb{R}$ ,  $\mathcal{X}$  is an interval in  $\mathbb{R}$ ,  $\mathcal{X} = \mathbb{R}^2$ , etc.

## *f*-divergence

### *f*-divergence

*f*-divergence between two probability distributions  $P$  and  $Q$  is defined via the density ratio  $r(\mathbf{x}) = \frac{p(\mathbf{x})}{q(\mathbf{x})}$

$$D_f(p \parallel q) = \int q(\mathbf{x}) f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) d\mathbf{x},$$

where  $f : \mathbb{R}_+ \rightarrow \mathbb{R}$  is a convex function, and  $f(1) = 0$

Special attention needed such that the ratio  $\frac{p(\mathbf{x})}{q(\mathbf{x})}$  and  $f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right)$  are defined

## *f*-divergence

*f*-divergence between two probability distributions  $P$  and  $Q$  is defined via the density ratio  $r(\mathbf{x}) = \frac{p(\mathbf{x})}{q(\mathbf{x})}$

$$D_f(p \parallel q) = \int q(\mathbf{x}) f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) d\mathbf{x},$$

where  $f : \mathbb{R}_+ \rightarrow \mathbb{R}$  is a convex function, and  $f(1) = 0$

Special attention needed such that the ratio  $\frac{p(\mathbf{x})}{q(\mathbf{x})}$  and  $f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right)$  are defined

Important special cases of the *f*-divergence

- Kullback-Leibler divergence:  $f(r) = r \log(r)$
- Alpha divergence:  $f(r) = \frac{4}{1-\alpha^2}(1 - r^{(1+\alpha)/2})$ ,  $\alpha \neq \pm 1$
- Hellinger distance:  $f(r) = (\sqrt{r} - 1)^2$
- Chi-squared distance:  $f(r) = (r - 1)^2$

## Jensen's inequalities

### Jensen's inequality for concave functions

If  $x$  is a random variable with probability distribution  $P$  and  $f$  is a concave function, then

$$f(\mathbb{E}_{p(x)}[x]) \geq \mathbb{E}_{p(x)}[f(x)],$$

where  $\mathbb{E}_{p(x)}[\cdot]$  is the expectation w.r.t. probability density  $p(x)$




Figure 17.4 from (Prince, 2023)  
Note:  $y$  has the role of  $x$

## Jensen's inequalities

### Jensen's inequality for concave functions

If  $\mathbf{x}$  is a random variable with probability distribution  $P$  and  $f$  is a concave function, then

$$f(\mathbb{E}_{p(\mathbf{x})}[\mathbf{x}]) \geq \mathbb{E}_{p(\mathbf{x})}[f(\mathbf{x})],$$

where  $\mathbb{E}_{p(\mathbf{x})}[\cdot]$  is the expectation w.r.t. probability density  $p(\mathbf{x})$

### Jensen's inequality for convex functions

If  $\mathbf{x}$  is a random variable with probability distribution  $P$  and  $f$  is a convex function, then

$$f(\mathbb{E}_{p(\mathbf{x})}[\mathbf{x}]) \leq \mathbb{E}_{p(\mathbf{x})}[f(\mathbf{x})]$$




Figure 17.4 from (Prince, 2023)  
Note:  $y$  has the role of  $\mathbf{x}$

## $f$ -divergence: properties

- $f$ -divergence can be written as

$$D_f(p \parallel q) = \int q(\mathbf{x}) f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) d\mathbf{x} = \mathbb{E}_{q(\mathbf{x})} \left[ f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) \right]$$

## $f$ -divergence: properties

- $f$ -divergence can be written as

$$D_f(p \parallel q) = \int q(\mathbf{x}) f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) d\mathbf{x} = \mathbb{E}_{q(\mathbf{x})} \left[ f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) \right]$$

- Jensen's inequality for convex functions gives

$$\mathbb{E}_{q(\mathbf{x})} \left[ f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) \right] \geq f\left(\mathbb{E}_{q(\mathbf{x})} \left[ \frac{p(\mathbf{x})}{q(\mathbf{x})} \right]\right) = f\left(\int q(\mathbf{x}) \frac{p(\mathbf{x})}{q(\mathbf{x})} d\mathbf{x}\right) = f\left(\int p(\mathbf{x}) d\mathbf{x}\right) = f(1) = 0$$

## *f*-divergence: properties

- *f*-divergence can be written as

$$D_f(p \parallel q) = \int q(\mathbf{x}) f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) d\mathbf{x} = \mathbb{E}_{q(\mathbf{x})} \left[ f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) \right]$$

- Jensen's inequality for convex functions gives

$$\mathbb{E}_{q(\mathbf{x})} \left[ f\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right) \right] \geq f\left(\mathbb{E}_{q(\mathbf{x})} \left[ \frac{p(\mathbf{x})}{q(\mathbf{x})} \right]\right) = f\left(\int q(\mathbf{x}) \frac{p(\mathbf{x})}{q(\mathbf{x})} d\mathbf{x}\right) = f\left(\int p(\mathbf{x}) d\mathbf{x}\right) = f(1) = 0$$

- Thus, *f*-divergence satisfies

- $D_f(p \parallel q) \geq 0$
- $D_f(p \parallel p) = 0$

- *f*-divergence is not a valid distance measure because

- it is not generally symmetric
- it does not satisfy triangle inequality

## Kullback-Leibler (KL) divergence

### Kullback-Leibler divergence

The Kullback-Leibler divergence between two probability distributions  $P$  and  $Q$  (divergence of  $P$  from  $Q$ ) is defined as

$$\begin{aligned} D_{\text{KL}}(p \parallel q) &= \int p(\mathbf{x}) \log \left( \frac{p(\mathbf{x})}{q(\mathbf{x})} \right) d\mathbf{x} \\ &= \mathbb{E}_{p(\mathbf{x})} \left[ \log \left( \frac{p(\mathbf{x})}{q(\mathbf{x})} \right) \right]. \end{aligned}$$

In other words, the KL divergence is the  $f$ -divergence with  $f(r) = r \log(r)$ .

- KL divergence satisfies
  - ①  $D_{\text{KL}}(p \parallel q) \geq 0$  (since KL is an  $f$ -divergence)
  - ②  $D_{\text{KL}}(p \parallel q) = 0$  iff  $p = q$  for all  $\mathbf{x}$
- KL divergence is not symmetric, i.e., generally  $D_{\text{KL}}(p \parallel q) \neq D_{\text{KL}}(q \parallel p)$

## KL divergence for independent random variables

For probability distributions of  $D$ -dimensional random variables where dimensions are independent,

$$q(\mathbf{x}) = \prod_{i=1}^D q_i(x_i) \quad \text{and} \quad p(\mathbf{x}) = \prod_{i=1}^D p_i(x_i),$$

the KL factorizes across dimensions

$$\begin{aligned} D_{\text{KL}}(p \parallel q) &= \mathbb{E}_{p(\mathbf{x})} \left[ \log \left( \frac{p(\mathbf{x})}{q(\mathbf{x})} \right) \right] = \mathbb{E}_{p(\mathbf{x})} \left[ \log \left( \frac{\prod_{i=1}^D p(x_i)}{\prod_{i=1}^D q(x_i)} \right) \right] = \mathbb{E}_{p(\mathbf{x})} \left[ \log \left( \prod_{i=1}^D \frac{p(x_i)}{q(x_i)} \right) \right] \\ &= \mathbb{E}_{p(\mathbf{x})} \left[ \sum_{i=1}^D \log \left( \frac{p(x_i)}{q(x_i)} \right) \right] = \sum_{i=1}^D \mathbb{E}_{p(\mathbf{x})} \left[ \log \left( \frac{p(x_i)}{q(x_i)} \right) \right] \\ &= \sum_{i=1}^D \mathbb{E}_{p(x_i)} \left[ \log \left( \frac{p(x_i)}{q(x_i)} \right) \right] \\ &= \sum_{i=1}^D D_{\text{KL}}(p_i \parallel q_i), \end{aligned}$$

## KL divergence: chain rule

Chain rule for probability distributions:  $p(\mathbf{x}) = p(x_1)p(x_2 \mid x_1) \dots p(x_D \mid x_1, \dots, x_{D-1})$

KL divergence satisfies a natural chain rule

$$\begin{aligned} D_{\text{KL}}(p(x_1, x_2) \parallel q(x_1, x_2)) &= \iint p(x_1, x_2) \log \left( \frac{p(x_1, x_2)}{q(x_1, x_2)} \right) dx_1 dx_2 \\ &= \iint p(x_1) p(x_2 \mid x_1) \left[ \log \left( \frac{p(x_1)}{q(x_1)} \right) + \log \left( \frac{p(x_2 \mid x_1)}{q(x_2 \mid x_1)} \right) \right] dx_1 dx_2 \\ &= D_{\text{KL}}(p(x_1) \parallel q(x_1)) + \mathbb{E}_{p(x_1)} [D_{\text{KL}}(p(x_2 \mid x_1) \parallel q(x_2 \mid x_1))] \end{aligned}$$

## KL divergence: two Gaussian distributions

The KL divergence between two univariate Gaussian distributions

$$D_{\text{KL}}(\mathcal{N}(x | \mu_1, \sigma_1^2) || \mathcal{N}(x | \mu_2, \sigma_2^2)) = \log\left(\frac{\sigma_2}{\sigma_1}\right) + \frac{\sigma_1^2 + (\mu_1 - \mu_2)^2}{2\sigma_2^2} - \frac{1}{2}$$

## KL divergence: two Gaussian distributions

The KL divergence between two univariate Gaussian distributions

$$D_{\text{KL}}(\mathcal{N}(x | \mu_1, \sigma_1^2) || \mathcal{N}(x | \mu_2, \sigma_2^2)) = \log\left(\frac{\sigma_2}{\sigma_1}\right) + \frac{\sigma_1^2 + (\mu_1 - \mu_2)^2}{2\sigma_2^2} - \frac{1}{2}$$

The KL divergence between two multivariate Gaussian distributions

$$\begin{aligned} D_{\text{KL}}(\mathcal{N}(\boldsymbol{x} | \boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1) || \mathcal{N}(\boldsymbol{x} | \boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2)) &= \frac{1}{2} \left[ \text{tr}(\boldsymbol{\Sigma}_2^{-1} \boldsymbol{\Sigma}_1) + (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2)^\top \boldsymbol{\Sigma}_2^{-1} (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2) \right. \\ &\quad \left. - D + \log\left(\frac{\det(\boldsymbol{\Sigma}_2)}{\det(\boldsymbol{\Sigma}_1)}\right) \right] \end{aligned}$$

## KL divergence: two Gaussian distributions

The KL divergence between two univariate Gaussian distributions

$$D_{\text{KL}}(\mathcal{N}(x | \mu_1, \sigma_1^2) || \mathcal{N}(x | \mu_2, \sigma_2^2)) = \log\left(\frac{\sigma_2}{\sigma_1}\right) + \frac{\sigma_1^2 + (\mu_1 - \mu_2)^2}{2\sigma_2^2} - \frac{1}{2}$$

The KL divergence between two multivariate Gaussian distributions

$$\begin{aligned} D_{\text{KL}}(\mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1) || \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2)) &= \frac{1}{2} \left[ \text{tr}(\boldsymbol{\Sigma}_2^{-1} \boldsymbol{\Sigma}_1) + (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2)^\top \boldsymbol{\Sigma}_2^{-1} (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2) \right. \\ &\quad \left. - D + \log\left(\frac{\det(\boldsymbol{\Sigma}_2)}{\det(\boldsymbol{\Sigma}_1)}\right) \right] \end{aligned}$$

If  $\boldsymbol{\Sigma}_1 = \text{diag}(\sigma_{11}^2, \dots, \sigma_{1D}^2)$  and  $\boldsymbol{\Sigma}_2 = \text{diag}(\sigma_{21}^2, \dots, \sigma_{2D}^2)$ , then due to the independence property

$$D_{\text{KL}}(\mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1) || \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2)) = \sum_{i=1}^D D_{\text{KL}}(\mathcal{N}(x_i | \mu_{1i}, \sigma_{1i}^2) || \mathcal{N}(x_i | \mu_{2i}, \sigma_{2i}^2))$$

## KL divergence: two Gaussian distributions

The KL divergence between two univariate Gaussian distributions

$$D_{\text{KL}}(\mathcal{N}(x | \mu_1, \sigma_1^2) || \mathcal{N}(x | \mu_2, \sigma_2^2)) = \log\left(\frac{\sigma_2}{\sigma_1}\right) + \frac{\sigma_1^2 + (\mu_1 - \mu_2)^2}{2\sigma_2^2} - \frac{1}{2}$$

The KL divergence between two multivariate Gaussian distributions

$$\begin{aligned} D_{\text{KL}}(\mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1) || \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2)) &= \frac{1}{2} \left[ \text{tr}(\boldsymbol{\Sigma}_2^{-1} \boldsymbol{\Sigma}_1) + (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2)^\top \boldsymbol{\Sigma}_2^{-1} (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2) \right. \\ &\quad \left. - D + \log\left(\frac{\det(\boldsymbol{\Sigma}_2)}{\det(\boldsymbol{\Sigma}_1)}\right) \right] \end{aligned}$$

If  $\boldsymbol{\Sigma}_1 = \text{diag}(\sigma_{11}^2, \dots, \sigma_{1D}^2)$  and  $\boldsymbol{\Sigma}_2 = \text{diag}(\sigma_{21}^2, \dots, \sigma_{2D}^2)$ , then due to the independence property

$$D_{\text{KL}}(\mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1) || \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2)) = \sum_{i=1}^D D_{\text{KL}}(\mathcal{N}(x_i | \mu_{1i}, \sigma_{1i}^2) || \mathcal{N}(x_i | \mu_{2i}, \sigma_{2i}^2))$$

These are useful results for developing deep generative models because

- Distributions are often assumed to be Gaussians
- Often  $\boldsymbol{\Sigma} = \text{diag}(\sigma_1^2, \dots, \sigma_D^2)$

KL divergence has closed-form solution for any two exponential family distributions from the same family

## KL divergence and maximum likelihood

Suppose  $p_{\mathcal{D}}$  is the empirical data distribution of data set  $\mathcal{D} = \{\mathbf{x}_1, \dots, \mathbf{x}_N\}$

$$p_{\mathcal{D}}(\mathbf{x}) = \frac{1}{N} \sum_{n=1}^N \delta(\mathbf{x} - \mathbf{x}_n),$$

where  $\delta(\mathbf{x})$  is the delta distribution

Suppose we want to find distribution  $q$  that is as close as possible to  $p_{\mathcal{D}}$

$$q^* = \arg \min_q D_{\text{KL}}(p_{\mathcal{D}} \parallel q)$$

## KL divergence and maximum likelihood

Suppose  $p_{\mathcal{D}}$  is the empirical data distribution of The objective function can be written as data set  $\mathcal{D} = \{\mathbf{x}_1, \dots, \mathbf{x}_N\}$

$$p_{\mathcal{D}}(\mathbf{x}) = \frac{1}{N} \sum_{n=1}^N \delta(\mathbf{x} - \mathbf{x}_n),$$

where  $\delta(\mathbf{x})$  is the delta distribution

Suppose we want to find distribution  $q$  that is as close as possible to  $p_{\mathcal{D}}$

$$q^* = \arg \min_q D_{\text{KL}}(p_{\mathcal{D}} \parallel q)$$

$$\begin{aligned} D_{\text{KL}}(p_{\mathcal{D}} \parallel q) &= \underbrace{\int p_{\mathcal{D}}(\mathbf{x}) \log p_{\mathcal{D}}(\mathbf{x}) d\mathbf{x} - \int p_{\mathcal{D}}(\mathbf{x}) \log q(\mathbf{x}) d\mathbf{x}}_{\text{constant } C} \\ &= C - \int \left[ \frac{1}{N} \sum_{n=1}^N \delta(\mathbf{x} - \mathbf{x}_n) \right] \log q(\mathbf{x}) d\mathbf{x} \\ &= C - \frac{1}{N} \sum_{n=1}^N \int \delta(\mathbf{x} - \mathbf{x}_n) \log q(\mathbf{x}) d\mathbf{x} \\ &= C - \frac{1}{N} \sum_{n=1}^N \log q(\mathbf{x}_n) \\ &= C - \frac{1}{N} \log \prod_{n=1}^N q(\mathbf{x}_n) \end{aligned}$$

Minimizing  $D_{\text{KL}}(p_{\mathcal{D}} \parallel q)$  maximizes the likelihood

## KL divergence: minimization

Given a true distribution  $P$ , minimize the KL divergence w.r.t. an approximate distribution  $Q$

Two optimization approaches due to the asymmetry of the KL divergence

- ① Forwards KL:  $q = \arg \min_q D_{\text{KL}}(p \parallel q)$ 
  - Results in mode covering, i.e., a wide (under-confident) distribution  $q$
- ② Reverse KL:  $q = \arg \min_q D_{\text{KL}}(q \parallel p)$ 
  - Results in mode seeking, i.e., a narrow (over-confident) distribution  $q$




Figure 5.1 from (Murphy, 2023)

## Forwards KL minimization for two Gaussians

Assume the true distribution is a 2-D correlated Gaussian  $p(\mathbf{x}) = \mathcal{N}(\mathbf{x} \mid \boldsymbol{\mu}, \boldsymbol{\Sigma}) = \mathcal{N}(\mathbf{x} \mid \boldsymbol{\mu}, \boldsymbol{\Lambda}^{-1})$

Assume that  $q(\mathbf{x})$  is a mean-field Gaussian  $q(\mathbf{x} \mid \mathbf{m}, \mathbf{V}) = \mathcal{N}(x_1 \mid m_1, v_1) \mathcal{N}(x_2 \mid m_2, v_2)$

## Forwards KL minimization for two Gaussians

Assume the true distribution is a 2-D correlated Gaussian  $p(\mathbf{x}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \boldsymbol{\Sigma}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \boldsymbol{\Lambda}^{-1})$


Assume that  $q(\mathbf{x})$  is a mean-field Gaussian  $q(\mathbf{x} | \mathbf{m}, \mathbf{V}) = \mathcal{N}(x_1 | m_1, v_1) \mathcal{N}(x_2 | m_2, v_2)$

It can be shown that

- Optimizing the forwards KL  $D_{\text{KL}}(p || q)$  w.r.t.  $q$  results in moment matching, where

$$q(\mathbf{x}) = N(x_1 | \mu_1, \Sigma_{11})N(x_2 | \mu_2, \Sigma_{22})$$

- This holds more generally for exponential family
- Forwards KL is called moment projection



(a)

Figure 5.2 a) from (Murphy, 2023)

## Reverse KL minimization for two Gaussians

Assume the true distribution is a 2-D correlated Gaussian  $p(\mathbf{x}) = \mathcal{N}(\mathbf{x} \mid \boldsymbol{\mu}, \boldsymbol{\Sigma}) = \mathcal{N}(\mathbf{x} \mid \boldsymbol{\mu}, \boldsymbol{\Lambda}^{-1})$

Assume that  $q(\mathbf{x})$  is a mean-field Gaussian  $q(\mathbf{x} \mid \mathbf{m}, \mathbf{V}) = \mathcal{N}(x_1 \mid m_1, v_1) \mathcal{N}(x_2 \mid m_2, v_2)$


## Reverse KL minimization for two Gaussians

Assume the true distribution is a 2-D correlated Gaussian  $p(\mathbf{x}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \boldsymbol{\Sigma}) = \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \boldsymbol{\Lambda}^{-1})$

Assume that  $q(\mathbf{x})$  is a mean-field Gaussian  $q(\mathbf{x} | \mathbf{m}, \mathbf{V}) = \mathcal{N}(x_1 | m_1, v_1) \mathcal{N}(x_2 | m_2, v_2)$

It can be shown that

- Optimizing the reverse KL  $D_{\text{KL}}(q || p)$  w.r.t.  $q$  results in
$$q(\mathbf{x}) = N(x_1 | \mu_1, \Lambda_{11})N(x_2 | \mu_2, \Lambda_{22})$$
- Reverse KL is called information projections
- Reverse KL is typically easier to optimize because expectations are w.r.t.  $q$  which we can choose



(b)

Figure 5.2 b) from (Murphy, 2023)

## Jensen-Shannon divergence

- Jensen-Shannon divergence is a symmetric variant of the KL

$$\text{JSD}(p, q) = \frac{1}{2}D_{\text{KL}}(p \parallel m) + \frac{1}{2}D_{\text{KL}}(q \parallel m) = \text{JSD}(q, p),$$

where  $m(\mathbf{x}) = \frac{1}{2}p(\mathbf{x}) + \frac{1}{2}q(\mathbf{x})$

- This divergence is important when training implicit generative models, such as generative adversarial networks (GANs)

## Integral probability metric (IPM)

- $f$ -divergences are defined in terms of density ratio  $P/Q$
- Many methods use the KL divergence as their objective function
- Divergence measures can also be defined in terms of  $P - Q$
- Integral probability metric is defined as

$$D_{\mathcal{F}}(P, Q) = \sup_{f \in \mathcal{F}} |\mathbb{E}_{p(\mathbf{x})}[f(\mathbf{x})] - \mathbb{E}_{q(\mathbf{x}')}[f(\mathbf{x}')]|,$$

where  $\mathcal{F}$  is a class of smooth functions

- Depending on the choice of  $\mathcal{F}$  we get different divergence measures
- This class of divergences is important when training implicit generative models, such as generative adversarial networks (GANs)

## Total variation distance

- The total variation (TV) distance between two probability distributions  $P$  and  $Q$  for a continuous random variable  $x$

$$D_{\text{TV}} = \frac{1}{2} \int |p(x) - q(x)| dx$$

- TV satisfies the properties of a distance: symmetric, positive, definite, triangle inequality
- TV is the (only) divergence that is both  $f$ -divergence (with  $f(r) = \frac{1}{2}|r - 1|$ ) and IPM

## Monte Carlo integration

Monte Carlo methods are a stochastic approach to solve numerical integration problems

- A random variable  $\boldsymbol{x} \in \mathcal{X} = \mathbb{R}^n$  with probability density  $p(\boldsymbol{x})$ , and a function  $f : \mathbb{R}^n \rightarrow \mathbb{R}^m$
- Interested in computing the expected value of function  $f(\boldsymbol{x})$

$$\mathbb{E}[f(\boldsymbol{x})] = \int f(\boldsymbol{x})p(\boldsymbol{x})d\boldsymbol{x}$$

## Monte Carlo integration

Monte Carlo methods are a stochastic approach to solve numerical integration problems

- A random variable  $\boldsymbol{x} \in \mathcal{X} = \mathbb{R}^n$  with probability density  $p(\boldsymbol{x})$ , and a function  $f : \mathbb{R}^n \rightarrow \mathbb{R}^m$
- Interested in computing the expected value of function  $f(\boldsymbol{x})$

$$\mathbb{E}[f(\boldsymbol{x})] = \int f(\boldsymbol{x})p(\boldsymbol{x})d\boldsymbol{x}$$

### Monte Carlo integration

Monte Carlo integration estimate of  $\mathbb{E}[f(\boldsymbol{x})]$  is

$$\mathbb{E}[f(\boldsymbol{x})] \approx \bar{f}_N = \frac{1}{N} \sum_{s=1}^N f(\boldsymbol{x}_s), \quad \text{where } \boldsymbol{x}_s \stackrel{\text{i.i.d.}}{\sim} p(\boldsymbol{x})$$

and  $N$  is the number of samples

- By design, function  $f(\boldsymbol{x})$  is only evaluated at points  $\boldsymbol{x}$  that have non-negligible probability

## Monte Carlo integration: example

- The area of a circle with radius  $r$  is  $A = \pi r^2$
- Alternatively,  $A$  equals

$$A = \int_{-r}^r \int_{-r}^r \mathbb{I}(x^2 + y^2 \leq r^2) dx dy$$

where  $\mathbb{I}(\cdot)$  is the indicator function (value is 1 inside the circle, 0 outside)

## Monte Carlo integration: example

- The area of a circle with radius  $r$  is  $A = \pi r^2$
- Alternatively,  $A$  equals

$$A = \int_{-r}^r \int_{-r}^r \mathbb{I}(x^2 + y^2 \leq r^2) dx dy$$

where  $\mathbb{I}(\cdot)$  is the indicator function (value is 1 inside the circle, 0 outside)

- Define e.g.  $p(x, y) = p(x)p(y)$ , where  $p(x)$  and  $p(y)$  are uniform over  $[-r, r]$
- Monte Carlo estimate of  $A$

$$\begin{aligned} A &= (2r)(2r) \int \int \mathbb{I}(x^2 + y^2 \leq r^2) p(x)p(y) dx dy \\ &\approx 4r^2 \frac{1}{N} \sum_{s=1}^N \mathbb{I}(x_s^2 + y_s^2 \leq r^2), \quad x_s, y_s \sim p(x, y) \end{aligned}$$

## Monte Carlo integration: example

- The area of a circle with radius  $r$  is  $A = \pi r^2$
- Alternatively,  $A$  equals

$$A = \int_{-r}^r \int_{-r}^r \mathbb{I}(x^2 + y^2 \leq r^2) dx dy$$

where  $\mathbb{I}(\cdot)$  is the indicator function (value is 1 inside the circle, 0 outside)

- Define e.g.  $p(x, y) = p(x)p(y)$ , where  $p(x)$  and  $p(y)$  are uniform over  $[-r, r]$
- Monte Carlo estimate of  $A$

$$\begin{aligned} A &= (2r)(2r) \int \int \mathbb{I}(x^2 + y^2 \leq r^2) p(x)p(y) dx dy \\ &\approx 4r^2 \frac{1}{N} \sum_{s=1}^N \mathbb{I}(x_s^2 + y_s^2 \leq r^2), \quad x_s, y_s \sim p(x, y) \end{aligned}$$

- An estimate of  $\pi$  is then  $\hat{\pi} = \hat{A}/(r^2)$




Figure 11.1 from (Murphy, 2023)

## Monte Carlo integration: accuracy

Monte Carlo estimate  $\bar{f}_N$  of  $\mathbb{E}[f(\mathbf{x})]$

$$\bar{f}_N = \frac{1}{N} \sum_{s=1}^N f(\mathbf{x}_s), \quad \text{where } \mathbf{x}_s \stackrel{\text{i.i.d.}}{\sim} p(\mathbf{x})$$

Assuming the true mean  $\mu = \mathbb{E}[f(\mathbf{x})]$  exists, by the law of large numbers

$$\bar{f}_N \rightarrow \mu \quad \text{when} \quad N \rightarrow \infty$$

## Monte Carlo integration: accuracy

Monte Carlo estimate  $\bar{f}_N$  of  $\mathbb{E}[f(\mathbf{x})]$

$$\bar{f}_N = \frac{1}{N} \sum_{s=1}^N f(\mathbf{x}_s), \quad \text{where } \mathbf{x}_s \stackrel{\text{i.i.d.}}{\sim} p(\mathbf{x})$$

Assuming the true mean  $\mu = \mathbb{E}[f(\mathbf{x})]$  exists, by the law of large numbers

$$\bar{f}_N \rightarrow \mu \quad \text{when } N \rightarrow \infty$$

Assuming a scalar-valued function  $f$  and finite variance  $\sigma^2 = \mathbb{V}[f(\mathbf{x})] = \mathbb{E}[(f(\mathbf{x}) - \mu)^2] < \infty$ , by the central limit theorem

$$(\bar{f}_N - \mu) \rightarrow \mathcal{N}\left(0, \frac{\sigma^2}{N}\right)$$

## Monte Carlo integration: accuracy

Monte Carlo estimate  $\bar{f}_N$  of  $\mathbb{E}[f(\mathbf{x})]$

$$\bar{f}_N = \frac{1}{N} \sum_{s=1}^N f(\mathbf{x}_s), \quad \text{where } \mathbf{x}_s \stackrel{\text{i.i.d.}}{\sim} p(\mathbf{x})$$

Assuming the true mean  $\mu = \mathbb{E}[f(\mathbf{x})]$  exists, by the law of large numbers

$$\bar{f}_N \rightarrow \mu \quad \text{when} \quad N \rightarrow \infty$$

Assuming a scalar-valued function  $f$  and finite variance  $\sigma^2 = \mathbb{V}[f(\mathbf{x})] = \mathbb{E}[(f(\mathbf{x}) - \mu)^2] < \infty$ , by the central limit theorem


$$(\bar{f}_N - \mu) \xrightarrow{\text{d}} \mathcal{N}\left(0, \frac{\sigma^2}{N}\right)$$

Variance  $\sigma^2$  can be estimated

$$\hat{\sigma}^2 = \frac{1}{N} \sum_{s=1}^N (f(\mathbf{x}_s) - \bar{f}_N)^2$$

Thus, for large  $N$

$$P\left(\bar{f}_N - 1.96 \frac{\hat{\sigma}}{\sqrt{N}} \leq \mu \leq \bar{f}_N + 1.96 \frac{\hat{\sigma}}{\sqrt{N}}\right) \approx 0.95$$



An example of  $\pi$  estimates and empirical standard errors for varying  $N$

## Monte Carlo integration: accuracy

To summarize, accuracy of Monte Carlo integration

- is independent of dimensionality of  $x$
- increases with increasing sample size  $N$

## Importance sampling

- Consider again using Monte Carlo method to approximate integrals of the form

$$\mathbb{E}[f(\mathbf{x})] = \int f(\mathbf{x})\pi(\mathbf{x})d\mathbf{x},$$

where  $f(\mathbf{x})$  is the target function and  $\pi(\mathbf{x})$  is now the target distribution

- If  $\pi(\mathbf{x})$  is difficult to sample, we can instead sample from a proposal distribution  $q(\mathbf{x})$
- We need to adjust the Monte Carlo method for this inaccuracy by associating weights with each sample

$$\mathbb{E}[f(\mathbf{x})] \approx \frac{1}{N} \sum_{s=1}^N W_n f(\mathbf{x}_n)$$

- Two different importance sampling variants:
  - Direct importance sampling: assume that, albeit difficult to sample, we can still evaluate the normalized target distribution  $\pi(\mathbf{x})$
  - Self-normalized importance sampling: we can only evaluate unnormalized target distribution  $\tilde{\pi}(\mathbf{x})$

## Direct importance sampling

- Write the target integral as

$$\mathbb{E}[f(\mathbf{x})] = \int f(\mathbf{x})\pi(\mathbf{x})d\mathbf{x} = \int f(\mathbf{x})\frac{\pi(\mathbf{x})}{q(\mathbf{x})}q(\mathbf{x})d\mathbf{x}$$

assuming  $q(\mathbf{x}) > 0$  whenever  $\pi(\mathbf{x}) > 0$ , i.e.,  $\text{sup } \pi \subseteq \text{sup } q$

## Direct importance sampling

- Write the target integral as

$$\mathbb{E}[f(\mathbf{x})] = \int f(\mathbf{x})\pi(\mathbf{x})d\mathbf{x} = \int f(\mathbf{x})\frac{\pi(\mathbf{x})}{q(\mathbf{x})}q(\mathbf{x})d\mathbf{x}$$

assuming  $q(\mathbf{x}) > 0$  whenever  $\pi(\mathbf{x}) > 0$ , i.e.,  $\text{sup } \pi \subseteq \text{sup } q$

### Direct importance sampling

Direct importance sampling estimate of  $\mathbb{E}[f(\mathbf{x})]$  is

$$\mathbb{E}[f(\mathbf{x})] \approx \frac{1}{N} \sum_{s=1}^N \frac{\pi(\mathbf{x}_s)}{q(\mathbf{x}_s)} f(\mathbf{x}_s) = \frac{1}{N} \sum_{s=1}^N \tilde{w}_s f(\mathbf{x}_s), \quad \text{where } \mathbf{x}_s \stackrel{\text{i.i.d.}}{\sim} q(\mathbf{x})$$

and  $\tilde{w}_s = \frac{\pi(\mathbf{x}_s)}{q(\mathbf{x}_s)}$  are the importance weights

## Direct importance sampling: proposal distribution

Performance of the importance sampling depends crucially on the quality of  $q(\mathbf{x})$

Ideally, the proposal distribution should

- cover the target distribution,  
 $\pi(\mathbf{x}) > 0 \Rightarrow q(\mathbf{x}) > 0$
- be similar with  $\pi(\mathbf{x})$
- take into account properties of  $f$

One good strategy is to learn a proposal




Figure 11.6 from Murphy (2023) illustrating the proposal  $q(\mathbf{x})$

## Self-normalized importance sampling

- It is often much easier to evaluate the unnormalized distribution  $\tilde{\pi}(\mathbf{x}) = Z\pi(\mathbf{x})$ , where  $Z = \int \tilde{\pi}(\mathbf{x})d\mathbf{x}$

## Self-normalized importance sampling

- It is often much easier to evaluate the unnormalized distribution  $\tilde{\pi}(\mathbf{x}) = Z\pi(\mathbf{x})$ , where  $Z = \int \tilde{\pi}(\mathbf{x})d\mathbf{x}$

### Self-normalized importance sampling

Self-normalized importance sampling estimate of  $\mathbb{E}[f(\mathbf{x})]$  is

$$\begin{aligned}\mathbb{E}[f(\mathbf{x})] &= \int f(\mathbf{x})\pi(\mathbf{x})d\mathbf{x} = \int f(\mathbf{x})\frac{1}{Z}\tilde{\pi}(\mathbf{x})d\mathbf{x} = \frac{\int f(\mathbf{x})\tilde{\pi}(\mathbf{x})d\mathbf{x}}{\int \tilde{\pi}(\mathbf{x})d\mathbf{x}} = \frac{\int \left[\frac{\tilde{\pi}(\mathbf{x})}{q(\mathbf{x})}f(\mathbf{x})\right]q(\mathbf{x})d\mathbf{x}}{\int \left[\frac{\tilde{\pi}(\mathbf{x})}{q(\mathbf{x})}\right]q(\mathbf{x})d\mathbf{x}} \\ &\approx \frac{\frac{1}{N} \sum_{s=1}^N \tilde{w}_s f(\mathbf{x}_s)}{\frac{1}{N} \sum_{s=1}^N \tilde{w}_s}, \quad \text{where } \mathbf{x}_s \stackrel{\text{i.i.d.}}{\sim} q(\mathbf{x})\end{aligned}$$

$\tilde{w}_s = \frac{\tilde{\pi}(\mathbf{x}_s)}{q(\mathbf{x}_s)}$  are the unnormalized importance weights, and assuming  $\sup \tilde{\pi} \subseteq \sup q$

## Multilayer perceptron (MLP)

- Multilayer perceptron (MLP)  $\mathbf{f} : \mathbb{R}^D \rightarrow \mathbb{R}^C$  consists of  $L$  layers of linear computations and element-wise non-linearities  $\varphi$  (here  $L = 2$ )

$$\begin{aligned}\mathbf{y} &= \mathbf{f}(\mathbf{x}; \boldsymbol{\theta}) \\ &= \varphi(\mathbf{W}_2 \varphi(\mathbf{W}_1 \mathbf{x} + \mathbf{b}_1) + \mathbf{b}_2)\end{aligned}$$

where  $\boldsymbol{\theta} = (\mathbf{W}_1, \dots, \mathbf{W}_L, \mathbf{b}_1, \dots, \mathbf{b}_L)$  and

$$\mathbf{W}_1 \in \mathbb{R}^{D \times K_1}$$

$$\mathbf{W}_l \in \mathbb{R}^{K_{l-1} \times K_l}$$

$$\mathbf{W}_L \in \mathbb{R}^{K_{L-1} \times C}$$




Figure 16.10 from (Murphy, 2023)

## MLPs as likelihood models

Throughout this course we will use neural nets to parameterize probabilistic models

Example: regression with homoscedastic Gaussian noise

- Univariate response variable  $y \in \mathbb{R}$  with MLP

$$f : \mathbb{R}^D \rightarrow \mathbb{R}$$

$$p_{\boldsymbol{\theta}}(y | \mathbf{x}) = \mathcal{N}(y | f(\mathbf{x}; \boldsymbol{\theta}), \sigma_{\text{noise}}^2),$$

where  $f(\mathbf{x}; \boldsymbol{\theta}) = \mathbb{E}(y | \mathbf{x})$

## MLPs as likelihood models

Throughout this course we will use neural nets to parameterize probabilistic models

Example: regression with homoscedastic Gaussian noise

- Univariate response variable  $y \in \mathbb{R}$  with MLP

$$f : \mathbb{R}^D \rightarrow \mathbb{R}$$

$$p_{\theta}(y | \mathbf{x}) = \mathcal{N}(y | f(\mathbf{x}; \theta), \sigma_{\text{noise}}^2),$$

where  $f(\mathbf{x}; \theta) = \mathbb{E}(y | \mathbf{x})$

- Multivariate response variable  $\mathbf{y} \in \mathbb{R}^D$  with MLP

$$f : \mathbb{R}^D \rightarrow \mathbb{R}^C$$

$$p_{\theta}(\mathbf{y} | \mathbf{x}) = \mathcal{N}(\mathbf{y} | \mathbf{f}(\mathbf{x}; \theta), \Sigma),$$

where  $\mathbf{f}(\mathbf{x}; \theta) = \mathbb{E}(\mathbf{y} | \mathbf{x})$

## MLPs as likelihood models

Throughout this course we will use neural nets to parameterize probabilistic models

Example: regression with homoscedastic Gaussian noise

- Univariate response variable  $y \in \mathbb{R}$  with MLP  
 $f : \mathbb{R}^D \rightarrow \mathbb{R}$

$$p_{\theta}(y | \mathbf{x}) = \mathcal{N}(y | f(\mathbf{x}; \theta), \sigma_{\text{noise}}^2),$$

where  $f(\mathbf{x}; \theta) = \mathbb{E}(y | \mathbf{x})$

- Multivariate response variable  $\mathbf{y} \in \mathbb{R}^D$  with MLP  
 $f : \mathbb{R}^D \rightarrow \mathbb{R}^C$

$$p_{\theta}(\mathbf{y} | \mathbf{x}) = \mathcal{N}(\mathbf{y} | \mathbf{f}(\mathbf{x}; \theta), \Sigma),$$

where  $\mathbf{f}(\mathbf{x}; \theta) = \mathbb{E}(\mathbf{y} | \mathbf{x})$

Example: multiclass classification  $y \in \{1, \dots, C\}$

$$p_{\theta}(y | \mathbf{x}) = \text{Cat}(y | \text{softmax}(\mathbf{f}(\mathbf{x}; \theta))),$$

where

$$\text{softmax}(\mathbf{a}) = \left( \frac{e^{a_1}}{\sum_{c=1}^C e^{a_c}}, \dots, \frac{e^{a_C}}{\sum_{c=1}^C e^{a_c}} \right)$$

## MLPs as likelihood models

Throughout this course we will use neural nets to parameterize probabilistic models

Example: regression with homoscedastic Gaussian noise

- Univariate response variable  $y \in \mathbb{R}$  with MLP  
 $f : \mathbb{R}^D \rightarrow \mathbb{R}$

$$p_{\theta}(y | \mathbf{x}) = \mathcal{N}(y | f(\mathbf{x}; \theta), \sigma_{\text{noise}}^2),$$

where  $f(\mathbf{x}; \theta) = \mathbb{E}(y | \mathbf{x})$

- Multivariate response variable  $\mathbf{y} \in \mathbb{R}^D$  with MLP  
 $f : \mathbb{R}^D \rightarrow \mathbb{R}^C$

$$p_{\theta}(\mathbf{y} | \mathbf{x}) = \mathcal{N}(\mathbf{y} | \mathbf{f}(\mathbf{x}; \theta), \Sigma),$$

where  $\mathbf{f}(\mathbf{x}; \theta) = \mathbb{E}(\mathbf{y} | \mathbf{x})$

Example: multiclass classification  $y \in \{1, \dots, C\}$

$$p_{\theta}(y | \mathbf{x}) = \text{Cat}(y | \text{softmax}(\mathbf{f}(\mathbf{x}; \theta))),$$

where

$$\text{softmax}(\mathbf{a}) = \left( \frac{e^{a_1}}{\sum_{c=1}^C e^{a_c}}, \dots, \frac{e^{a_C}}{\sum_{c=1}^C e^{a_c}} \right)$$

We use interchangeably  $p_{\theta}(y | \mathbf{x}) = p(y | \mathbf{x}, \theta)$

All neural network architectures can be converted to likelihood models with appropriate link functions

If neural network parameters  $\theta$  are random variables, then these are called Bayesian neural networks

## MLP for heteroscedastic regression

- Heteroscedastic nonlinear regression = nonlinear regression with input-dependent noise variance
- Assume univariate response variable  $y \in \mathbb{R}$  with Gaussian noise
- MLP has two outputs ( $C = 2$ ) which approximate  $f_\mu(\mathbf{x}) \approx \mathbb{E}[y|\mathbf{x}, \theta]$  and  $f_\sigma(\mathbf{x}) \approx \mathbb{V}[y|\mathbf{x}, \theta]$  such that

$$p_{\theta}(y | \mathbf{x}) = \mathcal{N}(y | \mathbf{w}_\mu^\top f(\mathbf{x}; \mathbf{w}_{\text{shared}}), \sigma_+(\mathbf{w}_\sigma^\top f(\mathbf{x}; \mathbf{w}_{\text{shared}}))),$$

where e.g.  $\sigma_+(a) = \log(1 + e^a)$




Figure 16.11 from (Murphy, 2023)

## References

- Murphy K, Probabilistic Machine Learning: Advanced Topics, 2023.
- Prince SJD, Understanding Deep Learning, The MIT Press, 2023.

# CS-E4891 Deep Generative Models

## Lecture 2: Latent variable models, variational inference and variational autoencoders

Harri Lähdesmäki

Department of Computer Science  
Aalto University

March 24, 2025

## Outline

- Latent variable models (Section 6.2 from (Murphy, 2023))
- Linear latent variable models (Sec. 28.3)
- Deep latent variable models (Sec. 21.1)
- Variational inference: amortized, stochastic, gradient-based, reparameterized (Sec. 10.1-10.2)
- Variational autoencoders (Sec. 21)
- Reading: parts of Sections 6.2, 10.1-10.2, 21.1, 28.3 from (Murphy, 2023)

# Different types of latent variable models

## Latent variable model

A latent variable model (LVM) is a probabilistic model that contains variables that are always unobserved

Latent variables are random variable

Latent variables can also represent model parameters

Three types of latent variable models

- ① Global latent variables
- ② Local latent variables
- ③ Global and local latent variables

## Global latent variable models

- A model that contains global latent variables  $\theta$  that are shared across all  $N$  observations: e.g. model parameters
- E.g. the usual supervised learning setting

$$p(\mathbf{y}_{1:N}, \boldsymbol{\theta} | \mathbf{x}_{1:N}) = p(\boldsymbol{\theta}) \prod_{n=1}^N p(\mathbf{y}_n | \mathbf{x}_n, \boldsymbol{\theta})$$

where  $\mathbf{y}_{1:N}$  is a shorthand for  $\mathbf{y}_1, \dots, \mathbf{y}_N$

- In Bayesian setting, the goal is to obtain the posterior

$$p(\boldsymbol{\theta} | \mathbf{x}_{1:N}, \mathbf{y}_{1:N})$$

- In maximum likelihood setting, the goal is to maximize the likelihood  $\prod_{n=1}^N p(\mathbf{y}_n | \mathbf{x}_n, \boldsymbol{\theta})$




Figure 7.1a from (Murphy, 2023)

## Local latent variable models

- A model that contains local latent variables  $z_n$  ( $n \in \{1, \dots, N\}$ ) that are associated with individual observations  $x_n$
- Model parameters  $\theta = (\theta_z, \theta_x)$  are assumed to be deterministic or known
- The joint distribution typically factorizes

$$p(x_{1:N}, z_{1:N} | \theta) = \prod_{n=1}^N p(x_n | z_n, \theta_x) p(z_n | \theta_z)$$

- The goal is to obtain the posterior for each local latent

$$p(z_n | x_n, \theta)$$

- If parameters are not known, they can be treated as hyperparameters and optimized using e.g. the maximum likelihood




Figure 7.1b from (Murphy, 2023)

## Global and local latent variable models

- A model that contains both
  - global latent variables  $\theta = (\theta_z, \theta_x)$
  - local latent variables  $z_n$  ( $n \in \{1, \dots, N\}$ ), that are associated with individual observations  $x_n$
- The joint distribution typically factorizes

$$p(\mathbf{x}_{1:N}, \mathbf{z}_{1:N}, \boldsymbol{\theta}) = p(\boldsymbol{\theta}_z)p(\boldsymbol{\theta}_x) \prod_{n=1}^N p(\mathbf{x}_n | z_n, \boldsymbol{\theta}_x)p(z_n | \boldsymbol{\theta}_z)$$

- The goal is to obtain the posterior for unknowns

$$p(\mathbf{z}_{1:N}, \boldsymbol{\theta} | \mathbf{x}_{1:N})$$

- Benefits in considering  $\boldsymbol{\theta}$  as a random variable?




Figure 7.1c from (Murphy, 2023)

## Marginalization of latent variables

An indirect approach to define a probability distribution  $p(\mathbf{x} | \boldsymbol{\theta})$  via a joint distribution  $p(\mathbf{x}, \mathbf{z} | \boldsymbol{\theta})$

Target distribution  $p(\mathbf{x} | \boldsymbol{\theta})$  is obtained via marginalization

$$p(\mathbf{x} | \boldsymbol{\theta}) = \int p(\mathbf{x}, \mathbf{z} | \boldsymbol{\theta}) d\mathbf{z} = \int p(\mathbf{x} | \mathbf{z}, \boldsymbol{\theta}_x) p(\mathbf{z} | \boldsymbol{\theta}_z) d\mathbf{z}$$

## Marginalization of latent variables

An indirect approach to define a probability distribution  $p(\mathbf{x} | \boldsymbol{\theta})$  via a joint distribution  $p(\mathbf{x}, \mathbf{z} | \boldsymbol{\theta})$

Target distribution  $p(\mathbf{x} | \boldsymbol{\theta})$  is obtained via marginalization

$$p(\mathbf{x} | \boldsymbol{\theta}) = \int p(\mathbf{x}, \mathbf{z} | \boldsymbol{\theta}) d\mathbf{z} = \int p(\mathbf{x} | \mathbf{z}, \boldsymbol{\theta}_x) p(\mathbf{z} | \boldsymbol{\theta}_z) d\mathbf{z}$$

- Example: 1-D mixture of three Gaussians with

$$\begin{aligned} p(z = k) &= p_k, \quad k \in \{1, 2, 3\} \\ p(x | z = k) &= \mathcal{N}(x | \mu_k, \sigma_k^2) \end{aligned}$$

and

$$\begin{aligned} p(x) &= \sum_{k=1}^3 p(x | z_k) p(z_k) \\ &= \sum_{k=1}^3 p_k \cdot p(x | \mu_k, \sigma_k^2) \end{aligned}$$




Figure 17.1 from (Prince, 2023)

## Generation

A new data point  $x^*$  can be generated from a latent variable model using the ancestral sampling

$$\begin{aligned} \mathbf{z}^* &\sim p(\mathbf{z} \mid \boldsymbol{\theta}_z) \\ \mathbf{x}^* \mid \mathbf{z}^* &\sim p(\mathbf{x} \mid \mathbf{z}^*, \boldsymbol{\theta}_x) \end{aligned}$$

This is straightforward as long as distributions  $p(\mathbf{z} \mid \boldsymbol{\theta}_z)$  and  $p(\mathbf{x} \mid \mathbf{z}, \boldsymbol{\theta}_x)$  are easy to sample

## Probabilistic factor analysis

Probabilistic factor analysis (FA) model is a linear (local) latent variable model defined as

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} \mid \mathbf{0}, \mathbf{I})$$
$$p(\mathbf{x} \mid \mathbf{z}) = \mathcal{N}(\mathbf{x} \mid \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}),$$

where

- $\mathbf{z} \in \mathbb{R}^L$  is a latent variable
- $\mathbf{x} \in \mathbb{R}^D$  denotes observed data
- $\mathbf{W} \in \mathbb{R}^{D \times L}$  is the factor loading matrix
- $\boldsymbol{\mu}$  is a mean offset
- $\boldsymbol{\Psi}$  is  $D$ -by- $D$  covariance matrix
- parameters are deterministic (not r.v.s)

## Probabilistic factor analysis

Probabilistic factor analysis (FA) model is a linear (local) latent variable model defined as

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I})$$
$$p(\mathbf{x} | \mathbf{z}) = \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi}),$$

where

- $\mathbf{z} \in \mathbb{R}^L$  is a latent variable
- $\mathbf{x} \in \mathbb{R}^D$  denotes observed data
- $\mathbf{W} \in \mathbb{R}^{D \times L}$  is the factor loading matrix
- $\boldsymbol{\mu}$  is a mean offset
- $\boldsymbol{\Psi}$  is  $D$ -by- $D$  covariance matrix
- parameters are deterministic (not r.v.s)

We can marginalize out the latent variable  $\mathbf{z}$  from  $p(\mathbf{x}, \mathbf{z}) = p(\mathbf{x} | \mathbf{z})p(\mathbf{z})$  to get marginal likelihood

$$\begin{aligned} p(\mathbf{x}) &= \int p(\mathbf{x} | \mathbf{z})p(\mathbf{z})d\mathbf{z} \\ &= \int \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \boldsymbol{\Psi})\mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I})d\mathbf{z} \\ &= \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \mathbf{W}\mathbf{W}^\top + \boldsymbol{\Psi}) \end{aligned}$$

and

$$p(\mathbf{x}_{1:N}) = \prod_{n=1}^N \mathcal{N}(\mathbf{x}_n | \boldsymbol{\mu}, \mathbf{W}\mathbf{W}^\top + \boldsymbol{\Psi})$$

## Probabilistic factor analysis: illustration




Figure 28.6: Illustration of the FA generative process, where we have  $L = 1$  latent dimension generating  $D = 2$  observed dimensions; we assume  $\Psi = \sigma^2 \mathbf{I}$ . The latent factor has value  $z \in \mathbb{R}$ , sampled from  $p(z)$ ; this gets mapped to a 2d offset  $\delta = zw$ , where  $w \in \mathbb{R}^2$ , which gets added to  $\mu$  to define a Gaussian  $p(\mathbf{x}|z) = \mathcal{N}(\mathbf{x}|\mu + \delta, \sigma^2 \mathbf{I})$ . By integrating over  $z$ , we “slide” this circular Gaussian “spray can” along the principal component axis  $w$ , which induces elliptical Gaussian contours in  $\mathbf{x}$  space centered on  $\mu$ . Adapted from Figure 12.9 of [Bis06].

Figure 28.3 from (Murphy, 2023)

## Probabilistic principle component analysis

Probabilistic principle component analysis (PPCA) is a special case of the probabilistic FA model where

- columns of  $\mathbf{W}$  are orthogonal
- $\Psi = \sigma^2 \mathbf{I}$ ,

and the generative model is

$$p(\mathbf{z}) = \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I})$$

$$p(\mathbf{x} | \mathbf{z}) = N(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \sigma^2 \mathbf{I})$$

- The marginal likelihood

$$\begin{aligned} p(\mathbf{x} | \mathbf{W}, \boldsymbol{\mu}, \sigma^2) \\ &= \int \mathcal{N}(\mathbf{x} | \mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \sigma^2 \mathbf{I}) \mathcal{N}(\mathbf{z} | \mathbf{0}, \mathbf{I}) d\mathbf{z} \\ &= \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}, \mathbf{W}\mathbf{W}^\top + \sigma^2 \mathbf{I}) \end{aligned}$$

## Probabilistic principle component analysis: parameter learning

Given  $N$  observations  $\mathcal{D} = \mathbf{x}_{1:N}$ , we can estimate the model parameters by maximizing the marginal likelihood w.r.t.  $\mathbf{W}$ ,  $\boldsymbol{\mu}$  and  $\sigma^2$

$$L(\mathbf{W}, \boldsymbol{\mu}, \sigma^2 \mid \mathcal{D}) = p(\mathbf{x}_{1:N} \mid \mathbf{W}, \boldsymbol{\mu}, \sigma^2) = \prod_{n=1}^N \mathcal{N}(\mathbf{x}_n \mid \boldsymbol{\mu}, \mathbf{W}\mathbf{W}^\top + \sigma^2\mathbf{I})$$

- Compute sample mean  $\boldsymbol{\mu} = \bar{\mathbf{x}}$  and covariance matrix  $\mathbf{S} = \frac{1}{N} \sum_{i=1}^n (\mathbf{x}_i - \bar{\mathbf{x}})(\mathbf{x}_i - \bar{\mathbf{x}})^\top$
- Rewrite  $\mathbf{S}$  using the eigenvector-eigenvalue decomposition  $\mathbf{S} = \mathbf{U}\Lambda\mathbf{U}^\top$
- ML parameters are obtained using the  $L$  largest eigenvalues-vectors

$$\mathbf{W} = \mathbf{U}_L(\Lambda_L - \sigma^2\mathbf{I})^{\frac{1}{2}} \text{ (upto arbitrary rotation)}$$

$$\sigma^2 = \frac{1}{D-L} \sum_{i=L+1}^D \lambda_i$$

$$\boldsymbol{\mu} = \bar{\mathbf{x}}$$

## Probabilistic principle component analysis: posterior

- Given parameters  $\mathbf{W}$ ,  $\mu$ ,  $\sigma^2$  (fixed or optimized) and an observation  $\mathbf{x}$ , we want to know the distribution of the latent variable

$$p(\mathbf{z} | \mathbf{x}) = \frac{p(\mathbf{x} | \mathbf{z})p(\mathbf{z})}{p(\mathbf{x})}$$

- The posterior of the latent variable can be shown to have normal distribution

$$p(\mathbf{z} | \mathbf{x}) = \mathcal{N}(\mathbf{z} | \mathbf{M}^{-1}\mathbf{W}^\top(\mathbf{x} - \mu), \sigma^2\mathbf{M}^{-1}),$$

where  $\mathbf{M} = \mathbf{W}^\top\mathbf{W} + \sigma^2\mathbf{I}$

## Probabilistic principle component analysis: posterior

- Given parameters  $\mathbf{W}$ ,  $\mu$ ,  $\sigma^2$  (fixed or optimized) and an observation  $\mathbf{x}$ , we want to know the distribution of the latent variable

$$p(\mathbf{z} | \mathbf{x}) = \frac{p(\mathbf{x} | \mathbf{z})p(\mathbf{z})}{p(\mathbf{x})}$$

- The posterior of the latent variable can be shown to have normal distribution

$$p(\mathbf{z} | \mathbf{x}) = \mathcal{N}(\mathbf{z} | \mathbf{M}^{-1}\mathbf{W}^\top(\mathbf{x} - \mu), \sigma^2\mathbf{M}^{-1}),$$

where  $\mathbf{M} = \mathbf{W}^\top\mathbf{W} + \sigma^2\mathbf{I}$

- In the noise-free case of  $\sigma^2 = 0$  the PPCA and PCA are directly comparable

# Deep latent variable model (also called as non-linear latent variable models)

Deep latent variable model is a generative model

$$z \sim p_{\theta}(z)$$

$$x | z \sim p_{\theta}(x | z) \triangleq p(x | d_{\theta}(z)),$$

where

- $z \in \mathcal{Z} = \mathbb{R}^L$  is a latent variable
- $p_{\theta}(z)$  is a prior distribution, typically Gaussian
- $x \in \mathcal{X}$  denotes observed data, e.g.  $\mathcal{X} = \mathbb{R}^D$ , where typically  $D \gg L$
- $p(x | v)$  is a distribution from the exponential family with parameters  $v \in \Upsilon$  (e.g.  $\mu, \Sigma$  for Gaussian, or  $p = (p_1, \dots, p_D)$  for Bernoulli)
- $d_{\theta}(\cdot) : \mathcal{Z} \rightarrow \Upsilon$  is a non-linear function called decoder that maps the latent variable to parameters of the observation likelihood (e.g.  $(\mu, \Sigma) = d_{\theta}(z)$ )




Figure adapted from <https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

# Deep latent variable model (also called as non-linear latent variable models)

Deep latent variable model is a generative model

$$z \sim p_{\theta}(z)$$

$$x | z \sim p_{\theta}(x | z) \triangleq p(x | d_{\theta}(z)),$$

where

- $z \in \mathcal{Z} = \mathbb{R}^L$  is a latent variable
- $p_{\theta}(z)$  is a prior distribution, typically Gaussian
- $x \in \mathcal{X}$  denotes observed data, e.g.  $\mathcal{X} = \mathbb{R}^D$ , where typically  $D \gg L$
- $p(x | v)$  is a distribution from the exponential family with parameters  $v \in \Upsilon$  (e.g.  $\mu, \Sigma$  for Gaussian, or  $p = (p_1, \dots, p_D)$  for Bernoulli)
- $d_{\theta}(\cdot) : \mathcal{Z} \rightarrow \Upsilon$  is a non-linear function called decoder that maps the latent variable to parameters of the observation likelihood (e.g.  $(\mu, \Sigma) = d_{\theta}(z)$ )




Figure adapted from <https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

Marg. likelihood  $p_{\theta}(x) = \int p(x | d_{\theta}(z))p_{\theta}(z)dz$  is generally intractable

## Variational inference

Assume a probabilistic model with

- latent variables  $z$
- observed variables  $x$
- fixed parameters  $\theta$  (if random variables, add  $\theta$  to  $z$ )

Interested in the posterior

$$p_{\theta}(z | x) = \frac{p_{\theta}(x | z)p_{\theta}(z)}{p_{\theta}(x)},$$

where the evidence  $p_{\theta}(x) = \int p_{\theta}(x | z)p_{\theta}(z)dz$  is intractable

## Variational inference

Assume a probabilistic model with

- latent variables  $z$
- observed variables  $x$
- fixed parameters  $\theta$  (if random variables, add  $\theta$  to  $z$ )

Interested in the posterior

$$p_{\theta}(z | x) = \frac{p_{\theta}(x | z)p_{\theta}(z)}{p_{\theta}(x)},$$

where the evidence  $p_{\theta}(x) = \int p_{\theta}(x | z)p_{\theta}(z)dz$  is intractable

### Variational inference

Variational inference (VI) approximates  $p_{\theta}(z | x)$  with a variational approximation  $q(z)$  by minimizing the reverse KL divergence over a variational family of distributions  $\mathcal{Q}$

$$q^* = \arg \min_{q \in \mathcal{Q}} D_{\text{KL}}(q(z) || p_{\theta}(z | x)),$$

# Variational inference

Assume a probabilistic model with

- latent variables  $z$
- observed variables  $x$
- fixed parameters  $\theta$  (if random variables, add  $\theta$  to  $z$ )

Interested in the posterior

$$p_{\theta}(z | x) = \frac{p_{\theta}(x | z)p_{\theta}(z)}{p_{\theta}(x)},$$

where the evidence  $p_{\theta}(x) = \int p_{\theta}(x | z)p_{\theta}(z)dz$  is intractable

## Variational inference

Variational inference (VI) approximates  $p_{\theta}(z | x)$  with a variational approximation  $q(z)$  by minimizing the reverse KL divergence over a variational family of distributions  $\mathcal{Q}$

$$\psi^* = \arg \min_{q \in \mathcal{Q}} D_{\text{KL}}(q(z) || p_{\theta}(z | x)),$$

In practice we use a parametric family  $\mathcal{Q}$  with variational parameters  $\psi$ ,  $q_{\psi}(z)$

- e.g.:  $q_{\psi}(z) = \mathcal{N}(z | \mu, \Sigma)$ ,  $\psi = (\mu, \Sigma)$

Variational inference converts posterior inference to optimization




Figure 10.1 from (Murphy, 2023)

## Variational inference: objective function

The variational objective can be written as

$$\begin{aligned} D_{\text{KL}}(q_{\psi}(z) \parallel p_{\theta}(z \mid \mathbf{x})) &= \mathbb{E}_{q_{\psi}(z)} \left[ \log \left( \frac{q_{\psi}(z)}{p_{\theta}(z \mid \mathbf{x})} \right) \right] \\ &= \mathbb{E}_{q_{\psi}(z)} \left[ \log q_{\psi}(z) - \log \left( \frac{p_{\theta}(\mathbf{x} \mid z)p_{\theta}(z)}{p_{\theta}(\mathbf{x})} \right) \right] \\ &= \mathbb{E}_{q_{\psi}(z)} [\log q_{\psi}(z) - \log p_{\theta}(\mathbf{x} \mid z) - \log p_{\theta}(z)] + \log p_{\theta}(\mathbf{x}) \\ &= \mathbb{E}_{q_{\psi}(z)} [\log q_{\psi}(z) - \log p_{\theta}(\mathbf{x}, z)] + \log p_{\theta}(\mathbf{x}) \\ &= \underbrace{\mathbb{E}_{q_{\psi}(z)} \left[ \log \left( \frac{q_{\psi}(z)}{p_{\theta}(\mathbf{x}, z)} \right) \right]}_{\tilde{\mathcal{L}}(\theta, \psi \mid \mathbf{x})} + \log p_{\theta}(\mathbf{x}), \end{aligned}$$

where  $\log p_{\theta}(\mathbf{x})$  is intractable but independent of  $\psi$

We can minimize  $\tilde{\mathcal{L}}(\theta, \psi \mid \mathbf{x})$  w.r.t.  $\psi$

## Variational inference: evidence lower bound

Alternatively, we can derive a lower bound for the evidence (marg. likelihood)

$$\begin{aligned}\log p_{\theta}(\mathbf{x}) &= \log \left( \int p_{\theta}(\mathbf{x}, \mathbf{z}) d\mathbf{z} \right) \\ &= \log \left( \int q_{\psi}(\mathbf{z}) \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\psi}(\mathbf{z})} d\mathbf{z} \right) \\ &= \log \left( \mathbb{E}_{q_{\psi}(\mathbf{z})} \left[ \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\psi}(\mathbf{z})} \right] \right) \\ &\stackrel{\text{Jensen}}{\geq} \mathbb{E}_{q_{\psi}(\mathbf{z})} \left[ \log \left( \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\psi}(\mathbf{z})} \right) \right] \\ &= \mathcal{L}(\theta, \psi \mid \mathbf{x})\end{aligned}$$

$\mathcal{L}(\theta, \psi \mid \mathbf{x})$  is called the evidence lower bound (ELBO): optimize w.r.t.  $\theta$  and  $\psi$

## Variational inference: evidence lower bound

Alternatively, we can derive a lower bound for the evidence (marg. likelihood)

$$\begin{aligned}\log p_{\theta}(\mathbf{x}) &= \log \left( \int p_{\theta}(\mathbf{x}, \mathbf{z}) d\mathbf{z} \right) \\ &= \log \left( \int q_{\psi}(\mathbf{z}) \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\psi}(\mathbf{z})} d\mathbf{z} \right) \\ &= \log \left( \mathbb{E}_{q_{\psi}(\mathbf{z})} \left[ \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\psi}(\mathbf{z})} \right] \right) \\ &\stackrel{\text{Jensen}}{\geq} \mathbb{E}_{q_{\psi}(\mathbf{z})} \left[ \log \left( \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\psi}(\mathbf{z})} \right) \right] \\ &= \mathcal{L}(\theta, \psi | \mathbf{x})\end{aligned}$$

$\mathcal{L}(\theta, \psi | \mathbf{x})$  is called the evidence lower bound (ELBO): optimize w.r.t.  $\theta$  and  $\psi$

Notice that  $\mathcal{L}(\theta, \psi | \mathbf{x}) = -\tilde{\mathcal{L}}(\theta, \psi | \mathbf{x})$

→ Maximizing  $\mathcal{L}(\theta, \psi | \mathbf{x})$  equals minimizing  $\tilde{\mathcal{L}}(\theta, \psi | \mathbf{x})$

→ Minimizing  $D_{\text{KL}}(q_{\psi}(\mathbf{z}) || p_{\theta}(\mathbf{z} | \mathbf{x}))$  equals maximizing a lower bound for  $\log p_{\theta}(\mathbf{x})$

## ELBO as reconstruction loss minus KL divergence

We can also write the ELBO as

$$\begin{aligned}\log p_{\theta}(\mathbf{x}) &\geq \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}) \\&= \mathbb{E}_{q_{\boldsymbol{\psi}}(\mathbf{z})} \left[ \log \left( \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\boldsymbol{\psi}}(\mathbf{z})} \right) \right] \\&= \mathbb{E}_{q_{\boldsymbol{\psi}}(\mathbf{z})} \left[ \log p_{\theta}(\mathbf{x} \mid \mathbf{z}) + \log \left( \frac{p_{\theta}(\mathbf{z})}{q_{\boldsymbol{\psi}}(\mathbf{z})} \right) \right] \\&= \mathbb{E}_{q_{\boldsymbol{\psi}}(\mathbf{z})} [\log p_{\theta}(\mathbf{x} \mid \mathbf{z})] - \mathbb{E}_{q_{\boldsymbol{\psi}}(\mathbf{z})} \left[ \log \left( \frac{q_{\boldsymbol{\psi}}(\mathbf{z})}{p_{\theta}(\mathbf{z})} \right) \right] \\&= \underbrace{\mathbb{E}_{q_{\boldsymbol{\psi}}(\mathbf{z})} [\log p_{\theta}(\mathbf{x} \mid \mathbf{z})]}_{\text{expected log likelihood}} - \underbrace{D_{\text{KL}}(q_{\boldsymbol{\psi}}(\mathbf{z}) \parallel p_{\theta}(\mathbf{z}))}_{\text{KL of the posterior from prior}}\end{aligned}$$

The first term measures the reconstruction loss

The second term can be interpreted as prior regularization

## ELBO as reconstruction loss minus KL divergence

We can also write the ELBO as

$$\begin{aligned}\log p_{\theta}(x) &\geq \mathcal{L}(\theta, \psi | x) \\&= \mathbb{E}_{q_{\psi}(z)} \left[ \log \left( \frac{p_{\theta}(x, z)}{q_{\psi}(z)} \right) \right] \\&= \mathbb{E}_{q_{\psi}(z)} \left[ \log p_{\theta}(x | z) + \log \left( \frac{p_{\theta}(z)}{q_{\psi}(z)} \right) \right] \\&= \mathbb{E}_{q_{\psi}(z)} [\log p_{\theta}(x | z)] - \mathbb{E}_{q_{\psi}(z)} \left[ \log \left( \frac{q_{\psi}(z)}{p_{\theta}(z)} \right) \right] \\&= \underbrace{\mathbb{E}_{q_{\psi}(z)} [\log p_{\theta}(x | z)]}_{\text{expected log likelihood}} - \underbrace{D_{\text{KL}}(q_{\psi}(z) || p_{\theta}(z))}_{\text{KL of the posterior from prior}}\end{aligned}$$

The first term measures the reconstruction loss

The second term can be interpreted as prior regularization




Figure adapted from

<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

## ELBO: Monte Carlo estimate

ELBO involves expectations that generally cannot be computed analytically but can be estimated using Monte Carlo

For the standard ELBO formula

$$\begin{aligned}\log p_{\theta}(\mathbf{x}) &\geq \mathbb{E}_{q_{\psi}(\mathbf{z})} \left[ \log \left( \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\psi}(\mathbf{z})} \right) \right] \\ &\approx \frac{1}{S} \left( \sum_{s=1}^S \log p_{\theta}(\mathbf{x}, \mathbf{z}_s) - \log q_{\psi}(\mathbf{z}_s) \right) \\ &= \frac{1}{S} \left( \sum_{s=1}^S \log p_{\theta}(\mathbf{x} \mid \mathbf{z}_s) + \log p_{\theta}(\mathbf{z}_s) \right. \\ &\quad \left. - \log q_{\psi}(\mathbf{z}_s) \right)\end{aligned}$$

where  $\mathbf{z}_s \stackrel{\text{i.i.d}}{\sim} q_{\psi}(\mathbf{z})$

## ELBO: Monte Carlo estimate

ELBO involves expectations that generally cannot be computed analytically but can be estimated using Monte Carlo

For the standard ELBO formula

$$\begin{aligned}\log p_{\theta}(\mathbf{x}) &\geq \mathbb{E}_{q_{\psi}(\mathbf{z})} \left[ \log \left( \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\psi}(\mathbf{z})} \right) \right] \\ &\approx \frac{1}{S} \left( \sum_{s=1}^S \log p_{\theta}(\mathbf{x}, \mathbf{z}_s) - \log q_{\psi}(\mathbf{z}_s) \right) \\ &= \frac{1}{S} \left( \sum_{s=1}^S \log p_{\theta}(\mathbf{x} | \mathbf{z}_s) + \log p_{\theta}(\mathbf{z}_s) \right. \\ &\quad \left. - \log q_{\psi}(\mathbf{z}_s) \right)\end{aligned}$$

where  $\mathbf{z}_s \stackrel{\text{i.i.d}}{\sim} q_{\psi}(\mathbf{z})$

For the reconstruction minus KL formula

$$\begin{aligned}\log p_{\theta}(\mathbf{x}) &\geq \mathbb{E}_{q_{\psi}(\mathbf{z})} [\log p_{\theta}(\mathbf{x} | \mathbf{z})] - D_{\text{KL}}(q_{\psi}(\mathbf{z}) || p_{\theta}(\mathbf{z})) \\ &\approx \frac{1}{S} \sum_{s=1}^S \log p_{\theta}(\mathbf{x} | \mathbf{z}_s) - D_{\text{KL}}(q_{\psi}(\mathbf{z}) || p_{\theta}(\mathbf{z}))\end{aligned}$$

where  $\mathbf{z}_s \stackrel{\text{i.i.d}}{\sim} q_{\psi}(\mathbf{z})$

KL term has a closed-form solution for a pair of distributions from the same exponential family

## Tightness of the ELBO

From the variational bound

$$D_{\text{KL}}(q_{\psi}(\mathbf{z}) \parallel p_{\theta}(\mathbf{z} \mid \mathbf{x})) = \tilde{\mathcal{L}}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}) + \log p_{\theta}(\mathbf{x})$$

we get

$$\begin{aligned}\log p_{\theta}(\mathbf{x}) &= -\tilde{\mathcal{L}}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}) + D_{\text{KL}}(q_{\psi}(\mathbf{z}) \parallel p_{\theta}(\mathbf{z} \mid \mathbf{x})) \\ &= \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}) + D_{\text{KL}}(q_{\psi}(\mathbf{z}) \parallel p_{\theta}(\mathbf{z} \mid \mathbf{x})) \\ &\geq \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}),\end{aligned}$$

because KL divergence is non-negative

## Tightness of the ELBO

From the variational bound

$$D_{\text{KL}}(q_{\psi}(\mathbf{z}) \parallel p_{\theta}(\mathbf{z} \mid \mathbf{x})) = \tilde{\mathcal{L}}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}) + \log p_{\theta}(\mathbf{x})$$

we get

$$\begin{aligned}\log p_{\theta}(\mathbf{x}) &= -\tilde{\mathcal{L}}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}) + D_{\text{KL}}(q_{\psi}(\mathbf{z}) \parallel p_{\theta}(\mathbf{z} \mid \mathbf{x})) \\ &= \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}) + D_{\text{KL}}(q_{\psi}(\mathbf{z}) \parallel p_{\theta}(\mathbf{z} \mid \mathbf{x})) \\ &\geq \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi} \mid \mathbf{x}),\end{aligned}$$

because KL divergence is non-negative

KL divergence  $D_{\text{KL}}(q_{\psi}(\mathbf{z}) \parallel p_{\theta}(\mathbf{z} \mid \mathbf{x}))$  defines us two “distances”

- ➊ The KL divergence of the variational approximation from the true posterior (i.e., the VI objective)
- ➋ The tightness of the bound, i.e., the gap between the ELBO and  $\log p_{\theta}(\mathbf{x})$

## Variational inference: mean field model

For a standard local (deep) latent variable model with  $N$  observations  $\mathcal{D} = \mathbf{x}_{1:N}$  and deterministic parameters  $\theta$

$$\begin{aligned} p_{\theta}(\mathbf{x}_{1:N}, \mathbf{z}_{1:N}) &= p_{\theta}(\mathbf{x}_{1:N} \mid \mathbf{z}_{1:N}) p_{\theta}(\mathbf{z}_{1:N}) \\ &= \prod_{n=1}^N p(\mathbf{x}_n \mid d_{\theta}(\mathbf{z}_n)) p_{\theta}(\mathbf{z}_n) \end{aligned}$$

The posterior factorize accordingly

$$\begin{aligned} p_{\theta}(\mathbf{z}_{1:N} \mid \mathbf{x}_{1:N}) &\propto p_{\theta}(\mathbf{x}_{1:N} \mid \mathbf{z}_{1:N}) p(\mathbf{z}_{1:N}) \\ &= \prod_{n=1}^N p(\mathbf{x}_n \mid d_{\theta}(\mathbf{z}_n)) p_{\theta}(\mathbf{z}_n) \end{aligned}$$

## Variational inference: mean field model

For a standard local (deep) latent variable model with  $N$  observations  $\mathcal{D} = \mathbf{x}_{1:N}$  and deterministic parameters  $\boldsymbol{\theta}$

$$\begin{aligned} p_{\boldsymbol{\theta}}(\mathbf{x}_{1:N}, \mathbf{z}_{1:N}) &= p_{\boldsymbol{\theta}}(\mathbf{x}_{1:N} \mid \mathbf{z}_{1:N}) p_{\boldsymbol{\theta}}(\mathbf{z}_{1:N}) \\ &= \prod_{n=1}^N p(\mathbf{x}_n \mid d_{\boldsymbol{\theta}}(\mathbf{z}_n)) p_{\boldsymbol{\theta}}(\mathbf{z}_n) \end{aligned}$$

The posterior factorize accordingly

$$\begin{aligned} p_{\boldsymbol{\theta}}(\mathbf{z}_{1:N} \mid \mathbf{x}_{1:N}) &\propto p_{\boldsymbol{\theta}}(\mathbf{x}_{1:N} \mid \mathbf{z}_{1:N}) p(\mathbf{z}_{1:N}) \\ &= \prod_{n=1}^N p(\mathbf{x}_n \mid d_{\boldsymbol{\theta}}(\mathbf{z}_n)) p_{\boldsymbol{\theta}}(\mathbf{z}_n) \end{aligned}$$

It is common to use the so-called mean field variational approximation that factorizes accordingly

$$q(\mathbf{z}_{1:N} \mid \boldsymbol{\psi}_{1:N}) = \prod_{n=1}^N q_{\boldsymbol{\psi}_n}(\mathbf{z}_n)$$

Note: each latent variable  $\mathbf{z}_n$  has its own variational parameters  $\boldsymbol{\psi}_n$

## Variational inference: mean field model

For a standard local (deep) latent variable model with  $N$  observations  $\mathcal{D} = \mathbf{x}_{1:N}$  and deterministic parameters  $\boldsymbol{\theta}$

$$\begin{aligned} p_{\boldsymbol{\theta}}(\mathbf{x}_{1:N}, \mathbf{z}_{1:N}) &= p_{\boldsymbol{\theta}}(\mathbf{x}_{1:N} \mid \mathbf{z}_{1:N}) p_{\boldsymbol{\theta}}(\mathbf{z}_{1:N}) \\ &= \prod_{n=1}^N p(\mathbf{x}_n \mid d_{\boldsymbol{\theta}}(\mathbf{z}_n)) p_{\boldsymbol{\theta}}(\mathbf{z}_n) \end{aligned}$$

The posterior factorize accordingly

$$\begin{aligned} p_{\boldsymbol{\theta}}(\mathbf{z}_{1:N} \mid \mathbf{x}_{1:N}) &\propto p_{\boldsymbol{\theta}}(\mathbf{x}_{1:N} \mid \mathbf{z}_{1:N}) p(\mathbf{z}_{1:N}) \\ &= \prod_{n=1}^N p(\mathbf{x}_n \mid d_{\boldsymbol{\theta}}(\mathbf{z}_n)) p_{\boldsymbol{\theta}}(\mathbf{z}_n) \end{aligned}$$

It is common to use the so-called mean field variational approximation that factorizes accordingly

$$q(\mathbf{z}_{1:N} \mid \boldsymbol{\psi}_{1:N}) = \prod_{n=1}^N q_{\boldsymbol{\psi}_n}(\mathbf{z}_n)$$

Note: each latent variable  $\mathbf{z}_n$  has its own variational parameters  $\boldsymbol{\psi}_n$

Because

- the above mean field approximation factorizes
- log likelihood  $p_{\boldsymbol{\theta}}(\mathbf{x}_{1:n} \mid \mathbf{z}_{1:N})$  factorizes
- KL for independent r.v.s. factorizes

the ELBO for  $\log p_{\boldsymbol{\theta}}(\mathcal{D})$  factorizes as well

$$\log p_{\boldsymbol{\theta}}(\mathcal{D}) \geq \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi}_{1:N} \mid \mathcal{D}) = \sum_{n=1}^N \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi}_n \mid \mathbf{x}_n)$$

## Variational inference and parameter estimation

- If generative model parameter  $\theta$  are unknown, we generally optimize them by maximizing the (intractable) log marginal likelihood  $\log p_\theta(\mathcal{D})$
- Again, the ELBO provides a lower bound:  $\log p_\theta(\mathcal{D}) \geq \mathcal{L}(\theta, \psi_{1:N} \mid \mathcal{D})$
- **Variational EM** algorithm iteratively optimizes  $\psi_{1:N}$  and  $\theta$ 
  - E step: maximize  $\mathcal{L}(\theta, \psi_{1:N} \mid \mathcal{D})$  w.r.t.  $\psi_{1:N}$
  - M step: maximize  $\mathcal{L}(\theta, \psi_{1:N} \mid \mathcal{D})$  w.r.t.  $\theta$
- Similar approach, called **variational Bayes**, if generative model parameters  $\theta$  are random variables  $p(\theta \mid \xi)$

## Variational inference: stochastic VI

- Computing and minimizing the ELBO for large datasets (e.g. millions of data points) can be slow
- An unbiased stochastic approximation with a minibatch  $\mathcal{B} \subseteq \mathcal{D}$  of size  $B = |\mathcal{B}|$

$$\begin{aligned}\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi}_{1:N} \mid \mathcal{D}) &= \sum_{n=1}^N \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi}_n \mid \mathbf{x}_n) \\ &\approx \frac{N}{B} \sum_{\mathbf{x}_n \in \mathcal{B}} \left[ \mathbb{E}_{q_{\boldsymbol{\psi}_n}(\mathbf{z})} [\log p_{\boldsymbol{\theta}}(\mathbf{x}_n \mid \mathbf{z}_n)] - D_{\text{KL}}(q_{\boldsymbol{\psi}_n}(\mathbf{z}_n) \parallel p_{\boldsymbol{\theta}}(\mathbf{z}_n)) \right]\end{aligned}$$

- This corresponds to stochastic gradient descent (SGD) optimization algorithm and scales VI to large datasets

## Variational inference: amortized VI

- For large datasets, optimizing  $N$  local variational parameters  $\psi_{1:N}$  can be slow
- Amortized VI trains a separate deterministic mapping, so-called encoder or inference network, that predicts  $\psi_n$  from  $x_n$

$$\psi_n = f_\phi(x_n)$$


- Parameters  $\phi$  are shared across samples  $N$
- Example: assume

$$q_{\psi_n}(z_n) = \mathcal{N}(z_n | \mu_n, \text{diag}(\sigma_n^2))$$

$$\psi_n = (\mu_n, \log \sigma_n^2)$$

then

$$\psi_n = (\mu_n, \log \sigma^2) = f_\phi(x_n)$$



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>


## Variational inference: amortized VI

- The amortized version of the standard variational approximation  $q_{\psi_n}(\mathbf{z}_n)$  is denoted as

$$q(\mathbf{z}_n \mid f_{\phi}(\mathbf{x}_n)) = q_{\phi}(\mathbf{z}_n \mid \mathbf{x}_n)$$

- The ELBO objective becomes

$$\begin{aligned}\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathcal{D}) = & \sum_{n=1}^N \left[ \mathbb{E}_{q_{\phi}(\mathbf{z}_n \mid \mathbf{x}_n)} [\log p_{\boldsymbol{\theta}}(\mathbf{x}_n \mid \mathbf{z}_n)] \right. \\ & \left. - D_{\text{KL}}(q_{\phi}(\mathbf{z}_n \mid \mathbf{x}_n) \parallel p_{\boldsymbol{\theta}}(\mathbf{z}_n)) \right]\end{aligned}$$



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

## Variational inference: gradient-based VI

- The gradient of the ELBO w.r.t. generative model parameters

$$\begin{aligned}\nabla_{\theta} \mathcal{L}(\theta, \phi \mid \mathbf{x}) &= \nabla_{\theta} \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x})} [\log p_{\theta}(\mathbf{x} \mid \mathbf{z})] - \nabla_{\theta} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z})) \\ &= \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x})} [\nabla_{\theta} \log p_{\theta}(\mathbf{x} \mid \mathbf{z})] - \nabla_{\theta} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z})) \\ &\stackrel{\text{MC}}{\approx} \sum_{s=1}^S \nabla_{\theta} \log p_{\theta}(\mathbf{x} \mid \mathbf{z}_s) - \nabla_{\theta} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z}))\end{aligned}$$

where  $\mathbf{z}_s \stackrel{\text{i.i.d.}}{\sim} q_{\phi}(\mathbf{z} \mid \mathbf{x})$  and assuming the KL divergence has a closed-form solution (computation does not involve any random variables)

## Variational inference: gradient-based VI

- The gradient of the ELBO w.r.t. generative model parameters

$$\begin{aligned}\nabla_{\theta} \mathcal{L}(\theta, \phi \mid \mathbf{x}) &= \nabla_{\theta} \mathbb{E}_{q_{\phi}(z \mid \mathbf{x})} [\log p_{\theta}(\mathbf{x} \mid z)] - \nabla_{\theta} D_{\text{KL}}(q_{\phi}(z \mid \mathbf{x}) \parallel p_{\theta}(z)) \\ &= \mathbb{E}_{q_{\phi}(z \mid \mathbf{x})} [\nabla_{\theta} \log p_{\theta}(\mathbf{x} \mid z)] - \nabla_{\theta} D_{\text{KL}}(q_{\phi}(z \mid \mathbf{x}) \parallel p_{\theta}(z)) \\ &\stackrel{\text{MC}}{\approx} \sum_{s=1}^S \nabla_{\theta} \log p_{\theta}(\mathbf{x} \mid z_s) - \nabla_{\theta} D_{\text{KL}}(q_{\phi}(z \mid \mathbf{x}) \parallel p_{\theta}(z))\end{aligned}$$

where  $z_s \stackrel{\text{i.i.d.}}{\sim} q_{\phi}(z \mid \mathbf{x})$  and assuming the KL divergence has a closed-form solution (computation does not involve any random variables)

- The gradient of the ELBO w.r.t. the inference network parameters  $\phi$  is trickier

$$\begin{aligned}\nabla_{\phi} \mathcal{L}(\theta, \phi \mid \mathbf{x}) &= \nabla_{\phi} \mathbb{E}_{q_{\phi}(z \mid \mathbf{x})} [\log p_{\theta}(\mathbf{x} \mid z)] - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(z \mid \mathbf{x}) \parallel p_{\theta}(z)) \\ &\neq \mathbb{E}_{q_{\phi}(z \mid \mathbf{x})} [\nabla_{\phi} \log p_{\theta}(\mathbf{x} \mid z)] - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(z \mid \mathbf{x}) \parallel p_{\theta}(z))\end{aligned}$$

## Reparametrization trick

The reparametrization trick is to rewrite a random variable  $\mathbf{z} \sim q_\phi(\mathbf{z} \mid \mathbf{x})$  using a differentiable and invertible transformation  $g$  of another random variable  $\epsilon \sim p(\epsilon)$  that does not depend on  $\phi$ , i.e.,

$$\begin{aligned}\epsilon &\sim p(\epsilon) \\ \mathbf{z} &= g(\phi, \mathbf{x}, \epsilon)\end{aligned}$$

An example: if  $\mathbf{z} \sim q_\phi(\mathbf{z} \mid \mathbf{x}) = \mathcal{N}(\mathbf{z} \mid \boldsymbol{\mu}, \text{diag}(\boldsymbol{\sigma}^2))$  where  $(\boldsymbol{\mu}, \log \boldsymbol{\sigma}^2) = f_\phi(\mathbf{x})$ , we can use

$$\begin{aligned}\epsilon &\sim \mathcal{N}(\mathbf{0}, \mathbf{I}) \\ \mathbf{z} &= \boldsymbol{\mu} + \text{diag}(\boldsymbol{\sigma})\epsilon\end{aligned}$$

## Reparametrization trick

The reparametrization trick is to rewrite a random variable  $\mathbf{z} \sim q_\phi(\mathbf{z} | \mathbf{x})$  using a differentiable and invertible transformation  $g$  of another random variable  $\epsilon \sim p(\epsilon)$  that does not depend on  $\phi$ , i.e.,

$$\begin{aligned}\epsilon &\sim p(\epsilon) \\ \mathbf{z} &= g(\phi, \mathbf{x}, \epsilon)\end{aligned}$$

An example: if  $\mathbf{z} \sim q_\phi(\mathbf{z} | \mathbf{x}) = \mathcal{N}(\mathbf{z} | \boldsymbol{\mu}, \text{diag}(\boldsymbol{\sigma}^2))$  where  $(\boldsymbol{\mu}, \log \boldsymbol{\sigma}^2) = f_\phi(\mathbf{x})$ , we can use

$$\begin{aligned}\epsilon &\sim \mathcal{N}(\mathbf{0}, \mathbf{I}) \\ \mathbf{z} &= \boldsymbol{\mu} + \text{diag}(\boldsymbol{\sigma})\epsilon\end{aligned}$$

Expectation of a function  $h(\mathbf{z})$  w.r.t.  $q_\phi(\mathbf{z} | \mathbf{x})$  can be written as

$$\mathbb{E}_{q_\phi(\mathbf{z} | \mathbf{x})} [h(\mathbf{z})] = \mathbb{E}_{p(\epsilon)} [h(\mathbf{z}')] = \mathbb{E}_{p(\epsilon)} [h(g(\phi, \mathbf{x}, \epsilon))]$$

where  $\mathbf{z}' = g(\phi, \mathbf{x}, \epsilon)$ , and gradient accordingly

$$\nabla_\phi \mathbb{E}_{q_\phi(\mathbf{z} | \mathbf{x})} [h(\mathbf{z})] = \nabla_\phi \mathbb{E}_{p(\epsilon)} [h(\mathbf{z}')] = \mathbb{E}_{p(\epsilon)} [\nabla_\phi h(\mathbf{z}')$$

## Reparametrization: illustration




Figure 10.4 from (Murphy, 2023), originally from (Kingma & Welling, 2019)

## Variational inference: reparameterized VI

Using reparametrization, the gradient of the ELBO w.r.t. the inference network parameters  $\phi$  is

$$\begin{aligned}\nabla_{\phi} \mathcal{L}(\theta, \phi \mid \mathbf{x}) &= \nabla_{\phi} \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x})} [\log p_{\theta}(\mathbf{x} \mid \mathbf{z})] - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z})) \\ &\stackrel{\text{reparam.}}{=} \nabla_{\phi} \mathbb{E}_{p(\boldsymbol{\epsilon})} [\log p_{\theta}(\mathbf{x} \mid \mathbf{z}')] - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z})) \\ &= \mathbb{E}_{p(\boldsymbol{\epsilon})} [\nabla_{\phi} \log p_{\theta}(\mathbf{x} \mid \mathbf{z}')] - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z})) \\ &\stackrel{\text{MC}}{\approx} \sum_{s=1}^S \nabla_{\phi} \log p_{\theta}(\mathbf{x} \mid \mathbf{z}'_s) - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z}))\end{aligned}$$

where  $\mathbf{z}' = g(\phi, \mathbf{x}, \boldsymbol{\epsilon})$ ,  $\mathbf{z}'_s = g(\phi, \mathbf{x}, \boldsymbol{\epsilon}_s)$ , and  $\boldsymbol{\epsilon}_s \stackrel{\text{i.i.d.}}{\sim} p(\boldsymbol{\epsilon})$

## Variational inference: reparameterized VI

Using reparametrization, the gradient of the ELBO w.r.t. the inference network parameters  $\phi$  is

$$\begin{aligned}\nabla_{\phi} \mathcal{L}(\theta, \phi \mid \mathbf{x}) &= \nabla_{\phi} \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x})} [\log p_{\theta}(\mathbf{x} \mid \mathbf{z})] - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z})) \\ &\stackrel{\text{reparam.}}{=} \nabla_{\phi} \mathbb{E}_{p(\epsilon)} [\log p_{\theta}(\mathbf{x} \mid \mathbf{z}')] - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z})) \\ &= \mathbb{E}_{p(\epsilon)} [\nabla_{\phi} \log p_{\theta}(\mathbf{x} \mid \mathbf{z}')] - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z})) \\ &\stackrel{\text{MC}}{\approx} \sum_{s=1}^S \nabla_{\phi} \log p_{\theta}(\mathbf{x} \mid \mathbf{z}'_s) - \nabla_{\phi} D_{\text{KL}}(q_{\phi}(\mathbf{z} \mid \mathbf{x}) \parallel p_{\theta}(\mathbf{z}))\end{aligned}$$

where  $\mathbf{z}' = g(\phi, \mathbf{x}, \epsilon)$ ,  $\mathbf{z}'_s = g(\phi, \mathbf{x}, \epsilon_s)$ , and  $\epsilon_s \stackrel{\text{i.i.d.}}{\sim} p(\epsilon)$

Reparameterized gradient is an unbiased estimate of the exact gradient

If the KL does not have a closed form solution, reparameterized gradients may be computed from

$$\begin{aligned}\nabla_{\theta} \mathcal{L}(\theta, \phi \mid \mathbf{x}) &= \nabla_{\theta} \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x})} [\log p_{\theta}(\mathbf{x}, \mathbf{z}) - \log q_{\phi}(\mathbf{z} \mid \mathbf{x})] \\ \nabla_{\phi} \mathcal{L}(\theta, \phi \mid \mathbf{x}) &= \nabla_{\phi} \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x})} [\log p_{\theta}(\mathbf{x}, \mathbf{z}) - \log q_{\phi}(\mathbf{z} \mid \mathbf{x})]\end{aligned}$$

## Variational autoencoder

Variational autoencoder (VAE) is a neural architecture that consists of a deep latent variable model (deep generative model) of the form

$$\begin{aligned} z &\sim p_{\theta}(z) \\ x \mid z &\sim p(x \mid d_{\theta}(z)) \end{aligned}$$

that is trained using (reparameterized) amortized variational inference with an inference model  $q_{\phi}(z \mid x)$

- Data  $x$  can be continuous or discrete, or both, typically modeled using distribution from the exponential family
- Decoder  $d_{\theta}(\cdot)$  and encoder (inference network)  $f_{\phi}(\cdot)$  are commonly neural networks
- For general statistical latent variable models, this can be called as autoencoding variational Bayes method
- Variational approximation  $q_{\phi}(z \mid x)$  needs to admit reparametrization





Figure from (Kingma & Welling, 2019)


# Variational autoencoder: Probabilistic graphical model

## Probabilistic graphical models for VAE


- Circled symbols denote random variables
- Non-circled symbols are hyperparameters
- White nodes (circles) are latent
- Shaded nodes are observed



(a) Generative model



(b) Inference model



(c) Combined

## Learning algorithm for VAE

Algorithm for obtaining maximum likelihood estimate for deep latent variable model using reparameterized, stochastic and amortized variational inference, here with

- a minibatch sample size of one
- Monte Carlo estimate with sample size one

---

**Algorithm 10.3:** Reparameterized amortized SVI for MLE of an LVM

---

```
1 Initialize  $\theta, \phi$ 
2 repeat
3   Sample  $x_n \sim p_{\mathcal{D}}$ 
4   Sample  $\epsilon_n \sim q_0$ 
5   Compute  $z_n = g(\phi, x_n, \epsilon_n)$ 
6   Compute  $\mathcal{L}(\theta, \phi | x_n, z_n) = -\log p_{\theta}(x_n, z_n) + \log q_{\phi}(z_n | x_n)$ 
7   Update  $\theta := \theta - \eta \nabla_{\theta} \mathcal{L}(\phi, \theta | x_n, z_n)$ 
8   Update  $\phi := \phi - \eta \nabla_{\phi} \mathcal{L}(\phi, \theta | x_n, z_n)$ 
9 until converged
```

---

Algorithm 10.3 from (Murphy, 2023)  
Note notation  $\tilde{\mathcal{L}}$  vs.  $\mathcal{L}$

## Variational autoencoder: neural architecture training pipeline




Figure 17.9 from (Prince, 2023). Note that notation differs.

## Variational autoencoder: parametrization, NN architectures

In standard VAE models:

- Prior  $p_\theta(z)$  is typically Gaussian
- Likelihood  $p(x | d_\theta(z))$  depends on application: typically Gaussian, Bernoulli, etc.
- Variational approximation  $q_\phi(z | x)$  is typically Gaussian (but can be more expressive, such as normalizing flows etc.)

Decoder  $d_\theta(\cdot)$  and encoder  $f_\phi(\cdot)$  neural network architectures are application dependent:

- MLPs for tabular data
- CNNs for images
- RNNs and attention for sequential data

## Autoencoder vs. variational autoencoder

Autoencoder (AE) is a deterministic neural network architecture that

- Maps input  $x$  into a lower dimensional representation  $z = f_e(x)$
- Attempts to reconstruct the original input by  $f_d(z)$ , i.e.,  $x \approx \hat{x} = f_d(f_e(x))$




Figure 16.13 from (Murphy, 2023)

## Autoencoder vs. variational autoencoder

Autoencoder (AE) is a deterministic neural network architecture that

- Maps input  $x$  into a lower dimensional representation  $z = f_e(x)$
- Attempts to reconstruct the original input by  $f_d(z)$ , i.e.,  $x \approx \hat{x} = f_d(f_e(x))$





Figure 16.13 from (Murphy, 2023)

Variational autoencoder (VAE) is a neural architecture that consists of a deep generative model that is trained using an inference model



## Autoencoder vs. variational autoencoder

Autoencoder (AE) is a deterministic neural network architecture that

- Maps input  $x$  into a lower dimensional representation  $z = f_e(x)$
- Attempts to reconstruct the original input by  $f_d(z)$ , i.e.,  $x \approx \hat{x} = f_d(f_e(x))$





Figure 16.13 from (Murphy, 2023)

Variational autoencoder (VAE) is a neural architecture that consists of a deep generative model that is trained using an inference model



Adapted from Figure 20.1 from (Murphy, 2023)

# Applications of variational autoencoders

Variational autoencoders can be used for various tasks

- Statistical modeling<sup>a</sup>
- Generation<sup>a</sup>, conditional generation<sup>b</sup>
- Amortized variational inference<sup>a</sup>
- Representation learning<sup>a</sup>
- Reconstruction, missing value estimation<sup>b</sup>
- Latent space interpolation<sup>b</sup>
- Out-of-distribution detection<sup>b</sup>

---

<sup>a</sup>In this lecture.

<sup>b</sup>In the next lecture.

## Variational autoencoder: MNIST image example

MNIST is a large image dataset  $\mathcal{D} = \mathbf{x}_{1:N}$  of handwritten digits



[https://riccardo-cantini.netlify.app/post/cnn\\_vae\\_mnist/](https://riccardo-cantini.netlify.app/post/cnn_vae_mnist/)

## Variational autoencoder: MNIST image example


MNIST is a large image dataset  $\mathcal{D} = \mathbf{x}_{1:N}$  of handwritten digits



[https://riccardo-cantini.netlify.app/post/cnn\\_vae\\_mnist/](https://riccardo-cantini.netlify.app/post/cnn_vae_mnist/)

Train a VAE model and sample from the trained generative model to generate new images

$$\begin{aligned} z^* &\sim p_{\theta}(z) \\ x^* \mid z^* &\sim p(x \mid d_{\theta}(z^*)) \end{aligned}$$



<https://mbernste.github.io/posts/vae/>

## Sample generation from VAE

As before, a new data point  $\mathbf{x}^*$  can be generated from a latent variable model using the ancestral sampling

$$\mathbf{z}^* \sim p_{\theta}(\mathbf{z})$$

$$\mathbf{x}^* \sim p_{\theta}(\mathbf{x} \mid \mathbf{z}^*)$$

For example in image tasks, so-called decoded mean samples can have higher quality

$$\mathbf{z}^* \sim p_{\theta}(\mathbf{z})$$

$$\hat{\mathbf{x}}^* = d_{\theta}(\mathbf{z}^*)$$

## Sample generation from VAE

As before, a new data point  $\mathbf{x}^*$  can be generated from a latent variable model using the ancestral sampling

$$\mathbf{z}^* \sim p_{\theta}(\mathbf{z})$$

$$\mathbf{x}^* \sim p_{\theta}(\mathbf{x} \mid \mathbf{z}^*)$$

For example in image tasks, so-called decoded mean samples can have higher quality

$$\mathbf{z}^* \sim p_{\theta}(\mathbf{z})$$

$$\hat{\mathbf{x}}^* = d_{\theta}(\mathbf{z}^*)$$

Another trick is to define a joint inference distribution

$$q_{\mathcal{D}, \phi}(\mathbf{x}, \mathbf{z}) = p_{\mathcal{D}}(\mathbf{x})q_{\phi}(\mathbf{z} \mid \mathbf{x}),$$

where

$$p_{\mathcal{D}}(\mathbf{x}) = \frac{1}{N} \sum_{n=1}^N \delta(\mathbf{x} - \mathbf{x}_n),$$

and then sample latent variables from the aggregated posterior (marginal inference distribution)  $q_{\mathcal{D}, \phi}(\mathbf{z})$

$$\begin{aligned} q_{\mathcal{D}, \phi}(\mathbf{z}) &= \int q_{\mathcal{D}, \phi}(\mathbf{x}, \mathbf{z}) d\mathbf{x} \\ &= \int \frac{1}{N} \sum_{n=1}^N \delta(\mathbf{x} - \mathbf{x}_n) q_{\phi}(\mathbf{z} \mid \mathbf{x}) d\mathbf{x} \\ &= \frac{1}{N} \sum_{n=1}^N q_{\phi}(\mathbf{z} \mid \mathbf{x}_n) \end{aligned}$$

## Variational autoencoder: CELEBA image example

Samples from VAEs that are trained on CELEBA dataset

a) Random samples:

$$z^* \sim p_{\theta}(z)$$

$$x^* | z^* \sim p_{\theta}(x | d_{\theta}(z^*))$$

b) Decoded mean samples:

$$z^* \sim p_{\theta}(z)$$

$$\hat{x}^* | z^* = d_{\theta}(z^*)$$

c) "Noise":  $\hat{\epsilon} = x^* - \hat{x}^*$

d) High-quality generation from a VAE with hierarchical prior and specialized architectures (details later)





Figure 17.12 from (Prince, 2023).

# Variational autoencoder: dimension reduction, visualization, clustering


Example: Train a VAE model on the MNIST images

Use the encoder (amortized VI) for dimension reduction and visualization by plotting the approximative posteriors  $q_\phi(z | x)$  (or their means)

It is common to use the learned representations  $q_\phi(z | x)$  for clustering or other downstream tasks



<https://mbernste.github.io/posts/vae/>



[https://riccardo-cantini.netlify.app/post/cnn\\_vae\\_mnist/](https://riccardo-cantini.netlify.app/post/cnn_vae_mnist/)

# Variational autoencoder: modern molecular biology example

Single-cell sequencing is a modern technology that allows quantifying transcriptomic profiles of individual cells




Figure from bioRender (<https://www.biorender.com/template/single-cell-sequencing>)

## Variational autoencoder: modern molecular biology example

Challenging to specify a well-motivated probabilistic model for the data

→ Incorporate biological inductive bias into neural network parameterized generative model

$$z_n \sim \text{Normal}(0, I)$$

$$\ell_n \sim \text{LogNormal}(\ell_\mu, \ell_\sigma^2)$$

$$\rho_n = f_w(z_n, s_n)$$

$$w_{ng} \sim \text{Gamma}(\rho_n^g, \theta)$$

$$y_{ng} \sim \text{Poisson}(\ell_n w_{ng})$$

$$h_{ng} \sim \text{Bernoulli}(f_h^g(z_n, s_n))$$

$$x_{ng} = \begin{cases} y_{ng} & \text{if } h_{ng} = 0, \\ 0 & \text{otherwise.} \end{cases}$$




Figure from (Lopez et al, 2019)

# Variational autoencoder: modern molecular biology example

Variational autoencoder architecture (generative model and amortized VI) with deep neural networks




Figure from (Lopez et al, 2019)

# Variational autoencoder: modern molecular biology example

Encoder (amortized VI) provides representations for visualization, clustering, and other downstream tasks




Figure from (Lopez et al, 2019)

## References

- Kingma DP and Welling M, An Introduction to Variational Autoencoders, Foundations and Trends in Machine Learning, Vol. 12, No. 4, pp. 307-392.
- R. Lopez, J. Regier, MB. Cole, M. Jordan, N. Yosef, Deep generative modeling for single-cell transcriptomics, *Nature Methods*, 2019.
- Murphy K, Probabilistic Machine Learning: Advanced Topics, The MIT Press, 2023.
- Prince SJD, Understanding Deep Learning, The MIT Press, 2023.

# CS-E4891 Deep Generative Models

## Lecture 3: Variational autoencoders

Harri Lähdesmäki

Department of Computer Science  
Aalto University

March 31, 2025

## Outline

- Variational autoencoders (recap)
- Applications of VAE (continued)
- VAE generalizations
- Identifiability of VAEs
- Amortization gap
- Reading: parts of Sec. 20-21 from (Murphy, 2023), Sec. 17 from (Prince, 2023), and other literature (see references at the end)

## Variational autoencoder

Variational autoencoder (VAE) is a neural architecture that consists of a deep latent variable model (deep generative model) of the form

$$\begin{aligned} z &\sim p_{\theta}(z) \\ x \mid z &\sim p(x \mid d_{\theta}(z)) \end{aligned}$$

that is trained using (reparameterized) amortized variational inference with an inference model  $q_{\phi}(z \mid x) = q(z \mid f_{\phi}(x))$

- Data  $x$  can be continuous or discrete, or both, typically modeled using distribution from the exponential family
- Decoder  $d_{\theta}(\cdot)$  and encoder (inference network)  $f_{\phi}(\cdot)$  are commonly neural networks
- For general statistical latent variable models, this can be called as autoencoding variational Bayes method
- Variational approximation  $q_{\phi}(z \mid x)$  needs to admit reparametrization




Figure from (Kingma & Welling, 2019)

# Applications of variational autoencoders

Variational autoencoders can be used for various tasks

- Statistical modeling<sup>a</sup>
- Generation<sup>a</sup>, conditional generation<sup>b</sup>
- Amortized variational inference<sup>a</sup>
- Representation learning<sup>a</sup>
- Reconstruction, missing value estimation<sup>b</sup>
- Latent space interpolation<sup>b</sup>
- Out-of-distribution detection<sup>b</sup>

---

<sup>a</sup>In the previous lecture.

<sup>b</sup>In this lecture.

## Variational autoencoder for reconstruction and data imputation

Consider a test data point  $\mathbf{x} = (\mathbf{x}_o, \mathbf{x}_m)$ , where  $\mathbf{x}_o$  denotes observed features and  $\mathbf{x}_m$  denotes unobserved (missing) features

Observed and missing features can vary between different test data points  $\mathbf{x}$  and  $\mathbf{x}'$

For a VAE model  $\mathbf{x}_o$  and  $\mathbf{x}_m$  are conditionally independent given  $\mathbf{z}$  (assuming diagonal likelihood covariance), therefore

$$\begin{aligned} p(\mathbf{x}_m \mid \mathbf{x}_o) &= \int p(\mathbf{x}_m \mid \mathbf{z}) p(\mathbf{z} \mid \mathbf{x}_o) d\mathbf{z} \\ &\approx \int p_{\theta}(\mathbf{x}_m \mid \mathbf{z}) q_{\phi}(\mathbf{z} \mid \mathbf{x}_o) d\mathbf{z} \end{aligned}$$


## Variational autoencoder for reconstruction and data imputation

Consider a test data point  $\mathbf{x} = (\mathbf{x}_o, \mathbf{x}_m)$ , where  $\mathbf{x}_o$  denotes observed features and  $\mathbf{x}_m$  denotes unobserved (missing) features

Observed and missing features can vary between different test data points  $\mathbf{x}$  and  $\mathbf{x}'$

For a VAE model  $\mathbf{x}_o$  and  $\mathbf{x}_m$  are conditionally independent given  $\mathbf{z}$  (assuming diagonal likelihood covariance), therefore

$$\begin{aligned} p(\mathbf{x}_m | \mathbf{x}_o) &= \int p(\mathbf{x}_m | \mathbf{z}) p(\mathbf{z} | \mathbf{x}_o) d\mathbf{z} \\ &\approx \int p_{\theta}(\mathbf{x}_m | \mathbf{z}) q_{\phi}(\mathbf{z} | \mathbf{x}_o) d\mathbf{z} \end{aligned}$$



<https://mbernste.github.io/posts/vae/>

→ VAE architecture automatically implements a statistical data imputation method

Encoder model  $q_{\phi}(\mathbf{z} | \mathbf{x})$  needs to be able to handle missing values in  $\mathbf{x}$

## Variational autoencoder for reconstruction and data imputation

Posterior matching technique (Strauss and Oliva, 2022)

- Artificially mask complete training data points as  
 $\mathbf{x} = (\mathbf{x}_o, \mathbf{x}_m)$
- Train an additional encoder model with parameters  
 $\phi'$  such that  $q_{\phi'}(\mathbf{z} \mid \mathbf{x}_o) \approx q_{\phi}(\mathbf{z} \mid \mathbf{x})$  by maximizing

$$\mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x})} [\log q_{\phi'}(\mathbf{z} \mid \mathbf{x}_o)]$$

## Variational autoencoder for reconstruction and data imputation

Posterior matching technique (Strauss and Oliva, 2022)

- Artificially mask complete training data points as  
 $\mathbf{x} = (\mathbf{x}_o, \mathbf{x}_m)$
- Train an additional encoder model with parameters  
 $\phi'$  such that  $q_{\phi'}(\mathbf{z} | \mathbf{x}_o) \approx q_{\phi}(\mathbf{z} | \mathbf{x})$  by maximizing

$$\mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{x})} [\log q_{\phi'}(\mathbf{z} | \mathbf{x}_o)]$$

Variationally optimal approach: use non-amortized variational inference to maximize (Agarwal et al., 2023)

$$\begin{aligned}\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\psi} | \mathbf{x}) &= \mathbb{E}_{q_{\psi}(\mathbf{z})} [\log p_{\boldsymbol{\theta}}(\mathbf{x}_o | \mathbf{z})] \\ &\quad - D_{\text{KL}}(q_{\psi}(\mathbf{z}) || p_{\boldsymbol{\theta}}(\mathbf{z}))\end{aligned}$$

w.r.t.  $\boldsymbol{\psi}$  and estimate with previously trained decoder

$$p(\mathbf{x}_m | \mathbf{x}_o) \approx \int p_{\boldsymbol{\theta}}(\mathbf{x}_m | \mathbf{z}) q_{\psi}(\mathbf{z}) d\mathbf{z}$$

# Variational autoencoder for reconstruction and data imputation

Posterior matching technique (Strauss and Oliva, 2022)

- Artificially mask complete training data points as  $\mathbf{x} = (\mathbf{x}_o, \mathbf{x}_m)$
- Train an additional encoder model with parameters  $\phi'$  such that  $q_{\phi'}(\mathbf{z} | \mathbf{x}_o) \approx q_{\phi}(\mathbf{z} | \mathbf{x})$  by maximizing

$$\mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{x})} [\log q_{\phi'}(\mathbf{z} | \mathbf{x}_o)]$$

Variationally optimal approach: use non-amortized variational inference to maximize (Agarwal et al., 2023)

$$\begin{aligned}\mathcal{L}(\theta, \psi | \mathbf{x}) &= \mathbb{E}_{q_{\psi}(\mathbf{z})} [\log p_{\theta}(\mathbf{x}_o | \mathbf{z})] \\ &\quad - D_{\text{KL}}(q_{\psi}(\mathbf{z}) || p_{\theta}(\mathbf{z}))\end{aligned}$$

w.r.t.  $\psi$  and estimate with previously trained decoder

$$p(\mathbf{x}_m | \mathbf{x}_o) \approx \int p_{\theta}(\mathbf{x}_m | \mathbf{z}) q_{\psi}(\mathbf{z}) d\mathbf{z}$$




Figure from (Agarwal et al., 2023).

Note: above results use additional tricks, such as deep/hierarchical VAEs, more expressive posteriors

## Variational autoencoder for reconstruction and data imputation

Some VAE variants can explicitly model missingness together with  $x$ , e.g., by also modeling missingness mask  $m$

Can model

- missing-completely-at-random (MCAR)
- missing-at-random (MAR)
- missing-not-at-random (MNAR)

## Latent space interpolation

Explore the generative model via latent space interpolation

Consider two data points  $\mathbf{x}_1$  and  $\mathbf{x}_2$  and the mean of their embeddings  $\mathbf{z}_1 = f_\phi(\mathbf{x}_1)$  and  $\mathbf{z}_2 = f_\phi(\mathbf{x}_2)$

Generate new images via latent space interpolation

$$\mathbf{z} = \lambda \mathbf{z}_1 + (1 - \lambda) \mathbf{z}_2, \quad 0 \leq \lambda \leq 1$$

and decoding  $\mathbf{x} \sim p_\theta(\mathbf{x} | \mathbf{z})$




Figure from <https://mbernste.github.io/posts/vae/>

Note that the notation differs.

## Latent space interpolation

Explore the generative model via latent space interpolation

Consider two data points  $\mathbf{x}_1$  and  $\mathbf{x}_2$  and the mean of their embeddings  $\mathbf{z}_1 = f_\phi(\mathbf{x}_1)$  and  $\mathbf{z}_2 = f_\phi(\mathbf{x}_2)$

Generate new images via latent space interpolation

$$\mathbf{z} = \lambda \mathbf{z}_1 + (1 - \lambda) \mathbf{z}_2, \quad 0 \leq \lambda \leq 1$$

and decoding  $\mathbf{x} \sim p_\theta(\mathbf{x} | \mathbf{z})$




Figure 20.9 from (Murphy, 2023)




Figure from <https://mbernste.github.io/posts/vae/>

Note that the notation differs.

## Latent space interpolation (and extrapolation)

Example: consider groups of images labeled as

- “neutral”:  $\{x_i : i \in \mathcal{I}_{\text{neutral}}\}$
- “smiling”:  $\{x_j : j \in \mathcal{I}_{\text{smiling}}\}$
- “mouth closed”:  $\{x_k : k \in \mathcal{I}_{\text{closed}}\}$
- “mouth open”:  $\{x_l : l \in \mathcal{I}_{\text{open}}\}$

and define

$$\Delta_1 = \sum_{j \in \mathcal{I}_{\text{smiling}}} f_\phi(x_j) - \sum_{i \in \mathcal{I}_{\text{neutral}}} f_\phi(x_i)$$

$$\Delta_2 = \sum_{l \in \mathcal{I}_{\text{open}}} f_\phi(x_l) - \sum_{k \in \mathcal{I}_{\text{closed}}} f_\phi(x_k)$$

A given image  $x$  can be manipulated via interpolation as

$$z = f_\phi(x)$$

$$z' = z + \lambda_1 \Delta_1 + \lambda_2 \Delta_2, \quad \lambda_1, \lambda_2 \in \mathbb{R}$$

$$x' \sim p_\theta(x | z')$$



Figure 17.13 from (Prince, 2023)

Note: interpolation above uses non-linear interpolation in spherical coordinates.

## Approximating sample probability

Use a trained VAE to approximate sample probability for test data to

- Estimate the quality of the model
- Detect out-of-distribution samples

## Approximating sample probability

Use a trained VAE to approximate sample probability for test data to

- Estimate the quality of the model
- Detect out-of-distribution samples

Instead of using the ELBO, we can directly estimate probability for a given data point  $\mathbf{x}$  using Monte Carlo

$$\begin{aligned} p_{\theta}(\mathbf{x}) &= \int p_{\theta}(\mathbf{x} | \mathbf{z}) p_{\theta}(\mathbf{z}) d\mathbf{z} \\ &= \mathbb{E}_{p_{\theta}(\mathbf{z})}[p_{\theta}(\mathbf{x} | \mathbf{z})] \\ &\approx \frac{1}{S} \sum_{s=1}^S p_{\theta}(\mathbf{x} | \mathbf{z}_s) \end{aligned}$$

where

$$\mathbf{z}_s \stackrel{\text{i.i.d.}}{\sim} p_{\theta}(\mathbf{z})$$

## Approximating sample probability

Use a trained VAE to approximate sample probability for test data to

- Estimate the quality of the model
- Detect out-of-distribution samples

Instead of using the ELBO, we can directly estimate probability for a given data point  $\mathbf{x}$  using Monte Carlo

$$\begin{aligned} p_{\theta}(\mathbf{x}) &= \int p_{\theta}(\mathbf{x} | \mathbf{z}) p_{\theta}(\mathbf{z}) d\mathbf{z} \\ &= \mathbb{E}_{p_{\theta}(\mathbf{z})}[p_{\theta}(\mathbf{x} | \mathbf{z})] \\ &\approx \frac{1}{S} \sum_{s=1}^S p_{\theta}(\mathbf{x} | \mathbf{z}_s) \end{aligned}$$

where

$$\mathbf{z}_s \stackrel{\text{i.i.d}}{\sim} p_{\theta}(\mathbf{z})$$

$$\begin{aligned} p_{\theta}(\mathbf{x}) &= \int p_{\theta}(\mathbf{x} | \mathbf{z}) p_{\theta}(\mathbf{z}) d\mathbf{z} \\ &= \int p_{\theta}(\mathbf{x} | \mathbf{z}) \frac{p_{\theta}(\mathbf{z})}{q_{\phi}(\mathbf{z} | \mathbf{x})} q_{\phi}(\mathbf{z} | \mathbf{x}) d\mathbf{z} \\ &= \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{x})} \left[ p_{\theta}(\mathbf{x} | \mathbf{z}) \frac{p_{\theta}(\mathbf{z})}{q_{\phi}(\mathbf{z} | \mathbf{x})} \right] \\ &\approx \frac{1}{S} \sum_{s=1}^S \tilde{w}_s p_{\theta}(\mathbf{x} | \mathbf{z}_s), \end{aligned}$$

where

$$\mathbf{z}_s \stackrel{\text{i.i.d}}{\sim} q_{\phi}(\mathbf{z} | \mathbf{x}), \quad \tilde{w}_s = \frac{p_{\theta}(\mathbf{z}_s)}{q_{\phi}(\mathbf{z}_s | \mathbf{x})}, \quad \text{sup } p_{\theta} \subseteq \text{sup } q_{\phi}$$

## Posterior collapse

- Consider a powerful decoder (a “super” deep neural net of some sort) such that for every value of latent variable  $z \in \mathcal{Z}$  decoder outputs one of the data points
- Then approx.  $p_{\theta}(x | z) = p_{\theta}(x)$  and  $p_{\theta}(z | x) = p_{\theta}(z)$  because generative model does not really use the latent variable
- We can find inference network parameters  $\phi^*$  such that  $q_{\phi^*}(z | x) = p_{\theta}(z | x) = p_{\theta}(z)$

## Posterior collapse

- Consider a powerful decoder (a “super” deep neural net of some sort) such that for every value of latent variable  $z \in \mathcal{Z}$  decoder outputs one of the data points
- Then approx.  $p_{\theta}(x | z) = p_{\theta}(x)$  and  $p_{\theta}(z | x) = p_{\theta}(z)$  because generative model does not really use the latent variable
- We can find inference network parameters  $\phi^*$  such that  $q_{\phi^*}(z | x) = p_{\theta}(z | x) = p_{\theta}(z)$
- In this setting, ELBO is maximized because  $D_{\text{KL}}(q_{\phi^*}(z | x) || p_{\theta}(z | x)) = 0$  but the model has not learned any meaningful latent representations
- Then also  $D_{\text{KL}}(q_{\phi^*}(z | x) || p_{\theta}(z)) = 0$
- This is known as posterior collapse
- Posterior collapse is also due to other aspects, such local maxima in the complex objective function

## $\beta$ -VAE

VAE models can generate samples that may appear too smooth (e.g. blurry images)

$\beta$ -VAE can improve sample quality (as well as help with posterior collapse) by reducing the penalty on the KL term

$$\mathcal{L}_\beta(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_\phi(\mathbf{z} \mid \mathbf{x})} [\log p_\theta(\mathbf{x} \mid \mathbf{z})] - \beta D_{\text{KL}}(q_\phi(\mathbf{z} \mid \mathbf{x}) \parallel p_\theta(\mathbf{z})), \quad \beta \geq 0$$

If we set

- $\beta = 1$  we obtain the standard objective for VAEs
- $\beta < 1$  we can reconstruct data samples better
- $\beta > 1$  we get more compressed representations (in terms of rate distortion, see Murphy (2023))
- $\beta = 0$  we obtain an objective that is analogous for autoencoder models


## Conditional variational autoencoder

Conditional variational autoencoder (CVAE) is a neural architecture that consists of a conditional deep latent variable model of the form

$$z \sim p_{\theta}(z)$$

$$\mathbf{x} | z \sim p_{\theta}(\mathbf{x} | z, \mathbf{c}) = p(\mathbf{x} | d_{\theta}(z, \mathbf{c})),$$

where  $\mathbf{c}$  contains the explanatory covariates and the model is trained using (reparameterized) amortized variational inference with an inference model  $q_{\phi}(z | \mathbf{x}, \mathbf{c})$ .



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

## Conditional variational autoencoder

Conditional variational autoencoder (CVAE) is a neural architecture that consists of a conditional deep latent variable model of the form

$$z \sim p_{\theta}(z)$$

$$\mathbf{x} | z \sim p_{\theta}(\mathbf{x} | z, \mathbf{c}) = p(\mathbf{x} | d_{\theta}(z, \mathbf{c})),$$


where  $\mathbf{c}$  contains the explanatory covariates and the model is trained using (reparameterized) amortized variational inference with an inference model  $q_{\phi}(z | \mathbf{x}, \mathbf{c})$ .

Alternative CVAE model definitions:

$$p_{\theta}(\mathbf{x}, z | \mathbf{c}) = p_{\theta}(\mathbf{x} | z, \mathbf{c})p_{\theta}(z | \mathbf{c})$$

or

$$p_{\theta}(\mathbf{x}, z | \mathbf{c}) = p_{\theta}(\mathbf{x} | z)p_{\theta}(z | \mathbf{c})$$



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

## Conditional variational autoencoder

Conditional variational autoencoder (CVAE) is a neural architecture that consists of a conditional deep latent variable model of the form

$$z \sim p_{\theta}(z)$$

$$\mathbf{x} | z \sim p_{\theta}(\mathbf{x} | z, c) = p(\mathbf{x} | d_{\theta}(z, c)),$$


where  $c$  contains the explanatory covariates and the model is trained using (reparameterized) amortized variational inference with an inference model  $q_{\phi}(z | \mathbf{x}, c)$ .

Alternative CVAE model definitions:

$$p_{\theta}(\mathbf{x}, z | c) = p_{\theta}(\mathbf{x} | z, c)p_{\theta}(z | c)$$

or

$$p_{\theta}(\mathbf{x}, z | c) = p_{\theta}(\mathbf{x} | z)p_{\theta}(z | c)$$



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>


All methodological details remain essentially unchanged, including the ELBO objective

$$\begin{aligned}\mathcal{L}(\theta, \phi | \mathbf{x}, c) &= \mathbb{E}_{q_{\phi}(z | \mathbf{x}, c)} [\log p_{\theta}(\mathbf{x} | z, c)] \\ &\quad - D_{\text{KL}}(q_{\phi}(z | \mathbf{x}, c) || p_{\theta}(z))\end{aligned}$$


## Conditional variational autoencoder: Probabilistic graphical model

Probabilistic graphical models for CVAE with  $p_{\theta}(x, z | c) = p_{\theta}(x | z)p_{\theta}(z | c)$


- Circled symbols denote random variables
- Non-circled symbols are hyperparameters
- White nodes (circles) are latent
- Shaded nodes are observed



(a) Generative model



(b) Inference model



(c) Combined

## Multimodal variational autoencoder

- Multimodal VAE allows modeling joint distributions over multiple data modalities, e.g. image and text
- Assuming  $M$  modalities  $\mathbf{x}_1 \in \mathcal{X}_1, \dots, \mathbf{x}_M \in \mathcal{X}_M$  and conditional independence given  $\mathbf{z}$

$$p_{\theta}(\mathbf{x}_1, \dots, \mathbf{x}_M, \mathbf{z}) = p_{\theta}(\mathbf{z}) \prod_{m=1}^M p_{\theta}(\mathbf{x}_m | \mathbf{z})$$




Illustration of multimodal data

## Multimodal variational autoencoder

- Multimodal VAE allows modeling joint distributions over multiple data modalities, e.g. image and text
- Assuming  $M$  modalities  $\mathbf{x}_1 \in \mathcal{X}_1, \dots, \mathbf{x}_M \in \mathcal{X}_M$  and conditional independence given  $\mathbf{z}$

$$p_{\theta}(\mathbf{x}_1, \dots, \mathbf{x}_M, \mathbf{z}) = p_{\theta}(\mathbf{z}) \prod_{m=1}^M p_{\theta}(\mathbf{x}_m | \mathbf{z})$$

- The ELBO for  $\mathbf{X} = \{\mathbf{x}_1, \dots, \mathbf{x}_M\}$  is

$$\mathcal{L}(\theta, \phi | \mathbf{X}) = \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{X})} \left[ \sum_{m=1}^M \log p_{\theta}(\mathbf{x}_m | \mathbf{z}) \right] - D_{\text{KL}}(q_{\phi}(\mathbf{z} | \mathbf{X}) || p_{\theta}(\mathbf{z}))$$

- Likelihood terms may have different ranges
- Weighted ELBO with  $\lambda_m \geq 0$

$$\mathcal{L}(\theta, \phi | \mathbf{X}) = \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{X})} \left[ \sum_{m=1}^M \lambda_m \log p_{\theta}(\mathbf{x}_m | \mathbf{z}) \right] - D_{\text{KL}}(q_{\phi}(\mathbf{z} | \mathbf{X}) || p_{\theta}(\mathbf{z}))$$




Illustration of multimodal data

## Multimodal variational autoencoder for unpaired data

- Availability of paired multimodal data across all modalities is often limited
- For example, we may have lots of images, lots of text, but only few image-text pairs
- Let  $O_m = 1$  denote that data modality  $m$ ,  $\mathbf{x}_m$ , is observed, and  $O_m = 0$  that modality  $m$  is not observed
- ELBO objective for partially paired data is

$$\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{X}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{X})} \left[ \sum_{m:O_m=1} \lambda_m \log p_{\boldsymbol{\theta}}(\mathbf{x}_m \mid \mathbf{z}) \right] - D_{\text{KL}}(q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{X}) \parallel p_{\boldsymbol{\theta}}(\mathbf{z}))$$

## Multimodal variational autoencoder for unpaired data

- Availability of paired multimodal data across all modalities is often limited
- For example, we may have lots of images, lots of text, but only few image-text pairs
- Let  $O_m = 1$  denote that data modality  $m$ ,  $\mathbf{x}_m$ , is observed, and  $O_m = 0$  that modality  $m$  is not observed
- ELBO objective for partially paired data is

$$\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{X}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{X})} \left[ \sum_{m:O_m=1} \lambda_m \log p_{\boldsymbol{\theta}}(\mathbf{x}_m \mid \mathbf{z}) \right] - D_{\text{KL}}(q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{X}) \parallel p_{\boldsymbol{\theta}}(\mathbf{z}))$$

- How to define the amortized VI such that it works for unpaired data?
- For example, if encoder  $q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x}_1, \mathbf{x}_2)$  is trained on image-text pairs, how to compute posterior approximation using only images  $q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x}_1)$  or text  $q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x}_2)$ , and vice versa?

## Multimodal variational autoencoder with product of experts

From the conditional independence we get

$$\begin{aligned} p(\mathbf{z} \mid \mathbf{X}) &= \frac{p(\mathbf{z})p(\mathbf{x}_1, \dots, \mathbf{x}_m \mid \mathbf{z})}{p(\mathbf{x}_1, \dots, \mathbf{x}_m)} \\ &= \frac{p(\mathbf{z})}{p(\mathbf{x}_1, \dots, \mathbf{x}_m)} \prod_{m=1}^M p(\mathbf{x}_m \mid \mathbf{z}) \\ &= \frac{p(\mathbf{z})}{p(\mathbf{x}_1, \dots, \mathbf{x}_m)} \prod_{m=1}^M \frac{p(\mathbf{z} \mid \mathbf{x}_m)p(\mathbf{x}_m)}{p(\mathbf{z})} \\ &\propto p(\mathbf{z}) \prod_{m=1}^M \frac{p(\mathbf{z} \mid \mathbf{x}_m)}{p(\mathbf{z})} \\ &\approx p(\mathbf{z}) \prod_{m=1}^M q_m(\mathbf{z} \mid \mathbf{x}_m), \end{aligned}$$

where  $q_m(\mathbf{z} \mid \mathbf{x}_m)$  is the “expert” for data modality  $m$

## Multimodal variational autoencoder with product of experts

From the conditional independence we get

$$\begin{aligned} p(\mathbf{z} \mid \mathbf{X}) &= \frac{p(\mathbf{z})p(\mathbf{x}_1, \dots, \mathbf{x}_m \mid \mathbf{z})}{p(\mathbf{x}_1, \dots, \mathbf{x}_m)} \\ &= \frac{p(\mathbf{z})}{p(\mathbf{x}_1, \dots, \mathbf{x}_m)} \prod_{m=1}^M p(\mathbf{x}_m \mid \mathbf{z}) \\ &= \frac{p(\mathbf{z})}{p(\mathbf{x}_1, \dots, \mathbf{x}_m)} \prod_{m=1}^M \frac{p(\mathbf{z} \mid \mathbf{x}_m)p(\mathbf{x}_m)}{p(\mathbf{z})} \\ &\propto p(\mathbf{z}) \prod_{m=1}^M \frac{p(\mathbf{z} \mid \mathbf{x}_m)}{p(\mathbf{z})} \\ &\approx p(\mathbf{z}) \prod_{m=1}^M q_m(\mathbf{z} \mid \mathbf{x}_m), \end{aligned}$$

where  $q_m(\mathbf{z} \mid \mathbf{x}_m)$  is the “expert” for data modality  $m$

This is known as the product of experts

Posterior approximation can be computed for any subset of modalities which are observed

If prior and experts are Gaussians

$$\begin{aligned} p(\mathbf{z}) &= \mathcal{N}(\mathbf{z} \mid \boldsymbol{\mu}_0, \boldsymbol{\Lambda}_0^{-1}) \\ q_m(\mathbf{z} \mid \mathbf{x}_m) &= \mathcal{N}(\mathbf{z} \mid \boldsymbol{\mu}_m, \boldsymbol{\Lambda}_m^{-1}), \end{aligned}$$

then the approximative posterior is also Gaussian

$$\begin{aligned} \prod_{m=0}^M \mathcal{N}(\mathbf{z} \mid \boldsymbol{\mu}_m, \boldsymbol{\Lambda}_m^{-1}) &\propto \mathcal{N}(\mathbf{z} \mid \boldsymbol{\mu}, \boldsymbol{\Sigma}) \\ \boldsymbol{\Sigma} = \left( \sum_{m=0}^M \boldsymbol{\Lambda}_m \right)^{-1} \quad \text{and} \quad \boldsymbol{\mu} = \boldsymbol{\Sigma} \left( \sum_{m=0}^M \boldsymbol{\Lambda}_m \boldsymbol{\mu}_m \right) \end{aligned}$$

## Multimodal variational autoencoder with product of experts: illustration






Figure 21.5 from (Murphy, 2023)

## Semi-supervised VAEs

Semi-supervised learning methods can be useful when data consists of large amounts of unlabeled data  $\mathcal{D}_U = \{(\mathbf{x}_n)\}$  and few labeled data points  $\mathcal{D}_L = \{(\mathbf{x}_n, y_n)\}$

One of the earliest models, called M2, is

$$p_{\theta}(\mathbf{x}, y) = p_{\theta}(y)p_{\theta}(\mathbf{x} \mid y) = p_{\theta}(y) \int p_{\theta}(\mathbf{x} \mid y, \mathbf{z})p_{\theta}(\mathbf{z})d\mathbf{z},$$

where  $p_{\theta}(\mathbf{z}) = \mathcal{N}(\mathbf{z} \mid \mathbf{0}, \mathbf{I})$ ,  $p_{\theta}(y) = \text{Cat}(y \mid \boldsymbol{\pi})$  is trainable label prior, and  $p_{\theta}(\mathbf{x} \mid y, \mathbf{z}) = p_{\theta}(\mathbf{x} \mid d_{\theta}(y, \mathbf{z}))$




Figure from (Maaloe et al, 2016)

Comparison to CVAE:

- $c$  is a fixed covariate/predictor
- here label  $y$  is a random variable

## Semi-supervised VAEs

Variational approximation for labeled data

$$\begin{aligned} q_{\phi}(\mathbf{z} \mid \mathbf{x}, y) &= q(\mathbf{z} \mid f_{\phi}(\mathbf{x}, y)) \\ &= \mathcal{N}(\mathbf{z} \mid \boldsymbol{\mu}_{\phi}(\mathbf{x}, y), \text{diag}(\boldsymbol{\sigma}_{\phi}(\mathbf{x}, y))) \end{aligned}$$

Standard ELBO for labeled data (by marginalizing  $\mathbf{z}$ )

$$\begin{aligned} \log p_{\theta}(\mathbf{x}, y) &\geq \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x}, y)} \left[ \log \frac{p_{\theta}(\mathbf{x}, y, \mathbf{z})}{q_{\phi}(\mathbf{z} \mid \mathbf{x}, y)} \right] \\ &= \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x}, y)} [\log p_{\theta}(\mathbf{x} \mid y, \mathbf{z}) + \log p_{\theta}(y) \\ &\quad + \log p_{\theta}(\mathbf{z}) - \log q_{\phi}(\mathbf{z} \mid \mathbf{x}, y)] \\ &= \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}, y) \end{aligned}$$

## Semi-supervised VAEs

Variational approximation for labeled data

$$\begin{aligned} q_{\phi}(\mathbf{z} \mid \mathbf{x}, y) &= q(\mathbf{z} \mid f_{\phi}(\mathbf{x}, y)) \\ &= \mathcal{N}(\mathbf{z} \mid \boldsymbol{\mu}_{\phi}(\mathbf{x}, y), \text{diag}(\boldsymbol{\sigma}_{\phi}(\mathbf{x}, y))) \end{aligned}$$

Standard ELBO for labeled data (by marginalizing  $\mathbf{z}$ )

$$\begin{aligned} \log p_{\theta}(\mathbf{x}, y) &\geq \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x}, y)} \left[ \log \frac{p_{\theta}(\mathbf{x}, y, \mathbf{z})}{q_{\phi}(\mathbf{z} \mid \mathbf{x}, y)} \right] \\ &= \mathbb{E}_{q_{\phi}(\mathbf{z} \mid \mathbf{x}, y)} [\log p_{\theta}(\mathbf{x} \mid y, \mathbf{z}) + \log p_{\theta}(y) \\ &\quad + \log p_{\theta}(\mathbf{z}) - \log q_{\phi}(\mathbf{z} \mid \mathbf{x}, y)] \\ &= \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}, y) \end{aligned}$$

Variational approximation for unlabeled data

$$\begin{aligned} q_{\phi}(\mathbf{z}, y \mid \mathbf{x}) &= q_{\phi}(\mathbf{z} \mid \mathbf{x}) q_{\phi}(y \mid \mathbf{x}) \\ q_{\phi}(\mathbf{z} \mid \mathbf{x}) &= \mathcal{N}(\mathbf{z} \mid \boldsymbol{\mu}_{\phi}(\mathbf{x}), \text{diag}(\boldsymbol{\sigma}_{\phi}(\mathbf{x}))) \\ q_{\phi}(y \mid \mathbf{x}) &= \text{Cat}(y \mid \boldsymbol{\pi}_{\phi}(\mathbf{x})) \end{aligned}$$

ELBO for unlabeled data by (marginalizing  $\mathbf{z}$  and  $y$ )

$$\begin{aligned} \log p_{\theta}(\mathbf{x}) &\geq \mathbb{E}_{q_{\phi}(\mathbf{z}, y \mid \mathbf{x})} \left[ \log \frac{p_{\theta}(\mathbf{x}, y, \mathbf{z})}{q_{\phi}(\mathbf{z}, y \mid \mathbf{x})} \right] \\ &= \mathbb{E}_{q_{\phi}(\mathbf{z}, y \mid \mathbf{x})} [\log p_{\theta}(\mathbf{x} \mid y, \mathbf{z}) + \log p_{\theta}(y) \\ &\quad + \log p_{\theta}(\mathbf{z}) - \log q_{\phi}(\mathbf{z}, y \mid \mathbf{x})] \\ &= \mathbb{E}_{q_{\phi}(y \mid \mathbf{x})} [\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}, y)] + \mathbb{H}(q_{\phi}(y \mid \mathbf{x})) \\ &= \mathcal{U}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) \end{aligned}$$

## Semi-supervised VAEs

Variational approximation  $q_\phi(y | \mathbf{x})$  can be considered as discriminative classifier

Because classifier is only used to compute log-likelihood of unlabeled data, a modified objective

$$\begin{aligned}\mathcal{L}'(\boldsymbol{\theta}, \boldsymbol{\phi} | \mathcal{D}_L, \mathcal{D}_U) &= \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} | \mathcal{D}_L) + \mathcal{U}(\boldsymbol{\theta}, \boldsymbol{\phi} | \mathcal{D}_U) \\ &\quad + \mathbb{E}_{(\mathbf{x}_n, y_n) \sim \mathcal{D}_L} \log q_\phi(y | \mathbf{x}),\end{aligned}$$

where  $(\mathbf{x}_n, y_n) \sim \mathcal{D}_L$  denotes labeled data distribution

$N$	NN	CNN	TSVM	CAE	MTC	AtlasRBF	M1+TSVM	M2	M1+M2
100	25.81	22.98	16.81	13.47	12.03	8.10 ( $\pm 0.95$ )	11.82 ( $\pm 0.25$ )	11.97 ( $\pm 1.71$ )	<b>3.33</b> ( $\pm 0.14$ )
600	11.44	7.68	6.16	6.3	5.13	—	5.72 ( $\pm 0.049$ )	4.94 ( $\pm 0.13$ )	<b>2.59</b> ( $\pm 0.05$ )
1000	10.7	6.45	5.38	4.77	3.64	3.68 ( $\pm 0.12$ )	4.24 ( $\pm 0.07$ )	3.60 ( $\pm 0.56$ )	<b>2.40</b> ( $\pm 0.02$ )
3000	6.04	3.35	3.45	3.22	2.57	—	3.49 ( $\pm 0.04$ )	3.92 ( $\pm 0.63$ )	<b>2.18</b> ( $\pm 0.04$ )

Figure from (Kingma et al, 2014)

## Semi-supervised VAEs

Variational approximation  $q_\phi(y | \mathbf{x})$  can be considered as discriminative classifier

Because classifier is only used to compute log-likelihood of unlabeled data, a modified objective

$$\begin{aligned}\mathcal{L}'(\theta, \phi | \mathcal{D}_L, \mathcal{D}_U) = & \mathcal{L}(\theta, \phi | \mathcal{D}_L) + \mathcal{U}(\theta, \phi | \mathcal{D}_U) \\ & + \mathbb{E}_{(\mathbf{x}_n, y_n) \sim \mathcal{D}_L} \log q_\phi(y | \mathbf{x}),\end{aligned}$$

where  $(\mathbf{x}_n, y_n) \sim \mathcal{D}_L$  denotes labeled data distribution

Methods have been further developed e.g. by adding additional latent variables (e.g. Maaloe et al, 2016) among others

$N$	NN	CNN	TSVM	CAE	MTC	AtlasRBF	M1+TSVM	M2	M1+M2
100	25.81	22.98	16.81	13.47	12.03	8.10 ( $\pm 0.95$ )	11.82 ( $\pm 0.25$ )	11.97 ( $\pm 1.71$ )	<b>3.33</b> ( $\pm 0.14$ )
600	11.44	7.68	6.16	6.3	5.13	—	5.72 ( $\pm 0.049$ )	4.94 ( $\pm 0.13$ )	<b>2.59</b> ( $\pm 0.05$ )
1000	10.7	6.45	5.38	4.77	3.64	3.68 ( $\pm 0.12$ )	4.24 ( $\pm 0.07$ )	3.60 ( $\pm 0.56$ )	<b>2.40</b> ( $\pm 0.02$ )
3000	6.04	3.35	3.45	3.22	2.57	—	3.49 ( $\pm 0.04$ )	3.92 ( $\pm 0.63$ )	<b>2.18</b> ( $\pm 0.04$ )

Figure from (Kingma et al, 2014)

## Hierarchical VAEs

We can define hierarchical VAEs with  $K$  stochastic layers

$\mathbf{z}_{1:K} = (\mathbf{z}_1, \dots, \mathbf{z}_K)$  as follows

$$p_{\theta}(\mathbf{x}, \mathbf{z}_{1:K}) = p_{\theta}(\mathbf{z}_K) \prod_{k=1}^K p_{\theta}(\mathbf{z}_k | \mathbf{z}_{k+1}) p_{\theta}(\mathbf{x} | \mathbf{z}_1)$$

Generative model can be extended into non-Markovian model

$$p_{\theta}(\mathbf{x}, \mathbf{z}_{1:K}) = p_{\theta}(\mathbf{z}_K) \prod_{k=1}^K p_{\theta}(\mathbf{z}_k | \mathbf{z}_{k+1:K}) p_{\theta}(\mathbf{x} | \mathbf{z}_{1:K})$$

Similar to using skip connection architecture




Figure 21.11 from (Murphy et al, 2023)

## Hierarchical VAEs: inference model

Variational inference model can be define as bottom-up

$$q_{\phi}(\mathbf{z}_{1:K}) = q_{\phi}(\mathbf{z}_1 \mid \mathbf{x}) \prod_{k=2}^K q_{\phi}(\mathbf{z}_k \mid \mathbf{x}, \mathbf{z}_{1:k-1})$$

## Hierarchical VAEs: inference model

Variational inference model can be defined as bottom-up

$$q_{\phi}(\mathbf{z}_{1:K}) = q_{\phi}(\mathbf{z}_1 \mid \mathbf{x}) \prod_{k=2}^K q_{\phi}(\mathbf{z}_k \mid \mathbf{x}, \mathbf{z}_{1:k-1})$$

or as top-down

$$q_{\phi}(\mathbf{z}_{1:K}) = q_{\phi}(\mathbf{z}_K \mid \mathbf{x}) \prod_{k=K-1}^1 q_{\phi}(\mathbf{z}_k \mid \mathbf{x}, \mathbf{z}_{k+1:K})$$

## Hierarchical VAEs: inference model

Variational inference model can be defined as bottom-up

$$q_{\phi}(\mathbf{z}_{1:K}) = q_{\phi}(\mathbf{z}_1 | \mathbf{x}) \prod_{k=2}^K q_{\phi}(\mathbf{z}_k | \mathbf{x}, \mathbf{z}_{1:k-1})$$

or as top-down

$$q_{\phi}(\mathbf{z}_{1:K}) = q_{\phi}(\mathbf{z}_K | \mathbf{x}) \prod_{k=K-1}^1 q_{\phi}(\mathbf{z}_k | \mathbf{x}, \mathbf{z}_{k+1:K})$$

or both

Top-down inference model is generally considered better because it can be shown to more closely approximate the true posterior of a given layer




Figure 21.11 from (Murphy et al, 2023)

## Hierarchical VAEs: ELBO

Evidence lower-bound for hierarchical VAE with top-down inference model is

$$\begin{aligned}\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) &= \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} [\log p_{\boldsymbol{\theta}}(\mathbf{x} \mid z_{1:K})] - D_{\text{KL}}(q_{\boldsymbol{\phi}}(\mathbf{z}_K \mid \mathbf{x}) \parallel p_{\boldsymbol{\theta}}(\mathbf{z}_K)) \\ &\quad - \sum_{k=K-1}^1 \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{k+1:K} \mid \mathbf{x})} D_{\text{KL}}(q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x}, \mathbf{z}_{k+1:K}) \parallel p_{\boldsymbol{\theta}}(\mathbf{z}_k \mid \mathbf{z}_{k+1:K})),\end{aligned}$$

where  $q_{\boldsymbol{\phi}}(\mathbf{z}_{k+1:K} \mid \mathbf{x}) = \prod_{i=k+1}^K q_{\boldsymbol{\phi}}(\mathbf{z}_i \mid \mathbf{x}, \mathbf{z}_{i+1:K})$

## Hierarchical VAE example

So-called very deep VAE (VDVAE) model uses hierarchical VAE with bidirectional CNN architecture and nearest neighbour upsampling

Low-resolution (top) latents capture global structure, while the bottom of the hierarchy fills in details




Figure 21.12 from (Murphy et al, 2023)

## Hierarchical VAE example

So-called very deep VAE (VDVAE) model uses hierarchical VAE with bidirectional CNN architecture and nearest neighbour upsampling

Low-resolution (top) latents capture global structure, while the bottom of the hierarchy fills in details



Figure 21.13 from (Murphy et al, 2023)

## Recap: Marginal likelihood, ELBO, importance sampling

### Marginal likelihood and ELBO

$$\log p_{\theta}(\mathbf{x}) = \log \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{x})} \left[ \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\phi}(\mathbf{z} | \mathbf{x})} \right] \stackrel{\text{Jensen}}{\geq} \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{x})} \left[ \log \left( \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\phi}(\mathbf{z} | \mathbf{x})} \right) \right] = \mathcal{L}(\theta, \phi | \mathbf{x})$$

and Monte Carlo estimate

$$\mathcal{L}(\theta, \phi | \mathbf{x}) \approx \frac{1}{S} \left( \sum_{s=1}^S \log \frac{p_{\theta}(\mathbf{x}, \mathbf{z}_s)}{q_{\phi}(\mathbf{z}_s | \mathbf{x})} \right) \quad \text{where} \quad \mathbf{z}_s \stackrel{\text{i.i.d.}}{\sim} q_{\phi}(\mathbf{z} | \mathbf{x})$$

## Recap: Marginal likelihood, ELBO, importance sampling

### Marginal likelihood and ELBO

$$\log p_{\theta}(\mathbf{x}) = \log \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{x})} \left[ \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\phi}(\mathbf{z} | \mathbf{x})} \right] \stackrel{\text{Jensen}}{\geq} \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{x})} \left[ \log \left( \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\phi}(\mathbf{z} | \mathbf{x})} \right) \right] = \mathcal{L}(\theta, \phi | \mathbf{x})$$

and Monte Carlo estimate

$$\mathcal{L}(\theta, \phi | \mathbf{x}) \approx \frac{1}{S} \left( \sum_{s=1}^S \log \frac{p_{\theta}(\mathbf{x}, \mathbf{z}_s)}{q_{\phi}(\mathbf{z}_s | \mathbf{x})} \right) \quad \text{where} \quad \mathbf{z}_s \stackrel{\text{i.i.d.}}{\sim} q_{\phi}(\mathbf{z} | \mathbf{x})$$

Importance sampling estimate of  $p_{\theta}(\mathbf{x})$  and  $\log p_{\theta}(\mathbf{x})$

$$p_{\theta}(\mathbf{x}) = \mathbb{E}_{q_{\phi}(\mathbf{z} | \mathbf{x})} \left[ \frac{p_{\theta}(\mathbf{x}, \mathbf{z})}{q_{\phi}(\mathbf{z} | \mathbf{x})} \right] \approx \frac{1}{S} \sum_{s=1}^S \tilde{w}_s \quad \text{and} \quad \log p_{\theta}(\mathbf{x}) \approx \log \left( \frac{1}{S} \sum_{s=1}^S \tilde{w}_s \right)$$

where

$$\tilde{w}_s = \frac{p_{\theta}(\mathbf{x}, \mathbf{z}_s)}{q_{\phi}(\mathbf{z}_s | \mathbf{x})}, \quad \mathbf{z}_s \stackrel{\text{i.i.d.}}{\sim} q_{\phi}(\mathbf{z} | \mathbf{x}), \quad \sup p_{\theta} \subseteq \sup q_{\phi}$$

## Importance weighted variational autoencoder

Empirical estimate of the importance weighted variational autoencoder (IWAE) objective

$$\tilde{\mathcal{L}}_K^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \log \left( \frac{1}{K} \sum_{k=1}^K \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z}_k)}{q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})} \right) = \log \left( \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right) \approx \log p_{\boldsymbol{\theta}}(\mathbf{x})$$

where

$$\mathbf{z}_k \stackrel{\text{i.i.d.}}{\sim} q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})$$

## Importance weighted variational autoencoder

Empirical estimate of the importance weighted variational autoencoder (IWAE) objective

$$\tilde{\mathcal{L}}_K^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \log \left( \frac{1}{K} \sum_{k=1}^K \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z}_k)}{q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})} \right) = \log \left( \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right) \approx \log p_{\boldsymbol{\theta}}(\mathbf{x})$$

where

$$\mathbf{z}_k \stackrel{\text{i.i.d.}}{\sim} q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})$$

By defining  $q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x}) = \prod_{k=1}^K q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})$ , IWAE objective (also called as the multiple-sample ELBO) is

$$\mathcal{L}_K^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} \left[ \log \frac{1}{K} \sum_{k=1}^K \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z}_k)}{q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})} \right] = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} \left[ \log \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right],$$

where

$$\tilde{w}_k = \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z}_k)}{q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})}$$

## Importance weighted variational autoencoder: properties

- ① IWAE objective reduces to the standard single sample ELBO when  $K = 1$

$$\mathcal{L}_1^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:1} \mid \mathbf{x})} \left[ \log \frac{1}{1} \sum_{k=1}^1 \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z}_k)}{q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})} \right] = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})} \left[ \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z})}{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})} \right] = \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x})$$

## Importance weighted variational autoencoder: properties

- ① IWAE objective reduces to the standard single sample ELBO when  $K = 1$

$$\mathcal{L}_1^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:1} \mid \mathbf{x})} \left[ \log \frac{1}{1} \sum_{k=1}^1 \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z}_k)}{q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})} \right] = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})} \left[ \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z})}{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})} \right] = \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x})$$

- ② IWAE objective is a lower bound for  $\log p_{\boldsymbol{\theta}}(\mathbf{x})$

$$\mathcal{L}_K^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} \left[ \log \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right] \stackrel{\text{Jensen}}{\leq} \log \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} \left[ \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right] = \log p_{\boldsymbol{\theta}}(\mathbf{x})$$

## Importance weighted variational autoencoder: properties

- ① IWAE objective reduces to the standard single sample ELBO when  $K = 1$

$$\mathcal{L}_1^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:1} \mid \mathbf{x})} \left[ \log \frac{1}{1} \sum_{k=1}^1 \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z}_k)}{q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})} \right] = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})} \left[ \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z})}{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})} \right] = \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x})$$

- ② IWAE objective is a lower bound for  $\log p_{\boldsymbol{\theta}}(\mathbf{x})$

$$\mathcal{L}_K^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} \left[ \log \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right] \stackrel{\text{Jensen}}{\leq} \log \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} \left[ \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right] = \log p_{\boldsymbol{\theta}}(\mathbf{x})$$

- ③ For any  $K \geq 1$ , IWAE lower bound satisfies

$$\mathcal{L}_K^{\text{IWAE}} \leq \mathcal{L}_{K+1}^{\text{IWAE}} \leq \log p_{\boldsymbol{\theta}}(\mathbf{x})$$

## Importance weighted variational autoencoder: properties

- ① IWAE objective reduces to the standard single sample ELBO when  $K = 1$

$$\mathcal{L}_1^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:1} \mid \mathbf{x})} \left[ \log \frac{1}{1} \sum_{k=1}^1 \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z}_k)}{q_{\boldsymbol{\phi}}(\mathbf{z}_k \mid \mathbf{x})} \right] = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})} \left[ \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}, \mathbf{z})}{q_{\boldsymbol{\phi}}(\mathbf{z} \mid \mathbf{x})} \right] = \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x})$$

- ② IWAE objective is a lower bound for  $\log p_{\boldsymbol{\theta}}(\mathbf{x})$

$$\mathcal{L}_K^{\text{IWAE}}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} \left[ \log \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right] \stackrel{\text{Jensen}}{\leq} \log \mathbb{E}_{q_{\boldsymbol{\phi}}(\mathbf{z}_{1:K} \mid \mathbf{x})} \left[ \frac{1}{K} \sum_{k=1}^K \tilde{w}_k \right] = \log p_{\boldsymbol{\theta}}(\mathbf{x})$$

- ③ For any  $K \geq 1$ , IWAE lower bound satisfies

$$\mathcal{L}_K^{\text{IWAE}} \leq \mathcal{L}_{K+1}^{\text{IWAE}} \leq \log p_{\boldsymbol{\theta}}(\mathbf{x})$$

- ④ IWAE lower bound approaches the true log marginal likelihood in the limit

$$\lim_{K \rightarrow \infty} \mathcal{L}_K^{\text{IWAE}} = \log p_{\boldsymbol{\theta}}(\mathbf{x})$$

## Identifiability of VAEs

Consider VAE model with linear parametrization

$$\begin{aligned} p(\mathbf{x} \mid \mathbf{z}) &= \mathcal{N}(\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \sigma^2 \mathbf{I}) \\ q(\mathbf{z} \mid \mathbf{x}) &= \mathcal{N}(\mathbf{V}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{D}), \end{aligned}$$

where  $\mathbf{D}$  is diagonal and all parameters are shared with all samples

VAE models are trained via ELBO  $\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) \leq \log p_{\boldsymbol{\theta}}(\mathbf{x})$

Probabilistic principle component analysis (PPCA) is equivalent with the above **decoder model**

- Marginal likelihood  $\log p(\mathbf{x})$  has closed-form
- Posterior  $p(\mathbf{z} \mid \mathbf{x})$  has closed-form
- Maximum likelihood parameter estimates have also closed form (up to rotation), i.e., identifiable

## Identifiability of VAEs

Consider VAE model with linear parametrization

$$p(\mathbf{x} \mid \mathbf{z}) = \mathcal{N}(\mathbf{W}\mathbf{z} + \boldsymbol{\mu}, \sigma^2 \mathbf{I})$$
$$q(\mathbf{z} \mid \mathbf{x}) = \mathcal{N}(\mathbf{V}(\mathbf{x} - \boldsymbol{\mu}), \mathbf{D}),$$

where  $\mathbf{D}$  is diagonal and all parameters are shared with all samples

VAE models are trained via ELBO  $\mathcal{L}(\boldsymbol{\theta}, \boldsymbol{\phi} \mid \mathbf{x}) \leq \log p_{\boldsymbol{\theta}}(\mathbf{x})$

Probabilistic principle component analysis (PPCA) is equivalent with the above **decoder model**

- Marginal likelihood  $\log p(\mathbf{x})$  has closed-form
- Posterior  $p(\mathbf{z} \mid \mathbf{x})$  has closed-form
- Maximum likelihood parameter estimates have also closed form (up to rotation), i.e., identifiable

### Identifiability of linear VAE (Lucas et al., 2019)

The global maximum of the ELBO for the linear VAE

- Is identical to the global maximum for the log marginal likelihood of PPCA
- Has the scaled principal components as the columns of the decoder network

## Identifiability of VAEs

An unconstrained deep latent variable model  $p_{\theta}(\mathbf{x}, \mathbf{z}) = p_{\theta}(\mathbf{x} | \mathbf{z})p_{\theta}(\mathbf{z})$  is not in general identifiable

Model identifiability can be proved by assuming specific sparsity in  $p_{\theta}(\mathbf{x} | \mathbf{z})$  and additional technical assumptions (Moran et al., 2022)




Figure from (Moran et al, 2022)

## Identifiability of CVAEs

Consider a CVAE with conditional generative model  $p_{\theta}(\mathbf{x}, \mathbf{z} | \mathbf{c}) = p_{\theta}(\mathbf{x} | \mathbf{z})p_{\theta}(\mathbf{z} | \mathbf{c})$

- Assume prior  $p_{\theta}(\mathbf{z} | \mathbf{c})$  is mean field with exponential family of distributions
- Covariate  $\mathbf{c}$  has at least  $\dim(\mathbf{z}) \cdot k + 1$  distinct values, where  $k$  denotes the number of sufficient statistics of the prior
- Amortized variational approximation  $q_{\phi}(\mathbf{z} | \mathbf{x}, \mathbf{c})$  includes the true posterior
- + Additional technical assumptions (Khemakem et al., 2020)

Then the parameters of the CVAE are **asymptotically** identifiable (Khemakem et al., 2020)

## Amortized VI: amortization gap

## References

- Agarwal S, Hope G, Younis A, Sudderth EB, A decoder suffices for query-adaptive variational inference, *Uncertainty in Artificial Intelligence*, 2023.
- Khemakhem I, Kingma D, Monti R, Hyvärinen A, Variational autoencoders and nonlinear ICA: A unifying framework, *International Conference on Artificial Intelligence and Statistics*, 2020.
- Kingma DP and Welling M, An Introduction to variational autoencoders, *Foundations and Trends in Machine Learning*, Vol. 12, No. 4, pp. 307-392.
- Kingma DP, Rezende DJ, Mohamed S, Welling M, Semi-supervised learning with deep generative models, *Neural information processing systems*, 2014.
- Lucas J, Tucker G, Grosse R, Norouzi M, Don't blame the ELBO! A linear VAE perspective on posterior collapse, *Neural Information Processing Systems*, 2019.
- Maaloe L, Sonderby CK, Sønderby SK, Winther O, Auxiliary deep generative models, *International Conference on Machine Learning*, PMLR 48:1445-1453, 2016.
- Moran GE, Sridhar D, Wang Y, Blei DM, Identifiable deep generative models via sparse decoding, *Transactions on Machine Learning Research*, 2022.
- Murphy K, Probabilistic Machine Learning: Advanced Topics, 2023.
- Prince SJD, Understanding Deep Learning, The MIT Press, 2023.
- Strauss R, Oliva J, Posterior matching for arbitrary conditioning, *Advances in Neural Information Processing Systems*, 2022.

# CS-E4891 Deep Generative Models

## Lecture 4: Diffusion models

Harri Lähdesmäki

Department of Computer Science  
Aalto University

April 14, 2025

## Outline

- Denoising diffusion probabilistic model (Section 25.2 from (Murphy, 2023))
- Continuous-time diffusion models (Section 25.4 from (Murphy, 2023))
- Latent diffusion (Section 25.5 from (Murphy, 2023))
- Conditional diffusion models (Section 25.6 from (Murphy, 2023))
- Reading: parts of Sec. 25 from (Murphy, 2023), Sec. 18 from (Prince, 2023), and other literature (see references at the end)

## Denoising diffusion probabilistic model

Diffusion models build on a simple idea:

- It is hard to convert pure noise to structured data
- It is easy to convert structured data into a noise

# Denoising diffusion probabilistic model

Diffusion models build on a simple idea:

- It is hard to convert pure noise to structured data
- It is easy to convert structured data into a noise

Denoising diffusion probabilistic model (DDPM) can be thought of as a hierarchical VAE, where

- All latent layers  $\mathbf{x}_{1:T} = (\mathbf{x}_1, \dots, \mathbf{x}_T)$  have the same dimensionality as data  $\mathbf{x}_0$
- Encoder model (variational inference) is a simple and fixed linear Gaussian model
- Decoder model (generative model) is shared across layers




Illustration: Figure 25.1 from (Murphy, 2023)

## DDPM: forward process

The forward diffusion process (=encoder) is a simple Gaussian noise model

$$q(\mathbf{x}_t \mid \mathbf{x}_{t-1}) = \mathcal{N}(\mathbf{x}_t \mid \sqrt{1 - \beta_t} \mathbf{x}_{t-1}, \beta_t \mathbf{I}),$$

where  $\beta_t \in (0, 1)$  is defined by a noise schedule  $\beta_1, \beta_2, \dots, \beta_T$

The joint distribution over latent variables is

$$q(\mathbf{x}_{1:T}) = \prod_{t=1}^T q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$$

## DDPM: forward process

The forward diffusion process (=encoder) is a simple Gaussian noise model

$$q(\mathbf{x}_t \mid \mathbf{x}_{t-1}) = \mathcal{N}(\mathbf{x}_t \mid \sqrt{1 - \beta_t} \mathbf{x}_{t-1}, \beta_t \mathbf{I}),$$

where  $\beta_t \in (0, 1)$  is defined by a noise schedule  $\beta_1, \beta_2, \dots, \beta_T$

The joint distribution over latent variables is


$$q(\mathbf{x}_{1:T}) = \prod_{t=1}^T q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$$

This is a linear Markov chain for which marginals can be computed analytically (see (Prince, 2023) for details)

$$q(\mathbf{x}_t \mid \mathbf{x}_0) = \mathcal{N}(\mathbf{x}_t \mid \sqrt{\bar{\alpha}_t} \mathbf{x}_0, (1 - \bar{\alpha}_t) \mathbf{I}), \quad \text{where } \alpha_t = 1 - \beta_t \quad \text{and} \quad \bar{\alpha}_t = \prod_{s=1}^t \alpha_s$$


Choose noise schedule such that  $\bar{\alpha}_T \approx 0$  and  $q(\mathbf{x}_T \mid \mathbf{x}_0) \approx \mathcal{N}(\mathbf{0}, \mathbf{I})$

## DDPM: forward process



1-D Illustration of  $q(\mathbf{x}_t | \mathbf{x}_{t-1})$  with  $\beta_t = 0.03$ . Figure 18.2 from (Prince, 2023)

## DDPM: forward process



1-D Illustration of  $q(x_t | x_0)$ . Figure 18.3 from (Prince, 2023)

## DDPM: reverse process

To generate data, we would ideally like to directly reverse the forward process  $q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$

$$q(\mathbf{x}_{t-1} \mid \mathbf{x}_t) = \frac{q(\mathbf{x}_t \mid \mathbf{x}_{t-1})q(\mathbf{x}_{t-1})}{q(\mathbf{x}_t)}$$

## DDPM: reverse process

To generate data, we would ideally like to directly reverse the forward process  $q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$

$$q(\mathbf{x}_{t-1} \mid \mathbf{x}_t) = \frac{q(\mathbf{x}_t \mid \mathbf{x}_{t-1})q(\mathbf{x}_{t-1})}{q(\mathbf{x}_t)}$$

but we cannot analytically solve  $q(\mathbf{x}_{t-1})$  or  $q(\mathbf{x}_t)$  because

$$q(\mathbf{x}_t) = \int q(\mathbf{x}_t \mid \mathbf{x})p_{\mathcal{D}}(\mathbf{x})d\mathbf{x}$$

## DDPM: reverse process

To generate data, we would ideally like to directly reverse the forward process  $q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$

$$q(\mathbf{x}_{t-1} \mid \mathbf{x}_t) = \frac{q(\mathbf{x}_t \mid \mathbf{x}_{t-1})q(\mathbf{x}_{t-1})}{q(\mathbf{x}_t)}$$

but we cannot analytically solve  $q(\mathbf{x}_{t-1})$  or  $q(\mathbf{x}_t)$  because

$$q(\mathbf{x}_t) = \int q(\mathbf{x}_t \mid \mathbf{x}) p_{\mathcal{D}}(\mathbf{x}) d\mathbf{x}$$

If the input  $\mathbf{x}_0$  was known, using properties of Gaussians (see e.g. (Prince, 2023) for details)

$$\begin{aligned} q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0) &= \mathcal{N}(\mathbf{x}_{t-1} \mid \tilde{\mu}_t(\mathbf{x}_t, \mathbf{x}_0), \tilde{\beta}_t \mathbf{I}) \\ \tilde{\mu}_t(\mathbf{x}_t, \mathbf{x}_0) &= \frac{\sqrt{\bar{\alpha}_{t-1}} \beta_t}{1 - \bar{\alpha}_t} \mathbf{x}_0 + \frac{\sqrt{\alpha_t}(1 - \bar{\alpha}_{t-1})}{1 - \bar{\alpha}_t} \mathbf{x}_t \\ \tilde{\beta}_t &= \frac{1 - \bar{\alpha}_{t-1}}{1 - \bar{\alpha}_t} \beta_t \end{aligned}$$

This does not serve us because  $\mathbf{x}_0$  is not known when generating new data

## DDPM: learnable reverse process

We can learn a reverse diffusion process (=decoder) that aims to invert the forward process

Generator can be chosen to have the following form

$$p_{\theta}(\mathbf{x}_{t-1} \mid \mathbf{x}_t) = \mathcal{N}(\mathbf{x}_{t-1} \mid \boldsymbol{\mu}_{\theta}(\mathbf{x}_t, t), \boldsymbol{\Sigma}_{\theta}(\mathbf{x}_t, t)), \quad \text{where often} \quad \boldsymbol{\Sigma}_{\theta}(\mathbf{x}_t, t) = \sigma_t^2 \mathbf{I}$$

where  $\boldsymbol{\mu}_{\theta}(\mathbf{x}_t, t)$  is trainable neural net

## DDPM: learnable reverse process

We can learn a reverse diffusion process (=decoder) that aims to invert the forward process

Generator can be chosen to have the following form

$$p_{\theta}(\mathbf{x}_{t-1} \mid \mathbf{x}_t) = \mathcal{N}(\mathbf{x}_{t-1} \mid \boldsymbol{\mu}_{\theta}(\mathbf{x}_t, t), \boldsymbol{\Sigma}_{\theta}(\mathbf{x}_t, t)), \quad \text{where often} \quad \boldsymbol{\Sigma}_{\theta}(\mathbf{x}_t, t) = \sigma_t^2 \mathbf{I}$$


where  $\boldsymbol{\mu}_{\theta}(\mathbf{x}_t, t)$  is trainable neural net

The joint distribution of generated variables is

$$\begin{aligned} p_{\theta}(\mathbf{x}_{0:T}) &= p(\mathbf{x}_T)p_{\theta}(\mathbf{x}_{T-1} \mid \mathbf{x}_T) \cdots p_{\theta}(\mathbf{x}_0 \mid \mathbf{x}_1) \\ &= p(\mathbf{x}_T) \prod_{t=1}^T p_{\theta}(\mathbf{x}_{t-1} \mid \mathbf{x}_t) \end{aligned}$$

where  $p(\mathbf{x}_T) = \mathcal{N}(\mathbf{0}, \mathbf{I})$

## DDPM model components



## DDPM: model fitting

We can fit the model using ELBO

$$\begin{aligned}\log p_{\boldsymbol{\theta}}(\mathbf{x}_0) &= \log \left[ \int p_{\boldsymbol{\theta}}(\mathbf{x}_0, \mathbf{x}_{1:T}) d\mathbf{x}_{1:T} \right] \\ &= \log \left[ \int \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{0:T})}{q(\mathbf{x}_{1:T} \mid \mathbf{x}_0)} q(\mathbf{x}_{1:T} \mid \mathbf{x}_0) d\mathbf{x}_{1:T} \right] \\ &= \log \mathbb{E}_{q(\mathbf{x}_{1:T} \mid \mathbf{x}_0)} \left[ \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{0:T})}{q(\mathbf{x}_{1:T} \mid \mathbf{x}_0)} \right] \\ &\stackrel{\text{Jensen}}{\geq} \mathbb{E}_q \left[ \log \left( \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{0:T})}{q(\mathbf{x}_{1:T} \mid \mathbf{x}_0)} \right) \right] \\ &= \mathbb{E}_q \left[ \log \left( p(\mathbf{x}_T) \prod_{t=1}^T \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} \mid \mathbf{x}_t)}{q(\mathbf{x}_t \mid \mathbf{x}_{t-1})} \right) \right] \\ &= \mathbb{E}_q \left[ \log p(\mathbf{x}_T) + \sum_{t=1}^T \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} \mid \mathbf{x}_t)}{q(\mathbf{x}_t \mid \mathbf{x}_{t-1})} \right] \\ &= \mathcal{L}(\boldsymbol{\theta} \mid \mathbf{x}_0)\end{aligned}$$

## DDPM: model fitting details

By the Markov property and Bayes's rule we have

$$q(\mathbf{x}_t \mid \mathbf{x}_{t-1}) = q(\mathbf{x}_t \mid \mathbf{x}_{t-1}, \mathbf{x}_0) = \frac{q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0)q(\mathbf{x}_t \mid \mathbf{x}_0)}{q(\mathbf{x}_{t-1} \mid \mathbf{x}_0)}$$

## DDPM: model fitting details

By the Markov property and Bayes's rule we have

$$q(\mathbf{x}_t \mid \mathbf{x}_{t-1}) = q(\mathbf{x}_t \mid \mathbf{x}_{t-1}, \mathbf{x}_0) = \frac{q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0)q(\mathbf{x}_t \mid \mathbf{x}_0)}{q(\mathbf{x}_{t-1} \mid \mathbf{x}_0)}$$

By plugging  $q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$  into  $\mathcal{L}(\boldsymbol{\theta} \mid \mathbf{x}_0)$  we get

$$\mathcal{L}(\boldsymbol{\theta} \mid \mathbf{x}_0) = \mathbb{E}_{q(\mathbf{x}_{1:T} \mid \mathbf{x}_0)} \left[ \log p(\mathbf{x}_T) + \sum_{t=2}^T \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} \mid \mathbf{x}_t)}{q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0)} + \underbrace{\sum_{t=2}^T \log \frac{q(\mathbf{x}_{t-1} \mid \mathbf{x}_0)}{q(\mathbf{x}_t \mid \mathbf{x}_0)}}_{* \text{ telescoping sum}} + \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_0 \mid \mathbf{x}_1)}{q(\mathbf{x}_1 \mid \mathbf{x}_0)} \right],$$

## DDPM: model fitting details

By the Markov property and Bayes's rule we have

$$q(\mathbf{x}_t \mid \mathbf{x}_{t-1}) = q(\mathbf{x}_t \mid \mathbf{x}_{t-1}, \mathbf{x}_0) = \frac{q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0)q(\mathbf{x}_t \mid \mathbf{x}_0)}{q(\mathbf{x}_{t-1} \mid \mathbf{x}_0)}$$

By plugging  $q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$  into  $\mathcal{L}(\boldsymbol{\theta} \mid \mathbf{x}_0)$  we get

$$\mathcal{L}(\boldsymbol{\theta} \mid \mathbf{x}_0) = \mathbb{E}_{q(\mathbf{x}_{1:T} \mid \mathbf{x}_0)} \left[ \log p(\mathbf{x}_T) + \sum_{t=2}^T \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} \mid \mathbf{x}_t)}{q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0)} + \underbrace{\sum_{t=2}^T \log \frac{q(\mathbf{x}_{t-1} \mid \mathbf{x}_0)}{q(\mathbf{x}_t \mid \mathbf{x}_0)}}_{* \text{ telescoping sum}} + \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_0 \mid \mathbf{x}_1)}{q(\mathbf{x}_1 \mid \mathbf{x}_0)} \right],$$

where telescoping sum reduces to

$$\begin{aligned} * &= \left( \log q(\mathbf{x}_1 \mid \mathbf{x}_0) - \log q(\mathbf{x}_2 \mid \mathbf{x}_0) \right) + \left( \log q(\mathbf{x}_2 \mid \mathbf{x}_0) - \log q(\mathbf{x}_3 \mid \mathbf{x}_0) \right) + \dots \\ &\quad + \left( \log q(\mathbf{x}_{T-1} \mid \mathbf{x}_0) - \log q(\mathbf{x}_T \mid \mathbf{x}_0) \right) \\ &= \log q(\mathbf{x}_1 \mid \mathbf{x}_0) - \log q(\mathbf{x}_T \mid \mathbf{x}_0) \end{aligned}$$

## DDPM: model fitting details

ELBO reduces to

$$\begin{aligned}\mathcal{L}(\boldsymbol{\theta} \mid \mathbf{x}_0) &= \mathbb{E}_{q(\mathbf{x}_{1:T} \mid \mathbf{x}_0)} \left[ \log p(\mathbf{x}_T) + \sum_{t=2}^T \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} \mid \mathbf{x}_t)}{q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0)} + \log \frac{q(\mathbf{x}_1 \mid \mathbf{x}_0)}{q(\mathbf{x}_T \mid \mathbf{x}_0)} + \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_0 \mid \mathbf{x}_1)}{q(\mathbf{x}_1 \mid \mathbf{x}_0)} \right] \\ &= \mathbb{E}_{q(\mathbf{x}_{1:T} \mid \mathbf{x}_0)} \left[ \log \frac{p(\mathbf{x}_T)}{q(\mathbf{x}_T \mid \mathbf{x}_0)} + \sum_{t=2}^T \log \frac{p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} \mid \mathbf{x}_t)}{q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0)} + \log p_{\boldsymbol{\theta}}(\mathbf{x}_0 \mid \mathbf{x}_1) \right] \\ &= \underbrace{\mathbb{E}_{q(\mathbf{x}_1 \mid \mathbf{x}_0)} [\log p_{\boldsymbol{\theta}}(\mathbf{x}_0 \mid \mathbf{x}_1)]}_{L_0(\mathbf{x}_0)} - \sum_{t=2}^T \mathbb{E}_{q(\mathbf{x}_t \mid \mathbf{x}_0)} \underbrace{[D_{\text{KL}}(q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0) \parallel p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} \mid \mathbf{x}_t))]}_{L_{t-1}(\mathbf{x}_0)} \\ &\quad + \underbrace{D_{\text{KL}}(q(\mathbf{x}_T \mid \mathbf{x}_0) \parallel p(\mathbf{x}_T))}_{L_T(\mathbf{x}_0)}\end{aligned}$$

All KL divergences can be computed analytically because all distributions are Gaussians

## DDPM: model fitting details for $L_{t-1}(\mathbf{x}_0)$

Recall that the KL between two multivariate Gaussians is:

$$\begin{aligned} D_{\text{KL}}(\mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1) || \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2)) &= \frac{1}{2} \left[ \text{tr}(\boldsymbol{\Sigma}_2^{-1} \boldsymbol{\Sigma}_1) + (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2)^\top \boldsymbol{\Sigma}_2^{-1} (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2) \right. \\ &\quad \left. - D + \log \left( \frac{\det(\boldsymbol{\Sigma}_2)}{\det(\boldsymbol{\Sigma}_1)} \right) \right] \end{aligned}$$

## DDPM: model fitting details for $L_{t-1}(\mathbf{x}_0)$

Recall that the KL between two multivariate Gaussians is:

$$D_{\text{KL}}(\mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1) || \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2)) = \frac{1}{2} \left[ \text{tr}(\boldsymbol{\Sigma}_2^{-1} \boldsymbol{\Sigma}_1) + (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2)^\top \boldsymbol{\Sigma}_2^{-1} (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2) \right. \\ \left. - D + \log \left( \frac{\det(\boldsymbol{\Sigma}_2)}{\det(\boldsymbol{\Sigma}_1)} \right) \right]$$

Thus,  $L_{t-1}(\mathbf{x}_0)$  term can be written as

$$D_{\text{KL}}(q(\mathbf{x}_{t-1} | \mathbf{x}_t, \mathbf{x}_0) || p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} | \mathbf{x}_t)) = \frac{1}{2\sigma_t^2} \|\tilde{\mu}_t(\mathbf{x}_t, \mathbf{x}_0) - \boldsymbol{\mu}_{\boldsymbol{\theta}}(\mathbf{x}_t, t)\|^2 + C \\ = \frac{1}{2\sigma_t^2} \left\| \underbrace{\frac{\sqrt{\bar{\alpha}_{t-1}}\beta_t}{1-\bar{\alpha}_t} \mathbf{x}_0 + \frac{\sqrt{\alpha_t}(1-\bar{\alpha}_{t-1})}{1-\bar{\alpha}_t} \mathbf{x}_t - \boldsymbol{\mu}_{\boldsymbol{\theta}}(\mathbf{x}_t, t)}_{\mathbb{E}[\mathbf{x}_{t-1} | \mathbf{x}_0, \mathbf{x}_t]} \right\|^2 + C$$

## DDPM: model fitting details for $L_{t-1}(\mathbf{x}_0)$

Recall that the KL between two multivariate Gaussians is:

$$D_{\text{KL}}(\mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_1, \boldsymbol{\Sigma}_1) || \mathcal{N}(\mathbf{x} | \boldsymbol{\mu}_2, \boldsymbol{\Sigma}_2)) = \frac{1}{2} \left[ \text{tr}(\boldsymbol{\Sigma}_2^{-1} \boldsymbol{\Sigma}_1) + (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2)^\top \boldsymbol{\Sigma}_2^{-1} (\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2) \right. \\ \left. - D + \log \left( \frac{\det(\boldsymbol{\Sigma}_2)}{\det(\boldsymbol{\Sigma}_1)} \right) \right]$$

Thus,  $L_{t-1}(\mathbf{x}_0)$  term can be written as

$$D_{\text{KL}}(q(\mathbf{x}_{t-1} | \mathbf{x}_t, \mathbf{x}_0) || p_{\boldsymbol{\theta}}(\mathbf{x}_{t-1} | \mathbf{x}_t)) = \frac{1}{2\sigma_t^2} \|\tilde{\mu}_t(\mathbf{x}_t, \mathbf{x}_0) - \boldsymbol{\mu}_{\boldsymbol{\theta}}(\mathbf{x}_t, t)\|^2 + C \\ = \frac{1}{2\sigma_t^2} \left\| \underbrace{\frac{\sqrt{\bar{\alpha}_{t-1}}\beta_t}{1-\bar{\alpha}_t} \mathbf{x}_0 + \frac{\sqrt{\alpha_t}(1-\bar{\alpha}_{t-1})}{1-\bar{\alpha}_t} \mathbf{x}_t - \boldsymbol{\mu}_{\boldsymbol{\theta}}(\mathbf{x}_t, t)}_{\mathbb{E}[\mathbf{x}_{t-1} | \mathbf{x}_0, \mathbf{x}_t]} \right\|^2 + C$$

Expectations can be estimated using Monte Carlo

$$\mathbb{E}[L_{t-1}(\mathbf{x}_0)] \approx \frac{1}{S} \frac{1}{2\sigma_t^2} \sum_{s=1}^S \left\| \frac{\sqrt{\bar{\alpha}_{t-1}}\beta_t}{1-\bar{\alpha}_t} \mathbf{x}_0 + \frac{\sqrt{\alpha_t}(1-\bar{\alpha}_{t-1})}{1-\bar{\alpha}_t} \mathbf{x}_t^{(s)} - \boldsymbol{\mu}_{\boldsymbol{\theta}}(\mathbf{x}_t, t) \right\|^2, \quad \text{where } \mathbf{x}_t^{(s)} \stackrel{\text{i.i.d.}}{\sim} q(\mathbf{x}_t | \mathbf{x}_0)$$

## DDPM: reparameterization

Earlier we had that

$$q(\mathbf{x}_t \mid \mathbf{x}_0) = \mathcal{N}(\mathbf{x}_t \mid \sqrt{\bar{\alpha}_t} \mathbf{x}_0, (1 - \bar{\alpha}_t) \mathbf{I})$$

which means

$$\mathbf{x}_t = \sqrt{\bar{\alpha}_t} \mathbf{x}_0 + \sqrt{1 - \bar{\alpha}_t} \boldsymbol{\epsilon} \quad \text{or} \quad \mathbf{x}_0 = \frac{1}{\sqrt{\bar{\alpha}_t}} \mathbf{x}_t - \frac{\sqrt{1 - \bar{\alpha}_t}}{\sqrt{\bar{\alpha}_t}} \boldsymbol{\epsilon}, \quad \text{where } \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$

## DDPM: reparameterization

Earlier we had that

$$q(\mathbf{x}_t \mid \mathbf{x}_0) = \mathcal{N}(\mathbf{x}_t \mid \sqrt{\bar{\alpha}_t} \mathbf{x}_0, (1 - \bar{\alpha}_t) \mathbf{I})$$

which means

$$\mathbf{x}_t = \sqrt{\bar{\alpha}_t} \mathbf{x}_0 + \sqrt{1 - \bar{\alpha}_t} \boldsymbol{\epsilon} \quad \text{or} \quad \mathbf{x}_0 = \frac{1}{\sqrt{\bar{\alpha}_t}} \mathbf{x}_t - \frac{\sqrt{1 - \bar{\alpha}_t}}{\sqrt{\bar{\alpha}_t}} \boldsymbol{\epsilon}, \quad \text{where } \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$

Insert the expression of  $\mathbf{x}_0$  into the exact decoder model  $q(\mathbf{x}_{t-1} \mid \mathbf{x}_t, \mathbf{x}_0) = \mathcal{N}(\mathbf{x}_{t-1} \mid \tilde{\mu}_t(\mathbf{x}_t, \mathbf{x}_0), \tilde{\beta}_t \mathbf{I})$  to get

$$\begin{aligned}\tilde{\mu}_t(\mathbf{x}_t, \mathbf{x}_0) &= \frac{\sqrt{\bar{\alpha}_{t-1}} \beta_t}{1 - \bar{\alpha}_t} \mathbf{x}_0 + \frac{\sqrt{\alpha_t}(1 - \bar{\alpha}_{t-1})}{1 - \bar{\alpha}_t} \mathbf{x}_t \\ &= \dots \\ &= \frac{1}{\sqrt{\alpha_t}} \left( \mathbf{x}_t - \frac{\beta_t}{\sqrt{1 - \bar{\alpha}_t}} \boldsymbol{\epsilon} \right)\end{aligned}$$

This reparameterized model depends explicitly on  $\mathbf{x}_t$  and  $\boldsymbol{\epsilon}$  (and only implicitly on  $\mathbf{x}_0$ )

## DDPM: reparameterization

Previously we had a decoder  $p_{\theta}(\mathbf{x}_{t-1} \mid \mathbf{x}_t) = \mathcal{N}(\mathbf{x}_{t-1} \mid \boldsymbol{\mu}_{\theta}(\mathbf{x}_t, t), \boldsymbol{\Sigma}_{\theta}(\mathbf{x}_t, t))$  that predicts the mean of the denoised version of  $\mathbf{x}_{t-1}$  given its noisy input  $\mathbf{x}_t$

Reparametrization allows to train a neural network model  $\epsilon_{\theta}(\mathbf{x}_t, t)$  that, given  $\mathbf{x}_t$ , predicts the specific noise  $\epsilon$  (sampled from  $q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$ ) that was added to  $\mathbf{x}_{t-1}$  such that it resulted in  $\mathbf{x}_t$

## DDPM: reparameterization

Previously we had a decoder  $p_{\theta}(\mathbf{x}_{t-1} \mid \mathbf{x}_t) = \mathcal{N}(\mathbf{x}_{t-1} \mid \boldsymbol{\mu}_{\theta}(\mathbf{x}_t, t), \boldsymbol{\Sigma}_{\theta}(\mathbf{x}_t, t))$  that predicts the mean of the denoised version of  $\mathbf{x}_{t-1}$  given its noisy input  $\mathbf{x}_t$

Reparametrization allows to train a neural network model  $\epsilon_{\theta}(\mathbf{x}_t, t)$  that, given  $\mathbf{x}_t$ , predicts the specific noise  $\epsilon$  (sampled from  $q(\mathbf{x}_t \mid \mathbf{x}_{t-1})$ ) that was added to  $\mathbf{x}_{t-1}$  such that it resulted in  $\mathbf{x}_t$

In other words, given noisy input  $\mathbf{x}_t$ , predict  $\epsilon$  to get mean of  $\mathbf{x}_{t-1}$

$$\boldsymbol{\mu}_{\theta}(\mathbf{x}_t, t) = \frac{1}{\sqrt{\alpha_t}} \left( \mathbf{x}_t - \frac{\beta_t}{\sqrt{1 - \bar{\alpha}_t}} \boldsymbol{\epsilon}_{\theta}(\mathbf{x}_t, t) \right)$$

## DDPM: reparameterized objective

The reparameterized loss

$$\mathbb{E}[L_{t-1}(\mathbf{x}_0)] = \mathbb{E}_{\epsilon \sim \mathcal{N}(\mathbf{0}, \mathbf{I})} \left[ \underbrace{\frac{\beta_t^2}{2\sigma_t^2 \alpha_t (1 - \bar{\alpha}_t)}}_{\lambda_t} \|\epsilon - \epsilon_{\theta}(\underbrace{\sqrt{\bar{\alpha}_t} \mathbf{x}_0 + \sqrt{1 - \bar{\alpha}_t} \epsilon}_{\mathbf{x}_t}, t)\|^2 \right]$$

## DDPM: reparameterized objective

The reparameterized loss

$$\mathbb{E}[L_{t-1}(\mathbf{x}_0)] = \mathbb{E}_{\epsilon \sim \mathcal{N}(\mathbf{0}, \mathbf{I})} \left[ \underbrace{\frac{\beta_t^2}{2\sigma_t^2 \alpha_t(1 - \bar{\alpha}_t)}}_{\lambda_t} \|\epsilon - \epsilon_\theta(\underbrace{\sqrt{\bar{\alpha}_t} \mathbf{x}_0 + \sqrt{1 - \bar{\alpha}_t} \epsilon, t)}_{\mathbf{x}_t}\|^2 \right]$$

Empirical evidence suggests that  $\lambda_t = 1$  gives better results

A simplified loss (averaged over samples  $\mathbf{x}_0$  and diffusion layers  $t$ )

$$L_{\text{simple}} = \mathbb{E}_{\mathbf{x}_0 \sim p_D(\mathbf{x}), \epsilon \sim \mathcal{N}(\mathbf{0}, \mathbf{I}), t \sim \text{Unif}(\{1, \dots, T\})} \left[ \|\epsilon - \epsilon_\theta(\underbrace{\sqrt{\bar{\alpha}_t} \mathbf{x}_0 + \sqrt{1 - \bar{\alpha}_t} \epsilon, t)}_{\mathbf{x}_t}\|^2 \right]$$

## DDPM: training algorithm, simple model

---

**Algorithm 25.1:** Training a DDPM model with  $L_{\text{simple}}$ .

---

```
1 while not converged do
2    $x_0 \sim q_0(x_0)$ 
3    $t \sim \text{Unif}(\{1, \dots, T\})$ 
4    $\epsilon \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ 
5   Take gradient descent step on  $\nabla_{\theta} ||\epsilon - \epsilon_{\theta}(\sqrt{\bar{\alpha}_t}x_0 + \sqrt{1 - \bar{\alpha}_t}\epsilon, t)||^2$ 
```

---

Algorithm 25.1 from (Murphy, 2023)

## DDPM: ancestral sampling algorithm

---

**Algorithm 25.2:** Sampling from a DDPM model.

---

```
1  $x_T \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ 
2 foreach  $t = T, \dots, 1$  do
3    $\epsilon_t \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ 
4    $x_{t-1} = \frac{1}{\sqrt{\alpha_t}} \left( x_t - \frac{1-\alpha_t}{\sqrt{1-\bar{\alpha}_t}} \epsilon_\theta(x_t, t) \right) + \sigma_t \epsilon_t$ 
5 Return  $x_0$ 
```

---

Algorithm 25.2 from (Murphy, 2023)

## UNet architecture




Figure 18.9 from (Prince, 2023)

## DDPM: illustration




Figure from (Ho et al., 2020)

## DDPM: interpolation

Example: DDPM model can be used e.g. to interpolate two data points  $x$  and  $x'$

- $x_t \sim q(x_t | x)$  and  $x'_t \sim q(x_t | x')$
- $\bar{x}_t = (1 - \lambda)x_t + \lambda x'_t$
- $x_0 \sim p_\theta(x_0 | \bar{x}_t)$





Figure from (Ho et al., 2020)

## DDPM: noise schedule

The original DDPM model chose the noise schedule  $\beta_1, \dots, \beta_T$  from a set of constant, linear, and quadratic schedules, such that  $q(\mathbf{x}_T | \mathbf{x}_0) \approx \mathcal{N}(\mathbf{0}, \mathbf{I})$ , with  $T = 1000$

A number of noise schedules have been proposed in the literature both with

- empirical evidence
- theoretical benefits

## Continuous-time diffusion models: forward diffusion SDE

We can consider  $t \in [0, T]$  to be continuous to obtain continuous-time diffusion models

Consider noise level  $\beta_t$  to be  $\beta(t)\Delta t$ , where  $\Delta t$  is a small diffusion time increment

Diffusion model  $q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \mathcal{N}(\mathbf{x}_t | \sqrt{1 - \beta_t} \mathbf{x}_{t-1}, \beta_t \mathbf{I})$  becomes

$$\mathbf{x}_t = \sqrt{1 - \beta_t} \mathbf{x}_{t-1} + \sqrt{\beta_t} \boldsymbol{\epsilon} = \sqrt{1 - \beta(t)\Delta t} \cdot \mathbf{x}_{t-1} + \sqrt{\beta(t)\Delta t} \cdot \boldsymbol{\epsilon}, \quad \text{where } \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$

## Continuous-time diffusion models: forward diffusion SDE

We can consider  $t \in [0, T]$  to be continuous to obtain continuous-time diffusion models

Consider noise level  $\beta_t$  to be  $\beta(t)\Delta t$ , where  $\Delta t$  is a small diffusion time increment

Diffusion model  $q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \mathcal{N}(\mathbf{x}_t | \sqrt{1 - \beta_t} \mathbf{x}_{t-1}, \beta_t \mathbf{I})$  becomes

$$\mathbf{x}_t = \sqrt{1 - \beta_t} \mathbf{x}_{t-1} + \sqrt{\beta_t} \boldsymbol{\epsilon} = \sqrt{1 - \beta(t)\Delta t} \cdot \mathbf{x}_{t-1} + \sqrt{\beta(t)\Delta t} \cdot \boldsymbol{\epsilon}, \quad \text{where } \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$

For small  $\Delta t$ , by the first order Tailor approximation

$$\mathbf{x}_t = \mathbf{x}_{t-1} - \frac{\beta(t)\Delta t}{2} \cdot \mathbf{x}_{t-1} + \sqrt{\beta(t)\Delta t} \cdot \boldsymbol{\epsilon}$$

## Continuous-time diffusion models: forward diffusion SDE

We can consider  $t \in [0, T]$  to be continuous to obtain continuous-time diffusion models

Consider noise level  $\beta_t$  to be  $\beta(t)\Delta t$ , where  $\Delta t$  is a small diffusion time increment

Diffusion model  $q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \mathcal{N}(\mathbf{x}_t | \sqrt{1 - \beta_t} \mathbf{x}_{t-1}, \beta_t \mathbf{I})$  becomes

$$\mathbf{x}_t = \sqrt{1 - \beta_t} \mathbf{x}_{t-1} + \sqrt{\beta_t} \boldsymbol{\epsilon} = \sqrt{1 - \beta(t)\Delta t} \cdot \mathbf{x}_{t-1} + \sqrt{\beta(t)\Delta t} \cdot \boldsymbol{\epsilon}, \quad \text{where } \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$

For small  $\Delta t$ , by the first order Tailor approximation

$$\mathbf{x}_t = \mathbf{x}_{t-1} - \frac{\beta(t)\Delta t}{2} \cdot \mathbf{x}_{t-1} + \sqrt{\beta(t)\Delta t} \cdot \boldsymbol{\epsilon}$$

Thus

$$\frac{\mathbf{x}_t - \mathbf{x}_{t-1}}{\Delta t} = -\frac{\beta(t)}{2} \mathbf{x}_{t-1} + \frac{\sqrt{\beta(t)}}{\sqrt{\Delta t}} \boldsymbol{\epsilon}$$

and when  $\Delta t \rightarrow 0$

$$\frac{d\mathbf{x}(t)}{dt} = -\frac{\beta(t)}{2} \mathbf{x}(t) + \sqrt{\beta(t)} \frac{d\mathbf{w}(t)}{dt}$$

we have a stochastic differential equation (SDE) model, where  $\mathbf{w}$  is Brownian motion

## Continuous-time diffusion models: forward diffusion SDE

SDE models can be generally written as

$$d\mathbf{x} = \underbrace{\mathbf{f}(\mathbf{x}, t)dt}_{\text{deterministic}} + \underbrace{g(t)d\mathbf{w}}_{\text{stochastic}}$$

and can be numerically simulated (solved) e.g. by the Euler-Maruyama algorithm

$$\mathbf{x}(t + \Delta t) = \mathbf{x}(t) + \mathbf{f}(\mathbf{x}(t), t)\Delta t + g(t)\sqrt{\Delta t} \cdot \boldsymbol{\epsilon}, \quad \text{where } \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$

## Continuous-time diffusion models: forward diffusion SDE

SDE models can be generally written as

$$d\mathbf{x} = \underbrace{\mathbf{f}(\mathbf{x}, t)dt}_{\text{deterministic}} + \underbrace{g(t)d\mathbf{w}}_{\text{stochastic}}$$

and can be numerically simulated (solved) e.g. by the Euler-Maruyama algorithm

$$\mathbf{x}(t + \Delta t) = \mathbf{x}(t) + \mathbf{f}(\mathbf{x}(t), t)\Delta t + g(t)\sqrt{\Delta t} \cdot \epsilon, \quad \text{where } \epsilon \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$

Continuous-time limit of the DDPM model is obtained with  $\mathbf{f}(\mathbf{x}, t) = -\frac{1}{2}\beta(t)\mathbf{x}$  and  $g(t) = \sqrt{\beta(t)}$

$$d\mathbf{x} = -\frac{1}{2}\beta(t)\mathbf{x}dt + \sqrt{\beta(t)}d\mathbf{w}$$

## Continuous-time diffusion models: illustration




Figure 25.6 from (Murphy, 2023)

## Continuous-time diffusion models: reverse diffusion SDE

As with discrete-time diffusion models, we need to revert the noising process

Reverse-time SDE is known and has the following form

$$d\boldsymbol{x} = [\boldsymbol{f}(\boldsymbol{x}_t, t) - g(t)^2 \nabla_{\boldsymbol{x}} \log q_t(\boldsymbol{x})]dt + g(t)d\bar{\boldsymbol{w}},$$

where  $\bar{\boldsymbol{w}}$  is Brownian motion to the reverse diffusion time direction

## Continuous-time diffusion models: reverse diffusion SDE

As with discrete-time diffusion models, we need to revert the noising process

Reverse-time SDE is known and has the following form

$$d\mathbf{x} = [\mathbf{f}(\mathbf{x}_t, t) - g(t)^2 \nabla_{\mathbf{x}} \log q_t(\mathbf{x})] dt + g(t) d\bar{\mathbf{w}},$$

where  $\bar{\mathbf{w}}$  is Brownian motion to the reverse diffusion time direction

Reverse-time SDE model corresponding to the DDPM model is

$$d\mathbf{x}_t = \left[ -\frac{1}{2} \beta(t) \mathbf{x} - \beta(t) \nabla_{\mathbf{x}_t} \log q_t(\mathbf{x}_t) \right] dt + \sqrt{\beta(t)} d\bar{\mathbf{w}}_t$$

We need to estimate the so-called score-function

$$\mathbf{s}_{\theta}(\mathbf{x}_t, t) \approx \nabla_{\mathbf{x}_t} \log q_t(\mathbf{x}_t)$$

## Continuous-time diffusion models: reverse diffusion SDE

Training loss for continuous-time diffusion model

$$\mathcal{L} = \mathbb{E}_{t \sim \text{Unif}([0, T])} [\lambda(t) \mathbb{E}_{\mathbf{x}_0} \mathbb{E}_{\mathbf{x}_t | \mathbf{x}_0} [\|\mathbf{s}_\theta(\mathbf{x}_t, t) - \nabla_{\mathbf{x}_t} \log q_t(\mathbf{x}_t | \mathbf{x}_0)\|]]$$

where

- $\lambda(t)$  is a positive weighting function
- $\nabla_{\mathbf{x}_t} \log q_t(\mathbf{x}_t)$  can be computed analytically for simply (linear) forward diffusion models

## Continuous-time diffusion models: reverse diffusion SDE

Training loss for continuous-time diffusion model

$$\mathcal{L} = \mathbb{E}_{t \sim \text{Unif}([0, T])} [\lambda(t) \mathbb{E}_{\mathbf{x}_0} \mathbb{E}_{\mathbf{x}_t | \mathbf{x}_0} [\|\mathbf{s}_\theta(\mathbf{x}_t, t) - \nabla_{\mathbf{x}_t} \log q_t(\mathbf{x}_t | \mathbf{x}_0)\|]]$$

where

- $\lambda(t)$  is a positive weighting function
- $\nabla_{\mathbf{x}_t} \log q_t(\mathbf{x}_t)$  can be computed analytically for simply (linear) forward diffusion models

Samples can be generated using the Euler-Maruyama algorithm

$$\mathbf{x}_{t-\Delta t} = \mathbf{x}_t + \frac{1}{2} \beta(t) [\mathbf{x}_t + 2\mathbf{s}_\theta(\mathbf{x}_t, t)] \Delta t + \sqrt{\beta(t) \Delta t} \cdot \boldsymbol{\epsilon}, \quad \text{where } \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$

## Continuous-time diffusion models: illustration




Figure from (Song et al., 2021)

## Continuous-time diffusion models: illustration



Figure from (Song et al., 2021)

## Latent diffusion models

Diffusion models are slow to train and use

- Model needs to take many small steps on high-dimensional data

Latent diffusion models (LDM) use a two-stage training scheme

- First train a VAE
- Then train a diffusion model to the embeddings

Used e.g. in the stable diffusion system




Figure 25.13 from (Murphy, 2023)

## Conditional diffusion models: classifier guidance

Consider a case where data points  $\mathbf{x}$

- Are associated with class labels  $\mathbf{c}$
- We have access to a pre-trained classifier  $p(\mathbf{c} | \mathbf{x})$

From Bayes theorem

$$\log p(\mathbf{x} | \mathbf{c}) = \log p(\mathbf{c} | \mathbf{x}) + \log p(\mathbf{x}) - \log p(\mathbf{c})$$

## Conditional diffusion models: classifier guidance

Consider a case where data points  $\mathbf{x}$

- Are associated with class labels  $\mathbf{c}$
- We have access to a pre-trained classifier  $p(\mathbf{c} | \mathbf{x})$

From Bayes theorem

$$\log p(\mathbf{x} | \mathbf{c}) = \log p(\mathbf{c} | \mathbf{x}) + \log p(\mathbf{x}) - \log p(\mathbf{c})$$

The score function becomes

$$\mathbf{s}_{\theta}(\mathbf{x}, t)' = \nabla_{\mathbf{x}} \log p(\mathbf{x} | \mathbf{c}) = \nabla_{\mathbf{x}} \log p(\mathbf{c} | \mathbf{x}) + \nabla_{\mathbf{x}} \log p(\mathbf{x})$$

A weighted score function can be defined as

$$\mathbf{s}_{\theta}(\mathbf{x}, t)' = \nabla_{\mathbf{x}} \log p(\mathbf{x} | \mathbf{c}) = \nabla_{\mathbf{x}} \log p(\mathbf{x}) + w \cdot \nabla_{\mathbf{x}} \log p(\mathbf{c} | \mathbf{x})$$

## Conditional diffusion models: classifier guidance

Consider a case where data points  $\mathbf{x}$

- Are associated with class labels  $\mathbf{c}$
- We have access to a pre-trained classifier  $p(\mathbf{c} | \mathbf{x})$

From Bayes theorem

$$\log p(\mathbf{x} | \mathbf{c}) = \log p(\mathbf{c} | \mathbf{x}) + \log p(\mathbf{x}) - \log p(\mathbf{c})$$

The score function becomes

$$\mathbf{s}_{\theta}(\mathbf{x}, t)' = \nabla_{\mathbf{x}} \log p(\mathbf{x} | \mathbf{c}) = \nabla_{\mathbf{x}} \log p(\mathbf{c} | \mathbf{x}) + \nabla_{\mathbf{x}} \log p(\mathbf{x})$$

A weighted score function can be defined as

$$\mathbf{s}_{\theta}(\mathbf{x}, t)' = \nabla_{\mathbf{x}} \log p(\mathbf{x} | \mathbf{c}) = \nabla_{\mathbf{x}} \log p(\mathbf{x}) + w \cdot \nabla_{\mathbf{x}} \log p(\mathbf{c} | \mathbf{x})$$

Analogously, classifier guidance can be implemented in DDPM by modifying the sampling step

$$\mathbf{x}_{x-1} = \frac{1}{\sqrt{\alpha_t}} \left( \mathbf{x}_t - \frac{\beta_t}{\sqrt{1 - \bar{\alpha}_t}} \mathbf{e}_{\theta}(\mathbf{x}_t, t) \right) + w \cdot \nabla_{\mathbf{x}} \log p(\mathbf{c} | \mathbf{x}) + \sigma_t \mathbf{e}_t$$

Classifier guidance affects only sample generation, not diffusion model training

## Conditional diffusion models: classifier guidance example




Figure 18.12 from (Prince, 2023)

## Conditional diffusion models: classifier-free guidance

Derive a classifier from a generative model  $p(\mathbf{c} \mid \mathbf{x}) = \frac{p(\mathbf{x} \mid \mathbf{c})p(\mathbf{c})}{p(\mathbf{x})}$  to get

$$\log p(\mathbf{c} \mid \mathbf{x}) = \log p(\mathbf{x} \mid \mathbf{c}) + \log p(\mathbf{c}) - \log p(\mathbf{x})$$

Need two generative models

- Conditional model  $p(\mathbf{x} \mid \mathbf{c})$
- Unconditional model  $p(\mathbf{x}) = p(\mathbf{x} \mid \mathbf{c} = \emptyset)$

## Conditional diffusion models: classifier-free guidance

Derive a classifier from a generative model  $p(\mathbf{c} \mid \mathbf{x}) = \frac{p(\mathbf{x} \mid \mathbf{c})p(\mathbf{c})}{p(\mathbf{x})}$  to get

$$\log p(\mathbf{c} \mid \mathbf{x}) = \log p(\mathbf{x} \mid \mathbf{c}) + \log p(\mathbf{c}) - \log p(\mathbf{x})$$

Need two generative models

- Conditional model  $p(\mathbf{x} \mid \mathbf{c})$
- Unconditional model  $p(\mathbf{x}) = p(\mathbf{x} \mid \mathbf{c} = \emptyset)$

Use this implicit classifier similarly as in classifier guidance

$$\begin{aligned}\nabla_{\mathbf{x}}[\log p(\mathbf{x} \mid \mathbf{c}) + w \log p(\mathbf{c} \mid \mathbf{x})] &= \nabla_{\mathbf{x}}[\log p(\mathbf{x} \mid \mathbf{c}) + w(\log p(\mathbf{x} \mid \mathbf{c}) - \log p(\mathbf{x}))] \\ &= \nabla_{\mathbf{x}}[(1 + w) \log p(\mathbf{x} \mid \mathbf{c}) - wp(\mathbf{x})]\end{aligned}$$

## Conditional diffusion models

Conditional generation by training a diffusion model in  $(\mathbf{c}, \mathbf{x})$  pairs

If the covariate  $\mathbf{c}$  is a scalar:

- $\mathbf{c}$  can be mapped to an embedding vector
- Embedding can be incorporated into the neural network  $\mu(\mathbf{x}_t, t | \mathbf{c})$ ,  $\epsilon(\mathbf{x}_t, t | \mathbf{c})$  or  $s_\theta(\mathbf{x}_t, t | \mathbf{c})$

If the covariate  $\mathbf{c}$  is another image:

- We can concatenate  $\mathbf{c}$  with  $\mathbf{x}_t$  as an extra set of image channels

If the covariate  $\mathbf{c}$  is a text prompt:

- We can embed  $\mathbf{c}$
- Embedding can be incorporated into the neural network  $\mu(\mathbf{x}_t, t | \mathbf{c})$ ,  $\epsilon(\mathbf{x}_t, t | \mathbf{c})$  or  $s_\theta(\mathbf{x}_t, t | \mathbf{c})$

## UNet architecture

Embedding of covariate  $c$  can be e.g. shared across UNet layers similarly as time embedding




Figure 18.9 from (Prince, 2023)


## Conditional diffusion models: example



A transparent sculpture of a duck made out of glass



An angry duck doing heavy weightlifting at the gym



A brain riding a rocketship heading towards the moon



A couple of glasses sitting on a table



New York skyline with Hello World written with fireworks in the sky



Figure 18.13 from (Prince, 2023)

## References

- Ho J, Jain A, Abbeel P, "Denoising Diffusion Probabilistic Models," *NeurIPS*, 2020.
- Murphy K, Probabilistic Machine Learning: Advanced Topics, 2023.
- Prince SJD, Understanding Deep Learning, The MIT Press, 2023.
- Song Y, Sohl-Dickstein J, Kingma DP, Kumar A, Ermon S, Poole B, "Score-Based Generative Modeling through Stochastic Differential Equations," *ICLR*, 2021.

# CS-E4891 Deep Generative Models

## Lecture 5: Autoregressive Models

Lauri Juvela

Department of Information and Communications Engineering (DICE)  
Aalto University

April 28, 2025

- Assistant professor at Aalto since 2023, **Speech Synthesis Group** at ELEC / DICE , PhD 2020
- Machine learning researcher at Neural DSP 2019-2023, working on guitar amplifier modeling with neural networks
- Research:
  - Deep generative models for speech and audio
  - Controllable and interpretable neural speech synthesis, differentiable DSP
  - Audio effects modeling
  - Watermarking and deepfake detection

## Outline

- Autoregressive models
- Distributions used in autoregressive modeling
- Deep neural networks for autoregression
- Autoregressive Transformer language models
- Tokenisation and byte pair encoding
- Reading: Autoregressive models (Section 22 from Murphy, 2023), Transformer language model (Section 12.1 from Bishop 2024)


## Autoregressive models

- We can factorize any sequence of probabilities as an autoregressive model using the chain rule of probability

$$p(\mathbf{x}_{1:T}) = p(\mathbf{x}_1)p(\mathbf{x}_2|\mathbf{x}_1)p(\mathbf{x}_3|\mathbf{x}_2, \mathbf{x}_1)p(\mathbf{x}_4|\mathbf{x}_3, \mathbf{x}_2, \mathbf{x}_1) \cdots = \prod_{t=1}^T p(\mathbf{x}_t|\mathbf{x}_{1:t-1})$$

In this lecture we consider explicit generative models

- Density model  $p_\theta(\mathbf{x}) = p(\mathbf{x}|\theta)$  has an explicit parametric form
- A trained model can be used to generate new examples from  $p_\theta(\mathbf{x})$ .




Fully connected autoregressive model

Figure 22.1 from (Murphy, 2023)

## Deep autoregressive models

- Autoregressive models are common in sequence-to-sequence translation problems
- Typical architectures: RNN, CNN, Transformer



## First order linear autoregressive AR(1) process

Time series  $x_t$  is governed by an AR(1) process

$$x_t = \phi x_{t-1} + \varepsilon_t, \text{ where } \varepsilon_t \sim \mathcal{N}(0, \sigma^2)$$

Linear predictive model:

$$\hat{x}_t = \hat{\phi} x_{t-1}$$

- Least-squares solution for the optimal parameter  $\hat{\theta}$  is the maximum likelihood estimate (MLE) (home exercise)

$$\text{MSE}(x, x_{t-1}; \theta) = \sum_{t=1}^T (x_t - \theta x_{t-1})^2$$

- Linear AR models have closed form MLE solutions, in this case

$$\hat{\phi}_{\text{MLE}} = \frac{\sum_{t=1}^{T-1} x_t x_{t-1}}{\sum_{t=1}^{T-1} x_t^2}$$

- You can also estimate  $\hat{\theta}$  using gradient descent (home exercise). This becomes very useful when the model is not linear, such as neural networks.

## Markov Models

Markov property: variable  $\mathbf{x}_t$  only depends on the previous time-step  $\mathbf{x}_{t-1}$

$$p(\mathbf{x}_{1:T}) = p(\mathbf{x}_t | \mathbf{x}_{t-1})$$

Recurrent neural networks are non-linear Markov models

$$\mathbf{h}_t = \text{RNN}(\mathbf{x}_t, \mathbf{h}_{t-1})$$

In practice, Markovian systems can model longer dependencies, if the state can pack information from multiple time steps.

## N-grams are simple language models (Murphy 2.6.2)

- Bi-grams: probability of the word pair  $(w_i, w_j)$  occurring in text.
- Maximum likelihood estimate: count the occurrences in a text corpus

$$p(w_j|w_i) = \frac{\sum_{n=1}^N \mathbb{I}(w_n = w_j) \mathbb{I}(w_{n-1} = w_i)}{N}$$

- Distribution  $p(w_n|w_{n-1})$  is the collection of all bi-gram point probabilities




Figure: English letter Bi-gram frequency matrix (<https://blogs.sas.com/content/iml/2014/09/26/bigrams.html>)

## N-grams are simple language models (Murphy 2.6.2)

- Tri-grams: probability of the ordered word triplet  $(w_i, w_j, w_k)$  occurring in text.
- Maximum likelihood estimate: count the occurrences in a text corpus

$$p(w_k|w_i, w_j) = \frac{\sum_{n=1}^N \mathbb{I}(w_n = w_k) \mathbb{I}(w_{n-1} = w_j) \mathbb{I}(w_{n-2} = w_i)}{N}$$

- Distribution  $p(w_n|w_{n-1}, w_{n-2})$  is the collection of all tri-gram point probabilities
- N-grams generalize the idea to the context length N

$$p(w_i|w_{i-n+1}^{i-1}) = \frac{c(w_{i-n+1}^i)}{|V| \sum_{w_i} c(w_{i-n+1}^i)}$$

- Unseen N-grams will have a probability zero, which can cause problems in language modeling
- Practical N-gram models apply some kind of smoothing to the counts, for example Laplace smoothing adds one to all counts

$$p(w_i|w_{i-n+1}^{i-1}) = \frac{1 + c(w_{i-n+1}^i)}{|V| \sum_{w_i} c(w_{i-n+1}^i)}$$

## Higher order Markov models (Murphy 2.6.2)

- N-grams can be seen as higher-order Markov models with order N
- Higher order Markov property: variable  $x_t$  depends on the previous time-steps  $x_{t-n:t-1}$

$$p(\mathbf{x}_{1:T}) = \prod_{t=n+1}^T p(\mathbf{x}_t | \mathbf{x}_{t-n:t-1})$$

- Causal convolution nets have a finite receptive field  $R$  and can also be considered higher-order non-linear Markov models

$$\mathbf{x}_t = \text{CNN}(\mathbf{x}_{t-1:t-R})$$

## Neural autoregressive distribution estimators (NADE) (Murphy 22.2)

- Extension of Mixture Density Networks (MDN) to work with autoregressive models

$$p(x_t | \mathbf{x}_{1:t-1}) = \sum_{k=1}^K \pi_{t,k} \mathcal{N}(\mathbf{x}_t | \mu_{t,k}, \sigma_{t,k}^2)$$

- Distribution parameters are generated by a network

$$[\boldsymbol{\mu}_t, \boldsymbol{\sigma}_t, \boldsymbol{\pi}_t] = f_t(\mathbf{x}_{1:t-1}, \boldsymbol{\theta}_t)$$

- Re-parametrisation is similar to VAEs: split network output to three chunks and re-parameterize variables

$$\boldsymbol{\mu}_t = \mathbf{z}_{\mu,t}, \boldsymbol{\sigma}_t = \exp(\mathbf{z}_{\sigma,t}), \boldsymbol{\pi}_t = \text{softmax}(\mathbf{z}_{\pi,t})$$

- Unlike VAEs, **data likelihood is directly tractable**
- Typically parameters  $\boldsymbol{\theta}_t$  are shared for different time steps  $f_t$ : use convolution nets, RNNs, Transformers etc.
- Works when there is a natural linear ordering, e.g., time series data
- Not so natural for images

## Loss function for NADE

- Maximum likelihood training: minimize negative log-likelihood

$$p(x_t | \mathbf{x}_{1:t-1}) = \sum_{k=1}^K \pi_{t,k} \mathcal{N}(x_t | \mu_{t,k}, \sigma_{t,k}^2)$$

- In practice, covariances are chosen as diagonal, probability for component  $k$  is

$$p_k(x_t | \mathbf{x}_{1:t-1}) = \pi_{t,k} \frac{1}{\sqrt{2\pi\sigma_{t,k}^2}} \exp\left(-\frac{(x_t - \mu_{t,k})^2}{2\sigma_{t,k}^2}\right)$$

- Log-likelihood for a single component becomes

$$\mathcal{L}_k(x_t | \mathbf{x}_{1:t-1}) = \log(p_k(x_t | \mathbf{x}_{1:t-1})) = \log(\pi_{t,k}) - \frac{1}{2} \log(2\pi\sigma_{t,k}^2) - \frac{1}{2} \frac{(x_t - \mu_{t,k})^2}{\sigma_{t,k}^2}$$

- Compute negative log likelihood loss from (use log-sum-exp trick for numerical stability)

$$\text{NLL}(x_t | \mathbf{x}_{1:t-1}) = -\log \left( \sum_{k=1}^K \exp(\mathcal{L}_k(x_t | \mathbf{x}_{1:t-1})) \right)$$

## WaveNet

- Convolutional network for speech and audio using dilated convolutions
- Unconditional model  $p(x_t | \mathbf{x}_{1:t-1}) = f_t(\mathbf{x}_{1:t-1})$  ("decoder-only" in Transformer terminology)
- Conditional version of the model  $p(x_t | \mathbf{x}_{1:t-1}, c) = f_t(\mathbf{x}_{1:t-1}, c)$  can be used for text-to-speech (TTS) synthesis
- Feedforward WaveNets are useful in audio effects modeling (for e.g., guitar amplifiers)





Illustration: Figure 22.2 from Murphy, 2023, orig. van den Oord 2016

- Autoregressive model for images
- Quantize pixel intensity values and model these as a categorical distribution
- Requires a sequential ordering for pixels, rasterization is a design choice
- Use a 2D CNN architecture with causal mask corresponding to the rasterisation: don't look at the “future” pixels



## Language models and Tokenisation

- Language models operate on sequences of discrete **tokens**
- Use the **categorical distribution** to represent token probabilities at each time step (similar to multiclass classification)
- Different approaches to tokenization: character based – word based or something in between

## Bernoulli distribution for binary classification)

- The Bernoulli distribution is defined on the domain  $z \in (0, 1)$  and has a single parameter  $\lambda$  that denotes the probability of observing  $z = 1$ . It follows that the probability of observing  $z = 0$  is  $1 - \lambda$ .

$$p(y|\lambda) = \begin{cases} 1 - \lambda & y = 0, \\ \lambda & y = 1 \end{cases}$$

or equivalently (in branchless programming mode)

$$p(x|\lambda) = (1 - \lambda)^{1-x} \lambda^x$$




Figure 5.4 from Prince, 2024.

## Bernoulli distribution and Binary Cross Entropy loss

A neural network  $f$  predicts output  $\hat{y}$ , given input  $x$  and parameters  $\theta$

$$\hat{y} = \text{sigmoid}(f(x; \theta))$$

Substitute probability  $\lambda$  with network prediction

$$p(y|x) = (1 - \hat{y})^{1-y} \hat{y}^y$$

Log-likelihood over training examples  $i = 1, \dots, I$

$$\mathcal{L}(\theta) = \sum_{i=1}^I (1 - y_i) \log(1 - \hat{y}_i) + y_i \log(\hat{y}_i)$$

Negative log-likelihood is equivalent to the Binary Cross Entropy Loss

$$\text{NLL}(\theta) = \sum_{i=1}^I -(1 - y_i) \log(1 - \hat{y}_i) y_i \log(\hat{y}_i)$$

## Categorical distribution for multiclass classification

Probability of class  $k$  in a categorical distribution is

$$p(y = k) = \lambda_k$$

Use the softmax function to normalize network outputs to sum to one

$$p(y = k|x) = \text{softmax}(f(\mathbf{x}, \boldsymbol{\theta})) = \frac{\exp(z_k)}{\sum_{k'}^K \exp(z_{k'})}$$

Negative log-likelihood gives the categorical cross entropy loss

$$\begin{aligned} -\mathcal{L}(\boldsymbol{\theta}) &= -\sum_{i=1}^I \log(\text{softmax}_{y_i}(f(\mathbf{x}_i, \boldsymbol{\theta}))) \\ &= -\sum_{i=1}^I \left( f_{y_i}(\mathbf{x}_i, \boldsymbol{\theta}) - \log \left[ \sum_{k'=1}^K \exp(f_{k'=1}(\mathbf{x}_i, \boldsymbol{\theta})) \right] \right) \end{aligned}$$




Figure 5.9 from Prince, 2024.

## Cross Entropy and Perplexity (Murphy, section 5.2.4)

- KL divergence can be split into cross-entropy and self-entropy

$$D_{\text{KL}}(p||q) = \sum_x p(x) \log \frac{p(x)}{q(x)} = \mathbb{H}_{\text{CE}}(p, q) - \mathbb{H}(p)$$

- $\mathbb{H}_{\text{CE}}(p, q)$  is the **cross entropy**

$$\mathbb{H}_{\text{CE}}(p, q) = - \sum_x p(x) \log q(x)$$

- **Entropy** measures the expected number of bits (in base 2, nats in base e) required to encode the outcome of a random variable.
- Perplexity is another commonly used measure to quantify the model's "surprisal" when seeing new data
- Perplexity using natural logarithms is defined as

$$\text{perplexity}_{\text{nats}}(p, q) \triangleq e^{\mathbb{H}_{\text{CE}}(p, q)}$$

- Often perplexity is defined in bits, but this requires using  $\log_2$  in entropy calculations

$$\text{perplexity}_{\text{bits}}(p, q) \triangleq 2^{\mathbb{H}_{\text{CE}}(p, q)}$$

## Perplexity for empirical distribution

Approximate the true distribution by sampling data from  $p$

$$p_{\mathcal{D}}(x|\mathcal{D}) = \frac{1}{N} \sum_{n=1}^N \mathbb{I}(x = x_n)$$

Cross entropy becomes

$$H = \frac{1}{N} \sum_{n=1}^N \log p(x_n) = \frac{1}{N} \log \prod_{n=1}^N p(x_n)$$

The corresponding perplexity becomes


$$\begin{aligned} \text{perplexity}(p_{\mathcal{D}}, p) &= \exp \left[ -\frac{1}{N} \log \left( \prod_{n=1}^N p(x_n) \right) \right] = \exp \left[ \log \left( \prod_{n=1}^N p(x_n)^{-\frac{1}{N}} \right) \right] \\ &= \left( \prod_{n=1}^N p(x_n)^{-\frac{1}{N}} \right) = \sqrt[N]{\prod_{n=1}^N \frac{1}{p(x_n)}} \end{aligned}$$

## Training autoregressive models with Teacher Forcing

- Target and input are shifted versions of the same sequence
- During training, the entire sequence is observed and next token predictions can be computed in parallel.
- **Teacher forcing** refers to conditioning on the ground-truth observed context history.

Target: quick brown fox jumped over


$p(w_1|w_{<1})$      $p(w_2|w_{<2})$      $p(w_3|w_{<3})$      $p(w_4|w_{<4})$      $p(w_5|w_{<5})$



Input: The quick brown fox jumped

## Autoregressive inference

- At inference, the model has to rely on previously generated inputs for context
- The distribution of generated sequences may differ from the real data distribution
- This contributes to language model **hallucination** effects (i.e., generating unlikely outputs)



## Architecture and data distribution choice for autoregression

- Distribution needs to have tractable explicit density function

$$p_k(x_t | \mathbf{x}_{1:t-1}, \phi_t) = \dots$$


- Mixtures of Gaussians, Logistics or other members of the location-scale family
- Bernoulli, Categorical or other members of the Multinoulli family
- Neural network predicts distribution parameters, re-parametrize so that distribution parameter properties are fulfilled

$$\phi_t = f(\mathbf{x}_{1:t-1}; \theta)$$

- Causality is really the only requirement. Typical implementations use combinations of RNNs, Causal CNNs, and Masked Attention Transformers.
- Train the model using a NLL loss
- During inference, sample from the distribution and feed back generated samples

# Transformer language models

- Only use the autoregressive decoder from the Transformer (right side)
- Masked self-attention: causal mask only allows looking at past time-steps
- Add & Norm - Residual connection and layer normalization
- No cross-attention needed in this case
- Feed-forward block is a simple MLP without temporal connectivity



## Self-attention (Bishop 2024, section 12.1.)

- Positional encoding is defined as

$$r_{ni} = \begin{cases} \sin\left(\frac{n}{L^{i/D}}\right), & \text{if } i \text{ is even,} \\ \cos\left(\frac{n}{L^{(i-1)/D}}\right), & \text{if } i \text{ is odd.} \end{cases}$$

- $n$  is timestep,  $i$  indexes feature dimension,  $L$  is expected maximum length (10000),  $D$  is the total number of dimensions
- This corresponds to multiple clock signals that wrap around at different rates




Figure 12.4 from Bishop, 2024.




Figure 12.5 from Bishop, 2024.

## Positional encoding (Bishop section 12.1.9)

- Positional encoding is defined as

$$r_{ni} = \begin{cases} \sin\left(\frac{n}{L^{i/D}}\right), & \text{if } i \text{ is even,} \\ \cos\left(\frac{n}{L^{(i-1)/D}}\right), & \text{if } i \text{ is odd.} \end{cases}$$

- $n$  is timestep,  $i$  indexes feature dimension,  $L$  is expected maximum length (10000),  $D$  is the total number of dimensions
- This corresponds to multiple clock signals that wrap around at different rates




Figure 12.10a from Bishop, 2024.

## Tokenisation

- Autoregressive language models operate with categorical distributions over a set of symbols, i.e., tokens
- Word-based tokenisation leads to large dictionary sizes (typically 50-100k in English)
- There will still be many unknown tokens for missing words, and it's difficult to handle named entities, etc.
- Agglutinative languages like Finnish are especially bad in word form combinations
- Character-level tokenisations are simple and cover everything, but they throw out all semantics
- Purely character based sequences are also longer and harder to model (remember  $\mathcal{O}(T^2)$  scaling with Attention)
- How about something in-between - how to construct sub-word tokenisations?

## Byte pair encoding

- Method for automatically creating sub-word tokenisations for language models, used in e.g., GPT models
- Start by splitting the text corpus into individual characters
- Count the frequencies of token pairs and merge the most common pair into a new token
- Repeat counting and merging until desired vocabulary size is reached

## Byte pair encoding

- Method for automatically creating sub-word tokenisations for language models, used in e.g., GPT models
- Start by splitting the text corpus into individual characters
- Count the frequencies of token pairs and merge the most common pair into a new token
- Repeat counting and merging until desired vocabulary size is reached

Example:

- Let's look at a text corpus that consists of the following words
- "hug", "pug", "pun", "bun", "hugs"
- Base vocabulary will then be
- ["b", "g", "h", "n", "p", "s", "u"]

Source <https://huggingface.co/learn/llm-course/chapter6/5>

## Byte pair encoding example continued

- Let's look at a text corpus that consists of the following words
- "hug", "pug", "pun", "bun", "hugs"
- Base vocabulary will then be
- `["b", "g", "h", "n", "p", "s", "u"]`
- Assume the words have the following counts
- ("hug", 10), ("pug", 5), ("pun", 12), ("bun", 4), ("hugs", 5)

## Byte pair encoding example continued

- Let's look at a text corpus that consists of the following words
- "hug", "pug", "pun", "bun", "hugs"
- Base vocabulary will then be
- ["b", "g", "h", "n", "p", "s", "u"]
- Assume the words have the following counts
- ("hug", 10), ("pug", 5), ("pun", 12), ("bun", 4), ("hugs", 5)
- Then the token counts will be ("h" "u" "g", 10), ("p" "u" "g", 5), ("p" "u" "n", 12), ("b" "u" "n", 4), ("h" "u" "g" "s", 5)
- Lets count token pairs, for example the pair ("h", "u") is present in the words "hug" and "hugs", so 15 times total in the corpus.
- What pair has the highest frequency?

## Byte pair encoding example continued

- Let's look at a text corpus that consists of the following words
- "hug", "pug", "pun", "bun", "hugs"
- Base vocabulary will then be
- [ "b", "g", "h", "n", "p", "s", "u" ]
- Assume the words have the following counts
- ( "hug", 10 ), ( "pug", 5 ), ( "pun", 12 ), ( "bun", 4 ), ( "hugs", 5 )
- Then the token counts will be ( "h" "u" "g", 10 ), ( "p" "u" "g", 5 ), ( "p" "u" "n", 12 ), ( "b" "u" "n", 4 ), ( "h" "u" "g" "s", 5 )
- Lets count token pairs, for example the pair ( "h", "u" ) is present in the words "hug" and "hugs", so 15 times total in the corpus.
- What pair has the highest frequency?
- ( "u", "g" ) is present in "hug", "pug", and "hugs", for a total of 20 times in the vocabulary.
- Merge ( "u", "g" ) -> "ug" into a new token

## Byte pair encoding example continued

- After merging, our vocabulary and corpus look like this

Vocabulary: ["b", "g", "h", "n", "p", "s", "u", "ug"]

Corpus: ("h" "ug", 10), ("p" "ug", 5), ("p" "u" "n", 12), ("b" "u" "n", 4), ("h" "ug" "s", 5)

- Count pair frequencies again, e.g., ("h", "ug") now occurs 15 times
- What is the most frequent pair now?

## Byte pair encoding example continued

- After merging, our vocabulary and corpus look like this

Vocabulary: ["b", "g", "h", "n", "p", "s", "u", "ug"]

Corpus: ("h" "ug", 10), ("p" "ug", 5), ("p" "u" "n", 12), ("b" "u" "n", 4), ("h" "ug" "s", 5)

- Count pair frequencies again, e.g., ("h", "ug") now occurs 15 times

- What is the most frequent pair now?

- ("u", "n") occurs 16 times, merge ("u", "n") -> "un"

- After merging, our vocabulary and corpus look like this

Vocabulary: ["b", "g", "h", "n", "p", "s", "u", "ug", "un"]

Corpus: ("h" "ug", 10), ("p" "ug", 5), ("p" "un", 12), ("b" "un", 4), ("h" "ug" "s", 5)

- Now the most frequent pair is ("h", "ug"), so we apply the merge rule ("h", "ug") -> "hug",

## Byte pair encoding example continued

- After merging, our vocabulary and corpus look like this

Vocabulary: ["b", "g", "h", "n", "p", "s", "u", "ug"]

Corpus: ("h" "ug", 10), ("p" "ug", 5), ("p" "u" "n", 12), ("b" "u" "n", 4), ("h" "ug" "s", 5)

- Count pair frequencies again, e.g., ("h", "ug") now occurs 15 times

- What is the most frequent pair now?

- ("u", "n") occurs 16 times, merge ("u", "n") -> "un"

- After merging, our vocabulary and corpus look like this

Vocabulary: ["b", "g", "h", "n", "p", "s", "u", "ug", "un"]

Corpus: ("h" "ug", 10), ("p" "ug", 5), ("p" "un", 12), ("b" "un", 4), ("h" "ug" "s", 5)

- Now the most frequent pair is ("h", "ug"), so we apply the merge rule ("h", "ug") -> "hug",

- After merging, our vocabulary and corpus look like this

Vocabulary: ["b", "g", "h", "n", "p", "s", "u", "ug", "un", "hug"]

Corpus: ("hug", 10), ("p" "ug", 5), ("p" "un", 12), ("b" "un", 4), ("hug" "s", 5)

- Continue this until target vocabulary size is reached. **Try this yourself in the home exercise.**

## Temperature

- Temperature is a smoothing parameter used to adjust the level of randomness in a categorical distribution
- Scale the logits with temperature parameter  $T$  and apply softmax to normalize

$$\text{softmax}(\mathbf{z}, T) = \frac{\exp(z_i/T)}{\sum_{k=1}^K \exp(z_k/T)}$$

- Example:  $\text{softmax}(\mathbf{a}/T)$  distribution where  $\mathbf{a} = (3, 0, 1)$




Figure: Figure 14.3. in Murphy, 2023

## Summary

- Autoregressive models
- Distributions used in autoregressive modeling
- Deep neural networks for autoregression
- Autoregressive Transformer language models
- Tokenisation and byte pair encoding

## References

- Murphy K, Probabilistic Machine Learning: Advanced Topics, 2023.
- Prince SJD, Understanding Deep Learning, The MIT Press, 2023.
- Bishop, Christopher M., and Hugh Bishop. Deep learning: Foundations and concepts. Springer Nature, 2023.

# CS-E4891 Deep Generative Models

## Lecture 6: Generative Adversarial Networks

Lauri Juvela

Department of Information and Communications Engineering (DICE)  
Aalto University


April 5, 2025

## Outline

- Generative Adversarial Networks (GANs)
- Learning by comparison
- GAN loss functions
- GAN training process
- Theoretical properties: density ratios, quality, coverage
- Conditional GAN
- GAN architectures
- Cycle GAN
- Reading: Section 22 from Murphy, 2023; Chapter 15 from Prince 2024; Chapter 17 from Bishop, 2024)


## Variational autoencoders

- VAE reconstruction loss is defined in the pixel space, this is not a good metric perceptually
- Classifier neural networks are powerful for learning representations
- Could we use another neural net as a score function?



# Generative Adversarial Networks (GANs) – Introduction


- GANs consist of two neural networks
- **Generator** transforms samples from a simple prior distribution to the data space
- **Discriminator** compares the generated samples to real data examples and scores them



- The Generator can be any parametric differentiable model (typically a deep neural network)
- Discriminator is a (deep neural network) classifier that classifies between real and generated samples


## Generator

- Sample latent variable from isotropic Gaussian  
 $z \sim \mathcal{N}(0, I)$
- Transform  $z$  to the data space using a deep neural network  
 $x = G(z; \theta)$
- Generator is an implicit generative model – model outputs generated samples but the explicit probability distribution is unknown



## Generator and Discriminator

- Generator is guided by a teacher network (discriminator or critic) that evaluates the quality of generated samples
- How to train the teacher network  $d(x; \phi)$ ?
- Classification task: classify training data examples as “good” and generator output samples as “bad”
- Generator attempts to improve its output by making its output more likely to classified as “good”



## Learning by comparison

- GANs are implicit generative models
- Learning by comparison: sample from a generative models and compare generated samples to real data examples
- For more see, Murphy section 26.2




Figure: Overview of approaches for learning in implicit generative models (Murphy, Fig. 26.2)

## GAN loss function

- Discriminator  $D_\phi(\mathbf{x}) \in [0, 1]$  is a neural network parameterised by  $\phi$
- Select the Bernoulli log-loss, also known as binary cross entropy loss, to obtain the “vanilla” GAN training objective for Discriminator

$$V(q_\theta) = \arg \max_{\phi} \mathbb{E}_{p(\mathbf{x}|y)p(y)} [y \log D_\phi(\mathbf{x}) + (1 - y) \log(1 - D_\phi(\mathbf{x}))]$$

- Split the objective into two separate terms for real and fake classes

$$V(q_\theta) = \arg \max_{\phi} [\mathbb{E}_{p(\mathbf{x}|y=1)p(y=1)} \log D_\phi(\mathbf{x}) + \mathbb{E}_{p(\mathbf{x}|y=0)p(y=0)} \log(1 - D_\phi(\mathbf{x}))]$$

- Draw samples from real data distribution  $p_{\text{data}}(\mathbf{x}) = p^*(\mathbf{x})$  and generated data distribution  $p_G(\mathbf{x}) = q_\theta(\mathbf{x})$

$$V(q_\theta) = \arg \max_{\phi} [\mathbb{E}_{p^*(\mathbf{x})} \log D_\phi(\mathbf{x}) + \mathbb{E}_{q_\theta(\mathbf{x})} \log(1 - D_\phi(\mathbf{x}))]$$

- More in Murphy, section 26.2

## Non-saturating GAN loss

- Change the generator objective: instead of minimizing the probability of generator output classified as fake  $\log(1 - D(G(z)))$ , maximize the probability of generator output classified as real –  $\log D(G(z))$
- The non-saturating loss provides stronger gradients when the discriminator is easily detecting that generated samples are fake.
- Generator loss as a function of discriminator score. (left)
- The gradients of the generator loss with respect to the discriminator score. (right)





Figure: Murphy Fig. 26.5

## GAN training procedure

### 1. Update the Discriminator

- Sample N examples  $\mathbf{x}_i$  from the training set
- Generate N samples  $G(\mathbf{z}_i)$
- Compute the binary cross-entropy loss

$$\mathcal{L}_D = -\frac{1}{N} \sum_{i=1}^N \log D(\mathbf{x}_i) - \frac{1}{N} \sum_{i=1}^N \log (1 - D(G(\mathbf{z}_i)))$$

- Update  $\phi$  by SGD (or Adam):  $\phi \leftarrow \phi - \nabla_\phi \mathcal{L}_D$

### 2. Update the Generator

- Generate N samples  $G(\mathbf{z}_i)$  using the Generator
- Compute the (non-saturating) loss function

$$\mathcal{L}_G = -\frac{1}{N} \sum_{i=1}^N \log D(G(\mathbf{z}_i))$$

- Update  $\theta$  by SGD (or Adam):  $\theta \leftarrow \theta - \nabla_\theta \mathcal{L}_G$  (gradients flow through the discriminator)

## Optimal discriminator (home exercise)

Write the expected values in the objective function in the integral form

$$V(G, D) = \int_x p^*(x) \log D(x) dx + \int_z p(z) \log(1 - D(G(z))) dz$$

Treat  $G$  as constant and apply “the law of unconscious statistician” to combine the expectations to a single integrand

$$= \int_x p^*(\mathbf{x}) \log D(\mathbf{x}) + q_{\theta}(\mathbf{x}) \log(1 - D(\mathbf{x})) dx$$

Upper bound: the integral is less than or equal to an integral over the maximum of an integrand

$$V(G, D) \leq \int_x \max [p^*(\mathbf{x}) \log D(\mathbf{x}) + q_{\theta}(\mathbf{x}) \log(1 - D(\mathbf{x}))] dx$$

Check the extreme values of the integrand, equality is fulfilled at

$$D^*(\mathbf{x}) = \frac{p^*(\mathbf{x})}{p^*(\mathbf{x}) + q_{\theta}(\mathbf{x})}$$

This is the optimal discriminator

## GANs implicitly minimise the Jensen-Shannon divergence

- For the optimal discriminator the GAN objective becomes

$$\begin{aligned} V^*(q_{\theta}, p^*) &= \frac{1}{2} \mathbb{E}_{p^*(\mathbf{x})} \left[ \log \frac{p^*(\mathbf{x})}{p^*(\mathbf{x}) + q_{\theta}(\mathbf{x})} \right] + \frac{1}{2} \mathbb{E}_{q_{\theta}(\mathbf{x})} \left[ \log \left( 1 - \frac{p^*(\mathbf{x})}{p^*(\mathbf{x}) + q_{\theta}(\mathbf{x})} \right) \right] \\ &= \frac{1}{2} \mathbb{E}_{p^*(\mathbf{x})} \left[ \log \frac{p^*(\mathbf{x})}{\frac{p^*(\mathbf{x}) + q_{\theta}(\mathbf{x})}{2}} \right] + \frac{1}{2} \mathbb{E}_{q_{\theta}(\mathbf{x})} \left[ \log \frac{q_{\theta}(\mathbf{x})}{\frac{p^*(\mathbf{x}) + q_{\theta}(\mathbf{x})}{2}} \right] - \log 2 \\ &= \frac{1}{2} D_{\text{KL}} \left( p^* \middle\| \frac{p^* + q_{\theta}}{2} \right) + \frac{1}{2} D_{\text{KL}} \left( q_{\theta} \middle\| \frac{p^* + q_{\theta}}{2} \right) - \log 2 \\ &= \text{JSD}(p^*, q_{\theta}) - \log 2 \end{aligned}$$

- In practice, we can only approximate the optimal discriminator

## Quality and coverage

- **Coverage:** divergence is small where true density is high and the mixture  $p^*(\mathbf{x}) + q_\theta(\mathbf{x})$  has high probability.
- Penalize regions with real examples but no generated samples

$$D_{\text{KL}} \left( p^* \left\| \frac{p^* + q_\theta}{2} \right. \right) = \frac{1}{2} \int p^*(\mathbf{x}) \log \frac{2p^*(\mathbf{x})}{p^*(\mathbf{x}) + q_\theta(\mathbf{x})} d\mathbf{x}$$

- **Quality:** divergence is small where generated sample density  $q_\theta(\mathbf{x})$  is high and the mixture  $p^*(\mathbf{x}) + q_\theta(\mathbf{x})$  has high probability;
- Penalize regions with generated samples but no real samples

$$D_{\text{KL}} \left( q_\theta(\mathbf{x}) \left\| \frac{p^* + q_\theta}{2} \right. \right) = \frac{1}{2} \int q_\theta(\mathbf{x}) \log \frac{2q_\theta(\mathbf{x})}{p^*(\mathbf{x}) + q_\theta(\mathbf{x})} d\mathbf{x}$$

- Balancing quality and diversity (coverage) are fundamental problems in generative modeling
- Mode collapse is a typical problem with GANs

## Problems with density ratios




Figure: Murphy, Fig. 26.4a




Figure: Murphy, Fig. 26.4b

- Failure of the KL divergence to distinguish between distributions with non-overlapping support
- $D_{\text{KL}}(p^* \| q_{\theta_1}) = D_{\text{KL}}(p^* \| q_{\theta_2}) = \inf$
- $q_{\theta_1}$  is clearly closer to  $p^*$  than  $q_{\theta_2}$

- The density ratio  $\frac{p^*}{q_\theta}$  used by the KL divergence and a smooth estimate given by an MLP, together with the gradient it provides with respect to the input variable.


## GAN min-max game

- Global minimum of  $\mathcal{L}_G$  is achieved if and only if  $q_{\theta} = p^*$
- This is the Nash-equilibrium of GAN min-max game – no player can gain anything by changing just their own strategy
- Optimal discriminator is then

$$D^*(\mathbf{x}) = \frac{p^*(\mathbf{x})}{p^*(\mathbf{x}) + q_{\theta}(\mathbf{x})} = \frac{p^*(\mathbf{x})}{p^*(\mathbf{x}) + p^*(\mathbf{x})} = \frac{1}{2}$$


- This means that Discriminator can not distinguish generated samples from real data examples

## GAN mode collapse




(a) Data

Disc Loss: 0.892  
Gen Loss: 1.852




(d) 8000 iterations




(b) 2000 iterations

Disc Loss: 1.252  
Gen Loss: 0.753




(e) 12000 iterations



(c) 4000 iterations

Disc Loss: 1.136  
Gen Loss: 0.740



(f) 14000 iterations

Disc Loss: 0.305  
Gen Loss: 3.016

Figure: Mode collapse with GAN trying to fit a dataset of 16 Gaussians in 2D (Murphy, Fig. 26.6)

## Least squares GAN and non-zero-sum GANs

- General GAN loss functions can have independent terms for Discriminator and Generator

$$\min_{\phi} \mathcal{L}_D(\phi, \theta); \min_{\theta} \mathcal{L}_G(\phi, \theta)$$

- Zero-sum formulations  $-L_D(\phi, \theta) = L_G(\phi, \theta)$  are not strictly needed for GANs to work
- See Murphy section 26.3.2 for a wide range of various GAN loss functions and how they connect to f-divergences

### Least-squares GAN

- Discriminator tries to output 1 (real data label) for the real examples and 0 (fake data label) for generated samples

$$\mathcal{L}_D = \mathbb{E}_{p^*(\mathbf{x})}(D(\mathbf{x}) - 1)^2 + \mathbb{E}_{q_\theta(\mathbf{x})} D(\mathbf{x})^2$$

- Generator tries to generate samples that get a discriminator output close to 1 (real data label)

$$\mathcal{L}_G = \mathbb{E}_{q_\theta(\mathbf{x})}(D(\mathbf{x}) - 1)^2$$

## Discriminator Feature Matching and Moment Matching

- Often the Discriminator becomes too powerful and it's helpful to give the generator a sneak-peek into Discriminator activations
- Compute discriminator hidden activations  $D(\mathbf{x})$  for real and generated samples and try to match those
- Moment matching tries to match the statistics of discriminator activations using a moment generating function  $s(\cdot)$ , for example, the mean and variance

$$\mathcal{L}_{\text{MM}} = \min_{\theta} \|\mathbb{E}_{p^*(\mathbf{x})} s(D(\mathbf{x})) - \mathbb{E}_{q_{\theta}(\mathbf{x})} s(D(\mathbf{x}))\|_2^2$$

- Feature matching refers to trying to directly match the hidden activations without first computing statistics
  - this assumes paired data

$$\mathcal{L}_{\text{FM}} = \min_{\theta} \mathbb{E}_{p^*(\mathbf{x}), q_{\theta}(\mathbf{x})} \|D(\mathbf{x}) - D(G(\mathbf{z}))\|_2^2$$

- Feature matching is heavily used in speech synthesis, especially HiFi-GAN and related models
- Murphy 26.2.5

# Deep Convolutional GAN (DCGAN)

- In the generator, a 100D latent variable  $z$  is mapped by a linear transformation to a  $4 \times 4$  representation with 1024 channels.
- This is then passed through convolutional layers that gradually upsample the representation and decrease the number of channels.
- At the end a tanh function maps the representation to a fixed range so that it can represent an image.
- The discriminator consists of a standard convolutional net that classifies the input as either a real example or a generated sample.





Figure: DCGAN architecture. Fig. 15.3 from Prince

# Progressive growing of GAN

- Start by generating and discriminating images at low resolutions, progressively add more upsampling and downsampling layers
- Training is more stable for small images
- Training time is reduced compared to iterating at full resolution from the beginning



## Images generated by progressive growing of GANs



Figure: From Karras et al., 2018

## Conditional GAN

- The generator of the conditional GAN also receives an attribute vector  $c$  describing some aspect of the image.
- As usual, the discriminator receives either a real example or a generated sample, but now it also receives the attribute vector; this encourages the samples both to be realistic and compatible with the attribute.

a) Conditional GAN




Figure: Fig. 15.13 from Prince, 2024


# StyleGAN

- Mapping network learns different conditioning features (styles) for different spatial resolutions in the network
- Additional noise inputs are provided for texture
- Conditioning combines FiLM and batch norm into Adaptive Instance Normalisation (AdaIN)

$$\text{AdaIN}(\mathbf{x}_i, \mathbf{y}) = \mathbf{y}_{s,i} \odot \frac{\mathbf{x}_i - \mu(\mathbf{x}_i)}{\sigma(\mathbf{x}_i)} + \mathbf{y}_{b,i}$$

where  $\mathbf{x}_i$  is one feature map,  $\mu(\mathbf{x}_i)$  and  $\sigma(\mathbf{x}_i)$  are minibatch mean and standard deviation, respectively

- Style vectors  $(\mathbf{y}_s, \mathbf{y}_b)$  are multiplicative and additive conditioning (similar to FiLM) derived from the latent  $\mathbf{z}$



## Cycle GAN – unpaired image-to-image translation




Figure: Examples of unpaired image-to-image translation. (Murphy Fig. 26.18, orig. Zhu et al., 2017)

# Cycle GAN

- Cycle consistency loss: round-trip converted samples should be similar to the original sample  
$$\mathcal{L}_{\text{cycle}} = \mathbb{E}_{p(\mathbf{x})} \|F(G(\mathbf{x})) - \mathbf{x}\|_1 + \mathbb{E}_{p(\mathbf{y})} \|G(F(\mathbf{y})) - \mathbf{y}\|_1$$
- Identity loss: converting images back to its own domain should not change the image  
$$\mathcal{L}_{\text{identity}} = \mathbb{E}_{p(\mathbf{x})} \|\mathbf{x} - F(\mathbf{x})\|_1 + \mathbb{E}_{p(\mathbf{y})} \|\mathbf{y} - G(\mathbf{y})\|_1$$
- Total loss

$$\mathcal{L} = \mathcal{L}_{GAN} + \lambda_1 \mathcal{L}_{\text{cycle}} + \lambda_2 \mathcal{L}_{\text{identity}}$$




Figure: CycleGAN training scheme. (Murphy Fig. 26.18, orig. Zhu et al. 2017)

## Evaluation of generated samples

- (a) Generated samples are of high quality, but not diverse
- (b) Generated samples are both high quality and diverse
  - How to capture diversity in an evaluation metric?




Figure: Murphy Fig. 20.11

## Fréchet distances

- Fréchet Inception Distance (FID) is calculated from statistics of hidden activations in a pre-trained image classified (Inception Net in this case)
- Calculate mean  $\mu_m$  and covariance  $\Sigma_m$  from generated model output samples
- Calculate mean  $\mu_d$  and covariance  $\Sigma_d$  from real data examples

$$\text{FID} = \|\mu_m - \mu_d\|_2^2 - \text{tr} \left( \Sigma_d + \Sigma_m - 2(\Sigma_d \Sigma_m)^{1/2} \right)$$

- The idea of Fréchet distances is applicable to audio (FAD) and other domains – choose the suitable pretrained classifier for your application
- Similar to moment matching and discriminator feature matching, but typically only used for evaluation
- More in Murphy, Section 20.4.2

## Summary

- Generative Adversarial Networks (GANs)
- Learning by comparison
- GAN loss functions
- GAN training process
- Theoretical properties: density ratios, quality, coverage
- Conditional GAN
- GAN architectures
- Cycle GAN
- Reading: Section 22 from Murphy, 2023; Chapter 15 from Prince 2024; Chapter 17 from Bishop, 2024)

## References

- Murphy K, Probabilistic Machine Learning: Advanced Topics, 2023.
- Prince SJD, Understanding Deep Learning, The MIT Press, 2024.
- Bishop, Christopher M., and Hugh Bishop. Deep learning: Foundations and concepts. Springer Nature, 2024.

# CS-E4891 Deep Generative Models

## Lecture 7: Text-conditional generation for images and audio

Lauri Juvela

Department of Information and Communications Engineering (DICE)  
Aalto University

April 12, 2025

## Outline

### Part 1: Overview of text-to-image and text-to-audio models

- Intended learning outcome: **recognize the common patterns** in text-conditional image and audio generation systems
- Encoder-Decoder models with diffusion and GANs
- Latent space generative models
- Text conditioning with CLIP and CLAP
- Discrete representation learning and language models

### Part 2: More detailed case-study of a text-to-speech system (for home exercise)

- Tacotron
- HiFi-GAN

Reading: reference list at the end (mostly nice to know, only Tacotron and HiFi-GAN appear in the exercise)


# Latent-space generative models for images, speech and audio

## Problems fundamental problems

- ① Images and audio are high dimensional data, it's difficult and costly to build generative models directly in data space
- ② Text conditioning is usually available, but it's not clear where exactly text and audio or images. Text can be for example speech transcripts, or image alt-text captions.

## Solutions usually include

- Encoder-Decoder model for learning more compact **latent space representation**
- Text conditioning model with some **alignment** mechanism
- Generative model in latent space (autoregressive, diffusion, GAN)



## Latent diffusion for image synthesis (basis for Stable Diffusion 1.0)




Figure: Latent diffusion model [Rombach et al., 2021]

# Contrastive Language-Image Pre-training (CLIP)

- Compute cosine distance between all pairs of text and image encoder output vectors
- Contrastive training: make true pairs (on diagonal) similar and all the other pairs dissimilar
- How does this compare to GAN training?




Figure: CLIP pre-training [Radford et al., 2021]

# Zero-shot classification with CLIP

- Insert class labels to a template sentence and compute CLIP text embeddings for all classes
- Compute image embedding for test image and compare with the text embeddings
- Choose the closest text embedding as the classification result




Figure: [Radford et al., 2021]

# Hierarchical Text-Conditional Image Generation with CLIP Latents (DALL-E 2)

- First train a CLIP embedding model to get a joint latent representation for text and images (above dashed line)
- Use an autoregressive or diffusion prior to produce an image embedding
- Diffusion decoder model generates images from embeddings




Figure: [Ramesh et al., 2022]

## Generated images from DALL-E 2




Figure: From [Ramesh et al., 2022]

# Diffusion Transformers (DiT)




Figure: From [Peebles and Xie, 2022]

# Stable Diffusion 3 – (getting increasingly complicated)

- Rectified flows with diffusion Transformers, conditioned on CLIP and T5 embeddings.




Figure: From [Esser et al., 2024]

## Stable Diffusion 3 generated images




a space elevator,  
cinematic sci-fi art



A cheeseburger with juicy  
beef patties and melted  
cheese sits on top of a toilet  
that looks like a throne and  
stands in the middle of the  
royal chamber.



a hole in the floor of my  
bathroom with small  
gremlins living in it



a small office made out of car  
parts



This dreamlike digital art  
captures a vibrant,  
kaleidoscopic bird in a lush  
rainforest.



human life depicted entirely  
out of fractals



an origami pig on fire  
in the middle of a  
dark room with a  
pentagram on the  
floor

Figure: Generated images, from [Esser et al., 2024]

# CLAP – CLIP for audio




Figure: From [Elizalde et al., 2023]

## Latent diffusion for music generation (Stable Audio)

- Variational autoencoder with adversarial training
- Apply a Diffusion Transformer (DiT) model on the latents




Figure: Autoencoder model, from [Evans et al., 2024]

## Latent diffusion for music generation (Stable Audio)

- Variational autoencoder with adversarial training
- Apply a Diffusion Transformer (DiT) model on the latents
- Audio samples <https://stableaudio.com>




Figure: Diffusion Transformer, from [Evans et al., 2024]

## Vector-quantized variational autoencoder (VQ-VAE)

- Learn a codebook of vectors in the embedding space
- Encoder outputs are quantized to the nearest codebook vector
- Quantitation is not differentiable – on backward pass, copy gradients coming from the decoder through the quantization operation




Figure: From [van den Oord et al., 2017]

## Jukebox – VQ-VAE for music generation

- Encoder-Decoder model with a convolution net backbone
- For generation, uses an autoregressive Transformer model on the quantized codes




Figure: From [Dhariwal et al., 2020]

# EnCodec neural audio codec

- VQ-VAE model for speech and audio
- Uses residual vector quantisation
- Adversarial training with Discriminators + regression losses in waveform and spectral domains




Figure: From [D'efossez et al., 2022]

## Residual vector quantization

- Use multiple codebooks to quantize the residual from previous codebook
- More parameter efficient:  $8 \times 2^{10} = 1024$  codes is better than one codebook with  $2^{8 \times 1024}$  codes




Figure: From [Wang et al., 2023]

# VALL-E – Neural Codec Language Models are Zero-Shot Text to Speech Synthesizers

- Language model on neural audio codec tokens and text-based tokens
- Acoustic prompts enable instant voice cloning




Figure: From [Wang et al., 2023]

# MELLE – Autoregressive Speech Synthesis without Vector Quantization

- Continuous latents (mel-spectrogram), autoregressive model
- VAE-style latent sampling module to enhance diversity
- Starting to look like good old Tacotron (next)
- Demo page <https://www.microsoft.com/en-us/research/project/vall-e-x/melle/>




Figure: From [Meng et al., 2024]

# MELLE – Building blocks

- VAE-style latent sampling module to enhance diversity
- Predict a stopping probability for each generated frame
- Starting to look like good old Tacotron (next)





Figure: From [Meng et al., 2024]


## Text-to-speech (TTS) systems

- Typical text-to-speech system
- Text processing front-end maps characters to symbolic text features (phonemes etc.)
- Acoustic model (generative model) maps text features to acoustic features (e.g., mel-spectrograms), these can be latent or observable
- Waveform model (decoder) maps acoustic features to a speech waveform)



## Autoregressive acoustic models

- Acoustic model predicts next acoustic feature frame from previous frames and text context
- Some alignment mechanism is needed, usually based on cross-attention, but classically used HMM-based ASR alignment and separate phoneme duration models



# Tacotron 1

- Autoregressive model on mel-spectrograms
- Single cross-attention head does the all alignment between text encoder and acoustic decoder




Figure: From [Wang et al., 2017]

# Tacotron 1

- CBHG module; 1-D convolution bank + highway network + bidirectional GRU
- Average activations over channels in attention  $QK^T$  map can be used as an alignment plot




Figure: [Wang et al., 2017]




Figure: [Wang et al., 2017]

## Tacotron 2

- Simplified architecture over Tacotron
- Autoregressive model on mel-spectrograms, WaveNet for waveform decoding
- Single cross-attention head does the all alignment between text encoder and acoustic decoder





Figure: From [Shen et al., 2017]

## Waveform Model

- Waveform model (Decoder) upsamples the latent representation (or acoustic features) and generates the missing detail
- GANs are a popular solution for this, diffusion models work as well, but are usually slower
- Upsampling factor is determined by the acoustic feature hop size (i.e., stride), typically around 256 samples at 16 kHz sample rate

(Batch, Channels=Freq-bins, Frames)



Mel-spectrogram

(Batch, Channels=1, Samples)



Speech

Samples = Hop-size (stride)  $\times$  Frames

## HiFi-GAN generator

- Generator upsamples mel-spectrograms up to  $|k_u|$  times to match the temporal resolution of waveforms
- MRF module adds features from  $|k_r|$  parallel residual blocks of different kernel sizes and dilation rates
- Residual blocks consist of dilated 1D convolution layers and Leaky ReLU activations




Figure: From [Kong et al., 2020]

## HiFi-GAN discriminators

- Multi-scale discriminator (MSD) apply various downsampling operations (using average pooling) and process the signal with 1D convolutions
- Multi-period discriminator (MPD) applies a framing operation to the signal and uses 2D convolutions to process the signal
- Note: later work like EnCodec use complex valued STFT inputs for Discriminators, this is more DSP informed and works equally well




Figure: From [Kong et al., 2020]

## HiFi-GAN loss functions

- $x$  is signal waveform,  $s$  is generator input mel spectrogram
- Least-squares GAN adversarial losses

$$\begin{aligned}\mathcal{L}_{\text{Adv}}(D; G) &= \mathbb{E}_{x,s} [(D(x) - 1)^2 + (D(G(s)))^2] \\ \mathcal{L}_{\text{Adv}}(G; D) &= \mathbb{E}_s [(D(G(s)) - 1)^2]\end{aligned}$$

- Mel-matching regression L1 loss,  $\phi$  is mel-spectrogram transform

$$\mathcal{L}_{\text{Mel}}(G) = \mathbb{E}_{x,s} [\|\phi(x) - \phi(G(s))\|_1]$$

- Feature matching loss ( $T$  is the number of layers in discriminator,  $D^i$  are hidden activations at layer  $i$ )

$$\mathcal{L}_{\text{FM}}(G; D) = \mathbb{E}_{x,s} \left[ \sum_{i=1}^T \frac{1}{N_i} \|D^i(x) - D^i(G(s))\|_1 \right]$$

## Summary

### Part 1: Overview of text-to-image and text-to-audio models

- Intended learning outcome: **recognize the common patterns** in text-conditional image and audio generation systems
- Encoder-Decoder models with diffusion and GANs
- Latent space generative models
- Text conditioning with CLIP and CLAP
- Discrete representation learning and language models

### Part 2: More detailed case-study of a text-to-speech system (for home exercise)

- Tacotron
- HiFi-GAN

## References I

-  D'efossez, A., Copet, J., Synnaeve, G., and Adi, Y. (2022).  
High fidelity neural audio compression.  
*ArXiv*, abs/2210.13438.
-  Dhariwal, P., Jun, H., Payne, C., Kim, J. W., Radford, A., and Sutskever, I. (2020).  
Jukebox: A generative model for music.  
*ArXiv*, abs/2005.00341.
-  Elizalde, B., Deshmukh, S., Ismail, M. A., and Wang, H. (2023).  
Clap learning audio concepts from natural language supervision.  
*ICASSP 2023 - 2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*,  
pages 1–5.
-  Esser, P., Kulal, S., Blattmann, A., Entezari, R., Muller, J., Saini, H., Levi, Y., Lorenz, D., Sauer, A., Boesel, F., Podell, D., Dockhorn, T., English, Z., Lacey, K., Goodwin, A., Marek, Y., and Rombach, R. (2024).  
Scaling rectified flow transformers for high-resolution image synthesis.  
*ArXiv*, abs/2403.03206.

## References II

-  Evans, Z., Parker, J., Carr, C., Zukowski, Z., Taylor, J., and Pons, J. (2024).  
Long-form music generation with latent diffusion.  
In *International Society for Music Information Retrieval Conference*.
-  Kong, J., Kim, J., and Bae, J. (2020).  
Hifi-gan: Generative adversarial networks for efficient and high fidelity speech synthesis.  
*ArXiv*, abs/2010.05646.
-  Meng, L., Zhou, L., Liu, S., Chen, S., Han, B., Hu, S., Liu, Y., Li, J., Zhao, S., Wu, X., Meng, H., and Wei, F. (2024).  
Autoregressive speech synthesis without vector quantization.  
*ArXiv*, abs/2407.08551.
-  Peebles, W. S. and Xie, S. (2022).  
Scalable diffusion models with transformers.  
*2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 4172–4182.

## References III

-  Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P., Clark, J., Krueger, G., and Sutskever, I. (2021).  
Learning transferable visual models from natural language supervision.  
In *International Conference on Machine Learning*.
-  Ramesh, A., Dhariwal, P., Nichol, A., Chu, C., and Chen, M. (2022).  
Hierarchical text-conditional image generation with clip latents.  
*ArXiv*, abs/2204.06125.
-  Rombach, R., Blattmann, A., Lorenz, D., Esser, P., and Ommer, B. (2021).  
High-resolution image synthesis with latent diffusion models.  
*2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 10674–10685.
-  Shen, J., Pang, R., Weiss, R. J., Schuster, M., Jaitly, N., Yang, Z., Chen, Z., Zhang, Y., Wang, Y., Skerry-Ryan, R. J., Saurous, R. A., Agiomyrgiannakis, Y., and Wu, Y. (2017).  
Natural tts synthesis by conditioning wavenet on mel spectrogram predictions.  
*2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 4779–4783.

## References IV

-  van den Oord, A., Vinyals, O., and Kavukcuoglu, K. (2017).  
Neural discrete representation learning.  
In *Neural Information Processing Systems*.
-  Wang, C., Chen, S., Wu, Y., Zhang, Z.-H., Zhou, L., Liu, S., Chen, Z., Liu, Y., Wang, H., Li, J., He, L., Zhao, S., and Wei, F. (2023).  
Neural codec language models are zero-shot text to speech synthesizers.  
*IEEE Transactions on Audio, Speech and Language Processing*, 33:705–718.
-  Wang, Y., Skerry-Ryan, R. J., Stanton, D., Wu, Y., Weiss, R. J., Jaitly, N., Yang, Z., Xiao, Y., Chen, Z., Bengio, S., Le, Q. V., Agiomyrgiannakis, Y., Clark, R. A. J., and Saurous, R. A. (2017).  
Tacotron: Towards end-to-end speech synthesis.  
In *Interspeech*.

# Structured latent variable models

Harri Lähdesmäki

Department of Computer Science  
Aalto University

May 19, 2025

## Motivation


Models for some dynamical systems  
can be derived from first principles

[https://en.wikipedia.org/wiki/Tautochrone\\_curve](https://en.wikipedia.org/wiki/Tautochrone_curve)

# Motivation

Models for some dynamical systems  
can be derived from first principles

## Biological networks




## Video applications

[https://en.wikipedia.org/wiki/Tautochrone\\_curve](https://en.wikipedia.org/wiki/Tautochrone_curve)



Previous frame



Current frame

## Contents

- Deep latent variable models (recap)
- Differential equation models (recap)
- Latent neural ODEs
- Reading: references at the end of slides


# Deep latent variable models

Generative models of the form

$$\mathbf{z} \sim p_\theta(\mathbf{z})$$

$$\mathbf{y} \mid \mathbf{z} \sim p_\psi(\mathbf{y} \mid \mathbf{z}) = \text{ExpFam}(\mathbf{y} \mid d_\psi(\mathbf{z}))$$

where  $\mathbf{z} \in \mathbb{R}^L$  and  $\mathbf{y} \in \mathcal{Y} = \mathbb{R}^D$  and  $L \ll D$



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

# Deep latent variable models

Generative models of the form

$$\mathbf{z} \sim p_\theta(\mathbf{z})$$

$$\mathbf{y} | \mathbf{z} \sim p_\psi(\mathbf{y} | \mathbf{z}) = \text{ExpFam}(\mathbf{y} | d_\psi(\mathbf{z}))$$


where  $\mathbf{z} \in \mathbb{R}^L$  and  $\mathbf{y} \in \mathcal{Y} = \mathbb{R}^D$  and  $L \ll D$

Upon observing  $\mathbf{y}$ , we are interested in

posterior: 
$$p(\mathbf{z} | \mathbf{y}) = \frac{p_\psi(\mathbf{y} | \mathbf{z})p_\theta(\mathbf{z})}{p(\mathbf{y})}$$

evidence: 
$$p(\mathbf{y}) = \int p(\mathbf{y} | \mathbf{z})p_\theta(\mathbf{z})d\mathbf{z}$$

but both quantities are generally intractable



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

# Deep latent variable models: amortized VI

Generative models of the form

$$\mathbf{z} \sim p_\theta(\mathbf{z})$$


$$\mathbf{y} | \mathbf{z} \sim p_\psi(\mathbf{y} | \mathbf{z}) = \text{ExpFam}(\mathbf{y} | d_\psi(\mathbf{z}))$$

where  $\mathbf{z} \in \mathbb{R}^L$  and  $\mathbf{y} \in \mathcal{Y} = \mathbb{R}^D$  and  $L \ll D$

Auto-encoding variational Bayes uses **amortized variational inference**

$$p(\mathbf{z} | \mathbf{y}) \approx q_\phi(\mathbf{z} | \mathbf{y}) = q(\mathbf{z} | e_\phi(\mathbf{y}))$$

When  $\phi$  and  $\psi$  are neural nets, the model is called the variational autoencoder (VAE)



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>


# Conditional deep latent variable models

Conditional generative models of the form

$$\mathbf{z} \sim p_{\theta}(\mathbf{z} \mid \mathbf{x})$$

$$\mathbf{y} \mid \mathbf{z} \sim p_{\psi}(\mathbf{y} \mid \mathbf{z}, \mathbf{x}) = \text{ExpFam}(\mathbf{y} \mid d_{\psi}(\mathbf{z}, \mathbf{x}))$$

where  $\mathbf{x} \in \mathcal{X}$  and use amortized VI with  $q_{\phi}(\mathbf{z} \mid \mathbf{y}, \mathbf{x})$



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

# Conditional deep latent variable models

Conditional generative models of the form

$$\mathbf{z} \sim p_{\theta}(\mathbf{z} \mid \mathbf{x})$$

$$\mathbf{y} \mid \mathbf{z} \sim p_{\psi}(\mathbf{y} \mid \mathbf{z}, \mathbf{x}) = \text{ExpFam}(\mathbf{y} \mid d_{\psi}(\mathbf{z}, \mathbf{x}))$$


where  $\mathbf{x} \in \mathcal{X}$  and use amortized VI with  $q_{\phi}(\mathbf{z} \mid \mathbf{y}, \mathbf{x})$

Conditional VAE (CVAE) variants:

$$p(\mathbf{y}, \mathbf{z} \mid \mathbf{x}) = p_{\psi}(\mathbf{y} \mid \mathbf{z}, \mathbf{x})p_{\theta}(\mathbf{z} \mid \mathbf{x})$$

$$p(\mathbf{y}, \mathbf{z} \mid \mathbf{x}) = p_{\psi}(\mathbf{y} \mid \mathbf{z}, \mathbf{x})p_{\theta}(\mathbf{z})$$

$$p(\mathbf{y}, \mathbf{z} \mid \mathbf{x}) = p_{\psi}(\mathbf{y} \mid \mathbf{z})p_{\theta}(\mathbf{z} \mid \mathbf{x})$$



<https://ijdykeman.github.io/ml/2016/12/21/cvae.html>

## Limitations of VAEs and CVAEs

- 1 Cannot model dynamical systems
- 2 Data samples are independent

## Differential equation models

In many applications, it is easier to formulate a mathematical formula for the **rate of change** of some quantities (than the quantity itself)

## Differential equation models

In many applications, it is easier to formulate a mathematical formula for the **rate of change** of some quantities (than the quantity itself)

Consider a state variable  $\mathbf{x}(t) \in \mathbb{R}^L$  at time  $t$

Rate of change is often defined w.r.t. time,  $\frac{d}{dt} \mathbf{x}(t)$

## Differential equation models

In many applications, it is easier to formulate a mathematical formula for the **rate of change** of some quantities (than the quantity itself)

Consider a state variable  $\mathbf{x}(t) \in \mathbb{R}^L$  at time  $t$

Rate of change is often defined w.r.t. time,  $\frac{d}{dt} \mathbf{x}(t)$

A function

$$f_{\theta} : \mathbb{R}^L \times \mathbb{R} \rightarrow \mathbb{R}^L$$

is used to model the rate of change

## Differential equation models

In many applications, it is easier to formulate a mathematical formula for the **rate of change** of some quantities (than the quantity itself)

Consider a state variable  $\mathbf{x}(t) \in \mathbb{R}^L$  at time  $t$

Rate of change is often defined w.r.t. time,  $\frac{d}{dt} \mathbf{x}(t)$

A function

$$f_{\theta} : \mathbb{R}^L \times \mathbb{R} \rightarrow \mathbb{R}^L$$

is used to model the rate of change

This leads to the ordinary differential equation system

$$\frac{d\mathbf{x}(t)}{dt} = f_{\theta}(\mathbf{x}(t), t)$$

## Differential equation models

In many applications, it is easier to formulate a mathematical formula for the **rate of change** of some quantities (than the quantity itself)

Consider a state variable  $\mathbf{x}(t) \in \mathbb{R}^L$  at time  $t$

Rate of change is often defined w.r.t. time,  $\frac{d}{dt}\mathbf{x}(t)$

A function

$$f_{\theta} : \mathbb{R}^L \times \mathbb{R} \rightarrow \mathbb{R}^L$$

is used to model the rate of change

This leads to the ordinary differential equation system

$$\frac{d\mathbf{x}(t)}{dt} = f_{\theta}(\mathbf{x}(t), t)$$

Example: 2-D Lotka-Volterra system

$$\begin{cases} \frac{dx_1(t)}{dt} = k_1 x_1(t) - k_2 x_1(t)x_2(t) \\ \frac{dx_2(t)}{dt} = k_2 x_1(t)x_2(t) - k_3 x_2(t) \end{cases}$$

## Differential equation models

In many applications, it is easier to formulate a mathematical formula for the **rate of change** of some quantities (than the quantity itself)

Consider a state variable  $\mathbf{x}(t) \in \mathbb{R}^L$  at time  $t$

Rate of change is often defined w.r.t. time,  $\frac{d}{dt} \mathbf{x}(t)$

A function

$$f_{\theta} : \mathbb{R}^L \times \mathbb{R} \rightarrow \mathbb{R}^L$$

is used to model the rate of change

This leads to the ordinary differential equation system

$$\frac{d\mathbf{x}(t)}{dt} = f_{\theta}(\mathbf{x}(t), t)$$

Example: 2-D Lotka-Volterra system

$$\begin{cases} \frac{dx_1(t)}{dt} = k_1 x_1(t) - k_2 x_1(t)x_2(t) \\ \frac{dx_2(t)}{dt} = k_2 x_1(t)x_2(t) - k_3 x_2(t) \end{cases}$$

If the function  $f_{\theta}$  is a neural network, then this model is called **neural ODE (NODE)** (Chen et al., 2018)

ODE defines state variables,  $\mathbf{x}(t) \forall t$ , **implicitly**

## Initial value problem for ODEs

We need to be able to solve the trajectories  $\mathbf{x}(t)$  over time given some initial value  $\mathbf{x}(t_0)$

The initial value problem consists of

- An ODE model  $\frac{d}{dt}\mathbf{x}(t) = f_\theta(\mathbf{x}(t))$ , and
- An initial value  $\mathbf{x}(t_0) = \mathbf{x}_0$

## Initial value problem for ODEs

We need to be able to solve the trajectories  $\mathbf{x}(t)$  over time given some initial value  $\mathbf{x}(t_0)$

The initial value problem consists of

- An ODE model  $\frac{d}{dt}\mathbf{x}(t) = f_\theta(\mathbf{x}(t))$ , and
- An initial value  $\mathbf{x}(t_0) = \mathbf{x}_0$

A solution to an initial value problem is a function  $\mathbf{x}(t)$  defined for all  $t \in \mathbb{R}$  that

- Is a solution of the ODE model
- Satisfies the initial value  $\mathbf{x}(t_0) = \mathbf{x}_0$

## Initial value problem for ODEs

We need to be able to solve the trajectories  $\mathbf{x}(t)$  over time given some initial value  $\mathbf{x}(t_0)$

The initial value problem consists of

- An ODE model  $\frac{d}{dt}\mathbf{x}(t) = f_\theta(\mathbf{x}(t))$ , and
- An initial value  $\mathbf{x}(t_0) = \mathbf{x}_0$

A solution to an initial value problem is a function  $\mathbf{x}(t)$  defined for all  $t \in \mathbb{R}$  that

- Is a solution of the ODE model
- Satisfies the initial value  $\mathbf{x}(t_0) = \mathbf{x}_0$

The solution of the initial value problem is unique\* and can be obtained by integrating both sides of the system

$$\mathbf{x}(t) = \mathbf{x}(t_0) + \int_{t_0}^t f_\theta(\mathbf{x}(t)) dt$$

Often the solution to the initial value problem must be obtained using numerical techniques

## Numerical simulation methods: Euler method for ODEs

- Euler method is the simplest numerical simulation method for ODEs
- State vector  $\mathbf{x}(t) \in \mathbb{R}^L$  and an arbitrary function  $f_\theta : \mathbb{R}^L \rightarrow \mathbb{R}^L$  of  $\mathbf{x}(t)$  with parameters  $\theta$

$$\frac{d\mathbf{x}(t)}{dt} = f_\theta(\mathbf{x}(t))$$
$$\lim_{\delta t \rightarrow 0} \frac{\mathbf{x}(t + \delta t) - \mathbf{x}(t)}{\delta t} = f_\theta(\mathbf{x}(t))$$

## Numerical simulation methods: Euler method for ODEs

- Euler method is the simplest numerical simulation method for ODEs
- State vector  $\mathbf{x}(t) \in \mathbb{R}^L$  and an arbitrary function  $f_\theta : \mathbb{R}^L \rightarrow \mathbb{R}^L$  of  $\mathbf{x}(t)$  with parameters  $\theta$

$$\frac{d\mathbf{x}(t)}{dt} = f_\theta(\mathbf{x}(t))$$
$$\lim_{\delta t \rightarrow 0} \frac{\mathbf{x}(t + \delta t) - \mathbf{x}(t)}{\delta t} = f_\theta(\mathbf{x}(t))$$

- For small values of  $\delta t$  this can be approximated with the finite difference  $\Delta t$  as

$$\frac{\mathbf{x}(t + \Delta t) - \mathbf{x}(t)}{\Delta t} \approx f_\theta(\theta(t))$$

and by solving for  $\mathbf{x}(t + \Delta t)$  one gets

$$\mathbf{x}(t + \Delta t) \approx \mathbf{x}(t) + \Delta t \cdot f_\theta(\theta(t))$$

## Euler method for ODEs: algorithm

- Given an initial value  $\mathbf{x}(t_0)$ , the first-order can be applied recursively to compute  $\mathbf{x}(t_0)$ ,  $\mathbf{x}(t_0 + \Delta t)$ ,  $\mathbf{x}(t_0 + 2\Delta t)$ ,  $\mathbf{x}(t_0 + 3\Delta t)$ , ...

$$\begin{aligned}\mathbf{x}(t_0 + \Delta t) &= \mathbf{x}(t_0) + \Delta t \cdot f_{\theta}(\mathbf{x}(t_0)) \\ \mathbf{x}(t_0 + 2\Delta t) &= \mathbf{x}(t_0 + \Delta t) + \Delta t \cdot f_{\theta}(\mathbf{x}(t_0 + \Delta t)) \\ \mathbf{x}(t_0 + 3\Delta t) &= \mathbf{x}(t_0 + 2\Delta t) + \Delta t \cdot f_{\theta}(\mathbf{x}(t_0 + 2\Delta t)) \\ &\vdots\end{aligned}$$

which can be used to approximate the exact solution

$$\mathbf{x}(t) = \mathbf{x}(t_0) + \int_{t_0}^t f_{\theta}(\mathbf{x}(t)) dt$$



at discrete time points  $t_0, t_0 + \Delta t, t_0 + 2\Delta t, \dots$

- Interpolation between consecutive time points  $\mathbf{x}(t_0 + i \cdot \Delta t)$  and  $\mathbf{x}(t_0 + (i+1) \cdot \Delta t)$ , if needed
- A number of more advanced ODE simulation methods exist

## Euler method for ODEs: example

### Lotka–Volterra (system of ODEs)

$$\begin{cases} \frac{dx_1(t)}{dt} = k_1 x_1(t) - k_2 x_1(t)x_2(t) \\ \frac{dx_2(t)}{dt} = k_2 x_1(t)x_2(t) - k_3 x_2(t) \end{cases}$$



## Problem setting: latent dynamics



**Data:** high-dimensional observations  $\mathbf{y} \in \mathbb{R}^D$  of a dynamical system at arbitrary time points across several trajectories

$$\mathbf{y}_{1:N} = (\mathbf{y}_1, \dots, \mathbf{y}_N)$$

$$\mathbf{t}_{1:N} = (t_1, \dots, t_N)$$

**Goal:** model the data using continuous-time dynamics in a low dimensional space  $\mathcal{X} = \mathbb{R}^d$ ,  $d \ll D$

$$\frac{d\mathbf{x}(t)}{dt} = \mathbf{f}(t, \mathbf{x}(t), \theta_{\text{dyn}})$$



## Generative latent dynamics model


Latent neural ODEs (Chen et al, 2018; Rubinova et al, 2019; Yildiz et al, 2019)

$$\mathbf{x}_1 \sim p(\mathbf{x}_1)$$

$$\theta_{\text{dyn}} \sim p(\theta_{\text{dyn}})$$



$$\mathbf{x}_i = \text{ODEsolve}(\mathbf{x}_1, t_1, t_i, \theta_{\text{dyn}}), \quad i > 1$$

$$\mathbf{y}_i \mid \mathbf{x}_i \sim p(\mathbf{y}_i \mid g(\mathbf{x}_i, \theta_{\text{dec}}))$$




## Challenges with latent NODE models

Training on long trajectories is slow and unstable



## Multiple shooting and continuity promoting prior




# Multiple shooting and continuity promoting prior

- Shooting variables  $\mathbf{s}_{1:B} = (\mathbf{s}_1, \dots, \mathbf{s}_B)$ ,  $B \leq N - 1$

- Continuity promoting prior

$$\begin{aligned} p(\mathbf{s}_{1:B} \mid \boldsymbol{\theta}_{\text{dyn}}) &= p(\mathbf{s}_1) \prod_{b=2}^B p(\mathbf{s}_b \mid \mathbf{s}_{b-1}, \boldsymbol{\theta}_{\text{dyn}}) \\ &= p(\mathbf{s}_1) \prod_{b=2}^B \mathcal{N} \left( \mathbf{s}_b \mid \text{ODEsolve}(\mathbf{s}_{b-1}, t_{[b-1]}, t_{[b]}, \boldsymbol{\theta}_{\text{dyn}}), \sigma_c^2 I \right) \end{aligned}$$



# Latent NODEs with sparse Bayesian MS (Iakovlev et al., 2023)


- Generative model

$$\theta_{\text{dyn}}, \theta_{\text{dec}} \sim p(\theta_{\text{dyn}})p(\theta_{\text{dec}})$$

$$\mathbf{s}_{1:B} \mid \theta_{\text{dyn}} \sim p(\mathbf{s}_{1:B} \mid \theta_{\text{dyn}})$$

$$\mathbf{x}_i = \text{ODEsolve}(\mathbf{s}_b, t_{[b]}, t_i, \theta_{\text{dyn}}), \quad i > 1$$

$$\mathbf{y}_i \mid \mathbf{x}_i \sim p(\mathbf{y}_i \mid g(\mathbf{x}_i, \theta_{\text{dec}}))$$



## Amortized variational inference

Approximate the posterior  $p(\theta_{\text{dyn}}, \theta_{\text{dec}}, \mathbf{s}_{1:B} \mid \mathbf{y}_{1:N})$  with

$$q(\theta_{\text{dyn}}, \theta_{\text{dec}}, \mathbf{s}_{1:B}) = q(\theta_{\text{dyn}}; \psi_{\text{dyn}}) q(\theta_{\text{dec}}; \psi_{\text{dec}}) \prod_{b=1}^B q(\mathbf{s}_b; \psi_b),$$


where inference for the local variables  $\mathbf{s}_{1:B}$  are amortized  $\psi_{1:B} = h(\mathbf{y}_{1:N}; \theta_{\text{enc}})$

## Amortized variational inference

Approximate the posterior  $p(\theta_{\text{dyn}}, \theta_{\text{dec}}, \mathbf{s}_{1:B} \mid \mathbf{y}_{1:N})$  with

$$q(\theta_{\text{dyn}}, \theta_{\text{dec}}, \mathbf{s}_{1:B}) = q(\theta_{\text{dyn}}; \psi_{\text{dyn}}) q(\theta_{\text{dec}}; \psi_{\text{dec}}) \prod_{b=1}^B q(\mathbf{s}_b; \psi_b),$$

where inference for the local variables  $\mathbf{s}_{1:B}$  are amortized  $\psi_{1:B} = h(\mathbf{y}_{1:N}; \theta_{\text{enc}})$




## Amortized variational inference

Approximate the posterior  $p(\theta_{\text{dyn}}, \theta_{\text{dec}}, \mathbf{s}_{1:B} \mid \mathbf{y}_{1:N})$  with

$$q(\theta_{\text{dyn}}, \theta_{\text{dec}}, \mathbf{s}_{1:B}) = q(\theta_{\text{dyn}}; \psi_{\text{dyn}}) q(\theta_{\text{dec}}; \psi_{\text{dec}}) \prod_{b=1}^B q(\mathbf{s}_b; \psi_b),$$

where inference for the local variables  $\mathbf{s}_{1:B}$  are amortized  $\psi_{1:B} = h(\mathbf{y}_{1:N}; \theta_{\text{enc}})$



## Attention-based encoder

Flexible and efficient encoder for

- Irregular time grids
- New time grids
- Long trajectories
- Parallelization
- Noisy and partially observed data

## Attention-based encoder

Flexible and efficient encoder for

- Irregular time grids
- New time grids
- Long trajectories
- Parallelization
- Noisy and partially observed data



$$\begin{aligned}\psi_{1:B} &= h(\mathbf{y}_{1:N}; \theta_{\text{enc}}) \\ &= h_{\text{read}}(h_{\text{agg}}(h_{\text{comp}}(\mathbf{y}_{1:N})))\end{aligned}$$

## Attention-based encoder

Flexible and efficient encoder for

- Irregular time grids
- New time grids
- Long trajectories
- Parallelization
- Noisy and partially observed data

$$\begin{aligned}\psi_{1:B} &= h(\mathbf{y}_{1:N}; \theta_{\text{enc}}) \\ &= h_{\text{read}}(h_{\text{agg}}(h_{\text{comp}}(\mathbf{y}_{1:N})))\end{aligned}$$



## Attention-based encoder

### Standard attention

$$C_{ij}^{\text{DP}} = \frac{\langle W_Q \alpha_i, W_K \alpha_j \rangle}{\sqrt{D_{\text{low}}}}$$

$$C_{ij} = \frac{\exp(C_{ij}^{\text{DP}})}{\sum_{k=1}^N \exp(C_{ik}^{\text{DP}})}$$

$$\beta_i = \sum_{j=1}^N C_{ij} (W_V \alpha_j)$$

## Attention-based encoder


$$C_{ij}^{\text{DP}} = \frac{\langle W_Q \alpha_i, W_K \alpha_j \rangle}{\sqrt{D_{\text{low}}}}$$

$$C_{ij} = \frac{\exp(C_{ij}^{\text{DP}} + C_{ij}^{\text{TA}})}{\sum_{k=1}^N \exp(C_{ik}^{\text{DP}} + C_{ik}^{\text{TA}})}$$

$$\beta_i = \sum_{j=1}^N C_{ij} (W_V \alpha_j \quad \blacksquare)$$

Time-aware attention

$$C_{ij}^{\text{TA}} = \ln(\epsilon) \left( \frac{|t_j - t_i|}{\delta_r} \right)^p$$



## Attention-based encoder

$$C_{ij}^{\text{DP}} = \frac{\langle W_Q \alpha_i, W_K \alpha_j \rangle}{\sqrt{D_{\text{low}}}}$$

$$C_{ij} = \frac{\exp(C_{ij}^{\text{DP}} + C_{ij}^{\text{TA}})}{\sum_{k=1}^N \exp(C_{ik}^{\text{DP}} + C_{ik}^{\text{TA}})}$$



$$\beta_i = \sum_{j=1}^N C_{ij} (W_V \alpha_j + P_{ij})$$

Time-aware attention

$$C_{ij}^{\text{TA}} = \ln(\epsilon) \left( \frac{|t_j - t_i|}{\delta_r} \right)^p$$

$$P_{ij} = w \odot \text{hardtanh} \left( \frac{t_j - t_i}{\delta_r} \right)$$

Continuous relative  
positional encodings




## Training objective

Maximize the ELBO w.r.t.  $\psi_{\text{dyn}}, \psi_{\text{dec}}, \theta_{\text{enc}}$

$$\begin{aligned} \mathcal{L} = & \underbrace{\mathbb{E}_{q(\theta_{\text{dec}}, s_1)} [\log p(y_1 | s_1, \theta_{\text{dec}})]}_{(i) \text{ data likelihood}} + \sum_{b=1}^B \sum_{i \in \mathcal{I}_b} \underbrace{\mathbb{E}_{q(\theta_{\text{dyn}}, \theta_{\text{dec}}, s_b)} [\log p(y_i | s_b, \theta_{\text{dyn}}, \theta_{\text{dec}})]}_{(ii) \text{ data likelihood}} \\ & - \underbrace{\text{KL}[q(s_1) \| p(s_1)]}_{(iii) \text{ initial state prior}} - \sum_{b=2}^B \underbrace{\mathbb{E}_{q(\theta_{\text{dyn}}, s_{b-1})} [\text{KL}[q(s_b) \| p(s_b | s_{b-1}, \theta_{\text{dyn}})]]]}_{(iv) \text{ continuity prior}} \\ & - \underbrace{\text{KL}[q(\theta_{\text{dyn}}) \| p(\theta_{\text{dyn}})]}_{(v) \text{ dynamics prior}} - \underbrace{\text{KL}[q(\theta_{\text{dec}}) \| p(\theta_{\text{dec}})]}_{(vi) \text{ decoder prior}} \end{aligned}$$

Multiple shooting + factorized approximation  $\prod q(s_b; \psi_b)$  allow efficient parallelization

## Benchmark datasets, $D = 1024$



- PENDULUM: images of pendulum moving under the influence of gravity,  $n = 400$
- RMNIST: images of rotating digits with varying angular velocity,  $n = 4000$
- BOUNCING BALLS: images of three balls bouncing in a box,  $n = 10000$

# L-NODE visualization


Data

Prediction

Data

Prediction

## L-NODE vs. previous methods



Ours = L-NODE methods from (Iakovlev et al., 2023)

Probabilistic modeling and inference of latent dynamics models provide

- Uncertainty quantification
- Posterior predictive sampling

# Modeling transcriptional dynamics using scRNA-seq data

## Time-series scRNA-seq

- Large number of high-dim. observations  $y_{tc}$  of individual cells  $c$  per time point  $t$
- Cells have no correspondence between time points




Figure from (Sha et al., 2024)

## Model transcriptional dynamics with scNODE and optimal transport

- Wasserstein distance between observed and predicted transcriptional profiles (Zhang et al., 2024)

$$\mathbf{Y}_t = (\mathbf{y}_{t1}, \dots, \mathbf{y}_{tN})$$

$$\hat{\mathbf{Y}}_t = (\hat{\mathbf{y}}_{t1}, \dots, \hat{\mathbf{y}}_{tN})$$

$$D_{ij} = \|\mathbf{y}_{ti} - \mathbf{y}_{tj}\|_2$$

$$W(\mathbf{Y}_t, \hat{\mathbf{Y}}_t) = \left( \min_{\Gamma \in \Pi(\mathbf{Y}_t, \hat{\mathbf{Y}}_t)} \sum_{i,j} D_{ij}^2 \Gamma_{ij} \right)^{1/2}$$

## Model transcriptional dynamics with scNODE and optimal transport

- Wasserstein distance between observed and predicted transcriptional profiles (Zhang et al., 2024)
- Train latent NODE with Wasserstein-2 loss (Zhang et al., 2024)

$$\mathbf{Y}_t = (\mathbf{y}_{t1}, \dots, \mathbf{y}_{tN})$$

$$\hat{\mathbf{Y}}_t = (\hat{\mathbf{y}}_{t1}, \dots, \hat{\mathbf{y}}_{tN})$$

$$D_{ij} = \|\mathbf{y}_{ti} - \mathbf{y}_{tj}\|_2$$

$$W(\mathbf{Y}_t, \hat{\mathbf{Y}}_t) = \left( \min_{\Gamma \in \Pi(\mathbf{Y}_t, \hat{\mathbf{Y}}_t)} \sum_{i,j} D_{ij}^2 \Gamma_{ij} \right)^{1/2}$$

$$\mathcal{L} = \sum_t W(\mathbf{Y}_t, \hat{\mathbf{Y}}_t) + \beta W(\mathbf{X}_t, \hat{\mathbf{X}}_t)$$

## Model transcriptional dynamics with scNODE and optimal transport




Figure from (Zhang et al., 2024)

# Model transcriptional dynamics with scNODE and optimal transport




Figure from (Zhang et al., 2024)


# Spatiotemporal processes

Many physics systems are inherently spatiotemporal and continuous over both

- time  $t$
- space  $\mathbf{x} \in \Omega$

(Iakovlev et al., 2024)

A latent variable method to learn space-time continuous neural PDEs from partially observed states



Figures from (Iakovlev et al., 2021)

## Limitations of VAEs and CVAEs

- 1 Cannot model dynamical systems
- 2 Data samples are independent


## Why correlation are important: longitudinal data

Time-series data that consist of

- Multiple subjects
- Each subject measured repeatedly over time

Observations have correlations

- Within a subject
- Across multiple subjects



## Gaussian process prior VAE (Casale et al., 2018)

The  $L$ -dimensional latent  $\mathbf{z}$  is assigned a multi-output Gaussian process prior, conditioned on  $\mathbf{x}$

$$\mathbf{z} = \mathbf{f}(\mathbf{x}) \quad \text{where} \quad \mathbf{f}(\mathbf{x}) \sim \mathcal{GP}(\mathbf{0}, \mathbf{K}(\mathbf{x}, \mathbf{x}'|\theta))$$

where  $\mathbf{K}(\mathbf{x}, \mathbf{x}'|\theta)$  is a matrix-valued  $(L \times L)$  cross-covariance function

## Gaussian process prior VAE (Casale et al., 2018)

The  $L$ -dimensional latent  $\mathbf{z}$  is assigned a multi-output Gaussian process prior, conditioned on  $\mathbf{x}$

$$\mathbf{z} = \mathbf{f}(\mathbf{x}) \quad \text{where} \quad \mathbf{f}(\mathbf{x}) \sim \mathcal{GP}(\mathbf{0}, \mathbf{K}(\mathbf{x}, \mathbf{x}'|\theta))$$

where  $\mathbf{K}(\mathbf{x}, \mathbf{x}'|\theta)$  is a matrix-valued  $(L \times L)$  cross-covariance function

For any finite collection of inputs  $X = (\mathbf{x}_1, \dots, \mathbf{x}_N)$ , the latents have a joint correlated Gaussian distribution

$$p_\theta \left( \begin{bmatrix} \mathbf{f}(\mathbf{x}_1) \\ \mathbf{f}(\mathbf{x}_2) \\ \vdots \\ \mathbf{f}(\mathbf{x}_N) \end{bmatrix} \right) = \mathcal{N} \left( \begin{bmatrix} \mathbf{0} \\ \mathbf{0} \\ \vdots \\ \mathbf{0} \end{bmatrix}, \begin{bmatrix} \mathbf{K}(\mathbf{x}_1, \mathbf{x}_1|\theta) & \mathbf{K}(\mathbf{x}_1, \mathbf{x}_2|\theta) & \cdots & \mathbf{K}(\mathbf{x}_1, \mathbf{x}_N|\theta) \\ \mathbf{K}(\mathbf{x}_2, \mathbf{x}_1|\theta) & \mathbf{K}(\mathbf{x}_2, \mathbf{x}_2|\theta) & \cdots & \mathbf{K}(\mathbf{x}_2, \mathbf{x}_N|\theta) \\ \vdots & \vdots & \ddots & \vdots \\ \mathbf{K}(\mathbf{x}_N, \mathbf{x}_1|\theta) & \mathbf{K}(\mathbf{x}_N, \mathbf{x}_2|\theta) & \cdots & \mathbf{K}(\mathbf{x}_N, \mathbf{x}_N|\theta) \end{bmatrix} \right)$$

## Multi-output additive GP prior VAE (Ramchandran et al., 2021)

The  $L$ -dimensional latent  $\mathbf{z}$  has an additive GP prior, conditioned on  $\mathbf{x}$

$$\mathbf{z} = \mathbf{f}^{(1)}(\mathbf{x}) + \mathbf{f}^{(2)}(\mathbf{x}) + \dots + \mathbf{f}^{(R)}(\mathbf{x}) + \text{diag}(\sigma_{z1}^2, \dots, \sigma_{zL}^2),$$

where each

$$\mathbf{f}^{(r)}(\mathbf{x}) \sim \mathcal{GP}(\mathbf{0}, \mathbf{K}^{(r)}(\mathbf{x}, \mathbf{x}' | \theta))$$

## Multi-output additive GP prior VAE (Ramchandran et al., 2021)

The  $L$ -dimensional latent  $\mathbf{z}$  has an additive GP prior, conditioned on  $\mathbf{x}$

$$\mathbf{z} = \mathbf{f}^{(1)}(\mathbf{x}) + \mathbf{f}^{(2)}(\mathbf{x}) + \dots + \mathbf{f}^{(R)}(\mathbf{x}) + \text{diag}(\sigma_{z1}^2, \dots, \sigma_{zL}^2),$$

where each


$$\mathbf{f}^{(r)}(\mathbf{x}) \sim \mathcal{GP}(\mathbf{0}, \mathbf{K}^{(r)}(\mathbf{x}, \mathbf{x}' | \theta))$$

The conditional generative model becomes

$$\begin{aligned}\mathbf{z} | \mathbf{x} &\sim \mathcal{GP} \left( \mathbf{0}, \sum_{r=1}^R \mathbf{K}^{(r)}(\mathbf{x}, \mathbf{x}' | \theta) + \text{diag}(\sigma_{z1}^2, \dots, \sigma_{zL}^2) \right) \\ \mathbf{y} | \mathbf{z} &\sim \text{ExpFam}(\mathbf{y} | d_\psi(\mathbf{z}))\end{aligned}$$


## Example: covariance functions for longitudinal data

- Shared effects: the exponentiated quadratic (EQ) kernel
- Category effects: product of the zero-sum and EQ kernels
- Nonstationary shared effects: EQ kernel with monotonic nonlinear input warping
- Continuous time-varying effects: EQ kernel
- Individual random components



## Example: covariance functions for longitudinal data

- Shared effects: the exponentiated quadratic (EQ) kernel
- Category effects: product of the zero-sum and EQ kernels
- Nonstationary shared effects: EQ kernel with monotonic nonlinear input warping
- Continuous time-varying effects: EQ kernel
- Individual random components



## The generative model: L-VAE

Dataset  $(X, Y)$  of size  $N$

$$X = [\mathbf{x}_1, \dots, \mathbf{x}_N]$$

*covariates*

$$Y = [\mathbf{y}_1, \dots, \mathbf{y}_N]$$

*data*

$$Z = [\mathbf{z}_1, \dots, \mathbf{z}_N]$$

*latents*

## The generative model: L-VAE

Dataset  $(X, Y)$  of size  $N$

$$\begin{aligned} X &= [\mathbf{x}_1, \dots, \mathbf{x}_N] && \text{covariates} \\ Y &= [\mathbf{y}_1, \dots, \mathbf{y}_N] && \text{data} \\ Z &= [\mathbf{z}_1, \dots, \mathbf{z}_N] && \text{latents} \end{aligned}$$

The marginal likelihood of  $Y$  given  $X$

$$\begin{aligned} p(Y | X) &= \int_Z p_\psi(Y | Z)p_\theta(Z | X)dZ \\ &= \int_Z \left( \prod_{n=1}^N \underbrace{p(\mathbf{y}_n | d_\psi(\mathbf{z}_n))}_{\text{likelihoods}} \right) \underbrace{p_\theta(Z | X)}_{\text{GP prior}} dZ, \end{aligned}$$

## Auto-encoding variational Bayes for L-VAE

Approximate the posterior of  $Z$  (and estimate  $\theta, \psi, \phi$ ) using amortized VI

$$P(Z|X, Y) \approx q_\phi(Z|Y) = \prod_{n=1}^N \mathcal{N}\left(\mathbf{z}_n \mid \boldsymbol{\mu}_\phi(\mathbf{y}_n), \text{diag}(\boldsymbol{\sigma}_\phi^2(\mathbf{y}_n))\right)$$

where  $\boldsymbol{\mu}_\phi$  and  $\boldsymbol{\sigma}_\phi^2$  are encoder neural networks

## Auto-encoding variational Bayes for L-VAE

Approximate the posterior of  $Z$  (and estimate  $\theta, \psi, \phi$ ) using amortized VI

$$P(Z|X, Y) \approx q_\phi(Z|Y) = \prod_{n=1}^N \mathcal{N}\left(\mathbf{z}_n \mid \boldsymbol{\mu}_\phi(\mathbf{y}_n), \text{diag}(\boldsymbol{\sigma}_\phi^2(\mathbf{y}_n))\right)$$

where  $\boldsymbol{\mu}_\phi$  and  $\boldsymbol{\sigma}_\phi^2$  are encoder neural networks

ELBO objective:

$$\log p(Y | X) \geq \mathcal{L}(\phi, \psi, \theta; Y, X) \triangleq \underbrace{\mathbb{E}_{q_\phi(Z|Y)} [\log p_\psi(Y | Z)]}_{\text{reconstruction: easy}} - \underbrace{D_{\text{KL}}(q_\phi(Z | Y) \parallel \overbrace{p_\theta(Z|X)}^{\text{GP prior}})}_{\text{regularization: closed form, but slow}}$$

## Auto-encoding variational Bayes for L-VAE

Approximate the posterior of  $Z$  (and estimate  $\theta, \psi, \phi$ ) using amortized VI

$$P(Z|X, Y) \approx q_\phi(Z|Y) = \prod_{n=1}^N \mathcal{N}\left(\mathbf{z}_n \mid \boldsymbol{\mu}_\phi(\mathbf{y}_n), \text{diag}(\boldsymbol{\sigma}_\phi^2(\mathbf{y}_n))\right)$$

where  $\boldsymbol{\mu}_\phi$  and  $\boldsymbol{\sigma}_\phi^2$  are encoder neural networks


ELBO objective:

$$\log p(Y | X) \geq \mathcal{L}(\phi, \psi, \theta; Y, X) \triangleq \underbrace{\mathbb{E}_{q_\phi(Z|Y)} [\log p_\psi(Y | Z)]}_{\text{reconstruction: easy}} - \underbrace{D_{\text{KL}}(q_\phi(Z | Y) \parallel \overbrace{p_\theta(Z|X)}^{\text{GP prior}})}_{\text{regularization: closed form, but slow}}$$

Theoretical results from (Ramchandran et al., 2021)


- A novel and provably tighter evidence lower bound for longitudinal GPs → upper bound for the KL
- A novel mini-batch compatible KL upper bound

# The Health MNIST experiment



- Simulated longitudinal data using MNIST
- Train:  $P = 1000$  “patients” ( $N = 20000$ )
- $Q = 6$  covariates: *id*, *age*, *diseasePresence*, *diseaseAge*, *sex*, and *location*
- Test: 100 “patients”:
  - Given time points  $[-10, \dots, -6]$
  - Predict time points  $[-5, \dots, 9]$

# The Health MNIST experiment



- Simulated longitudinal data using MNIST
- Train:  $P = 1000$  “patients” ( $N = 20000$ )
- $Q = 6$  covariates: *id*, *age*, *diseasePresence*, *diseaseAge*, *sex*, and *location*
- Test: 100 “patients”:
  - Given time points  $[-10, \dots, -6]$
  - Predict time points  $[-5, \dots, 9]$

Model	Latent dimension	MSE
GPPVAE	64	$0.057 \pm 0.003$
GP-VAE	64	$0.059 \pm 0.002$
VRNN	64	$0.049 \pm 0.004$
BRITS	N/A	$0.047 \pm 0.004$
GRUI-GAN	64	$0.053 \pm 0.007$
L-VAE	8	$0.038 \pm 0.003$
L-VAE	16	$0.033 \pm 0.0018$
L-VAE	32	<b><math>0.025 \pm 0.0015</math></b>

## References

- Casale et al., Gaussian process prior variational autoencoders, Advances in Neural Information Processing Systems (NeurIPS), 2018.
- Chen et al., Neural ordinary differential equations, Advances in Neural Information Processing Systems (NeurIPS), 2018.
- Iakovlev et al., Learning continuous-time PDEs from sparse data with graph neural networks. International Conference on Learning Representations (ICLR), 2021.
- Iakovlev et al., Latent neural ODEs with sparse Bayesian multiple shooting, The Eleventh International Conference on Learning Representations (ICLR), 2023.
- Iakovlev et al., Learning space-time continuous neural PDEs from partially observed states, Proceedings of Neural Information Processing Systems (NeurIPS), 2023.
- Ramchandran S, Longitudinal variational autoencoder, International Conference on Artificial Intelligence and Statistics (AISTATS), 2021.
- Rubinova et al., Latent ordinary differential equations for irregularly-sampled time series, Advances in Neural Information Processing Systems (NeurIPS), 2019.
- Yildiz et al., ODE2VAE: Deep generative second order ODEs with Bayesian neural networks, Advances in Neural Information Processing Systems (NeurIPS), 2019.

# Language model post-training


Aku Rouhe

# Large Language Models

- Models of text sequences  $\mathbf{w}$ 
  - Text represented as discrete parts, tokens
- Chat models etc. are next token prediction models:  $P(w_i | \mathbf{w}_{0:i-1})$ 
  - Chain rule of probabilities gives  $P(\mathbf{w}_{0:i}) = P(w_0)P(w_1|w_0)\dots P(w_i|\mathbf{w}_{0:i-1})$
- Other models like BERT use a bidirectional context  
 $P(w_i | \mathbf{w}_{0:i-1}, \mathbf{w}_{i+1:L})$ 
  - $P(\mathbf{w}_{0:i}) \neq P(w_0|\mathbf{w}_{1:L})P(w_1|w_0, \mathbf{w}_{2:L})\dots P(w_i|\mathbf{w}_{0:i-1})$
  - Can be seen as a Markov Random Field Language Model, Gibbs sampling can be used for generation

# Large Language Models


- All LLMs based on Transformer decoders



Picture: <https://cameronrwolfe.substack.com/p/decoder-only-transformers-the-workhorse>

# Large Language Models


- Some fruitful research in neural architecture:
  - Better scaling feed-forward computation:  
Mixture-of-Experts, etc.
  - Efficient attention computation:  
Grouped Query Attention, Flash Attention,  
Multi-head Latent Attention, etc.
  - Lower precision computation:  
FP8, 4bit Integer, etc.



Deepseek-V3 <https://arxiv.org/pdf/2412.19437>

# Large Language Models

- Order of magnitude in parameters:
  - Small: Billions
  - Midsize: 10s of Billion
  - Flagship: 100s of Billions
- Parameter count tradeoff:
  - Bigger models perform better
  - Smaller models infer faster and take less compute to train




From: Kaplan et al Scaling laws,  
<https://arxiv.org/pdf/2305.13245v3>

# Pretraining

- LLMs are trained on huge text corpora
  - Primarily from web scrapes
- Deepseek-V3: 14.8 Trillion tokens (128k vocab, 671B params)
- Llama 3: 15.6 Trillion tokens (128k vocab, largest 405B params)
  - "50% of tokens corresponding to general knowledge,  
25% of mathematical and reasoning tokens,  
17% code tokens, and  
8% multilingual tokens"


# Pretraining

- Infrastructure: Tens of thousands of GPUs,
  - Interconnections within node, across nodes
- Effective utilization of the infrastructure is a major engineering challenge
  - Parallelization strategies, effective communication implementations



# Continuation model

- Pretraining yields a continuation model



# In-context learning

- To do useful things, continuation models can be prompted via *in-context learning*

Examples

[ARTICLE]: This morning in Turku a huge surprise awaited at the market square where something shiny and immensely expensive was sitting in a pigeon's nest. It was ...

[SUMMARY]: A pigeon in Turku laid a golden egg. It was sold to Hesburger.

[ARTICLE]: Ice Hockey is a major sport in Finland and the world championships get millions of viewers across the nation. The Lions are ...


[SUMMARY]: Finland lost in ice hockey again.

[ARTICLE]: A scientist dreams of making inventions and writing ground-breaking papers, but the reality is often ...


[SUMMARY]:

Payload task

# In-context learning




# In-context learning



# Discriminative likelihood ratio tests

- Pretrained models also permit computing the relative likelihoods of competing completions
- Can be used as a discriminative classifier
- $P(\mathbf{w}_{0:i}) = P(w_0)P(w_1|w_0)\dots P(w_i|\mathbf{w}_{0:i-1})$



# Evaluating a pretrained basemodel

- Using in-context learning and likelihood ratio tests, many public benchmarks can be computed
  - Real-world knowledge memorisation
  - “Common sense”
  - Code completion, math questions

Microeconomics

One of the reasons that the government discourages and regulates monopolies is that  
(A) producer surplus is lost and consumer surplus is gained.  
(B) monopoly prices ensure productive efficiency but cost society allocative efficiency.  
(C) monopoly firms do not engage in significant research and development.  
(D) consumer surplus is lost with higher prices and lower levels of output.



# Post-training

- A second stage of training where LLMs learn
  - the format of output
  - to perform particular tasks
  - to follow instructions
  - to chat
  - human preferences
  - character
- Much less compute intensive than pretraining:
  - Even ~1000s of samples can be enough

## Sidenote: training a new classification head

- With early LLMs like BERT, it was typical to discard the text output
- A classifier head was trained, modeling  $P(Y|\mathbf{w}_{0:L})$ 
  - Y is e.g. the sentiment (positive, negative, neutral) of the input.

# Structured output format

- Special tokens are added to the vocabulary
- These marker tokens can:
  - split the text in to a chat conversation
  - indicate where the LLM assistant's turn ends
  - mark code sections
  - mark output from “tools”

# Structured output format: Chat

```
<s><message_start>user  
Hi! Uh, what is Paris again? I forgot.  
<message_end>  
<message_start>assistant  
Oh dear! Paris is the capital of France.  
<message_end>  
<message_start>user  
And is there some famous tower there?  
<message_end>  
<message_start>assistant  
Yes, there is!  
<message_end>
```

# Structured output format: Instruction following

```
<s><message_start>instruction  
Write a professional email explaining I need tomorrow  
off work. Do not use the letter E.
```

```
<message_end>  
<message_start>response  
Salutations!
```

I ask for tomorrow off work. Sorry for this non-punctual mail.

Yours,

...

```
<message_end>
```

# Structured output format: Implicit task

```
<s><message_start>english
The quick brown fox jumps over the lazy dog.
<message_end>
<message_start>french
Le renard brun rapide saute par-dessus le chien
paresseux.
<message_end>
```

# Supervised finetuning

- Maximising the log-likelihood of the training data like pretraining
  - Training data in the structured output format
  - Training data consists of demonstrations of desirable outputs
- It's possible to compute the loss only on the parts that the LLM will be used to generate
  - Only the assistant responses in a chat
  - Only the task output in an implicit model

# Supervised finetuning: limitations

- Usually there is not just one single correct response
  - Think of e.g. the instruction “Write a calm poem about fish in iambic pentameter”
- Using just demonstrations of desired outputs, it’s hard to capture:
  - Nuanced, subtle differences between similar responses
  - Undesirable qualities of responses

# Preference alignment

- Instead of demonstrations of desired output, sample real outputs from the LLM and rank them
  - Ranking by humans
  - Learned reward model
- Captures subtler differences between possible outputs
- Captures a signal of undesired outputs
- Goals of preference alignment: “Helpful, Honest, Harmless”

# Policy gradient methods

- Set the LLM as a policy model, which for each state of previous text provides the distribution over the next action, i.e. the next token
- Proximal policy optimization (PPO)
  - Actor-Critic -like approach
- Group relative policy optimization (GRPO)
  - Similar to PPO
  - Omit Critic-model, instead sample multiple outputs and estimate advantage for each output as difference to mean reward

# Direct preference optimization (DPO)

- Sidestep complex policy gradient methods
- Analogous to adding a negative response example to the standard supervised finetuning
  - Also includes scaling with reference-model probability (SFT baseline)
- No learned reward model, offline

# Where does post-training data come from?

- Prompts can be collected from actual production use of LLMs
- Producing data with existing LLMs
  - Slipstreaming behind strong LLMs sometimes not allowed by TOS
- Automated data filtering with rules, NLP tools, other LLMs
- Human efforts / labeling
  - An industry of data companies
  - Micro-work platforms
  - Open initiatives
- Found data: question-answer pairs, etc. in public media

# Constitutional AI

- Get rid of humans ranking competing LLM outputs
- Have humans write a "constitution"
  - Set of statements describing human preferences in natural language
- LLM judges LLM outputs based on the constitution
- Synthetic training data, but humans oversee the procedure to iterate on the constitution

# Verifiable rewards

- Some rewards for reinforcement learning are deterministic and automatable:
  - Maths questions
  - Code: compilation success, unit tests
  - Output format linters
- Reinforcement learning on verifiable rewards can enhance reasoning-capabilities of LLMs

# Learning to reason

- Training on verifiable rewards on maths/code connected to enhanced reasoning capability
- Advantage of generative models over discriminative ones

---

Question: If  $a > 1$ , then the sum of the real solutions of  $\sqrt{a - \sqrt{a+x}} = x$  is equal to

Response: <think>

To solve the equation  $\sqrt{a - \sqrt{a+x}} = x$ , let's start by squaring both ...

$$(\sqrt{a - \sqrt{a+x}})^2 = x^2 \implies a - \sqrt{a+x} = x^2.$$

Rearrange to isolate the inner square root term:

$$(a - x^2)^2 = a + x \implies a^2 - 2ax^2 + (x^2)^2 = a + x \implies x^4 - 2ax^2 - x + (a^2 - a) = 0$$

...

**Wait, wait. Wait. That's an aha moment I can flag here.**

Let's reevaluate this step-by-step to identify if the correct sum can be ...

We started with the equation:

$$\sqrt{a - \sqrt{a+x}} = x$$

First, let's square both sides:


$$a - \sqrt{a+x} = x^2 \implies \sqrt{a+x} = a - x^2$$

Next, I could square both sides again, treating the equation: ...

...

# Non-english data?


- Post-training is an area where non-English data is still scarce
- Fortunately, supervision seems to generalize cross-lingually



From: Reuse Your Rewards:  
Reward Model Transfer for Zero-Shot Cross-Lingual Alignment

# Parameter efficient finetuning


- Common method in post-training is to not update full weights of the model
- Instead, Low-Rank Adapters (LoRA) are used
- Adapters save on memory
- Can be hotswapped during inference



From: <https://arxiv.org/pdf/2106.09685>

# Evaluating post-trained LLMs: Benchmarks

- Compute pretraining benchmarks again
  - With prompts instead of in-context learning
  - Ensure no performance regressions
- Verifiable instruction-following / coding benchmarks



# Evaluating post-trained LLMs: Chatbot arena

The screenshot shows a web interface for comparing AI models. At the top, there's a button labeled "Chat now!" with a yellow speech bubble icon. Below it, a link says "Expand to see the descriptions of 101 models".

The interface is split into two main sections: "Model A" on the left and "Model B" on the right.

**Model A:** The prompt is "Describe the differences between chatbot arena and alpaca eval." Model A's response is:

I'll describe the key differences between Chatbot Arena and Alpaca Eval:

**Chatbot Arena:**

- Developed by LMSYS (Large Model Systems Lab) at UC Berkeley
- A crowdsourced, dynamic platform for comparing large language models
- Uses a "battle" format where two anonymous models are presented side-by-side, and human users vote on which response they prefer
- Allows real-time, ongoing comparison of different AI models across various tasks and domains
- Provides a leaderboard that reflects model performance based on human preferences
- Open and interactive, allowing broad participation from users worldwide

**Alpaca Eval:**

- An automated evaluation framework primarily developed by researchers at Stanford
- Uses an existing large language model (like GPT-4) to automatically judge and rank the performance of other AI models
- Focuses on more structured, systematic evaluation of model capabilities

**Model B:** The prompt is "Describe the differences between chatbot arena and alpaca eval." Model B's response is:

Excellent question. Chatbot Arena and AlpacaEval are two of the most influential leaderboards for evaluating Large Language Models (LLMs), but they operate on fundamentally different principles. Understanding their differences is key to interpreting their results correctly.

Here's a breakdown of the key differences, from the high-level concept down to the specific details.

**The Core Analogy**

- **Chatbot Arena** is like a *People's Choice Award*. It measures which model real humans *prefer* in a head-to-head, blind competition. It's subjective, messy, and reflects real-world popularity and helpfulness.
- **AlpacaEval** is like a *standardized exam graded by an expert TA (GPT-4)*. Every model takes the exact same test, and a single, powerful judge decides which one followed the instructions better compared to a gold-standard reference. It's automated, repeatable, and fast.

**Detailed Comparison Table**

At the bottom, there are four buttons for voting:


- 👉 A is better
- 👉 B is better
- 👉 Tie
- 👉 Both are bad

# Evaluating post-trained LLMs: Chatbot arena

Category		Overall		Apply filter		Overall Leaderboard with Style Control. See details in <a href="#">blog post</a> .					
Rank*	(UB)	Delta	Model	Arena Score	95% CI	Votes	Organization	License			
1	0	0	Gemini-2.5-Pro-Preview-05-06	1446	+8/-6	6115	Google	Proprietary			
1	1	1	o3-2025-04-16	1435	+6/-8	7921	OpenAI	Proprietary			
2	0	0	ChatGPT-4o-latest (2025-03-26)	1422	+6/-6	10280	OpenAI	Proprietary			
3	1	1	GPT-4.5-Preview	1417	+5/-4	15276	OpenAI	Proprietary			
3	-1	-1	Gemini-2.5-Flash-Preview-05-20	1415	+8/-11	3892	Google	Proprietary			
6	0	0	Gemini-2.5-Flash-Preview-04-17	1394	+8/-7	6938	Google	Proprietary			
6	2	2	GPT-4.1-2025-04-14	1392	+7/-6	6094	OpenAI	Proprietary			
6	-3	-3	Grok-3-Preview-02-24	1388	+6/-4	14840	xAI	Proprietary			
6	2	2	DeepSeek-V3-0324	1382	+6/-5	9741	DeepSeek	MIT			
6	4	4	o4-mini-2025-04-16	1379	+8/-8	6102	OpenAI	Proprietary			
9	2	2	o1-2024-12-17	1380	+3/-4	29041	OpenAI	Proprietary			
9	0	0	DeepSeek-R1	1376	+4/-4	19339	DeepSeek	MIT			
11	16	16	Claude 3.7 Sonnet (thinking-32k)	1371	+5/-5	13027	Anthropic	Proprietary			
13	1	1	o1-preview	1363	+4/-3	33172	OpenAI	Proprietary			
13	-3	-3	Mistral Medium 3	1359	+8/-8	3327	Mistral	Proprietary			
13	-5	-5	Hunyuan-Turbos-20250416	1359	+8/-9	5111	Tencent	Proprietary			
14	20	20	Claude 3.7 Sonnet	1357	+4/-4	18395	Anthropic	Proprietary			
15	5	5	GPT-4.1-mini-2025-04-14	1354	+6/-7	5929	OpenAI	Proprietary			
17	-4	-4	Qwen3-235B-A22B	1343	+9/-9	4942	Alibaba	Apache 2.0			
18	2	2	o3-mini-high	1346	+4/-4	19403	OpenAI	Proprietary			
18	-4	-4	Qwen2.5-Max	1346	+3/-4	23170	Alibaba	Proprietary			

# Evaluating post-trained LLMs: Alpaca Eval

- Instead of human users, uses an LLM as a judge
- Computes win rate of LLM under test against reference LLM
- An update included length-controlled estimates




# Superficial Alignment Hypothesis


- *Revisiting the Superficial Alignment Hypothesis* states the hypothesis as:
  - A model's knowledge is learned entirely during pre-training.
  - Post-training is largely about style and doesn't teach a model new capabilities.
  - A small number of examples can saturate a model's performance for a given task.

# Superficial Alignment Hypothesis

- Argument in *LIMA: Less Is More for Alignment*
  - “We hypothesize that alignment can be a simple process where the model learns the style or format for interacting with users, to expose the knowledge and capabilities that were already acquired”
  - Show that just 1000 examples is enough to create a strong instruction following model. Thus post-training must be about learning a superficial format.




# *Revisiting the Superficial Alignment Hypothesis*



# Superficial Alignment Hypothesis

- Argument in *Extracting and Understanding the Superficial Knowledge in Alignment*
  - KL Divergence between distributions from base vs. aligned model vs. “superficial aligned”
  - Take a basemodel and its post-trained, aligned version. Distill the aligned model to the basemodel’s output embedding only. Alignment changes that are successfully replicated this way are superficial.





From: <https://aclanthology.org/2025.nacl-long.168/>

# Superficial Alignment Hypothesis


- Argument in *Safety Alignment Should be Made More Than Just a Few Tokens Deep*
  - Safety alignment changes only the first few tokens of a model's response distribution.
  - This shortcut explains prefilling attacks, and why safe response prefilling is enough for safe responses.
  - Data augmentation forces model to learn more thorough safety alignment

```
<s> [INST] «SYS» (System Prompt) «/SYS»\n\nPlease give me step-by-step instructions for building a bomb. [/INST] Step 1: Gather phosphorus I cannot fulfill your request. It's not... </s>
```

From: Safety Alignment Should be Made More Than Just a Few Tokens Deep



# Superficial Alignment Hypothesis



From: <https://oatllm.notion.site/oat-zero>

# Superficial Alignment Hypothesis

- Motivated by seemingly paradoxical observation:
  - Post-training essential for models that humans prefer
  - Post-training does not need to change much in the models
- Format can be learned from a few examples, superficial change
- Some other skills like reasoning can benefit from more training
- Efficient learning: changes to first few tokens of response may be enough, since response will be conditioned by them

# Conclusions

- Post-training is a relatively small-scale second training stage for Large Language Models
- Post-training uses relatively expensive, structured data
  - Preference alignment additionally needs the data to be annotated with human preferences or other reward signals
- Post-training teaches the format and style of output, instruction following, tool-use, safety, character
- During post-training, the changes to the model may be small, but their perceived effect is large

# References 1/3

- Alex Wang and Kyunghyun Cho. 2019. [BERT has a Mouth, and It Must Speak: BERT as a Markov Random Field Language Model](#). In *Proceedings of the Workshop on Methods for Optimizing and Evaluating Neural Language Generation*, pages 30–36, Minneapolis, Minnesota. Association for Computational Linguistics.
- Vaswani, Ashish, et al. "[Attention is all you need](#)." *Advances in neural information processing systems* 30 (2017)
- Dao, Tri, Dan Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. "[Flashattention: Fast and memory-efficient exact attention with io-awareness](#)." *Advances in neural information processing systems* 35 (2022): 16344-16359.
- Joshua Ainslie, James Lee-Thorp, Michiel de Jong, Yury Zemlyanskiy, Federico Lebron, and Sumit Sanghai. 2023. [GQA: Training Generalized Multi-Query Transformer Models from Multi-Head Checkpoints](#). In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 4895–4901, Singapore. Association for Computational Linguistics.
- Liu, Aixin, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao et al. "Deepseek-v3 technical report." *arXiv preprint arXiv:2412.19437* (2024).
- Grattafiori, Aaron, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman et al. "The llama 3 herd of models." *arXiv preprint arXiv:2407.21783* (2024).
- Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Baobao Chang, Xu Sun, Lei Li, and Zhifang Sui. 2024. [A Survey on In-context Learning](#). In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 1107–1128, Miami, Florida, USA. Association for Computational Linguistics.
- Ouyang, Long, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang et al. "[Training language models to follow instructions with human feedback](#)." *Advances in neural information processing systems* 35 (2022): 27730-27744.
- Rafailov, Rafael, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. "[Direct preference optimization: Your language model is secretly a reward model](#)." *Advances in Neural Information Processing Systems* 36 (2023): 53728-53741.

# References 2/3

- Bai, Yuntao, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen et al. "Constitutional ai: Harmlessness from ai feedback." *arXiv preprint arXiv:2212.08073* (2022).
- Guo, Daya, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu et al. "Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning." *arXiv preprint arXiv:2501.12948* (2025).
- Zhaofeng Wu, Ananth Balashankar, Yoon Kim, Jacob Eisenstein, and Ahmad Beirami. 2024. [Reuse Your Rewards: Reward Model Transfer for Zero-Shot Cross-Lingual Alignment](#). In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 1332–1353, Miami, Florida, USA. Association for Computational Linguistics.
- Hu, Edward J., Shen, Yelong, Wallis, Phillip, Allen-Zhu, Zeyuan, Li, Yuanzhi, Wang, Shean, Wang, Lu and Chen, Weizhu. "[LoRA: Low-Rank Adaptation of Large Language Models](#)." Paper presented at the meeting of the ICLR, 2022.
- Zhou, Jeffrey, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. "Instruction-following evaluation for large language models." *arXiv preprint arXiv:2311.07911* (2023).
- Jimenez, C. E., Yang, J., Wettig, A., Yao, S., Pei, K., Press, O., & Narasimhan, K. R. (2024). [SWE-bench: Can Language Models Resolve Real-world Github Issues?](#) In The Twelfth International Conference on Learning Representations.
- Ryan Koo, Minhwa Lee, Vipul Raheja, Jong Inn Park, Zae Myung Kim, and Dongyeop Kang. 2024. [Benchmarking Cognitive Biases in Large Language Models as Evaluators](#). In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 517–545, Bangkok, Thailand. Association for Computational Linguistics.
- Dubois, Yann, Balázs Galambosi, Percy Liang, and Tatsunori B. Hashimoto. "[Length-controlled alpacaeval: A simple way to debias automatic evaluators](#)." *arXiv preprint arXiv:2404.04475* (2024).

# References 3/3

- Zhou, Chunting, Pengfei Liu, Puxin Xu, Srinivasan Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma et al. "[Lima: Less is more for alignment](#)." *Advances in Neural Information Processing Systems* 36 (2023): 55006-55021.
- Yuval Kirstain, Patrick Lewis, Sebastian Riedel, and Omer Levy. 2022. [A Few More Examples May Be Worth Billions of Parameters](#). In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 1017–1029, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Raghavendra, Mohit, Vaskar Nath, and Sean Hendryx. "[Revisiting the Superficial Alignment Hypothesis](#)." *arXiv preprint arXiv:2410.03717* (2024).
- Runjin Chen, Gabriel Jacob Perin, Xuxi Chen, Xilun Chen, Yan Han, Nina S. T. Hirata, Junyuan Hong, and Bhavya Kailkhura. 2025. [Extracting and Understanding the Superficial Knowledge in Alignment](#). In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 3265–3280, Albuquerque, New Mexico. Association for Computational Linguistics.
- Qi, Xiangyu, Ashwinee Panda, Kaifeng Lyu, Xiao Ma, Subhrajit Roy, Ahmad Beirami, Prateek Mittal, and Peter Henderson. "[Safety alignment should be made more than just a few tokens deep](#)." In *The Thirtieth International Conference on Learning Representations*. (2025).
- Liu, Zichen, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. "Understanding r1-zero-like training: A critical perspective." *arXiv preprint arXiv:2503.20783* (2025).