

Are some problems more difficult than others?

Problem Integer Program $\rightarrow \Pi_{\mathbf{P}}$









Can all problems be solved with this pipeline?

Is this efficient?



Can all problems be solved with this pipeline?

Is this efficient?



Can all problems be solved with this pipeline?

Is this efficient?

Outline: Complexity Classes

Introduction: Why care about complexity?

- Decision Problems
 - Definition
 - Example: Minimum Cost Set Cover
- Difficulty Classes
 - P
 - NP
 - Co-NP

Learning objectives:

You are able to

- describe a decision problem
- describe a polynomial time checkable certificate
- state the definitions of three complexity classes


Introduction: Why care about complexity?

From Garey and Johnson's book Computers and Intractability (1979):

Your boss hands you a problem and tells you to find an efficent algorithm.

The problem is tricky. You work days and nights.

A week later, you have not found a good algorithm. You tell your boss...





"I can't find an efficient algorithm, I guess I'm just too dumb."

You can tell from the cast of characters it is 1979...

That feels bad.

What if you could **prove** that finding an efficient algorithm to the problem is impossible?




"I can't find an efficient algorithm, because no such algorithm is possible!"

That feels much better!

That feels **much** better!

However, nobody knows how to prove this.

But we can prove something like this...



"I can't find an efficient algorithm, but neither can all these famous people."

Source: <u>Garey, Michael R.</u>; <u>Johnson, D. S.</u> (1979), Computers and Intractability: A Guide to the Theory of NP-Completeness, W. H. Freeman.

Almost as good.

This type of proofs relate to a problem's complexity class.

Almost as good.

"The set of problems not solvable by famous people".

This type of proofs relate to a problem's complexity class.

Almost as good.

This type of proofs relate to a problem's complexity class.

Today's goal: Learn about complexity classes and understand their algorithmic implications.

Why? Sets standards for what is reasonable to expect.

Outline

• Introduction: Why care about Hardness?

- Decision Problems
 - Definition
 - Example: Set Cover
- Difficulty Classes
 - P
 - NP
 - Co-NP

Decision Problems: example

A **decision problem** is a problem Π with binary output.

I.e. the solution is either **True** or **False**.

Decision Problems: example

A **decision problem** is a problem \prod with binary output.

I.e. the solution is either **True** or **False**.

Example (Decision Set Cover):

Input: n elements and m subsets, integer k > 0.

Goal: *Decide* if a set cover of size ≤ k exists

Decision Problems: details matter!

Small differences in the problem can mean large difference in difficulty!

Decision Problems: Many forms

Small differences in the problem can mean large difference in difficulty!

Example (Decision Set Cover):

Input: n elements and m subsets, integer k > 0.

Goal: Decide if a set cover of size ≤ k exists

Not trivial....

Decision Problems: Many forms

Small differences in the problem can mean large difference in difficulty!

Example (Decision Set Cover):

Input: n elements and m subsets, integer k > 0.

Goal: Decide if a set cover of size ≤ k exists

Not trivial....

Example (Easy Set cover):

Input: n elements and m subsets

Goal: Decide if a set cover exists

Piece of cake!

Outline

- Introduction: why care about Hardness?
- Decision Problems: formalizing a problem
 - Definition
 - Example: Set Cover
- Difficulty Classes
 - P
 - NP
 - Co-NP
 - Relationships

There are many complexity classes. This lecture covers the most common 3.

P (Polynomial Time)

This is the class of problems that can be solved in polynomial time.

There are many complexity classes. We cover the most common 3.

P (Polynomial Time)

This is the class of problems that can be solved in polynomial time.

For problems in P your boss can expect you to code an efficient algoritm.

There are many complexity classes. We cover the most common 3.

P (Polynomial Time)

This is the class of problems that can be solved in polynomial time.

For problems in P your boss can expect you to code an efficient algoritm.

Computation will eventually finish

There are many complexity classes. We cover the most common 3.

P (Polynomial Time)

This is the class of problems that can be solved in polynomial time.

Examples (Problems in P):

- Stable Matching
- Minimum Spanning Tree (MST)
- 2-Approximation to Minimum Vertex Cover

How do we prove a problem is in P?

Show a polynomial time algorithm!

How do we prove a problem is in P?

Show a polynomial time algorithm!

Examples (we designed the algorithms):

- Stable Matching
- Minimum Spanning Tree (MST)
- 2-Approximation to Minimum Vertex Cover

How do we prove a problem is in P?

Show a polynomial time algorithm!

Examples (we designed the algorithms):

- Stable Matching
- Minimum Spanning Tree (MST)
- 2-Approximation to Minimum Vertex Cover

How do we prove a problem is in P?

Show a polynomial time algorithm!

Examples (we designed the algorithms):

- Stable Matching
- Minimum Spanning Tree (MST)
- 2-Approximation to Minimum Vertex Cover

Is there a vertex cover of size k?

Outline

- Introduction: why care about Hardness?
- Decision Problems: formalizing a problem
 - Definition
 - Example: Set Cover
- Difficulty Classes
 - P
 - NP
 - Co-NP
 - Relationships

NP = (Non-deterministic Polynomial Time)

Call instance I of problem a Yes-instance if the solution to the decision problem is True.

A problem is in NP if for every Yes-instance there is a *certificate* that can be verified in polynomial time.

NP = (Non-deterministic Polynomial Time)

Call instance I of problem Π a Yes-instance if the solution to the decision problem is True.

A problem is in NP if for every Yes-instance there is a *certificate* that can be verified in polynomial time.

Complexity Classes: NP

NP = (Non-deterministic Polynomial Time)

Call instance I of problem Π a Yes-instance if the solution to the decision problem is True.

A problem Π is in NP if for every Yes-instance there is a *certificate* that can be verified in polynomial time.

Proving a problem is in NP

A problem Π is in NP if for every Yes-instance there is a *certificate* that can be verified in polynomial time.

To prove a problem is in NP we need the following:

- 1. A proof that every Yes-instance has a Yes-certificate
- 2. An algorithm that correctly verifies a given certificate in polynomial time.

Proving a problem is in NP - Example

Example (Decision Set Cover):

Input: n elements and m subsets, integer k > 0.

Goal: Decide if a set cover of size $\leq k$ exists

Claim: (Decision) Set Cover is in NP.

Proof. Every Yes-instance has a set cover with no more than *k* subsets.

Certificate: w.l.o.g let $\{S_1, S_2, ..., S_q\}$ be the set cover, where $q \le k \le m$.

To show: Can verify that all n elements are covered in polynomial time.

Go over each S_i in turn and mark every element as covered. There are at most m sets, each containing at most n elements, so this takes O(nm) time.

Complexity Classes: NP - an example

Example (Decision Set Cover):

Input: n elements and m subsets, integer k > 0.

Goal: Decide if a set cover of size $\leq k$ exists

Claim: (Decision) Set Cover is in NP.

This exists because we assume a Yes-instance

Proof. Every Yes-instance has a set cover with no more than *k* subsets.

Certificate: w.l.o.g let $\{S_1, S_2, ..., S_q\}$ be the set cover, where $q \le k \le m$.

To show: Can verify that all n elements are covered in polynomial time.

Go over each S_i in turn and mark every element as covered. There are at most m sets, each containing at most n elements, so this takes O(nm) time.

Complexity Classes: NP - an example

Example (Decision Set Cover):

Input: n elements and m subsets, integer k > 0.

Goal: Decide if a set cover of size $\leq k$ exists

Claim: (Decision) Set Cover is in NP.

Proof. Every Yes-instance has a set cover with no more than k subsets

Certificate: w.l.o.g let $\{S_1, S_2, ..., S_q\}$ be the set cover, where $q \leq k \leq m$.

To show: Can verify that all n elements are covered in polynomial time.

Go over each S_i in turn and mark every element as covered. There are at most m sets, each containing at most n elements, so this takes O(nm) time.

Given it exists, we can assume the certificate is known.

Outline

- Introduction: why care about Hardness?
- Decision Problems: formalizing a problem
 - Definition
 - Example: Set Cover
- Difficulty Classes
 - P
 - NP
 - Co-NP
 - Relationships

Complexity Classes: co-NP

Co-NP = "complement"-NP

Call instance I of problem \prod a No-instance if its solution to the decision problem is False.

A problem Π is in co-NP if for every No-instance there is a *certificate* that can be verified in polynomial time.

Proving a problem is in co-NP

The proof structure is the same as for NP


Proving a problem is in co-NP

The proof structure is the same as for NP


Example problem:

Is a number *x* a prime?

In a No-instance, provide the factors.




This is how most people think the classes relate.



This is how most people think the classes relate.

Proven relationships:

P is in NP and in co-NP




This is how most people think the classes relate.

There are problems that are both in co-NP and NP but not in P

Proven relationships:

P is in NP and in co-NP




This is how most people think the classes relate.

There are problems that are both in co-NP and NP but not in P

Open problems:

P =? NP (\$1 million prize)

NP = ? co - NP



This is how most people think the classes relate.

What most think:

 $P \neq NP$

 $NP \neq co-NP$

Outline

- Introduction: why care about Hardness?
- Decision Problems: formalizing a problem
 - Definition
 - Example: Set Cover
- Difficulty Classes
 - P
 - NP
 - Co-NP
 - Relationships

Next part: Reductions

Proving one problem is harder than another.