

MCBench: A Multicontext Safety Assessment Benchmark for Omni Large Language Models

Manh Luong¹, Tamas Abraham², Junae Kim², Amar Kaur², Rollin Omari², Gholamreza Haffari¹,
Trang Vu¹, Lizhen Qu¹, Dinh Phung¹

¹ Monash University, Australia

² Defence Science and Technology Group, Australia

{tien.luong, gholamreza.haffari, trang.vul, lizhen.qu, dinh.phung}.monash.edu,
{amas.abraham, junae.kim, amar.kaur, rollin.omari}@companyA.com

Abstract

Existing multimodal safety benchmarks focus solely on visual inputs and cannot assess Omni Large Language Models (LLMs) that process vision, audio, and text. We introduce MCBench, a benchmark with 1196 scenarios spanning four safety categories that require integrating multiple modalities for accurate safety assessment. Each unsafe scenario is paired with a minimally different safe counterpart to assess model sensitivity. Our evaluations of state-of-the-art models reveal significant challenges. Omni LLMs struggle with subtle or non-physical risks but perform better when salient visual or acoustic cues are present. Analysis of reasoning traces shows that, although models can extract modality-specific information, they often fail to integrate these cues effectively for safety judgments. Our findings reveal that current Omni LLMs lack robust cross-modal reasoning in safety-critical settings, underscoring the need for improved architectures and training strategies for multimodal safety.

Index Terms: multimodal model, safety assessment, multimodal benchmark

1. Introduction

Large language models (LLMs) have expanded beyond text-only processing through recent advances in multimodal training data [1, 2, 3] and architectural innovations [4, 5, 6]. Recent work has developed Omni LLMs capable of processing vision, audio, and speech simultaneously [7, 8]. These models demonstrate strong performance on complex multimodal reasoning tasks and are increasingly deployed in real-world applications ranging from virtual assistants [9] to the healthcare domain [10]. As Omni LLMs become more ubiquitous in safety-sensitive applications, ensuring their reliability in identifying and responding to unsafe situations becomes critical.

Current multimodal safety benchmarks [11, 12, 13] focus exclusively on visual content, evaluating scenarios where visual cues alone provide sufficient information for safety assessment. This design limits evaluation to visual language models and cannot assess omnimodal models that process vision, audio, and speech jointly. While omnimodal benchmarks exist [14, 15], they evaluate general reasoning capabilities rather than safety-specific reasoning. Moreover, existing safety benchmarks rely on single-modality scenarios, failing to reflect real-world complexity where safety assessment requires synthesizing information across multiple modalities, including visual, acoustic, and linguistic contexts.

To address these gaps, we introduce MCBench, the first multimodal, multicontext safety benchmark tailored for evaluat-

ing the safety-awareness of Omni LLMs in the multicontext setting. Table 1 illustrates the comparison between our benchmark and existing multimodal safety benchmarks. MCBench consists of 1196 multicontext safety scenarios across four coarse-grained taxonomies: physical harm, social harm, illegal harm, and property damage. To study the oversensitivity and insensitivity of Omni LLMs, we collect unsafe scenarios paired with corresponding safe scenarios that differ only in minimal contextual elements. Thus, the benchmark dataset consists of unsafe-safe scenario pairs. We first explore fine-grained categories and scenario pairs by collaborating with the Claude-Sonnet-4.5 model to better cover real-world safety situations. Then, we leverage existing generative models to generate corresponding multimodal inputs (audio and images) for each scenario. To ensure the quality of the benchmark, we include human experts in both the scenario design and data generation phases to filter out unrealistic scenarios and low-quality multimodal inputs.

We conduct a safety-awareness analysis of widely used open-source and proprietary Omni LLMs using MCBench. The results reveal three key findings regarding the safety-awareness of the evaluated models. First, current Omni LLMs struggle to assess safety in social and legal liability scenarios, while they perform well on physical harm and property damage categories. Second, visual context is challenging but provides informative cues that help models make accurate safety assessments. Third, failures in safety assessment arise primarily from limitations in Omni LLMs’ reasoning. More specifically, although these models can successfully extract ground-truth predicates from multimodal inputs, which are necessary for making safety assessments, they often fail to combine these cues to make accurate predictions. Furthermore, our ablation studies reveal that current Omni LLMs lack robust mechanisms for balanced multicontext integration. When encountering ambiguous cues, these models exhibit oversensitivity, focusing on a single potentially concerning signal while ignoring contradictory evidence from other modalities. This leads to systematic false positives on safe scenarios, where isolated cues might appear concerning without proper contextual integration.

To summarise, our contributions are threefold:

- We introduce MCBench, which focuses on evaluating the safety-awareness of Omni LLMs in the multicontext setting.
- We analyze state-of-the-art open-source and proprietary models on our benchmark. The analysis reveals that existing Omni LLMs struggle with scenarios involving subtle or non-physical safety risks (Social Harm and Illegal Harm), while performing substantially better on categories with salient visual and acoustic cues (Physical Harm and Property Damage).

Benchmark	Modality	Multicontext	Safety Situation		Ground-truth predicate
			safe	unsafe	
MOSSBench [16]	V	×	✓	×	×
MMSBench [11]	V	×	✓	✓	×
RMS dataset [12]	V	×	✓	✓	×
OmniBench [14]	A+V	✓	×	×	×
MCBench (Ours)	A+V+S	✓	✓	✓	✓

Table 1: Comparison of MCBench with other omnimodal and safety benchmarks. MCBench focuses on evaluating the safety-awareness of Omni LLMs in multicontext scenarios. A, V, and S denote audio, vision, and speech utterance, respectively.

- By analyzing reasoning traces, we find that models can extract relevant information but lack effective cross-modal integration capabilities. Models also exhibit oversensitivity, making safety judgments based on single concerning cues rather than holistically evaluating all available evidence.

2. Multimodal Multicontext Safety Benchmark

2.1. Overview

Problem definition. We define the problem of multimodal multicontext safety as follows: Given a triplet of omnimodal situational data $T = \{I, A, S\}$, where I, A, and S denote an image, an audio clip, and a speech utterance, respectively, a model must classify the safety label $R(I, A, S) \in \{\text{safe}, \text{unsafe}\}$ based on the input modalities. Since safety assessment is determined by the combination of visual, acoustic, and linguistic contexts, multimodal language models must effectively aggregate information cues across all modalities to make accurate safety assessments.

Dataset description. We curate the Multimodal Multicontext Safety Benchmark (MCBench), which consists of unsafe-safe scenario pairs, to evaluate how effectively multimodal language models assess safety levels in complex scenarios where context is derived from three modalities: vision, audio, and speech. As shown in Figure 1, each data instance consists of a natural language query and a multimodal context representing the current situation. The multimodal context comprises an image, an audio clip, and a speech utterance. Furthermore, the ground-truth label is provided along with the corresponding predicate to determine the safety assessment of the input situation. The predicate is a critical component of our benchmark, as it enables a deeper analysis of Omni LLMs’ ability to aggregate multimodal inputs for decision-making.

Benchmark taxonomy. Figure 2 demonstrates the safety taxonomy evaluated in our benchmark for multimodal language models. We adopt three existing coarse-grained categories: physical harm, property damage, and illegal harm, from prior work [11] and propose social harm as a new category to provide a more comprehensive coverage of multicontext safety scenarios. The fine-grained categories in [11] focus primarily on visual context for safety assessment and thus do not adequately cover multicontext safety scenarios. To address this gap, we define new fine-grained categories for each coarse-grained category to better align with the multicontext safety problem. The complete taxonomy is detailed below:

- Physical harm consists of three fine-grained categories, Violence & Weaponized Threats, Environmental Hazards, and Public Safety & Medical Emergencies, covering safety concerns in general domains, such as child and public safety.
- Social harm covers safety concerns related to social aspects and is subcategorized into Identity-based Exclusion (e.g. hate speech and discrimination), Information-related Violations (e.g. misinformation and social manipulation), and Exploitation & Interpersonal Harm (e.g. harassment and bullying).
- Illegal harm includes safety concerns involving activities that lead to illegal consequences, subcategorized into Crimes Against People (e.g. child exploitation and weapon offenses) and Crimes Against Systems & Property (e.g. financial and cyber crimes)
- Property damage covers safety scenarios related to harmful behaviors that cause critical damage to either person or property, divided into Energy & Utility System Hazards (e.g. gas leak and fires), Environmental & Structural Threats (e.g. weather-related damage), and Chemical, Industrial & Vehicular Damage (e.g. hazardous materials and industrial failures)

2.2. Data Collection

To construct MCBench, we design a two-phase data collection framework. In the first phase, we leverage large language models to generate diverse safety scenarios for each coarse-grained category in our taxonomy. In the second phase, we use image and audio generation models to create synthetic multimodal content for each scenario. Figure 3 demonstrates the data generation framework for MCBench.

Phase 1: Multimodal Safety Scenario Generation. We leverage Claude-Sonnet-4.5 [17] to systematically develop fine-grained subcategories for each of our four coarse-grained safety categories. We provide the model with detailed definitions and examples for each coarse-grained category, and then iteratively prompt it to propose granular subcategories, which are refined by human experts. Through this process, we obtain two to three fine-grained subcategories per coarse-grained category.

In the next step, we prompt Claude-Sonnet-4.5 to generate unsafe scenarios for each fine-grained subcategory. To ensure that scenarios require reasoning across multiple modalities, we first instruct the model to formulate unsafe scenarios using an If-Then logical structure: $L = \text{IF } < \text{condition 1} > \text{ AND } < \text{condition 2} > \text{ AND } \dots \text{ THEN UNSAFE}$, where multiple contextual conditions collectively lead to an unsafe situation. We then generate corresponding safe scenarios by modifying one or two conditions in each unsafe scenario, creating paired instances that differ only in minimal contextual elements. For each unsafe-safe scenario pair, we prompt the model to generate detailed textual descriptions that serve as prompts for image and audio generative models in Phase 2. Specifically, we obtain a tuple (T_I, T_A, S, R, L) , where T_I and T_A are textual




Figure 1: A benchmark data demonstration





Figure 2: Benchmark taxonomy covers 4 coarse-grained categories.

Phase 1: Multicontext Safety Scenario Generation



Phase 2: Multicontext Data Generation




Figure 3: The overall pipeline of benchmark construction which consists of two phases: the multicontext safety scenario generation and multicontext data generation.

descriptions for the image and audio context, S is a speech utterance, $R \in \{\text{safe}, \text{unsafe}\}$ is the ground-truth safety label, and L is the If-Then predicate for the safety assessment.

In the final step, we manually verify and refine the generated scenarios. We eliminate scenarios that are unrealistic or contain logical flaws inconsistent with common-sense knowledge. We also review and correct the If-Then predicates, ensuring that each predicate provides sound reasoning for the safety assessment and aligns with real-world understanding.

Phase 2: Multimodal Data Generation. Using the textual descriptions from Phase 1, we synthesize contextual images with Gemini-Flash-2.5 [7] and contextual audio with Stable Audio 1.0 [18]. We directly use image descriptions T_I as prompts for the image generation model to generate the corresponding image I . However, some scenarios involving sensitive content (e.g., child safety) cannot be generated due to the safety policies of Gemini-Flash-2.5. We exclude these scenarios from the benchmark because they lack a complete multimodal context. For audio generation, we observe that current audio generation models excel at synthesizing single sound events but struggle with complex multi-event soundscapes. Therefore,

we decompose complex audio descriptions T_A into individual sound events and generate them separately. For instance, the contextual audio description "A pill bottle opens, followed by the writing of a farewell note" can be decomposed into the template (sound event 1, relationship, sound event 2). We prompt Claude-Sonnet-4.5 to extract this structured representation from each T_A and then generate the corresponding audio A , where the temporal relationship is either "followed by" or "simultaneous". Each sound event is then synthesized as a 6-second audio clip using Stable Audio 1.0. Finally, we combine the clips based on their relationship: sequential clips are concatenated end-to-end, while simultaneous clips are overlaid with a 3-second overlap to create a natural blend.

As a final quality control step, we manually verify the alignment between the generated multimodal content (images and audio) and the textual scenario descriptions from Phase 1. Instances where the synthesized content does not accurately reflect the intended scenario are removed from the dataset. Through this curation process, we obtain the final benchmark dataset $\mathcal{D} = \{(I_i, A_i, S_i, R_i, L_i)\}_{i=1}^N$, where each instance consists of: (1) a multimodal context (I_i, A_i, S_i) containing an

image, an audio clip, and a speech utterance; (2) a ground-truth safety label $R_i \in \{\text{safe}, \text{unsafe}\}$; and (3) a predicate L_i explaining the safety assessment. Table 2 summarizes the dataset statistics. MCBench contains 1196 multimodal scenarios spanning four coarse-grained safety categories.

Category	# Samples	# Percentage
I. Physical Harm	300	25.1%
• Violence & Weaponized Threats	90	7.5%
• Environment Hazards	150	12.6%
• Public Safety & Medical Emergencies	60	5.0%
II. Social Harm	300	25.1%
• Identity-based Exclusion	80	6.7%
• Information-related Violations	60	5.0%
• Exploitation & Interpersonal Harm	160	13.4%
III. Illegal Harm	296	24.7%
• Crimes Against Persons	166	13.9%
• Crimes Against Systems & Property	130	10.8%
IV. Property Damage	300	25.1%
• Energy & Utility System Hazards	110	9.2%
• Environmental & Structural Threats	110	9.2%
• Industrial & Vehicular Damage	80	6.7%
Total	1196	100%

Table 2: Data Statistics for Multimodal Situational Safety Categories with Percentages.

3. Experiments

3.1. Experimental Setup

Evaluated MLLMs. We evaluate both open-source and proprietary models on MCBench. The evaluated open-source MLLMs include the Qwen-Omni2.5 [8] (3B and 7B models), AnyGPT [19], InternOmni [20], Baichuan-Omni1.5 [21], and OmniVinci [22]. For proprietary models, we conduct experiments with Gemini-Flash-2.5 [7] and GPT-4o-mini [23].

Evaluation metric. Since all models respond with a reasoning trace for each safety scenario, we leverage the LLM-as-a-judge method [24] to classify the free-form text response to safety assessment prediction $R \in \{\text{safe}, \text{unsafe}\}$. The GPT-4o model is used as the judge model to evaluate the responses of Omni LLMs. To address high variance in LLM-based evaluation, we perform five independent runs for each model and report the average results. We use accuracy as the evaluation metric to analyze the multicontext safety understanding capability of MLLMs.

3.2. Main Results

We evaluate both open-source models and proprietary models. All models are evaluated using a ‘‘General Prompt’’ that elicits chain-of-thought reasoning [25]. Specifically, the prompt instructs models to follow a three-step process: first, analyze the given image; second, extract contextual information from the audio and speech utterance; and finally, assess the safety level by aggregating information from all modalities.

Table 3 demonstrates the performance of state-of-the-art Omni LLMs on multimodal safety assessment across the four coarse-grained categories in MCBench. This table reveals several key findings. First, all Omni LLMs perform above random chance, demonstrating basic multimodal safety reasoning capability. Second, even the best-performing models achieve modest accuracy: Gemini-Flash-2.5 and Qwen-Omni-2.5-3B both

reach approximately 64.5% average accuracy, indicating that MCBench poses significant challenges for both proprietary and open-source models. Third, we observe category-specific challenges, particularly for the Social Harm and Illegal Harm categories. Some open-source models (InternOmni, OmniVinci, Baichuan-Omni-1.5) exhibit oversensitivity in the Social Harm category, classifying safe scenarios as unsafe at a rate below that of a random classifier. Conversely, other open-source models, Qwen-Omni-2.5 family and AnyGPT, show insensitivity to unsafe Social Harm scenarios. Even proprietary models struggle with this category: Gemini-Flash-2.5 achieves 44% accuracy on unsafe Social Harm cases. Similar patterns emerge for Illegal Harm. This finding indicates that state-of-the-art Omni LLMs struggle to combine information cues across multimodal context inputs to make safety judgments for intangible and hidden effects, such as social and legal liability scenarios. In contrast, models perform substantially better on Physical Harm and Property Damage categories, suggesting these domains involve more recognizable visual and acoustic cues.

3.3. Textual Alternatives for Visual and Audio Context

To understand the impact of each modality on model performance, we conduct experiments using textual alternatives for visual and acoustic contexts. We use the image caption and audio description from Phase 1 data collection in Section. 2.2 as the textual alternative for image and audio, respectively. We conduct textual alternatives experiments with Qwen-Omni-2.5 family and InternOmni as they achieve performance comparable to Gemini-Flash-2.5. Furthermore, we evaluate the GPT-4o model in the textual audio alternative setting to understand the performance of proprietary models for multicontext safety.




Figure 4: Performance Comparison between Image-Audio Context and Textual Image Alternatives.

Textual Image Alternatives. We replace image context with an image description to understand the impact of visual context in safety assessment. Figure 4 illustrates the performance comparison between image-audio context and textual image alternative settings. We can observe that models’ performance improves significantly with textual image description as visual context. This suggests that Omni LLMs struggle to extract relevant information cues from images for making safety judgments.

Textual Audio Alternatives. To assess the contribution

Models	Physical harm		Social harm		Illegal harm		Property damage		Avg
	Safe	Unsafe	Safe	Unsafe	Safe	Unsafe	Safe	Unsafe	
Random	50.0 $\pm$ 0.0	50.0 $\pm$ 0.0	50.0 $\pm$ 0.0	50.0 $\pm$ 0.0	50.0 $\pm$ 0.0	50.0 $\pm$ 0.0	50.0 $\pm$ 0.0	50.0 $\pm$ 0.0	50.0 $\pm$ 0.0
Qwen-Omni2.5-3B	92.6 $\pm$ 1.5	69.3 $\pm$ 1.2	82.6 $\pm$ 1.1	22.6 $\pm$ 2.2	28.6 $\pm$ 2.3	67.1 $\pm$ 1.6	86.6 $\pm$ 1.5	66.6 $\pm$ 1.3	64.5$\pm$1.6
Qwen-Omni2.5-7B	72.6 $\pm$ 1.6	62.0 $\pm$ 1.4	78.0 $\pm$ 1.5	32.0 $\pm$ 1.8	50.6 $\pm$ 1.7	46.6 $\pm$ 1.5	70.0 $\pm$ 1.3	30.0 $\pm$ 1.8	55.2 $\pm$ 1.6
AnyGPT	87.3 $\pm$ 1.5	56.0 $\pm$ 1.2	78.0 $\pm$ 1.4	22.6 $\pm$ 1.9	59.3 $\pm$ 2.1	44.5 $\pm$ 1.5	86.0 $\pm$ 1.6	44.6 $\pm$ 1.6	59.8 $\pm$ 1.6
InternOmni	85.3 $\pm$ 1.7	62.0 $\pm$ 1.5	28.6 $\pm$ 1.4	76.6 $\pm$ 1.8	54.0 $\pm$ 1.9	58.2 $\pm$ 1.7	75.3 $\pm$ 1.5	62.0 $\pm$ 1.8	62.7 $\pm$ 1.6
OmniVinci	42.0 $\pm$ 1.9	70.0 $\pm$ 1.7	34.0 $\pm$ 2.1	75.3 $\pm$ 2.2	40.0 $\pm$ 1.9	72.6 $\pm$ 2.1	16.6 $\pm$ 2.4	92.6 $\pm$ 1.4	55.4 $\pm$ 2.0
Baichuan-Omni-1.5	80.6 $\pm$ 1.4	58.6 $\pm$ 1.6	31.3 $\pm$ 2.0	56.6 $\pm$ 1.9	49.3 $\pm$ 2.3	58.2 $\pm$ 1.7	70.0 $\pm$ 1.8	60.6 $\pm$ 1.7	58.1 $\pm$ 1.8
Gemini-Flash-2.5	78.6 $\pm$ 1.2	80.6 $\pm$ 1.0	62.6 $\pm$ 1.1	44.0 $\pm$ 1.3	32.6 $\pm$ 1.3	73.3 $\pm$ 1.1	59.3 $\pm$ 1.2	84.6 $\pm$ 1.0	64.4$\pm$1.2

Table 3: Accuracy of Omni LLMs for making safety assessments under Chain-of-Thought prompt setting. We evaluate each model five times using The GPT-4o model as a LLM-as-a-judge and report the average results along with standard deviation.




Figure 5: Performance Comparison between Image-Audio Context and Textual Audio Alternatives.

of audio context, we replace actual audio with textual descriptions while keeping images unchanged. Figure 5 presents the results. Models exhibit divergent behaviors: larger models (Gemini-Flash-2.5 and Qwen-Omni-2.5-7B) achieve higher accuracy when given textual audio descriptions instead of actual audio, while smaller models (Qwen-Omni-2.5-3B and InternOmni) perform worse. These results indicate that more capable models can effectively extract relevant information from text descriptions and integrate it with visual context, whereas smaller models are limited in multicontext information aggregation. The superiority of GPT-4o in the textual audio alternatives setting supports this finding. Furthermore, the performance gain is modest, suggesting that acoustic features provide limited additional discriminative information for safety judgment.

Textual Image and Audio Alternatives. We conduct a pure textual alternatives experiment to remove the effect of multimodal perception and delve deeper into the safety assessment of Omni LLMs. Figure 6 presents results when models make safety assessments using only textual descriptions of images and audio, rather than actual multimodal inputs. GPT-4o achieves the highest performance in this text-only setting, demonstrating superior text comprehension and reasoning capabilities. Notably, larger models (InternOmni, Qwen2-Omni-2.5-7B, and Gemini-Flash-2.5) show substantial performance improvements compared to their multimodal performance, while the smaller Qwen2-Omni-2.5-3B exhibits min-




Figure 6: Performance Comparison between Image-Audio Context and Text-only Alternatives.

imal improvement. This pattern suggests that model capacity plays a critical role in effectively processing and integrating textual descriptions for safety assessment, with larger models better able to leverage rich textual information even without direct access to visual and acoustic signals.

3.4. Failure Diagnosis

To understand why models make incorrect safety assessments, we analyze their reasoning traces through the lens of two key capabilities: perception and reasoning. Perception refers to extracting relevant information from multimodal inputs, while reasoning refers to integrating perceived information to make safety judgments. To evaluate these capabilities separately, we conduct two complementary analyses. First, to assess perception quality, we compare models’ reasoning traces against ground-truth predicates to identify whether errors stem from misperception of contextual cues or from faulty reasoning despite correct perception. Second, to isolate reasoning ability, we provide models with ground-truth predicates as input and evaluate whether they can make accurate safety assessments when given correct contextual information. This approach reveals whether models fail due to perception errors or reasoning failures. We focus our analysis on Qwen-Omni-2.5 3B, Qwen-Omni-2.5 7B, and Gemini-Flash-2.5. The Qwen-Omni-2.5 variants enable us to examine how model scale affects perception and reasoning capabilities, while Gemini-Flash-2.5




Figure 7: Perception alignment scores, ranging from 0 to 1, for Gemini-Flash-2.5 and Qwen-omni-2.5 (3B, 7B) across the four coarse-grained categories in MCBench. A score of 1 indicates complete alignment between model reasoning traces and ground-truth rationales, while 0 indicates complete misalignment.

provides insight into state-of-the-art proprietary model performance.

Evaluation metric for perception-alignment. We leverage ground-truth safety judgment predicates to evaluate perception alignment between reasoning traces and the ground-truth multicontext information. We formulate the alignment evaluation between them as an entailment prediction task. Let $L = \{p_i\}_{i=1}^N$ denote a predicate consisting of N premises p_i . For each premise, we first construct an entailment query

$$\text{query} = \text{Premise} : \langle \text{reasoning trace} \rangle \backslash \text{Hypothesis} : \langle p_i \rangle$$

Next, we prompt the Claude-Sonnet-4.5 model to predict the entailment outcome $o_i \in \{\text{entail}, \text{likely entail}, \text{not entail}\}$ between the given reasoning trace and the predicate premise p_i . The entailment outcome is then discretized as follows:

$$s_i = \begin{cases} 1, & \text{if } o_i = \text{entail} \\ 0.5, & \text{if } o_i = \text{likely entail} \\ 0, & \text{if } o_i = \text{not entail} \end{cases}$$

The perception alignment score is computed as follows:

$$\text{p_align} = \frac{\sum_{i=1}^{|L|} s_i}{|L|}$$

The perception alignment score is in the range of 0 to 1, where 1 indicates complete alignment and 0 indicates complete misalignment.

3.4.1. Perception Diagnosis

We conduct an ablation study measuring the perception alignment score in the reasoning traces of the evaluated Omni LLMs. Figure 7 presents the perception alignment scores for three models: Gemini-Flash-2.5 and the Qwen2-Omni-2.5 family (3B and 7B), in the four coarse-grained categories of MCBench. The Qwen-Omni-2.5 7B model demonstrates higher perception alignment than its smaller 3B counterpart, suggesting that model scale improves the ability to extract relevant contextual information from multimodal inputs. However, when comparing perception alignment to task accuracy, despite lower perception scores, Qwen2-Omni-2.5 3B achieves significantly higher accuracy (64.5%) than the 7B model (55.2%). This inverse

relationship suggests that the 3B model may rely on shallow heuristics or spurious correlations rather than genuine multimodal reasoning. In other words, the smaller model exploits shortcuts that yield correct predictions without requiring accurate perception of all relevant contextual cues. The Gemini model shows the highest perception alignment score between its responses and the ground-truth premises, which also corresponds to the highest accuracy in safety judgment. This pattern reveals that the Gemini model is able to extract relevant information cues from complex multimodal inputs to make accurate safety judgments.

Although the Gemini model demonstrates an excellent multimodal perception capability for the illegal harm category, achieving the highest perception alignment score (0.698), it exhibits oversensitivity in the unsafe subset of this category. As demonstrated in Figure 8, the Qwen-Omni-2.5 family and Gemini models successfully extract relevant information cues for making a safety assessment; however, they fail to make an accurate assessment. The main cause is that they overlook the extracted information cues and focus solely on the speech utterance to make an appropriate safety judgment. The prior work [16] observes the same issue with visual LLMs. These results highlight a fundamental challenge: current Omni LLMs struggle to effectively integrate information across modalities for safety assessment, suggesting the need for architectures or training strategies that enforce balanced multimodal reasoning.

3.4.2. Reasoning Diagnosis

We conduct an ablation study to examine the root causes of inaccurate safety assessments in our benchmark by evaluating Omni LLMs under different settings. These experimental settings are designed to disentangle the effect of perception ability on safety predictions.

Setting 1: The original setting, which is used to evaluate Omni LLMs in Table. 3. In this setting, Omni LLMs make safety assessment predictions from multimodal context inputs: image, audio, and speech.

Setting 2: Omni LLMs make safety assessments from the ground-truth predicates to remove the impact of perception. This setting enables Omni LLMs to focus on the reasoning part to predict the safety situation.

Table 4 presents an ablation study comparing two inference




Figure 8: An oversensitive safety assessment example of Omni LLMs for the Illegal Harm category in MCBench. Although all three models are capable of generating ground-truth premises, they failed to combine the extracted information cues from multimodal inputs. Therefore, they make a wrong safety assessment prediction.

conditions: models making safety assessments (1) using only multimodal inputs versus (2) using ground-truth predicates. The results reveal a striking pattern of oversensitivity when models are provided with explicit reasoning context.

Oversensitivity on Safe Scenarios. When given ground-truth predicates, models incorrectly classify safe scenarios as unsafe at significantly higher rates. Qwen-Omni-2.5 3B and 7B show performance drops of 46% and 37.17% on safe scenarios, respectively, while Gemini-Flash-2.5 shows a drop of 16.83%. This oversensitivity in context-rich settings aligns with findings in visual language models [16] and text-only LLMs [26, 27, 28].

Improved Sensitivity on Unsafe Scenarios. Conversely, all models improve in detecting unsafe scenarios: Qwen-Omni-2.5 models gain 41.84% (3B model) and 55.99% (7B model), while Gemini-Flash-2.5 reaches near-perfect performance 99.82%, increasing from 70.65%. These effects suggest that explicit reasoning context biases models toward conservative predictions, improving recall on unsafe cases but at the cost of precision on safe ones.

Table 5 presents a representative example of model oversensitivity in safe scenarios from the Physical Harm category. In this example, all models receive ground-truth predicates that accurately describe the multimodal context, yet they still incorrectly classify the safe scenario as unsafe. The reasoning traces reveal a common error pattern: models focus on a single salient cue, namely the text notification, while discounting other contextual information. Based solely on the presence of a phone notification, the models conclude that the driver is actively using their phone, constituting distracted driving. In other words, they fail to perform holistic multicontext reasoning and instead anchor their judgments on isolated, potentially misleading cues. This error pattern recurs across safe scenarios in MCBench, ex-

plaining the oversensitivity observed in Table 4. Current Omni LLMs demonstrate a tendency toward false positives when encountering ambiguous or potentially concerning cues, exaggerating risks rather than carefully weighing all available evidence. This suggests that models lack robust mechanisms for balanced multicontext reasoning in safety assessment.

4. Related Work

Multimodal Large Language Models. Recent advances in multimodal training data [1, 2, 3] and architectural innovations [4, 5, 6] have enabled large language models to extend beyond text-only processing. Visual language models [29, 30, 31] can interpret images and videos alongside textual queries, while audio language models [32, 33, 34, 35] are able to handle acoustic information alongside text queries. Recent works [8, 7, 21, 22, 36] go beyond handling two modalities to develop Omni LLMs. However, despite significant progress in model capabilities, the field lacks comprehensive multimodal safety benchmarks to systematically evaluate how reliably these models handle safety-critical scenarios that require reasoning across multiple modalities.

Safety Benchmark for MLLMs. The rapid advancement of multimodal language models has created an urgent need for safety-focused evaluation benchmarks. Early safety benchmarks [26, 37] for LLMs focus on safety context awareness in the textual modality, evaluating whether models can appropriately respond to potentially harmful textual inputs. Extending this work to visual modalities, benchmarks such as MM-SafetyBench [11] and the RMS dataset [12] assess visual language models' ability to respond appropriately to unsafe queries. Other multimodal safety benchmarks focus on

Setting	Model	Safety Scenario (%)		Change from Setting 1 (%)	
		Safe	Unsafe	Δ Safe	Δ Unsafe
1	Gemini-Flash-2.5	58.32	70.65	–	–
	Qwen-Omni-2.5-3B	72.66	56.44	–	–
	Qwen-Omni-2.5-7B	67.83	42.64	–	–
2	Gemini-Flash-2.5	41.49	99.82	↓ 16.83	↑ 29.17
	Qwen-Omni-2.5-3B	26.66	98.29	↓ 46.00	↑ 41.85
	Qwen-Omni-2.5-7B	30.66	98.63	↓ 37.17	↑ 55.99

Table 4: Accuracy of open-sourced and proprietary models for making safety assessment across different settings on safety scenarios. Setting 1 is the original setting, which is used to evaluate Omni LLMs and report results in Table. 3. Setting 2 is to remove the effect of perception ability, thus, Omni LLMs make safety assessments from ground-truth predicates. Δ denotes the change relative to Setting 1.

Query context	Query Input: (driving) AND (text notification) AND (voice command) Label: Safe
Qwen-Omni-2.5 3B	Well, let’s think about this. Driving while using text notifications or voice commands can be unsafe. Text notifications can distract you from the road, and voice commands might also take your attention away from driving. So, I’d say this situation is unsafe
Qwen-Omni-2.5 7B	Well, it depends on the context. If you’re driving and getting text notifications or voice commands while driving, that’s generally unsafe. Texting while driving is illegal in many places and can cause accidents. Voice commands can be a bit tricky too. If the voice commands are from a navigation system or something that’s not distracting, it might be okay. But if they’re from a phone call or other non-driving-related thing, it could be dangerous. So, in general, it’s not safe to do these things while driving
Gemini-Flash-2.5	Here’s a safety assessment based on the factors provided: $\backslash$ $\backslash$ $\backslash$ Factors: driving AND text notification AND voice command $\backslash$ $\backslash$ $\backslash$ Assessment: Unsafe $\backslash$ $\backslash$ $\backslash$ Reasoning: While voice command technology can be a safer alternative to physically interacting with a phone while driving, the presence of a text notification introduces a significant safety risk. Even with voice command, the act of receiving and processing a text message (even if the content is read aloud and a response is dictated) can be a substantial cognitive distraction. $\backslash$ $\backslash$ $\backslash$ Cognitive Distraction: The brain is still engaged in understanding the message, formulating a reply, and potentially feeling pressure to respond promptly. This diverts mental resources away from the primary task of driving, which requires constant attention to the road, other vehicles, and potential hazards. $\backslash$ $\backslash$ $\backslash$ Context Switching: Even with voice commands, the driver is switching their focus between the driving environment and the communication task. This switching can lead to missed visual cues or delayed reactions. $\backslash$ $\backslash$ $\backslash$ Urgency of Notifications: Text notifications often imply a degree of urgency, which can further increase the driver’s desire to engage, even if they are using voice commands. $\backslash$ $\backslash$ $\backslash$ Therefore, the combination of driving and receiving a text notification, even when voice commands are available, creates an unsafe situation due to the inherent cognitive distraction.

Table 5: A demonstration for the exaggeration issue of Omni LLMs on safe scenarios in our benchmark data. The exaggeration issue in the reasoning trace is highlighted in red color.

the oversensitivity of multimodal LLMs, including the MOSS-Bench [16] and the MMSafeAware benchmark [13]. However, all the aforementioned safety benchmarks evaluate the safety capabilities of visual LLMs; currently, there are no dedicated safety benchmarks for Omni LLMs. Although there are recent benchmarks for Omni LLMs, they focus on general capabilities such as question-answering [14] or spatial awareness [15] rather than safety assessment. This gap motivates our work: MCBench is the first comprehensive safety benchmark designed specifically for Omni LLMs that process visual, audio, and speech simultaneously.

5. Conclusion

We introduce a new multicontext multimodal safety benchmark, called MCBench, to examine the safety-awareness of Omni LLMs. Unlike existing benchmarks that rely on single-modality cues, MCBench scenarios require integrating infor-

mation across vision, audio, and speech to determine a safety assessment, reflecting the complexity of real-world safety situations. This design makes MCBench a rigorous testbed for advancing the development of safe Omni LLMs. Through analysis of reasoning traces for popular open-source and proprietary models, we find that existing models fail to aggregate extracted cues from multicontext to make accurate predictions, often overlooking critical contextual cues when making safety judgments. In addition, models are oversensitive in safe scenarios, making safety judgments on single concerning cues rather than considering all available evidence. This finding suggests that future research should focus on enhancing information aggregation across modalities to enhance the safety-awareness of Omni LLMs.

6. Generative AI Use Disclosure

The authors used Generative AI for grammar checking and polishing the manuscript. All research design, methodology, analysis, and scientific content are the original work of the authors, who take full responsibility for the publication.

7. References

- [1] C. Schuhmann, R. Beaumont, R. Vencu, C. W. Gordon, R. Wightman, M. Cherti, T. Coombes, A. Katta, C. Mullis, M. Wortsman, P. Schramowski, S. R. Kundurthy, K. Crowson, L. Schmidt, R. Kaczmarczyk, and J. Jitsev, "LAION-5b: An open large-scale dataset for training next generation image-text models," in *Thirty-sixth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2022. [Online]. Available: <https://openreview.net/forum?id=M3Y74vmsMcY>
- [2] M. Bain, A. Nagrani, G. Varol, and A. Zisserman, "Frozen in time: A joint video and image encoder for end-to-end retrieval," in *IEEE International Conference on Computer Vision*, 2021.
- [3] X. Mei, C. Meng, H. Liu, Q. Kong, T. Ko, C. Zhao, M. D. Plumbley, Y. Zou, and W. Wang, "WavCaps: A ChatGPT-assisted weakly-labelled audio captioning dataset for audio-language multimodal research," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, pp. 1–15, 2024.
- [4] J.-B. Alayrac, J. Donahue, P. Luc, A. Miech, I. Barr, Y. Hasson, K. Lenc, A. Mensch, K. Millican, M. Reynolds, R. Ring, E. Rutherford, S. Cabi, T. Han, Z. Gong, S. Samangooei, M. Monteiro, J. Menick, S. Borgeaud, A. Brock, A. Nematzadeh, S. Sharifzadeh, M. Binkowski, R. Barreira, O. Vinyals, A. Zisserman, and K. Simonyan, "Fleming: a visual language model for few-shot learning," in *Advances in Neural Information Processing Systems*, A. H. Oh, A. Agarwal, D. Belgrave, and K. Cho, Eds., 2022. [Online]. Available: <https://openreview.net/forum?id=EbMuimAbPbs>
- [5] J. Li, D. Li, S. Savarese, and S. Hoi, "Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models," in *International conference on machine learning*. PMLR, 2023, pp. 19 730–19 742.
- [6] Y. Gong, Y.-A. Chung, and J. Glass, "AST: Audio Spectrogram Transformer," in *Proc. Interspeech 2021*, 2021, pp. 571–575.
- [7] G. Comanici, E. Bieber, M. Schaekermann, I. Pasupat, N. Sachdeva, I. Dhillon, M. Blistein, O. Ram, D. Zhang, E. Rosen *et al.*, "Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities," *arXiv preprint arXiv:2507.06261*, 2025.
- [8] J. Xu, Z. Guo, J. He, H. Hu, T. He, S. Bai, K. Chen, J. Wang, Y. Fan, K. Dang *et al.*, "Qwen2. 5-omni technical report," *arXiv preprint arXiv:2503.20215*, 2025.
- [9] S. Pichai, D. Hassabis, and K. Kavukcuoglu, "Introducing gemini 2.0: Our new ai model for the agentic era," The Keyword (Google Blog), December 2024, accessed: 2026-01-14. [Online]. Available: <https://blog.google/technology/google-deepmind/google-gemini-ai-update-december-2024/>
- [10] G. Corrado and Y. Matias, "Multimodal medical ai," Google Research Blog, August 2023, accessed: 2026-01-14. [Online]. Available: <https://research.google/blog/multimodal-medical-ai/>
- [11] K. Zhou, C. Liu, X. Zhao, A. Compalas, D. Song, and X. E. Wang, "Multimodal situational safety," in *The Thirteenth International Conference on Learning Representations*, 2025. [Online]. Available: <https://openreview.net/forum?id=I9bEi6LNgt>
- [12] J. Qu, L. Li, B. Zhang, Y. Yan, and J. Shao, "Self-adaptive dataset construction for real-world multimodal safety scenarios," in *Findings of the Association for Computational Linguistics: EMNLP 2025*, C. Christodoulopoulos, T. Chakraborty, C. Rose, and V. Peng, Eds. Suzhou, China: Association for Computational Linguistics, Nov. 2025, pp. 16 805–16 829. [Online]. Available: <https://aclanthology.org/2025.findings-emnlp.912/>
- [13] W. Wang, X. Liu, K. Gao, J.-t. Huang, Y. Yuan, P. He, S. Wang, and Z. Tu, "Can't see the forest for the trees: Benchmarking multimodal safety awareness for multimodal LLMs," in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, W. Che, J. Nabende, E. Shutova, and M. T. Pilehvar, Eds. Vienna, Austria: Association for Computational Linguistics, Jul. 2025, pp. 16 993–17 006. [Online]. Available: <https://aclanthology.org/2025.acl-long.832/>
- [14] Y. Li, G. Zhang, Y. Ma, R. Yuan, K. Zhu, H. Guo, Y. Liang, J. Liu, Z. M. Wang, J. Yang, S. Wu, X. Qu, J. Shi, X. Zhang, Z. Yang, Y. WEN, Y. Wang, S. Li, Z. Zhang, R. Liu, E. Benetos, W. Huang, and C. Lin, "OmniBench: Towards the future of universal omni-language models," in *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2025. [Online]. Available: <https://openreview.net/forum?id=SSF4qgsNYE>
- [15] M. Chen, Z. Cui, X. Liu, J. Xiang, C. Zheng, J. Li, and E. Shlizerman, "SAVVY: Spatial awareness via audio-visual LLMs through seeing and hearing," in *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. [Online]. Available: <https://openreview.net/forum?id=zwCb9cKHpd>
- [16] X. Li, H. Zhou, R. Wang, T. Zhou, M. Cheng, and C.-J. Hsieh, "Is your multimodal language model oversensitive to safe queries?" in *The Thirteenth International Conference on Learning Representations*, 2025. [Online]. Available: <https://openreview.net/forum?id=QsA3YzNUxA>
- [17] Anthropic, "Claude 4.5," 2025. [Online]. Available: <https://www.anthropic.com/news/claude-sonnet-4-5>
- [18] Z. Evans, J. D. Parker, C. Carr, Z. Zukowski, J. Taylor, and J. Pons, "Stable audio open," in *ICASSP 2025-2025 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2025, pp. 1–5.
- [19] J. Zhan, J. Dai, J. Ye, Y. Zhou, D. Zhang, Z. Liu, X. Zhang, R. Yuan, G. Zhang, L. Li *et al.*, "Anygpt: Unified multimodal llm with discrete sequence modeling," in *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2024, pp. 9637–9662.
- [20] L. Chen *et al.*, "Internomni: Extending internvl with audio modality," *CoRR*, vol. abs/2409.18042, 2024. [Online]. Available: arxiv.org
- [21] Y. Li, J. Liu, T. Zhang, S. Chen, T. Li, Z. Li, L. Liu, L. Ming, G. Dong, D. Pan *et al.*, "Baichuan-omni-1.5 technical report," *arXiv preprint arXiv:2501.15368*, 2025.
- [22] H. Ye, C.-H. H. Yang, A. Goel, W. Huang, L. Zhu, Y. Su, S. Lin, A.-C. Cheng, Z. Wan, J. Tian *et al.*, "Omnivinci: Enhancing architecture and data for omni-modal understanding llm," *arXiv preprint arXiv:2510.15870*, 2025.
- [23] J. Achiam, S. Adler, S. Agarwal, L. Ahmad, I. Akkaya, F. L. Aleman, D. Almeida, J. Altschmidt, S. Altman, S. Anadkat *et al.*, "Gpt-4 technical report," *arXiv preprint arXiv:2303.08774*, 2023.
- [24] L. Zheng, W.-L. Chiang, Y. Sheng, S. Zhuang, Z. Wu, Y. Zhuang, Z. Lin, Z. Li, D. Li, E. Xing, H. Zhang, J. E. Gonzalez, and I. Stoica, "Judging LLM-as-a-judge with MT-bench and chatbot arena," in *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023. [Online]. Available: <https://openreview.net/forum?id=uccHPGDlao>
- [25] J. Wei, X. Wang, D. Schuurmans, M. Bosma, F. Xia, E. Chi, Q. V. Le, D. Zhou *et al.*, "Chain-of-thought prompting elicits reasoning in large language models," *Advances in neural information processing systems*, vol. 35, pp. 24 824–24 837, 2022.
- [26] G. Sun, X. Zhan, S. Feng, P. C. Woodland, and J. Such, "CASE-Bench: Context-Aware SafeTy Benchmark for Large Language Models," in *ICML*, 2025.

- [27] P. Röttger, H. Kirk, B. Vidgen, G. Attanasio, F. Bianchi, and D. Hovy, “XSTest: A test suite for identifying exaggerated safety behaviours in large language models,” in *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, K. Duh, H. Gomez, and S. Bethard, Eds. Mexico City, Mexico: Association for Computational Linguistics, Jun. 2024, pp. 5377–5400. [Online]. Available: <https://aclanthology.org/2024.naacl-long.301/>
- [28] J. Cui, W.-L. Chiang, I. Stoica, and C.-J. Hsieh, “OR-bench: An over-refusal benchmark for large language models,” in *Proceedings of the 42nd International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, A. Singh, M. Fazel, D. Hsu, S. Lacoste-Julien, F. Berkenkamp, T. Maharaj, K. Wagstaff, and J. Zhu, Eds., vol. 267. PMLR, 13–19 Jul 2025, pp. 11 515–11 542. [Online]. Available: <https://proceedings.mlr.press/v267/cui25a.html>
- [29] H. Liu, C. Li, Q. Wu, and Y. J. Lee, “Visual instruction tuning,” in *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. [Online]. Available: <https://openreview.net/forum?id=w0H2xGHlkW>
- [30] Y. Shu, Z. Liu, P. Zhang, M. Qin, J. Zhou, Z. Liang, T. Huang, and B. Zhao, “Video-xl: Extra-long vision language model for hour-scale video understanding,” in *Proceedings of the Computer Vision and Pattern Recognition Conference*, 2025, pp. 26 160–26 169.
- [31] Z. Chen, J. Wu, W. Wang, W. Su, G. Chen, S. Xing, M. Zhong, Q. Zhang, X. Zhu, L. Lu *et al.*, “Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks,” in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2024, pp. 24 185–24 198.
- [32] S. Ghosh, S. Kumar, A. Seth, C. K. R. Evuru, U. Tyagi, S. Sakshi, O. Nieto, R. Duraiswami, and D. Manocha, “Gama: A large audio-language model with advanced audio understanding and complex reasoning abilities,” *arXiv preprint arXiv:2406.11768*, 2024.
- [33] M. Luong, K. Nguyen, D. Phung, G. Haffari, and L. Qu, “Unbiased sliced wasserstein kernels for high-quality audio captioning,” in *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. [Online]. Available: <https://openreview.net/forum?id=83HJrZigZ>
- [34] S. Ghosh, A. Goel, J. Kim, S. Kumar, Z. Kong, S. gil Lee, C.-H. H. Yang, R. Duraiswami, D. Manocha, R. Valle, and B. Catanzaro, “Audio flamingo 3: Advancing audio intelligence with fully open large audio language models,” in *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. [Online]. Available: <https://openreview.net/forum?id=FjByDpDVIO>
- [35] Y. Gong, H. Luo, A. H. Liu, L. Karlinsky, and J. R. Glass, “Listen, think, and understand,” in *The Twelfth International Conference on Learning Representations*, 2024. [Online]. Available: <https://openreview.net/forum?id=nBZBPXdJIC>
- [36] J. Han, K. Gong, Y. Zhang, J. Wang, K. Zhang, D. Lin, Y. Qiao, P. Gao, and X. Yue, “Onellm: One framework to align all modalities with language,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.
- [37] T. Xie, X. Qi, Y. Zeng, Y. Huang, U. M. Schwag, K. Huang, L. He, B. Wei, D. Li, Y. Sheng, R. Jia, B. Li, K. Li, D. Chen, P. Henderson, and P. Mittal, “SORRY-bench: Systematically evaluating large language model safety refusal,” in *The Thirteenth International Conference on Learning Representations*, 2025. [Online]. Available: <https://openreview.net/forum?id=YfKNaRktan>