原 · · · · · · · · · · · · · · · · · · ·		SANCE THE			商民	ed a
e - Slug Rejector	177	F-1776	Bar - Curtain Support			Resistor (6,800 ohr
Nut	178	L-135	Amplifier Chassis With Lettering		233 S-102B	2B Resistor (130,000 to 9 (1/2 Watt)
Switch	180	F-262	Terminal Strip			Resistor
	181	F-266	Terminal Strip		236 S-105B	5B Resistor (10,000 ohms) (2 watt)
ter - Total Selections	182	F-267	Octal Socket			
ket - Solenoid (Counter)	3	7071-1	Capacitos (40 mid) (430 Voits)	75004		Capacitor
yer - Solenoid			(15 Mfd)		240 S-210K	
Clevis	184	F-1685	Capacitor (15 Mfd) (450 Volts)		242 S-200C	Capacitor
r - Actuation (Counter)			(10 Mid) (450 Voits)			Capacitor
tor Switch, Terminal Box and			(20 Mfd) (150 Volts)			
ess Assembly (Includes No's 92,	185	F-1686	Capacitor (20 Mfd) (150 Volts)			
157 and No's 159 thru 166)			(20 Mfd) (150 Volts)		246 F-1285	285 Adaptor Plate
Light Shield Assembly (Includes	186	F-1667	Octal Socket			5
e (Credit Ilnit)	188	F-255	Grömmet	Property of the second		
nbly of 5¢, 10¢ & 25¢ Stops	189	F-1692	Tube Slug			
on Spring	190	F-1671	Switch			
10¢ Plunger	191	F-1249	Knob			Hairpin Clip
n Spring - 5¢ & 10¢ Plungers	192	S-720A	Cartridge Fuse (2 Amp::)			
ner Ring	193	L-136	Transformer - Output		253 H-16	Dia Clouis
t Wheei	194	L-137	Transformer - Power			2
- Itatchet Wheel	195	F-1689	Speaker Connection Chart			
sid Assemble	190	F -213	6SA7 Tube			
Operating Dunger	198	F -1688	SNT CT Title			
Credit Switch Assembly	199	F-1072	61.6-G Tube			erast.
Switch Assembly	200	F-195	504-G Tube			
Magnet	201	S-102U	Resistor (18 ohms) (1/2 watt)			
ement Adjustment	202			7 2 1	262 F-447	
Holder & Frame Stiffener	203	S-102H			264 H-63	Drive Arm (Record Rack)
Jar	204	S 104D	Resistor (410,000 onms) (1/2 watt)			
r - Mounting	206		(2,700 onms)			5 Tension Spring (Counter Lever)
r Mount	207	S-103A	(1.200 ohms) (1			
& Pawi Lever Assembly	208	S-105A	(680 ohms) (2			
met	209	S-110C	Resistor (150 ohms) (5 watt)		268 F-264	Selector Magnet Bank
ing Box nontact)	210	S-110D	Resistor (10,000 ohms) (5 watt)			
Contact)	212	S-210E	Capacitor (005 mfd) (400 volts)			
acle - 2 Pole need 3	-213	S-210P		I		
it it	214	S-210L	Capacitor (.01 mfd) (400 volts)		Z/3 L-9	Fransier Assembly (Includes No. 3 213
ass Assembly	215	S-2101	Capacitor (.003 mfd) (400 volts)		274 L-7	
5 Contact)	217	S-200D	-		-	
6 Contact)	218	H-72	CHOOK		275 F-18	
4 Contact)	219	S-104B	(470 ohms) (1/2		977 I.99	Transfer Arm & Outer Shoe Assembly
ap (2 Contact)	220	S-104C	Resistor (360 ohms) (1/2 watt) Resistor (1800 ohms) (1/2 watt)		_	
les No's 168 thru 173)	222	S-102J	(2,200 ohms)		279 F-85	
	223	S-104G	(3,900 ohms)			
Assembly in Strip Assembly	224	S-104J	Resistor (8,200 ohms) (1/2 watt)			
atton Assembly	226	S-102A	(47,600 ohms) (1/		1	
ession Spring	227	S-104L			ANIT	Made C
t Spring Assembly	228	S-102G	Resister (220,000 ohms) (1/2 watt)			
Short	677	9-1021		STATE OF STATE OF THE PROPERTY OF THE PROPERTY OF THE PARTY OF THE PAR	Safety County of the last	