

## Nicholas LaJoie, ECE 331, HW2

```
// Author: Nicholas LaJoie
// ECE 331 - Homework 2
// Date: 2/2/17
```

### 1. Package commands:

- a. `aptitude search weather-util`
- b. `sudo apt-get install weather-util`
- c. `dpkg -L weather-util`
- d. `sudo apt-get remove weather-util`

### 2. avrdude commands:

- a. `sudo apt-get source avrdude`
- b. `wget http://savannah.nongnu.org/bugs/download.php?file_id=32171`  
`sudo mv download.php\?file_id=32171 /usr/share/avrdude-6.1/endpoint.patch`
- c. `sudo patch -i endpoint.patch`
- d. `sudo apt-get build-dep avrdude`
- e. `sudo dpkg-source --commit`
- f. `sudo dpkg-buildpackage -us -uc`
- g. `sudo dpkg -i avrdude`
- h. I don't think I ended up doing this process correctly...here's what I added in the commit for part e:

Description: Applying endpoint patch for avrdude

This is where I'm supposed to provide more info as to what this patch is doing, but unfortunately, I'm not entirely sure.

<More text here from the commit - stuff about the patch source, date, etc.>

### 3. Link command: `ln -s /sys/var/adm/armv7/hf skywalker`

### 4. Total BLOCK program:

```
// Author: Nicholas LaJoie
// File: prob4.c
// Date: 1/25/17
// Description: Print total number of BLOCKS used by list of files passed on command line.
// Sources: https://linux.die.net/man/2/stat
```

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/types.h>
#include <sys/stat.h>
#include <unistd.h>
```

```
int main(int argc, char * argv[])
{
    int i, blocksum = 0;
    struct stat s;

    if (argc < 2) {
        perror("No arguments passed.\n");
        return 1;
    }
    // Call each command line argument with 'stat' and parse data for # of blocks
    for (i = 1; i < argc; i++) {
        if (stat(argv[i], &s) == -1) {
            perror("Stat error");
        }
        else {
            blocksum += (int) s.st_blocks;
        }
    }
    printf("%d\n", blocksum);

    return 0;
}
```

### 5. Glob BLOCK program:

## Nicholas LaJoie, ECE 331, HW2

- a. ./prob5 '/usr/local/images/\*.jpg'
- b. Source code:

```
// Author: Nicholas LaJoie
// File: prob5.c
// Date: 1/31/17
// Description: Print total number of BLOCKS used by single glob passed on command line.
// Sources: https://linux.die.net/man/2/stat and https://linux.die.net/man/3/glob

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/types.h>
#include <sys/stat.h>
#include <unistd.h>
#include <glob.h>

int main(int argc, char * argv[])
{
    int i, blocksum = 0;
    struct stat s;
    glob_t g;

    // Only one command line argument is passed - a single glob.
    if (argc != 2) {
        perror("Incorrect number of arguments passed.\n");
        return 1;
    }
    // Call single glob, call each result with 'stat' for # of blocks
    if (glob(argv[1], GLOB_DOOFFS, NULL, &g) != 0) {
        perror("Glob error");
    }
    else {
        for (i = 0; i < g.gl_pathc; i++) {
            if (stat(g.gl_pathv[i], &s) == -1) {
                perror("Stat error");
            }
            else {
                blocksum += (int) s.st_blocks;
            }
        }
        printf("%d\n", blocksum);

        return 0;
    }
}
```

## 6. debugfs:

Run debugfs using the command:  
sudo debugfs /dev/<partition>  
(ex. sudo debugfs /dev/mmcblk0p7)

- a. show\_super\_stats
- b. stat /bin/ls
- c. ncheck 11