WAZP

MONOPHONIC SYNTHESIZER

Update History

Version 1.0.5



TICCO ROSS | ticcoross.gumroad.com

Update History

Version 1.0.5

- New HOLD switch in the KEYBOARD section: the last note keeps sounding after you release the key.
- The SYNC arrow is shorter and now stops at the section divider instead of crossing into the oscillator section.

Version 1.0.4

- Full Q is now stable at every cutoff: it rings very hard on every note instead of blooming into a delayed whistle at high cutoffs.
- The preset list is bigger and easier to read.
- A yellow arrow on the panel now shows that SYNC acts on the oscillators.
- Fixed: the left -/+ filter knob is now the control oscillator (LFO) amount and the right one the control envelope amount, matching the arrows on the panel.

Version 1.0.3

- The control oscillator now sweeps the filter much harder, as on the original design (up to +/- 8 kHz).
- Control oscillator range extended to 1 kHz for audio-rate filter and pitch modulation; it restarts on every note.
- NOISE and RND control-oscillator shapes now use raw pink noise.
- New two-stage filter: much stronger resonance that screams and self-oscillates at full Q.
- Output drive stage after the filter for a louder, grittier sound.
- Click the preset display to see the full preset list (factory and your own) and pick any preset directly.

Version 1.0.2

- The manual now has a clear macOS security warning section explaining how to open the installer.
- Documentation and repository text updated.

Version 1.0.1

- The SYNC, OFF and ON labels are back on the panel next to the sync switch.
- The preset window shows the preset name as soon as the plug-in opens.

Version 1.0.0

- First release of WAZP as an AU / VST3 / LV2 plug-in and standalone app for macOS, Windows and Linux.
- Two oscillators with 32' - 2' ranges, OFF / pulse / sawtooth, pulse width 10 - 90 % and oscillator 2 pitch.
- New: oscillator SYNC switch, in the place of the old BEND knob.
- New: MIXER section with separate OSC 1 and OSC 2 levels.
- Control oscillator (sine, square, noise, random) with pitch modulation and noise source.
- Resonant LO / BAND / HI filter with bipolar envelope and control-oscillator modulation.
- VCA and control envelopes with REPEAT mode, sustain level and delay.