HX1500i POWER TABLE		
MODEL	RPS0132	
PART NO.	75-005686	
AC INPUT RATING		
AC INPUT	100-240V	
INPUT CURRENT	15-9A	
FREQUENCY	47~63Hz	
	MAX LOAD	MAX OUTPUT
+3.3V	25A	150W
+5V	25A	
+12V	125A	1500W
+5VSB	3.5A	17.5W
TOTAL POWER	1200W (100V – 115V) 1500W (115V – 240V)	

HX1500i CABLE LISTING						
QTY	CABLE	CONNECTORS PER CABLE	TOTAL CONNECTORS	CONNECTOR SPACING	TOTAL LENGTH	CABLE TYPE
1	Modular ATX 24-Pin 	1	1	-	610mm (± 10mm)	DEBOSSED
2	EPS / ATX 12V 8-Pin (4+4)	1	2	-	750mm (± 10mm)	DEBOSSED
2	2x8-Pin to 12V-2x6 Cable	1	2	-	650mm (± 10mm)	DEBOSSED
5	PCIe 8-Pin (6+2)	1	5	-	650mm (± 10mm)	DEBOSSED
2	SATA (4 Straight SATA) 	4	8	505mm, 115mm, 115mm, 115mm	850mm (± 10mm)	DEBOSSED
2	PATA (3 Straight PATA) 	3	6	550mm, 100mm, 100mm	750mm (± 10mm)	DEBOSSED
1	USB (Type-C) to 10-1-Pin 	1	1	-	525mm (± 25mm)	ROUND

Tech Specs	
Cybenetics Efficiency	Platinum
Cybenetics Noise	A-
PATA Connector	6
EPS Connector	2
SATA Connector	8
Fan Bearing Technology	Fluid Dynamic Bearing
Modular	Fully
Cable Type	Type 4
PCIe Connector	5
Zero RPM Mode	Yes
PSU Form Factor	ATX
Multi GPU Ready	Yes
Fan Size MM	140mm
Continuous Power W	1500 Watts
ATX Connector	1
ATX12V Version	3.1
MTBF Hours	100,000 hours
80 PLUS Efficiency	Platinum
Warranty	10 Year
Weight	5.042Kg