

Note:

- Instead of using array maybe use classes and attributes
-> should be more performance optimized
- > class: dataset
-> attributes: e.g. dataset.accelerationX1
- Logging optional depending on uC performance
- All Status changes should be communicated with telemetry
- Instead of Booleans use Status byte and check for status byte
- Telemetry communication by SLAVE onReceive
-> interrupt

Statusbyte structure (should be send to telemetry at the beginning of each loop):

- 1 byte (char)
- States:
 - 0000 0000 (0) [0x00]: Pad Idle
 - 0000 0001 (1) [0x01]: Main deploy setpoint set
 - 0000 0010 (2) [0x02]: Continuity positive
 - 0000 0011 (3) [0x03]: Armed
 - 0000 0100 (4) [0x04]: Liftoff detected
 - 0000 0101 (5) [0x05]: Booster Burnout/Coasting
 - 0000 0110 (6) [0x06]: Apogee detected
 - 0000 0111 (7) [0x07]: Pyro 1 signal sent (drogue)
 - 0000 1000 (8) [0x08]: Pyro2 signal sent (drogue)
 - 0000 1001 (9) [0x09]: Drogue deployment detected
 - 0000 1010 (10) [0x0A]: Pyro3 signal sent (main)
 - 0000 1011 (11) [0x0B]: Pyro4 signal sent (main)
 - 0000 1100 (12) [0x0C]: Main deployment detected
 - 0000 1101 (13) [0x0D]: Landed
 - 0000 1110 (14) [0x0E]: ABORT - Failed to initialize
 - 0000 1111 (15) [0x0F]: ABORT - No continuity

