Packet Tracer - Configure NAT for IPv4

Addressing Table

Device	Interface	IP Address
R1	S0/1/0	10.1.1.1/30
	G0/0/0	192.168.10.1/24
R2	S0/1/0	10.1.1.2/30
	S0/1/1	10.2.2.1/30
	G0/0/1	209.165.200.225/27
	G0/0/0	192.168.20.1/24
R3	S0/1/1	10.2.2.2/30
	G0/0/0	192.168.30.1/24
PC1	NIC	192.168.10.10/24
PC2	NIC	192.168.30.10/24
local.pka	NIC	192.168.20.254/24
Outside PC	NIC	209.165.201.14/28
cisco.pka	NIC	209.165.201.30/28

Objectives

- Configure Dynamic NAT with PAT
- Configure Static NAT

Background / Scenario

In this lab, you will configure a router with dynamic NAT with PAT. This will translate addresses from the three internal LANs to a single outside address. In addition, you will configure static NAT to translate an internal server address to an outside address.

Instructions

In this activity you will only configure router R2.

- Use a named ACL to permit the addresses from LAN1, LAN2, and LAN3 to be translated. Specify the LANs in this order. Use the name **R2NAT**. The name you use must match this name exactly.
- Create a NAT pool named **R2POOL**. The pool should use the **first** address from the **209.165.202.128/30** address space. The pool name you use must match this name exactly. All translated addresses must use this address as their outside address.
- Configure NAT with the ACL and NAT pool that you have created.

© 2019 - 2026 Cisco and/or its affiliates. All rights reserved. Cisco Public

- Configure static NAT to map the local.pka server inside address to the **second** address from the **209.165.202.128/30** address space.
- Configure the interfaces that will participate in NAT.

© 2019 - 2026 Cisco and/or its affiliates. All rights reserved. Cisco Public