

REPORT S11L4

```
[analyst@secOps ~]$ ls -l
total 32
-rw-r--r-- 1 tcpdump tcpdump 5122 Jun 16 16:21 capture.pcap
drwxr-xr-x 2 analyst analyst 4096 Jun 18 12:39 Desktop
drwxr-xr-x 2 analyst analyst 4096 Jun 16 14:45 Documents
drwxr-xr-x 2 analyst analyst 4096 Jun 16 14:45 Downloads
drwxr-xr-x 9 analyst analyst 4096 Jan 14 2023 lab.support.files
drwxr-xr-x 2 analyst analyst 4096 Jan 12 2023 second_drive
-rw----- 1 analyst analyst 1 Jun 18 12:47 space.txt.save
[analyst@secOps ~]$ ls -la
total 132
drwxr-x--- 13 analyst analyst 4096 Jun 18 12:47 .
drwxr-xr-x 9 root root 4096 Jun 16 14:43 ..
-rw----- 1 analyst analyst 296 Jun 18 12:47 .bash_history
-rw-r--r-- 1 analyst analyst 220 Jan 6 2022 .bash_logout
-rw-r--r-- 1 analyst analyst 94 Feb 10 2023 .bashrc
drwx----- 7 analyst analyst 4096 Jun 16 14:54 .cache
-rw-r--r-- 1 tcpdump tcpdump 5122 Jun 16 16:21 capture.pcap
drwx----- 17 analyst analyst 4096 Jun 16 16:09 .config
drwx----- 3 analyst analyst 4096 Jun 16 14:54 .dbus
drwxr-xr-x 2 analyst analyst 4096 Jun 18 12:39 Desktop
-rw-r--r-- 1 analyst analyst 23 Jun 16 14:45 .dmrc
drwxr-xr-x 2 analyst analyst 4096 Jun 16 14:45 Documents
drwxr-xr-x 2 analyst analyst 4096 Jun 16 14:45 Downloads
drwx----- 3 analyst analyst 4096 Feb 10 2023 .gnome
-rw-r--r-- 1 analyst analyst 5 Feb 10 2023 .hidden
drwxr-xr-x 9 analyst analyst 4096 Jan 14 2023 lab.support.files
drwxr-xr-x 3 analyst analyst 4096 Feb 10 2023 .local
drwx----- 4 analyst analyst 4096 Jun 16 14:54 .mozilla
-rw-r--r-- 1 analyst analyst 807 Jan 6 2022 .profile
drwxr-xr-x 2 analyst analyst 4096 Jan 12 2023 second_drive
-rw----- 1 analyst analyst 1 Jun 18 12:47 space.txt.save
-rw-r--r-- 1 analyst analyst 0 Jun 16 14:46 .sudo_as_admin_successful
-rw-r---- 1 analyst analyst 5 Jun 18 12:37 .vboxclient-clipboard.pid
-rw-r---- 1 analyst analyst 5 Jun 18 12:37 .vboxclient-draganddrop.pid
-rw-r---- 1 analyst analyst 5 Jun 18 12:37 .vboxclient-seamless.pid
-rw-r---- 1 analyst analyst 5 Jun 18 12:37 .vboxclient-vmsvga-session-tty7.pid
-rw----- 1 analyst analyst 50 Jun 18 12:37 .Xauthority
-rw----- 1 analyst analyst 6373 Jun 18 12:47 .xsession-errors
-rw----- 1 analyst analyst 14399 Jun 16 16:59 .xsession-errors.old
[analyst@secOps ~]$ cat .bashrc
EDITOR=vim
```

```
PS1='\[\e[1;32m\][\u@secOps \W]\$'\[\e[0m\] '
alias ls="ls --color"
alias vi="vim"
[analyst@secOps ~]$ ls /etc
adduser.conf      init              pulse
alsa              init.d            python3
alternatives      initramfs-tools  python3.10
anacrontab        inputrc          rc0.d
apache2           iproute2         rc1.d
apm               issue            rc2.d
apparmor          issue.net        rc3.d
apparmor.d        java-11-openjdk  rc4.d
appport           john             rc5.d
```

apt	kernel	rc6.d
bash.bashrc	landscape	rc.local
bash_completion	ldap	rcS.d
bash_completion.d	ld.so.cache	resolv.conf
bindresvport.blacklist	ld.so.conf	rmt
binfmt.d	ld.so.conf.d	rpc
byobu	legal	rsyslog.conf
ca-certificates	libao.conf	rsyslog.d
ca-certificates.conf	libaudit.conf	scite
ca-certificates.conf.dpkg-old	libblockdev	screenrc
cloud	libnl-3	security
compizconfig	libpaper.d	selinux
console-setup	libreoffice	sensors3.conf
cron.d	lightdm	sensors.d
cron.daily	lighttpd	services
cron.hourly	locale.alias	shadow
cron.monthly	locale.gen	shadow-
crontab	localtime	shells
cron.weekly	logcheck	skel
crypttab	login.defs	smi.conf
dbus-1	logrotate.conf	snort
dconf	logrotate.d	sos
debconf.conf	lsb-release	sound
debian_version	machine-id	speech-dispatcher
default	magic	ssh
deluser.conf	magic.mime	ssl
depmod.d	manpath.config	subgid
dhcp	mate-settings-daemon	subgid-
dictionaries-common	mime.types	subuid
dkms	mke2fs.conf	subuid-
dpkg	modprobe.d	sudo.conf
e2scrub.conf	modules	sudoers
emacs	modules-load.d	sudoers.d
environment	mtab	sudo_logsrvd.conf
environment.d	multipath	sysctl.conf
ethertypes	nanorc	sysctl.d
firefox	netconfig	systemd
fonts	netplan	terminfo
freeradius	network	timezone
freetds	networkd-dispatcher	tlp.d
fstab	NetworkManager	tmpfiles.d
ftplib	networks	ubuntu-advantage
fuse.conf	newt	ucf.conf
gai.conf	nftables.conf	udev
ghostscript	nginx	udisks2
gimp	nsswitch.conf	ufw
glvnd	ntp.conf	update-manager
gnome	oinkmaster.conf	update-motd.d
groff	openvswitch	update-notifier
group	opt	UPower
group-	os-release	vdpa-wrapper.cfg
grub.d	PackageKit	vim
gshadow	pam.conf	vmware-tools
gshadow-	pam.d	vsftpd.conf
gss	papersize	vtrgb
gtk-2.0	passwd	wgetrc
gtk-3.0	passwd-	wireshark
guest-session	perl	wpa_supplicant
hdparm.conf	pm	X11
host.conf	pnm2ppa.conf	xattr.conf
hostname	polkit-1	xdg
hosts	pollinate	xinetd.conf
hosts.allow	ppp	xinetd.d

```

hosts.deny          profile          xrdp
ifplugd             profile.d        zsh_command_not_found
inetd.conf          protocols
[analyst@secOps ~]$ cat /etc/bash.bashrc
# System-wide .bashrc file for interactive bash(1) shells.

# To enable the settings / commands in this file for login shells as well,
# this file has to be sourced in /etc/profile.

# If not running interactively, don't do anything
[ -z "$PS1" ] && return

# check the window size after each command and, if necessary,
# update the values of LINES and COLUMNS.
shopt -s checkwinsize

# set variable identifying the chroot you work in (used in the prompt below)
if [ -z "${debian_chroot:-}" ] && [ -r /etc/debian_chroot ]; then
    debian_chroot=$(cat /etc/debian_chroot)
fi

# set a fancy prompt (non-color, overwrite the one in /etc/profile)
# but only if not SUDOing and have SUDO_PS1 set; then assume smart user.
if ! [ -n "${SUDO_USER}" ] -a -n "${SUDO_PS1}" ]; then
    PS1="${debian_chroot:+($debian_chroot)}\u@h:\w\$ "
fi

# Commented out, don't overwrite xterm -T "title" -n "icontitle" by default.
# If this is an xterm set the title to user@host:dir
#case "$TERM" in
#xterm*|rxvt*)
#    PROMPT_COMMAND='echo -ne "\033]0;${USER}@${HOSTNAME}: ${PWD}\007"'
#    ;;
#*)
#    ;;
#esac

# enable bash completion in interactive shells
#if ! shopt -oq posix; then
# if [ -f /usr/share/bash-completion/bash_completion ]; then
#     . /usr/share/bash-completion/bash_completion
# elif [ -f /etc/bash_completion ]; then
#     . /etc/bash_completion
# fi
#fi

# sudo hint
if [ ! -e "$HOME/.sudo_as_admin_successful" ] && [ ! -e "$HOME/.hushlogin" ]; then
    case " $(groups) " in *\ admin\ *|*\ sudo\ *)
        if [ -x /usr/bin/sudo ]; then
            cat <<-EOF
            To run a command as administrator (user "root"), use "sudo <command>".
            See "man sudo_root" for details.

            EOF
        fi
    esac
fi

# if the command-not-found package is installed, use it
if [ -x /usr/lib/command-not-found -o -x /usr/share/command-not-found/command-not-found ]; then
    function command_not_found_handle {
        # check because c-n-f could've been removed in the meantime

```

```

        if [ -x /usr/lib/command-not-found ]; then
            /usr/lib/command-not-found -- "$1"
            return $?
        elif [ -x /usr/share/command-not-found/command-not-found ]; then
            /usr/share/command-not-found/command-not-found -- "$1"
            return $?
        else
            printf "%s: command not found\n" "$1" >&2
            return 127
        fi
    }
fi

[analyst@secOps ~]$ nano .barsher
[analyst@secOps ~]$ sudo nano -l /etc/nginx/custom_server.conf
[sudo] password for analyst:
[analyst@secOps ~]$ sudo pkill
pkill: no matching criteria specified
Try `pkill --help' for more information.
[analyst@secOps ~]$ sudo pkill nginx
[analyst@secOps ~]$

```