

Ising Model

Bartosz Banasik (229760)

April 30, 2019

- Below are located 3 pairs of graphs. Each of them shows the configuration of the spins for a given size of the system at a fixed temperature. For the left panel, the size of the lattice equal 20×20 and for the right equal 100×100 . For figure 1 and 2 $T < T_c (T = 1)$, for figure 3 and 4 $T \simeq T_c (T = 2.26)$, for figure 5 and 6 $T > T_c (T = 5)$.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

2. Observation of the flips between states $m = +1$ and $m = -1$ at a low temperature ($T < T_c$) $T = 1.7$.
For the lattice of size 10×10




Figure 7

3. On the graphs below there are located respectively the temperature dependence of the mean value of magnetization 8, energy 9, susceptibility 10 and specific heat 11 for different size of the system ($L=10,50,100$). Figures for $K = 530000 MCS$, $k_0 = 30000 MCS$ and $k = \frac{K-k_0}{100} = 5000$ - equilibrium configurations that have been analyzed.




Figure 8




Figure 9




Figure 10




Figure 11

4. The graph below 12 presents the temperature dependence of the mean value of Binders cumulant for a few values of the linear size of the system ($L=10,50,100$). Based on the temperature dependence of Binders cumulant for different sizes of the system. From graphs, we see that cross point is $T_c \approx 2.269$.




Figure 12

5. Finite-size scaling close to the critical point using theoretical values of critical exponents $\beta = \frac{1}{8}$, $\nu = 1$ for the 2D Ising model.




Figure 13

```

0      PROGRAM ising
      IMPLICIT NONE
      integer, parameter :: L = 10
      integer, dimension(L,L) :: S
      ! PBC
      integer, dimension(L) :: NI, PI
      ! number of MCS
      integer :: k = 530000
      real :: T = 0
      ! array to store prob acceptance for
      ! given T
10     real, dimension(-8:8) :: Tex
      ! T sampling
      real, dimension(50) :: Ta
      real :: ma, ea, avgm, avgm2
      real :: sus, avge, avge2, heatc
      real :: bind_m4, bind_m2
      real :: bind

      integer :: i, j, counter

20     DO I=1,L
          NI(I)=I+1
          PI(I)=I-1
      ENDDO
      NI(L)=1
      PI(1)=L

      call init_Ta_reg(Ta)

30     call initS(S, L)

      ! open(unit=2, file="sus100.csv")
      ! write(2, *) "T,m,L"
      ! open(unit=3, file="heat100.csv")
      ! write(3, *) "T,e,L"
      open(unit=4, file="finite10.csv")
      write(4, *) "T,m,L"

      do j=1,50
40         print *, 2*j, "%"
          T = ta(j)
          ! initialize exp(-de/T) array
          call initTex(tex,T)
          ma = 0
          ea = 0
          avge = 0
          avge2 = 0
          avgm = 0
          avgm2 = 0
          counter = 0
          bind_m4 = 0
          bind_m2 = 0
          do i=1,k
50             call mcs(t)
             if ((i >= 30000) .and. (mod(i,100) == 0)) then
                 ! write(2, *) i, ",", calc_m()
                 avgm = avgm + abs(calc_m())
                 avgm2 = avgm2 + (calc_m())**2
                 ma = ma + abs(calc_m())
                 ea = ea + calc_ener()
                 avge = avge + calc_ener2()
                 avge2 = avge2 + (calc_ener2())**2
                 bind_m4 = bind_m4 + (calc_m2())**4
                 bind_m2 = bind_m2 + (calc_m2())**2
                 counter = counter + 1
             end if
          enddo
          ma = ma/float(counter)
          ea = ea/float(counter)
          avge = avge/float(counter)
          avge2 = avge2/float(counter)
          avgm = avgm/float(counter)
          avgm2 = avgm2/float(counter)
          bind_m4 = bind_m4/float(counter)
          bind_m2 = bind_m2/float(counter)
          sus = ((L*L)/T)*(avgm2 - (avgm**2))
          heatc = (1/(float(L**2)*(T**2)))*(avge2 - (avge**2))
          bind = 1 - (bind_m4/(3* (bind_m2**2)))
          ! write(3, *) T, ",", ea, ",", L
          ! write(2, *) T, ",", sus, ",", L

80

```

```

      ! write(3, *) T, ",", heatc, ",", L
      ! write(4, *) T, ",", bind, ",", L
      write(4, *) T, ",", ma, ",", L
      enddo
      ! close(2)
      ! close(3)
      close(4)

      contains

      function calc_m() result(m)
      real :: m
      integer :: i,j
      m = 0
      do i=1,L
          do j=1,L
              m = m + S(i,j)
          enddo
      enddo
      m = m/(L*L)
      end function calc_m

      function calc_m2() result(m)
      real :: m
      integer :: i,j
      m = 0
      do i=1,L
          do j=1,L
              m = m + S(i,j)
          enddo
      enddo
      end function calc_m2

      function calc_ener() result(en)
      real :: en
      integer :: i, j, su
      en = 0
      do i=1,L
          do j=1,L
              su = S(NI(i), j) + &
                  S(PI(i), j) + &
                  S(i, NI(j)) + &
                  S(i, PI(j))
              en = en + ((-su) * S(i,j))
          enddo
      enddo
      en = en/((L*L)*2.0)
      end function calc_ener

      function calc_ener2() result(en)
      real :: en
      integer :: i, j, su
      en = 0
      do i=1,L
          do j=1,L
              su = S(NI(i), j) + &
                  S(PI(i), j) + &
                  S(i, NI(j)) + &
                  S(i, PI(j))
              en = en + ((-su) * S(i,j))
          enddo
      enddo
      en = en/(2.0)
      end function calc_ener2

      function calc_du(x, y) result(du)
      integer :: du
      integer, intent(in) :: x,y
      integer :: su ! suma

      su = S(NI(x), y) + &
          S(PI(x), y) + &
          S(x, NI(y)) + &
          S(x, PI(y))
      du = 2 * S(x,y) * su
      end function calc_du

```

```

160      subroutine trial(i, j, t)
          integer, intent(in) :: i, j
          real, intent(in) :: t
          integer :: du
          real :: paccept, ptrial

          du = calc_du(i, j)
          if (du < 0) then
              S(i,j) = -S(i,j)
          else
              call random_number(paccept)
              ptrial = tex(du)
170             if (paccept <= ptrial) then
                  s(i,j) = -s(i,j)
260             end if
          endif
      end subroutine trial

      subroutine mcs(t)
          real, intent(in) :: t
          integer i, j

180          do i=1,L
              do j=1,L
                  call trial(i,j,t)
              enddo
          enddo
      end subroutine mcs

      subroutine print_S_out()
          integer :: i, j
          do i=1,L
190             print *, S(i,:)
          enddo
      end subroutine print_S_out

      subroutine print_S()
          integer :: i, j
          open(unit=2, file="lattice5-100.csv")
          write(2, *) "x,y,m"
          do i=1,L
              do j=1,L
200                 write(2, *) i, ", ", j, ", ", S(i,j)
              enddo
          enddo
          close(2)
      end subroutine print_S

      END PROGRAM

      subroutine initTex(tex,tmp)
          real, dimension(-8:8), intent(inout) :: tex
          real, intent(inout) :: tmp
          integer :: i
          do i=-8,8,4
              tex(i) = exp((-i)/tmp)
          enddo
      end subroutine initTex

      subroutine initS(s, l)
          integer, intent(in) :: L
          integer, dimension(1,1) :: S
220          integer :: i,j
          do i=1,L
              do j=1,L
                  S(i,j) = 1
              enddo
          enddo
      end subroutine initS

      subroutine init-Ta(ta)
          real, intent(inout), dimension(50) :: ta
          integer :: i, j = 0
230          do i=1,10
              ta(i) = 1.5 + i * ((2.0-1.5)/10)
          enddo

          j=1
          do i=11,40
              ta(i) = 2.0 + j * ((2.7-2.0)/30)
              j = j+1
          enddo

240          j = 0
          do i=41,50
              ta(i) = 2.7 + j * ((3.5-2.7)/10)
              j = j+1
          enddo
      end subroutine init-Ta

      subroutine init-Ta_100(ta)
          real, intent(inout), dimension(50) :: ta
          integer :: i, j = 0
          do i=1,10
              ta(i) = 1.5 + i * ((2.2-1.5)/10)
          enddo

          j=1
          do i=11,40
              ta(i) = 2.2 + j * ((2.5-2.2)/30)
              j = j+1
          enddo

          j = 1
          do i=41,50
              ta(i) = 2.5 + j * ((3.5-2.5)/10)
              j = j+1
          enddo
      end subroutine init-Ta_100

      subroutine init-Ta_reg(ta)
          real, intent(inout), dimension(50) :: ta
          integer :: i
          do i=1,50
              ta(i) = 1.5 + i * ((3.5-1.5)/50)
          enddo
      end subroutine init-Ta_reg

      subroutine init-Ta_bind(ta)
          real, intent(inout), dimension(50) :: ta
          integer :: i
          do i=1,50
              ta(i) = 1.8 + i * ((2.5-1.8)/50)
          enddo
      end subroutine init-Ta_bind

      subroutine init-Ta_flip(ta)
          real, intent(inout), dimension(50) :: ta
          integer :: i
          do i=1,50
              ta(i) = 1.8 + i * ((2.5-1.8)/50)
          enddo
      end subroutine init-Ta_flip

```