

model

March 29, 2020

1 Application of continuous wavelet transform to feature extraction

1.1 Bartosz Banasik: 229760

Needed imports:

```
[0]: import os
      from pathlib import Path
      import numpy as np
      import pywt
      import matplotlib.pyplot as plt

      import tensorflow as tf
      from tensorflow.keras.utils import to_categorical
      from tensorflow.keras.layers import Dense, Conv2D, Flatten, MaxPooling2D
      from tensorflow.keras import Sequential
      from tensorflow.keras.optimizers import Adadelta
      from tensorflow.keras.callbacks import ModelCheckpoint
      from tqdm import tqdm
      import h5py
```

1.2 Download and unpack the data

For data description look into the README.txt file. There is a chance that you will need to change the download file. Please check [UCI HAR dataset](#).

```
[0]: !wget https://archive.ics.uci.edu/ml/machine-learning-databases/00240/
      ↪UCI%20HAR%20Dataset.zip

--2020-03-28 22:36:15-- https://archive.ics.uci.edu/ml/machine-learning-
databases/00240/UCI%20HAR%20Dataset.zip
Resolving archive.ics.uci.edu (archive.ics.uci.edu)... 128.195.10.252
Connecting to archive.ics.uci.edu (archive.ics.uci.edu)|128.195.10.252|:443...
connected.
HTTP request sent, awaiting response... 200 OK
Length: 60999314 (58M) [application/x-httpd-php]
Saving to: 'UCI HAR Dataset.zip'
```

UCI HAR Dataset.zip 100%[=====>] 58.17M 73.1MB/s in 0.8s

2020-03-28 22:36:21 (73.1 MB/s) - 'UCI HAR Dataset.zip' saved
[60999314/60999314]

```
[0]: !unzip "UCI HAR Dataset.zip"
```

```
Archive: UCI HAR Dataset.zip
  creating: UCI HAR Dataset/
  inflating: UCI HAR Dataset/.DS_Store
    creating: __MACOSX/
    creating: __MACOSX/UCI HAR Dataset/
  inflating: __MACOSX/UCI HAR Dataset/._DS_Store
  inflating: UCI HAR Dataset/activity_labels.txt
  inflating: __MACOSX/UCI HAR Dataset/._activity_labels.txt
  inflating: UCI HAR Dataset/features.txt
  inflating: __MACOSX/UCI HAR Dataset/._features.txt
  inflating: UCI HAR Dataset/features_info.txt
  inflating: __MACOSX/UCI HAR Dataset/._features_info.txt
  inflating: UCI HAR Dataset/README.txt
  inflating: __MACOSX/UCI HAR Dataset/._README.txt
    creating: UCI HAR Dataset/test/
    creating: UCI HAR Dataset/test/Inertial Signals/
  inflating: UCI HAR Dataset/test/Inertial Signals/body_acc_x_test.txt
    creating: __MACOSX/UCI HAR Dataset/test/
    creating: __MACOSX/UCI HAR Dataset/test/Inertial Signals/
  inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/. _body_acc_x_test.txt
    inflating: UCI HAR Dataset/test/Inertial Signals/body_acc_y_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/. _body_acc_y_test.txt
    inflating: UCI HAR Dataset/test/Inertial Signals/body_acc_z_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/. _body_acc_z_test.txt
    inflating: UCI HAR Dataset/test/Inertial Signals/body_gyro_x_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/. _body_gyro_x_test.txt
    inflating: UCI HAR Dataset/test/Inertial Signals/body_gyro_y_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/. _body_gyro_y_test.txt
    inflating: UCI HAR Dataset/test/Inertial Signals/body_gyro_z_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/. _body_gyro_z_test.txt
    inflating: UCI HAR Dataset/test/Inertial Signals/total_acc_x_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/. _total_acc_x_test.txt
    inflating: UCI HAR Dataset/test/Inertial Signals/total_acc_y_test.txt
```

```

    inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/._total_acc_y_test.txt
    inflating: UCI HAR Dataset/test/Inertial Signals/total_acc_z_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/Inertial
Signals/._total_acc_z_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/._Inertial Signals
    inflating: UCI HAR Dataset/test/subject_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/._subject_test.txt
    inflating: UCI HAR Dataset/test/X_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/._X_test.txt
    inflating: UCI HAR Dataset/test/y_test.txt
    inflating: __MACOSX/UCI HAR Dataset/test/._y_test.txt
    inflating: __MACOSX/UCI HAR Dataset/._test
    creating: UCI HAR Dataset/train/
    creating: UCI HAR Dataset/train/Inertial Signals/
    inflating: UCI HAR Dataset/train/Inertial Signals/body_acc_x_train.txt
    creating: __MACOSX/UCI HAR Dataset/train/
    creating: __MACOSX/UCI HAR Dataset/train/Inertial Signals/
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._body_acc_x_train.txt
    inflating: UCI HAR Dataset/train/Inertial Signals/body_acc_y_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._body_acc_y_train.txt
    inflating: UCI HAR Dataset/train/Inertial Signals/body_acc_z_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._body_acc_z_train.txt
    inflating: UCI HAR Dataset/train/Inertial Signals/body_gyro_x_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._body_gyro_x_train.txt
    inflating: UCI HAR Dataset/train/Inertial Signals/body_gyro_y_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._body_gyro_y_train.txt
    inflating: UCI HAR Dataset/train/Inertial Signals/body_gyro_z_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._body_gyro_z_train.txt
    inflating: UCI HAR Dataset/train/Inertial Signals/total_acc_x_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._total_acc_x_train.txt
    inflating: UCI HAR Dataset/train/Inertial Signals/total_acc_y_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._total_acc_y_train.txt
    inflating: UCI HAR Dataset/train/Inertial Signals/total_acc_z_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/Inertial
Signals/._total_acc_z_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/._Inertial Signals
    inflating: UCI HAR Dataset/train/subject_train.txt
    inflating: __MACOSX/UCI HAR Dataset/train/._subject_train.txt
    inflating: UCI HAR Dataset/train/X_train.txt

```

```

inflating: __MACOSX/UCI HAR Dataset/train/._X_train.txt
inflating: UCI HAR Dataset/train/y_train.txt
inflating: __MACOSX/UCI HAR Dataset/train/._y_train.txt
inflating: __MACOSX/UCI HAR Dataset/._train
inflating: __MACOSX/._UCI HAR Dataset

```

1.3 Load the data

Read 9 component signals from "Inertial Signals" directory and read corresponding labels from y*.txt file. Labels are from 1-6, but to use categorical features from keras library we need them to start from 0. We also transpose X array to obtain in each record 128 samples for 9 components.

```

[0]: def readData(root_directory: str):
    root_path = Path(root_directory)
    p = root_path / "Inertial Signals"
    x_paths = sorted(list(p.glob('*.txt')))
    y_path = list(root_path.glob('y*.txt'))[0]

    x = []
    print(x_paths)
    for x_p in x_paths:
        x.append(np.loadtxt(x_p, dtype=np.float32))

    y = to_categorical(np.loadtxt(y_path, dtype=np.int8) - 1 )
    return np.transpose(np.array(x), (1, 2, 0)), y

```

1.4 Continuous wavelet transform

Below is simple example of Continuous wavelet transform.

```

[0]: def myCWT(vector):
    wavelet = "morl"
    coeff, freqs = pywt.cwt(vector, np.arange(1,129), wavelet)
    return coeff

```

1.5 Create CNN input

Take the created arrays and apply CWT to each 9 components of each record. The result array shape should be (n_samples, 128, 128, 9). We're using morlet real wavelet, and scale from 1 to 128.

```

[0]: def CWT(x, size):
    records = x.shape[0]
    components = x.shape[2]

    scale = np.arange(1, size + 1)
    wavelet = 'morl'

```

```

ret_arr = np.ndarray(shape=(records, size, size, components), dtype=np.
↪float32)
for r in tqdm(range(records)):
    for c in range(components):
        coeffs, _ = pywt.cwt(x[r, :, c], scale, wavelet)
        ret_arr[r, :, :, c] = coeffs
return ret_arr

```

```

[0]: x_train, y_train = readData("UCI HAR Dataset/train")
x_test, y_test = readData("UCI HAR Dataset/test")
x_train = CWT(x_train, 128)
x_test = CWT(x_test, 128)

```

```

[PosixPath('UCI HAR Dataset/train/Inertial Signals/body_acc_x_train.txt'),
PosixPath('UCI HAR Dataset/train/Inertial Signals/body_acc_y_train.txt'),
PosixPath('UCI HAR Dataset/train/Inertial Signals/body_acc_z_train.txt'),
PosixPath('UCI HAR Dataset/train/Inertial Signals/body_gyro_x_train.txt'),
PosixPath('UCI HAR Dataset/train/Inertial Signals/body_gyro_y_train.txt'),
PosixPath('UCI HAR Dataset/train/Inertial Signals/body_gyro_z_train.txt'),
PosixPath('UCI HAR Dataset/train/Inertial Signals/total_acc_x_train.txt'),
PosixPath('UCI HAR Dataset/train/Inertial Signals/total_acc_y_train.txt'),
PosixPath('UCI HAR Dataset/train/Inertial Signals/total_acc_z_train.txt')]
[PosixPath('UCI HAR Dataset/test/Inertial Signals/body_acc_x_test.txt'),
PosixPath('UCI HAR Dataset/test/Inertial Signals/body_acc_y_test.txt'),
PosixPath('UCI HAR Dataset/test/Inertial Signals/body_acc_z_test.txt'),
PosixPath('UCI HAR Dataset/test/Inertial Signals/body_gyro_x_test.txt'),
PosixPath('UCI HAR Dataset/test/Inertial Signals/body_gyro_y_test.txt'),
PosixPath('UCI HAR Dataset/test/Inertial Signals/body_gyro_z_test.txt'),
PosixPath('UCI HAR Dataset/test/Inertial Signals/total_acc_x_test.txt'),
PosixPath('UCI HAR Dataset/test/Inertial Signals/total_acc_y_test.txt'),
PosixPath('UCI HAR Dataset/test/Inertial Signals/total_acc_z_test.txt')]

100%|      | 7352/7352 [13:08<00:00,  9.32it/s]
100%|      | 2947/2947 [05:16<00:00,  9.32it/s]

```

Due to high memory usage it's good to clear the garbage at the time.

```

[0]: import gc
gc.collect()

```

```

[0]: 22

```

```

[0]: print(x_train.shape, y_train.shape)
print(x_test.shape, y_test.shape)
print(x_train.dtype)
print(x_train.nbytes)

```

```

(7352, 128, 128, 9) (7352, 6)
(2947, 128, 128, 9) (2947, 6)

```

```
float32
4336386048
```


1.6 Pick one record and see all 9 components

Here we're gonna pick one record and display all 9 components that were produced from CWT.

```
[0]: def plot(x, y):
      labels = ["Walking", "Walking upstairs", "Walking downstairs", "Sitting",
↪ "Standing", "Laying"]
      fig, ax = plt.subplots(nrows=3, ncols=3, figsize=(12, 12))
      for index, ax_id in enumerate(ax.flat):
          ax_id.imshow(x[:, :, index], aspect='auto', cmap="jet")
      fig.suptitle(labels[np.argmax(y)])
      plt.show()
```

```
[0]: plot(x_test[4], y_test[4])
```

Standing




1.7 Pick one component and display for different activity


Here we're gonna plot CWT coefficients for different activities to just one chosen component.

```
[0]: def find_indexes(y):  
    indexes = []  
    y_n = np.argmax(y, axis=-1)  
    for label in sorted(np.unique(y_n)):  
        indexes.append(np.where(y_n == label)[0][0])  
    return indexes
```

```
[0]: def plot2(x, component, indexes):
    labels = ["Walking", "Walking upstairs", "Walking downstairs", "Sitting", "Standing", "Laying"]
    fig, ax = plt.subplots(nrows=2, ncols=3, figsize=(12, 6))
    for ui, ax_id, idx in zip([i for i in range(7)], ax.flat, indexes):
        ax_id.imshow(x[idx,:,:],component,aspect='auto', cmap="jet")
        ax_id.set_title(labels[ui])
    plt.show()
```

```
[0]: idxs = find_indexes(y_test)
plot2(x_test, 1, idxs)
plot2(x_test, 7, idxs)
```





1.8 Create CNN model

As in the task description we're creating the simple CNN with 2 convolutional and 2 MaxPooling layers. After that we're adding flat classifier with 2 fully connected layers. On the output layer we have 6 neurons.

```
[0]: import gc
gc.collect()
```

[0]: 0

```
[0]: #create model
model = Sequential()#add model layers
model.add(Conv2D(32, kernel_size=5,
                 activation='relu',
                 input_shape=(128,128,9)
                )
)
model.add(MaxPooling2D(pool_size=2))
model.add(Conv2D(64, kernel_size=5,
                 activation='relu'
                )
)
model.add(MaxPooling2D(pool_size=2))
model.add(Flatten())
model.add(Dense(1024, activation = 'relu'))
model.add(Dense(512, activation = 'relu'))
model.add(Dense(6, activation='softmax'))
```

This is classification to 6 different classes, so at the end of our classifier we have `softmax` activation function. We're gonna use `Adadelta` optimizer and *categorical_crossentropy* as a loss function.

```
[0]: model.compile(loss='categorical_crossentropy',
                  optimizer=tf.keras.optimizers.Adadelta(),
                  metrics=['accuracy'])
```

```
[0]: history = model.fit(
    x_train, y_train,
    validation_split=0.2,
    batch_size=16, epochs=10, verbose=1,
    shuffle=True,
)
```


```
Epoch 1/10
368/368 [=====] - 8s 22ms/step - loss: 1.0972 -
accuracy: 0.7472 - val_loss: 0.6372 - val_accuracy: 0.8532
Epoch 2/10
368/368 [=====] - 8s 20ms/step - loss: 0.4945 -
accuracy: 0.8672 - val_loss: 0.3999 - val_accuracy: 0.8770
Epoch 3/10
368/368 [=====] - 8s 20ms/step - loss: 0.3432 -
accuracy: 0.8963 - val_loss: 0.3210 - val_accuracy: 0.8858
Epoch 4/10
368/368 [=====] - 7s 20ms/step - loss: 0.2768 -
accuracy: 0.9114 - val_loss: 0.2850 - val_accuracy: 0.9055
Epoch 5/10
368/368 [=====] - 7s 20ms/step - loss: 0.2377 -
accuracy: 0.9163 - val_loss: 0.2720 - val_accuracy: 0.9014
Epoch 6/10
368/368 [=====] - 7s 20ms/step - loss: 0.2107 -
accuracy: 0.9254 - val_loss: 0.2544 - val_accuracy: 0.9082
Epoch 7/10
368/368 [=====] - 7s 20ms/step - loss: 0.1913 -
accuracy: 0.9308 - val_loss: 0.2448 - val_accuracy: 0.9137
Epoch 8/10
368/368 [=====] - 7s 20ms/step - loss: 0.1762 -
accuracy: 0.9395 - val_loss: 0.2408 - val_accuracy: 0.9150
Epoch 9/10
368/368 [=====] - 7s 20ms/step - loss: 0.1647 -
accuracy: 0.9418 - val_loss: 0.2363 - val_accuracy: 0.9211
Epoch 10/10
368/368 [=====] - 7s 20ms/step - loss: 0.1544 -
accuracy: 0.9468 - val_loss: 0.2332 - val_accuracy: 0.9143
```

Plot the loss and accuracy.

```
[0]: def plot_graphs(history):
    # summarize history for accuracy
    acc_key = "accuracy"
    fig, (ax1, ax2) = plt.subplots(1,2, figsize=(12,6))
    ax1.plot(history.history[acc_key])
    ax1.plot(history.history['val_' + acc_key])
    ax1.set_title('model accuracy')
    ax1.set_ylabel('accuracy')
    ax1.set_xlabel('epoch')
    ax1.legend(['train', 'test'], loc='upper left')

    # summarize history for loss
    ax2.plot(history.history['loss'])
    ax2.plot(history.history['val_loss'])
    ax2.set_title('model loss')
    ax2.set_ylabel('loss')
    ax2.set_xlabel('epoch')
    ax2.legend(['train', 'test'], loc='upper left')
    plt.show()

plot_graphs(history)
```



We see that during training our validation accuracy reaches 91% and is not far away from the training accuracy. This means that the model generalize well. Now lets check what is the estimation of the real accuracy:

```
[0]: test_score = model.evaluate(x_test, y_test, verbose=0)
print('Test loss: {}, Test accuracy: {}'.format(test_score[0], test_score[1]))
```

Test loss: 0.2667182981967926, Test accuracy: 0.9049881100654602

[0]: