

Sameer Sir Classes, Jabalpur  
Auth Exam Center Oracle, Microsoft  
9407077858

### LCM ( Least Common Multiple )

LCM of two numbers is the smallest number which can be divided by both numbers.

For example, LCM of 15 and 20 is 60, and  
LCM of 5 and 7 is 35.


---

### WAP TO FIND LCM

```
#include <stdio.h>
int main()
{
    int n1, n2, max;
    printf("Enter two positive integers\n ");
    scanf("%d%d", &n1, &n2);

    // maximum number between n1 and n2 is stored in max
    max = (n1 > n2) ? n1 : n2 ;

    while (1) // infinite loop
    {
        if ( max % n1 == 0 && max % n2 == 0 )
        {
            printf("The LCM of %d and %d is %d.", n1, n2, max);
            break;
        }
        max++;
    }
}
```



Sameer Sir Classes, Jabalpur  
Auth Exam Center Oracle, Microsoft  
9407077858

-----  
 $n1 = 2, n2 = 3$

$\text{max} = (2 > 3) ? 2 : 3 ;$   
 $\text{max} = 3$

$\text{max} \% n1 == 0 \quad \&\& \quad \text{max} \% n2 == 0$

$\text{max} = 3 \quad 3 \% 2 == 0 \quad \&\& \quad 3 \% 3 == 0 \quad \text{F}$

$\text{max} = 4 \quad 4 \% 2 == 0 \quad \&\& \quad 4 \% 3 == 0 \quad \text{F}$

$\text{max} = 5 \quad 5 \% 2 == 0 \quad \&\& \quad 5 \% 3 == 0 \quad \text{F}$

$\text{max} = 6 \quad 6 \% 2 == 0 \quad \&\& \quad 6 \% 3 == 0 \quad \text{T break}$

$\text{LCM} = \text{max} = 6$

-----  
**Highest Common Factor (HCF) : OR**  
**Greatest Common Divisor (GCD) :**  
-----

The HCF or GCD of two integers is the **largest integer**

that can exactly divide both numbers (without a remainder).

For example, HCF of 12 and 18 is 6. AND  
HCF of 16 and 32 is 16. AND  
HCF of 12 and 15 is 3.

Sameer Sir Classes, Jabalpur  
Auth Exam Center Oracle, Microsoft  
9407077858

**WAP to Find HCF OR GCD of two Numbers**

```
#include <stdio.h>
```

```
int main()
{
    int n1, n2, i, gcd;

    printf("Enter two integers:\n ");

    scanf("%d%d", &n1, &n2);
    for( i = 1 ; i <= n1 && i <= n2 ; i++ )
    {
        // Checks if i is factor of both integers

        if( n1 % i == 0 && n2 % i == 0 )
            gcd = i;
    }

    printf("G.C.D of %d and %d is %d\n", n1, n2, gcd);
}
```

-----

HCF of 12 and 18 is 6.

n1 = 12 , n2 = 18

n1 % i == 0 && n2 % i == 0                      gcd = i

Sameer Sir Classes, Jabalpur  
Auth Exam Center Oracle, Microsoft  
9407077858

i = 1    12 % 1 == 0 && 18 % 1 == 0    T    gcd = 1

i = 2    12 % 2 == 0 && 18 % 2 == 0    T    gcd = 2

i = 3    12 % 3 == 0 && 18 % 3 == 0    T    gcd = 3

i = 4    12 % 4 == 0 && 18 % 4 == 0    F

i = 5    12 % 5 == 0 && 18 % 5 == 0    F

i = 6    12 % 6 == 0 && 18 % 6 == 0    T    gcd = 6

.  
. .  
.

i = 12    12 % 12 == 0 && 18 % 12 == 0    F

$$\text{LCM} * \text{GCD} = (\text{N1} * \text{N2})$$

$$\text{LCM} = (\text{N1} * \text{N2}) / \text{GCD} ;$$

---

## WAP TO FIND LCM USING GCD

```
#include <stdio.h>
int main()
{
    int n1 , n2 , i , min , gcd , LCM ;

    printf("Enter two positive integers:\n ");

    scanf("%d%d", &n1, &n2);

    // minimum number between n1 and n2 is stored in min
    min = (n1 < n2) ? n1 : n2 ;

    for ( i = 1 ; i <= min ; i++ )
    {
        // check if i is a factor of both integers

        if ( n1 % i == 0 && n2 % i == 0 )
            gcd = i;

    }

    LCM = (n1 * n2) / gcd;

    printf("The LCM  of %d and %d is %d\n" , n1, n2, LCM);

    printf("THE GCD  of %d and %d is %d\n" , n1, n2 , gcd);

}
```

## **E.G. OF break STATEMENT**

### **PRIME NO.**

```
#include<stdio.h>
```

```
int main()
{
    int i , n , t = 1 ;

    printf(" ENTER NO \n ");
    scanf( "%d", &n);

    for( i = 2 ; i <= n-1 ; i++)
    {
        t = n % i ; // remainder

        if( t == 0 )
        {
            break;
        }
        // imp for --> end

    }

    if( t != 0 )
    {
        printf(" PRIME NO \n");
    }
    else
    {
        printf(" NOT PRIME NO OR COMPOSITE NO. \n ");
    }
}
```

Sameer Sir Classes, Jabalpur  
Auth Exam Center Oracle, Microsoft  
9407077858

---

**trace:-** 1.  $n = 5$  ;  
for  $i = 2$  to  $4$

$i = 2$   $t = 5 \% 2 = 1$

$i = 3$   $t = 5 \% 3 = 2$

$i = 4$   $t = 5 \% 4 = 1$  ✓

if(  $t \neq 0$  )

PRIME NO.

---

2.  $n = 9$   
for  $i = 2$  to  $8$

$i = 2$   $t = 9 \% 2 = 1$

$i = 3$   $t = 9 \% 3 = 0$  ✓

if(  $t == 0$  )

break ;  $i = 4, 5, 6, 7, 8$  X

if(  $t \neq 0$  ) X

NOT PRIME NO. OR COMPOSITE NO.

---

3.  $n = 2$  ,  $t = 1$  // IMP

for  $i = 2$  to  $1$  X

if(  $t \neq 0$  ) if(  $t$  ) // true  
prime no.

---


## CONTINUE STATEMENT

**WAP FOR PRINT 1 TO 100 NO. EXCEPT 20 TO 30.**

```
#include<stdio.h>
```

```
int main()
{
    int i;

    for( i = 1 ; i <= 100 ; i++ )
    {
        if( i >= 20 && i <= 30 )
        {
            CONTINUE;
        }
        printf("%d\t" , i);
    }
}
```



---

## WITHOUT USING CONTINUE STATEMENTS

```
for( i = 1 ; i <= 100 ; i++ )
{
    if( ! ( i >= 20 && i <= 30 ) )
    {
        printf("%d\t" , i);
    }
}
```



## FIBONACCI SERIES

**0 1 1 2 3 5 8 13 .....**  
given

e.g. n = 4      0    1    1    2    3  
                 0th 1st 2nd 3rd 4th

---

```
#include<stdio.h>
int main()
{
    int i , n , a = 0 , b = 1 , c ;

    printf(" ENTER NO \n ");
    scanf("%d", &n);

    printf("%4d%4d", a , b); // 0    1

    for( i = 1 ; i <= n-1 ; i++)
    {
        c = a + b ;
        printf("%4d", c);

        a = b ; // imp ( new a and b )
        b = c ;
    }
}
```

## **JUMPING STATEMENT**

**goto :- TO MOVE PERTICULAR LINE NO.**

**syntax**  
**goto lebel;**

---

BASIC , PASCAL --> GOTO  
AVOID GOTO

---

**PRINT 1 TO 10 USING if()**

```
#include<stdio.h>
int main()
{
    int i = 1;

    p : printf(" %d\n",i);

    i++;

    if( i <= 10 )
    {
        goto p ;
    }
}
```