

ASSIGNMENT-13.3

Name: D. Sravika Reddy

H-T No: 2403a510d0

Batch No: 05

Course: AI Assisted Coding

✓ Task Description #1 - Remove Repetition

Task: Provide AI with the following redundant code and ask it to refactor

Python Code

```
def calculate_area(shape, x, y=0):  
    if shape == "rectangle":  
        return x * y  
    elif shape == "square":  
        return x * x  
    elif shape == "circle":  
        return 3.14 * x * x
```

Expected Output

- Refactored version with dictionary-based dispatch or separate functions.
 - Cleaner and modular design
- ✓ #Prompt: Refactor the following redundant code to remove repetition. Use a dictionary-based dispatch or separate functions for each shape to make the design cleaner and more modular.

✓ Code & Output:

```
13.3-01.py > ...
1  def calculate_area(shape, x, y=0):
2      if shape == "rectangle":
3          return x * y
4      elif shape == "square":
5          return x * x
6      elif shape == "circle":
7          return 3.14 * x * x
8      else:
9          raise ValueError("Unknown shape")
10 # Example usage:
11 print(calculate_area("rectangle", 4, 5))
12 print(calculate_area("square", 4))
13 print(calculate_area("circle", 3))
14 # Output / Test cases
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
PS C:\Users\sravi\OneDrive\Desktop\AIAC> & C:/ProgramData/anaconda3/
.py
20
16
28.259999999999998
```

✓ Refactored Code & Output:

```
13.3-1.py > ...
1  def rectangle_area(x, y):
2      return x * y
3  def square_area(x, _=0):
4      return x * x
5  def circle_area(x, _=0):
6      return 3.14 * x * x
7  area_dispatch = {
8      "rectangle": rectangle_area,
9      "square": square_area,
10     "circle": circle_area
11 }
12 def calculate_area(shape, x, y=0):
13     if shape not in area_dispatch:
14         raise ValueError("Unknown shape")
15     return area_dispatch[shape](x, y)
16 # Example usage:
17 print(calculate_area("rectangle", 4, 5))
18 print(calculate_area("square", 4))
19 print(calculate_area("circle", 3))
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
PS C:\Users\sravi\OneDrive\Desktop\AIAC> & C:/ProgramData/anaconda3/
20
16
28.259999999999998
```

✓ Explanation for the Original Code:

The function `calculate_area` computes the area for three different shapes based on the `shape` argument:

- If the shape is "rectangle", it multiplies `x` and `y` to get the area.
- If the shape is "square", it returns `x * x` (area of a square).
- If the shape is "circle", it returns `3.14 * x * x` (area of a circle with radius `x`).
- If the shape is not recognized, it raises a `ValueError`.

Example usage:

- `calculate_area("rectangle", 4, 5)` returns 20
- `calculate_area("square", 4)` returns 16
- `calculate_area("circle", 3)` returns 28.26

✓ Explanation for the Refactored Code (from previous answer):

The refactored version separates the area calculation for each shape into its own function and uses a dictionary (`area_dispatch`) to map shape names to these functions. The main `calculate_area` function looks up the appropriate function and calls it.

Benefits of the refactored approach:

- **Modularity:** Each shape's logic is isolated, making the code easier to maintain and extend.
- **Readability:** The main function is cleaner and easier to understand.
- **Extensibility:** Adding new shapes only requires defining a new function and updating the dictionary.

Both versions correctly calculate areas, but the refactored version is more maintainable and scalable for larger applications.

✓ Task Description #2 - Error Handling in Legacy Code

Task: Legacy function without proper error handling

Python Code

```
def read_file(filename):
```

```
    f = open(filename, "r")
```

```
    data = f.read()
```

```
    f.close()
```


```
    return data
```

Expected Output:

AI refactors with with open() and try-except:

- ✓ #Prompt: Refactor the following legacy function to include proper error handling and resource management using with open() and a try-except block.

✓ Code & Output:



```
13.3-02.py > read_file
1  def read_file(filename):
2      """
3      Reads the contents of a file safely with error handling.
4      Args:
5      |   filename (str): The path to the file.
6      Returns:
7      |   str: The file contents, or an error message if reading fails.
8      """
9      try:
10         with open(filename, "r") as f:
11             data = f.read()
12             return data
13     except FileNotFoundError:
14         return "Error: File not found."
15     except IOError as e:
16         return f"I/OError: {e}"
17 # Example usage:
18 print(read_file("sample.txt"))    # Output: Hello, world!
19 print(read_file("missing.txt"))  # Output: Error: File not found.
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS Python + - □ □ ...

```
PS C:\Users\sravi\OneDrive\Desktop\AIAC> & C:/ProgramData/anaconda3/python.exe c:/Users/sravi/Desktop/AIAC/13.3-02.py
Error: File not found.
Error: File not found.
```

✓ Explanation:

- Uses with open() for automatic file closing, even if an error occurs.
- Handles FileNotFoundError and general IOError with user-friendly messages.
- Returns the file contents if successful, or an error message otherwise.
- This approach is safer and more robust than the legacy code

✓ Task Description #3 - Complex Refactoring

Task: Provide this legacy class to AI for readability and modularity

improvements:

Python Code

class Student:

```
def __init__(self, n, a, m1, m2, m3):
```

```
    self.n = n
```

```
    self.a = a
```

```
    self.m1 = m1
```

```
    self.m2 = m2
```

```
    self.m3 = m3
```

```
    def details(self):
```

```
        print("Name:", self.n, "Age:", self.a)
```

```
    def total(self):
```

```
        return self.m1+self.m2+self.m3
```

Expected Output:

- AI improves naming (name, age, marks).
- Adds docstrings.
- Improves print readability.
- Possibly uses sum(self.marks) if marks stored in a list.

✓ #Prompt: Refactor the following legacy Student class to improve readability and modularity. Use descriptive variable names, add docstrings, improve print formatting, and consider storing marks in a list to simplify calculations.

✓ Code & Output:

```
13.3-3.py > ...
1 class Student:
2     def __init__(self, n, a, m1, m2, m3):
3         self.n = n
4         self.a = a
5         self.m1 = m1
6         self.m2 = m2
7         self.m3 = m3
8     def details(self):
9         print("Name:", self.n, "Age:", self.a)
10    def total(self):
11        return self.m1+self.m2+self.m3
12    def average(self):
13        return (self.m1+self.m2+self.m3)/3
14 s1 = Student("Alice", 20, 85, 90, 95)
15 s1.details() # Output: Name: Alice Age: 20
16 print("Total Marks:", s1.total()) # Output: Total Marks: 270
17 print("Average Marks:", s1.average()) # Output: Average Marks: 90.0
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS Python + v

PS C:\Users\sravi\OneDrive\Desktop\AIAC> & C:/ProgramData/anaconda3/python.exe c:/Users/top/AIAC/13.3-3.py
Name: Alice Age: 20
Total Marks: 270
Average Marks: 90.0

✓ Refactored Code & Output:

```
1 class Student:
2     """
3     Represents a student with name, age, and a list of marks.
4     """
5
6     def __init__(self, name, age, marks):
7         """
8         Initialize a Student object.
9
10        Args:
11            name (str): The student's name.
12            age (int): The student's age.
13            marks (list of int): List of marks for the student.
14        """
15        self.name = name
16        self.age = age
17        self.marks = marks
18
19    def details(self):
20        """Print the student's name and age."""
21        print(f"Name: {self.name}, Age: {self.age}")
22
23    def total(self):
24        """Return the total of all marks."""
25        return sum(self.marks)
26
27    # Example usage and output
28    student = Student("Alice", 20, [85, 90, 95])
29    student.details() # Output: Name: Alice, Age: 20
30    print(student.total()) # Output: 270
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS Python + v

Name: Alice, Age: 20
270

Explanation:

- Variable names are now descriptive (name, age, marks).
- Marks are stored as a list, allowing easy calculation with `sum(self.marks)`.
- Docstrings are added for the class and methods.
- The details method uses f-strings for clearer output.
- The code is now more modular, readable, and easier to maintain or extend.

Task Description #4 - Inefficient Loop Refactoring

Task: Refactor this inefficient loop with AI help

Python Code

```
nums = [1,2,3,4,5,6,7,8,9,10]
```

```
squares = []
```


```
for i in nums:
```

```
    squares.append(i * i)
```

Expected Output: AI suggested a list comprehension

#Prompt: Refactor this inefficient loop with AI help

Code & Output:



```
1  # Refactored using list comprehension
2  nums = [1,2,3,4,5,6,7,8,9,10]
3  squares = [i * i for i in nums]
4  print(squares) # Output: [1, 4, 9, 16, 25, 36, 49, 64, 81, 100]
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS Python + - [] [X] [] [X]

```
PS C:\Users\sravi\OneDrive\Desktop\AIAC> & C:/ProgramData/anaconda3/python.exe c:/Users/sravi/OneDrive/Desktop/AIAC/Untitled-2.py
[1, 4, 9, 16, 25, 36, 49, 64, 81, 100]
PS C:\Users\sravi\OneDrive\Desktop\AIAC>
```

Explanation:

- The original loop is replaced with a list comprehension, which is more concise and efficient in Python.
- This approach creates the squares list in a single line, improving readability and performance for large lists.

