Vežba 6 – Dodatak

OSI Model				
Layer		Data unit	Function[3]	Examples
Host layers	7. Application	Data	High-level APIs, including resource sharing, remote file access, directory services and virtual terminals	HTTP, FTP, SMTP
	6. Presentation		Translation of data between a networking service and an application; including character encoding, data compression and encryption/decryption	ASCII, EBCDIC, JPEG
	5. Session		Managing communication sessions, i.e. continuous exchange of information in the form of multiple back-and-forth transmissions between two nodes	RPC, PAP
	4. Transport	Segments	Reliable transmission of data segments between points on a network, including segmentation, acknowledgement and multiplexing	TCP, UDP
Media layers	3. Network	Packet/Datagram	Structuring and managing a multi-node network, including addressing, routing and traffic control	IPv4, IPv6, IPsec, AppleTalk
	2. Data link	Bit/Frame	Reliable transmission of data frames between two nodes connected by a physical layer	PPP, IEEE 802.2, L2TP
	1. Physical	Bit	Transmission and reception of raw bit streams over a physical medium	DSL, USB

TCP Header

Offsets Octet		0								1								2								3							
Octet	Bit	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
0	0	Source port																Destination port														
4	32	Sequence number																															
8	64	Acknowledgment number (if ACK set)																															
12	96	Data offset				Reserved 0 0 0				NS	CWR	ECE	URG	ACK	PSH	RST	SYN	FIN	Window Size														
16	128	Checksum																Urgent pointer (if URG set)														
20 ...	160 ...	Options (if *data offset* > 5. Padded at the end with "0" bytes if necessary.) ...																															

UDP Header

Offsets Octet		0								1								2								3							
Octet	Bit	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
0	0	Source port																Destination port															
4	32	Length																Checksum															

IPv4 Header Format

Offsets	Octet	0								1								2								3							
Octet	Bit	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
0	0	Version				IHL				DSCP						ECN		Total Length															
4	32	Identification																Flags			Fragment Offset											
8	64	Time To Live								Protocol								Header Checksum															
12	96	Source IP Address																															
16	128	Destination IP Address																															
20	160	Options (if IHL > 5)