

Puppet Mastery Part-8 (Practical 17) — Ruby Foundations for Puppet, Puppet DSL, and Custom Function Integration

```
ubuntu@puppet-agent01: ~  
ubuntu@puppet-agent01:~$ ruby --version  
ruby 3.0.2p107 (2021-07-07 revision 0db68f0233) [x86_64-linux-gnu]  
ubuntu@puppet-agent01:~$ irb  
irb(main):001:0> puts "Hello Puppet"  
Hello Puppet  
=> nil  
irb(main):002:0> name = "WEB-01"  
=> "WEB-01"  
irb(main):003:0> puts name  
WEB-01  
=> nil  
irb(main):004:0> name.class  
=> String  
irb(main):005:0> backends = ["WEB-01","WEB-02","WEB-03"]  
=> ["WEB-01", "WEB-02", "WEB-03"]  
irb(main):006:0> backends.class  
=> Array  
irb(main):007:0> backends[0]  
=> "WEB-01"  
irb(main):008:0> backends << "WEB-04"  
=> ["WEB-01", "WEB-02", "WEB-03", "WEB-04"]  
irb(main):009:1* servers = {  
irb(main):010:1*   "web01" => "10.0.0.10",  
irb(main):011:1*   "web02" => "10.0.0.11",
```

```
ubuntu@puppet-agent01: ~  
WEB-01  
=> nil  
irb(main):004:0> name.class  
=> String  
irb(main):005:0> backends = ["WEB-01","WEB-02","WEB-03"]  
=> ["WEB-01", "WEB-02", "WEB-03"]  
irb(main):006:0> backends.class  
=> Array  
irb(main):007:0> backends[0]  
=> "WEB-01"  
irb(main):008:0> backends << "WEB-04"  
=> ["WEB-01", "WEB-02", "WEB-03", "WEB-04"]  
irb(main):009:1* servers = {  
irb(main):010:1*   "web01" => "10.0.0.10",  
irb(main):011:1*   "web02" => "10.0.0.11",  
irb(main):012:1*   "web03" => "10.0.0.12"  
irb(main):013:0> }  
=> {"web01"=>"10.0.0.10", "web02"=>"10.0.0.11", "web03"=>"10.0.0.12"}  
irb(main):014:0> servers.class  
=> Hash  
irb(main):015:0> servers["web01"]  
=> "10.0.0.10"  
irb(main):016:0> servers.length  
=> 3
```

```
irb(main):001:1* servers = {  
irb(main):002:1*   "web-01" => "10.0.0.1",  
irb(main):003:1*   "web-02" => "10.0.0.2",  
irb(main):004:1*   "web-03" => "10.0.0.3"  
irb(main):005:0> }  
=> {"web-01"=>"10.0.0.1", "web-02"=>"10.0.0.2", "web-03"=>"10.0.0.3"}  
irb(main):006:0> servers.class  
=> Hash  
irb(main):007:1* servers.each do |name,ip|  
irb(main):008:1*   puts "#{name} -> #{ip}"  
irb(main):009:0> end  
web-01 -> 10.0.0.1  
web-02 -> 10.0.0.2  
web-03 -> 10.0.0.3  
=> {"web-01"=>"10.0.0.1", "web-02"=>"10.0.0.2", "web-03"=>"10.0.0.3"}  
irb(main):010:0> |
```

```
ubuntu@puppet-agent01: ~  
ubuntu@puppet-agent01:~$ irb  
irb(main):001:1* servers = {  
irb(main):002:1*   "web01" => "10.0.0.10",  
irb(main):003:1*   "web02" => "10.0.0.11",  
irb(main):004:1*   "web03" => "10.0.0.12"  
irb(main):005:0> }  
=> {"web01"=>"10.0.0.10", "web02"=>"10.0.0.11", "web03"=>"10.0.0.12"}  
irb(main):006:1* servers.each do |name,ip|  
irb(main):007:1*   puts name  
irb(main):008:0> end  
web01  
web02  
web03  
=> {"web01"=>"10.0.0.10", "web02"=>"10.0.0.11", "web03"=>"10.0.0.12"}  
irb(main):009:0> numbers = [1,2,3,4]  
=> [1, 2, 3, 4]  
irb(main):010:1* numbers.map do |x|  
irb(main):011:1*   x*2  
irb(main):012:0> end  
=> [2, 4, 6, 8]  
irb(main):013:1* numbers.select do |x|  
irb(main):014:1*   x>3  
irb(main):015:0> end  
=> [4]
```

```
ubuntu@puppet-agent01: ~  
irb(main):034:1*   puts "Hello #{name}"  
irb(main):035:0> end  
=> :greet  
irb(main):036:0> greet("vishnu")  
Hello Vishnu  
=> nil  
irb(main):037:1* def deployment_identity(role,environment)  
irb(main):038:1*   "#{environment}-#{role}"  
irb(main):039:0> end  
=> :deployment_identity  
irb(main):040:0> get=deployment_identity("web","development")  
=> "development-web"  
irb(main):041:0> puts get  
development-web  
=> nil  
irb(main):042:0> exit  
ubuntu@puppet-agent01:~$ nano ruby_practical.rb  
ubuntu@puppet-agent01:~$ ruby ruby_practical.rb  
Backend Servers:  
web01 -> 10.0.0.10  
web02 -> 10.0.0.11  
web03 -> 10.0.0.12  
Package Manager: apt  
ubuntu@puppet-agent01:~$ 0
```