

Catalog Placements Assignment

Duration: 1.5 hours

Testing Environment/IDE: Use any IDE or environment you are comfortable with

Language: Any language except Python is allowed

Submission: Push your code to **GitHub** and verify the submission with us manually.

Problem Statement

In this assignment, you'll work on a simplified version of Shamir's Secret Sharing algorithm.

Consider an unknown polynomial of degree m . You would require $m+1$ roots of the polynomial to solve for the coefficients, represented as $k = m + 1$.

An unknown polynomial of degree m can be represented as:

$$f(x) = a_m x^m + a_{m-1} x^{m-1} + \dots + a_1 x + c$$

Where:

- $f(x)$ is the polynomial function
- m is the degree of the polynomial
- $a_m, a_{m-1}, \dots, a_1, c$ are coefficients (real numbers)
- $a_m \neq 0$ (since it's the highest degree term, ensuring the polynomial is of degree m)

This representation shows that a polynomial of degree m is a sum of terms, where each term is a coefficient multiplied by a power of x . The highest power of x is m , and the powers decrease by 1 for each subsequent term until we reach the constant term c , which has no x .

The task is to find the constant term i.e, ' c ' of the polynomial with the given roots. However, the points are not provided directly but in a specific format.

You need to read the input from the test cases provided in JSON format.

Sample Test Case:

```
{ "keys": { "n": 4, "k": 3 }, "1": { "base": "10", "value": "4" }, "2": {  
  "base": "2", "value": "111" }, "3": { "base": "10", "value": "12" }, "6":  
  { "base": "4", "value": "213" } }
```

n: The number of roots provided in the given JSON

k: The minimum number of roots required to solve for the coefficients of the polynomial

$k = m + 1$, where m is the degree of the polynomial

Root Format Example:

```
"2": { "base": "2", "value": "111" }
```

Consider the above root as (x, y):

- x is the key of the object (in this case, $x = 2$)
- y value is encoded with a given base
- Decode y value: 111 in base 2 is 7
- Therefore, $x = 2$ and $y = 7$

You can use any known method to find the coefficients of the polynomial, such as:

- Lagrange interpolation
- Matrix method
- Gauss elimination

Solve for the constant term of the polynomial, typically represented as c.

Assignment Checkpoints:

- 1. Read the Test Case (Input) from a JSON file
 - Parse and read the input provided in JSON format from a separate file, which contains a series of polynomial roots

- 2. Decode the Y Values
 - Correctly decode the Y values that are encoded using different bases
- 3. Find the Secret (C)
 - Calculate the secret c using the decoded Y values and any known method

Output: Print 'c'.

Hint: Although you can't test your code against the test case in a testing environment, you can double-check it manually by solving the polynomial on paper and comparing the outputs.

Good luck!

Find the second testcase here.

```
{ "keys": { "n": 9, "k": 6 }, "1": { "base": "10", "value":  
"28735619723837" }, "2": { "base": "16", "value": "1A228867F0CA" }, "3":  
{ "base": "12", "value": "32811A4AA0B7B" }, "4": { "base": "11", "value":  
"917978721331A" }, "5": { "base": "16", "value": "1A22886782E1" }, "6": {  
"base": "10", "value": "28735619654702" }, "7": { "base": "14", "value":  
"71AB5070CC4B" }, "8": { "base": "9", "value": "122662581541670" }, "9":  
{ "base": "8", "value": "642121030037605" } }
```