

Day 2: Java Bootcamp

1. Create a class Student with instance variables:

name

rollNo

Create a method display() that uses a local variable

college = "ABC Engineering College" and displays all details.

Sample output:

name: Raj

Roll NO: 101

College: ABC Engineering College.

```
class Student {
```

```
    String name;
```

```
    int rollNo;
```

```
    void display() {
```

```
        String college = "ABC Engineering College";
```

```
        System.out.println("Name: " + name);
```

```
        System.out.println("Roll No: " + rollNo);
```

```
        System.out.println("College: " + college);
```

```
    }
```

```
    public static void main(String[] args) {
```

```
        Student s = new Student();
```

```
        s.name = "Raj";
```

```
        s.rollNo = 101;
```

```
        s.display();
```

```
    }
```

```
}
```


Output :

Name: Raj

Roll NO: 101

College: ABC Engineering College.

2. Employee salary

Create a class Employee with an instance variable basicSalary.

Inside a method calculatesalary(), declare a local variable

bonus = 5000 and display the total salary

Sample output:

Basic salary: 30000

Bonus : 5000

Total salary: 35000

Employee salary

Class Employee {

double basicSalary;

void calculatesalary() {

double bonus = 5000;

double totalSalary = basicSalary + bonus;

System.out.println("Basic salary:" + basicSalary);

System.out.println("Bonus:" + bonus);

System.out.println("Total salary:" + totalSalary);

}


```

public static void main (String [] args) {
    Employee emp = new Employee();
    emp.basicSalary = 30000;
    emp.calculateSalary();
}
}

```

output :

Basic salary : 30000.0

Bonus : 5000.0

Total salary : 35000.0

3) Rectangle Area

Create a class Rectangle with instance variables

length

breadth

Inside a method findArea(), declare a local variable area and calculate the area of the rectangle

Sample output :

Length = 10

Breadth = 5

Area = 50.

Rectangle Area (Java Program) Find Area using class

Class Rectangle {

int length;

int breadth;

void findArea() {

int area = length * breadth;

System.out.println("length = " + length);

System.out.println("Breadth = " + breadth);

System.out.println("Area = " + area);

}

public static void main (String [] args) {

Rectangle r = new Rectangle ();

r.length = 10;

r.breadth = 5;

r.findArea();

}

}

Output :

length = 10

Breadth = 5

Area = 50.

21) Bank Account

Create a class BankAccount with an instance variable balance

Inside a method deposit(), declare a local variable depositAmount and update the balance.

Sample output:

Current Balance : 10000

Deposit Amount : 2000

Updated Balance : 12000

```
class BankAccount {
```

```
    double balance;
```

```
    void deposit() {
```

```
        double depositAmount = 2000;
```

```
        System.out.println("Current Balance:" + balance);
```

```
        balance = balance + depositAmount;
```

```
        System.out.println("Deposit Amount:" + depositAmount);
```

```
        System.out.println("Updated Balance:" + balance);
```

```
    }
```

```
    public static void main (String [] args) {
```

```
        BankAccount account = new BankAccount();
```

```
        account.balance = 10000;
```

```
        account.deposit();
```

```
    }
```

```
}
```


output :

Current Balance : 10000.0

Deposit Amount : 2000.0

Updated Balance : 12000.0

5. Circle Area

Create a class circle with an instance variable radius.
Inside a method calculateArea(), declare a local variable
 $\pi = 3.14$ and calculate the area of the circle.

Sample output :

Radius = 7

Area = 153.86

class Circle {

double radius;

void calculateArea() {

double $\pi = 3.14$;

double area = $\pi * \text{radius} * \text{radius}$;

System.out.println("Radius = " + radius);

System.out.println("Area = " + area);

}

public static void main (String[] args) {

Circle c = new Circle();

c.radius = 7;

c.calculateArea();

}

}

Output:

Radius = 7.0

Area = 153.86